EXERCISE

Multimodal actions

Transfer: one route is more common

Find the squared-error minimizer u; compare it with the mode.

$$P(A = -2 \mid o) = \tfrac{3}{4}, \quad P(A = 2 \mid o) = \tfrac{1}{4}$$

- A random action at fixed observation o
- u deterministic prediction to optimize

DL §3.8; course exercise · Goodfellow et al. (2016)

SOLUTION

Multimodal actions

Transfer: one route is more common

Solution 1 / 1

Choose the conditional mean

A is the random action; u is a deterministic prediction.

---

1. Squared error is minimized by $u^* = \mathbb{E}[A \mid o]$.
2. $u^* = \frac{3}{4}(-2) + \frac{1}{4}(2) = -\frac{3}{2} + \frac{1}{2} = -1$.
3. The mode is -2, while the minimum-risk mean is -1.

DL §3.8; course exercise · Goodfellow et al. (2016)

RESULT

Multimodal actions

Transfer: one route is more common

Find the squared-error minimizer u; compare it with the mode.

$$P(A = -2 \mid o) = \tfrac{3}{4}, \quad P(A = 2 \mid o) = \tfrac{1}{4}$$

A random action at fixed observation o

u deterministic prediction to optimize

> **Check** $u^* = -1$; a mean need not be a mode.

DL §3.8; course exercise · Goodfellow et al. (2016)

EXERCISE

Multimodal actions

A distribution and its mean answer different questions

Fixed observation; equally likely actions -2 and 2.
Compare: conditional mean vs a random draw.

Diffusion Policy §4.1; course exercise · Chi et al. (2023/2024)

SOLUTION

Multimodal actions

A distribution and its mean answer different questions

Solution 1 / 1

Compare the operations

A is drawn from the two-point action distribution.

---

1. $\mathbb{E}[A \mid o] = 0$: averaging returns one fixed value.
2. $A \sim p(\cdot \mid o)$: sampling returns -2 or 2, each with probability one half.
3. A correct distribution can still have an unusable mean.

Diffusion Policy §4.1; course exercise · Chi et al. (2023/2024)

RESULT

Multimodal actions

A distribution and its mean answer different questions

Fixed observation; equally likely actions -2 and 2.
Compare: conditional mean vs a random draw.

> **Check** Sampling preserves the two choices.

Diffusion Policy §4.1; course exercise · Chi et al. (2023/2024)

EXERCISE

Forward diffusion

Check the conditional mean and covariance

Find the conditional mean and covariance of x_k.

$$x_k = \sqrt{1-\beta_k}\, x_{k-1} + \sqrt{\beta_k}\, z_k$$

- $x_{k-1} \in R^d$ fixed previous state
- $0 < \beta_k < 1$ fixed transition variance
- $z_k \sim \mathcal{N}(0, I_d)$ independent fresh noise

DDPM Eq.2; DL §3.8 · Ho, Jain & Abbeel (2020) · Goodfellow et al. (2016)

SOLUTION

Forward diffusion

Check the conditional mean and covariance

Solution 1 / 1

Conditioning fixes the input

z_k has mean zero and covariance I.

1. $\mathbb{E}[x_k \mid x_{k-1}] = \sqrt{1-\beta_k}\, x_{k-1}$.
2. $x_k - \mathbb{E}[x_k \mid x_{k-1}] = \sqrt{\beta_k} z_k$.
3. $\mathrm{Cov}(x_k \mid x_{k-1}) = \beta_k I$.

DDPM Eq.2; DL §3.8 · Ho, Jain & Abbeel (2020) · Goodfellow et al. (2016)

RESULT

Forward diffusion

Check the conditional mean and covariance

Find the conditional mean and covariance of x_k.

$$x_k = \sqrt{1-\beta_k}\, x_{k-1} + \sqrt{\beta_k}\, z_k$$

$x_{k-1} \in R^d$	fixed previous state
$0 < \beta_k < 1$	fixed transition variance
$z_k \sim \mathcal{N}(0, I_d)$	independent fresh noise

> **Check** Mean $\sqrt{1-\beta_k}x_{k-1}$; covariance $\beta_k I$.

DDPM Eq.2; DL §3.8 · Ho, Jain & Abbeel (2020) · Goodfellow et al. (2016)

EXERCISE

Forward diffusion

Transfer: variance is not the noise multiplier

Compute the realized x_k; show both coefficients.

$$x_k = \sqrt{1-\beta_k}\, x_{k-1} + \sqrt{\beta_k}\, z_k$$
$$\beta_k = 0.36, \quad x_{k-1} = 2, \quad z_k = -1$$

β_k variance

x_{k-1}, z_k given scalar values

DDPM Eq.2; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Forward diffusion

Transfer: variance is not the noise multiplier

Solution 1 / 1

Compute coefficients before the state

The fresh noise draw is $z_k = -1$.

1. $\sqrt{1-\beta_k} = \sqrt{0.64} = 0.8$, and $\sqrt{\beta_k} = 0.6$.
2. $x_k = 0.8 \times 2 + 0.6 \times (-1) = 1.6 - 0.6 = 1$.
3. Using 0.36 as the noise multiplier would give the wrong variance.

DDPM Eq.2; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Forward diffusion

Transfer: variance is not the noise multiplier

Compute the realized x_k; show both coefficients.

$$x_k = \sqrt{1-\beta_k}\, x_{k-1} + \sqrt{\beta_k}\, z_k$$
$$\beta_k = 0.36, \quad x_{k-1} = 2, \quad z_k = -1$$

β_k variance

x_{k-1}, z_k given scalar values

> **Check** $x_k = 0.8(2) + 0.6(-1) = 1.$

DDPM Eq.2; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

Forward diffusion

Transfer: a two-component action

Compute x, then recover the sampled noise.

$$x_0 = \begin{bmatrix} 2 \\ -1 \end{bmatrix},\ \epsilon = \begin{bmatrix} -0.5 \\ 1 \end{bmatrix},\ \alpha = 0.8,\ \sigma = 0.6$$

$x_0, \epsilon \in \mathbb{R}^2$	clean and noise column vectors
$x = \alpha x_0 + \sigma \epsilon$	noisy vector; component index differs from diffusion index

DDPM Eq.4; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Forward diffusion

Transfer: a two-component action

Solution 1 / 1

Apply the rule componentwise

x, x_0, ϵ are two-component column vectors.

1. $x_1 = 0.8(2) + 0.6(-0.5) = 1.3.$
2. $x_2 = 0.8(-1) + 0.6(1) = -0.2.$
3. $(x - 0.8x_0)/0.6 = (-0.5, 1)^T = \epsilon.$

DDPM Eq.4; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Forward diffusion

Transfer: a two-component action

Compute x, then recover the sampled noise.

$$x_0 = \begin{bmatrix} 2 \\ -1 \end{bmatrix},\ \epsilon = \begin{bmatrix} -0.5 \\ 1 \end{bmatrix},\ \alpha = 0.8,\ \sigma = 0.6$$

$x_0, \epsilon \in \mathbb{R}^2$	clean and noise column vectors
$x = \alpha x_0 + \sigma \epsilon$	noisy vector; component index differs from diffusion index

> **Check** $x = (1.3, -0.2)^T$.

DDPM Eq.4; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

Forward diffusion

The marginal covariance also contains data spread

Find the mean and covariance of X_k.

$$X_k = \alpha_k X_0 + \sigma_k \epsilon, \quad X_0 \perp \epsilon$$

$X_0, X_k \in R^d$ random clean/noisy dataset vectors

μ_0, Σ_0 finite clean-data mean/covariance

$\epsilon \sim \mathcal{N}(0, I_d)$ independent of X_0

DDPM Eq.4; DL §3.8 · Ho, Jain & Abbeel (2020) · Goodfellow et al. (2016)

SOLUTION

Forward diffusion

The marginal covariance also contains data spread

Solution 1 / 1

Average over examples and noise

X_0 is random; ϵ is independent and centered.

1. $\mathbb{E}[X_k] = \alpha_k \mathbb{E}[X_0] + \sigma_k \mathbb{E}[\epsilon] = \alpha_k \mu_0.$
2. $X_k - \mu_k = \alpha_k (X_0 - \mu_0) + \sigma_k \epsilon.$
3. $\mathrm{Cov}(X_k) = \alpha_k^2 \Sigma_0 + \sigma_k^2 I$; cross terms vanish by independence.

DDPM Eq.4; DL §3.8 · Ho, Jain & Abbeel (2020) · Goodfellow et al. (2016)

RESULT

Forward diffusion

The marginal covariance also contains data spread

Find the mean and covariance of X_k.

$$X_k = \alpha_k X_0 + \sigma_k \epsilon, \quad X_0 \perp \epsilon$$

$X_0, X_k \in R^d$ random clean/noisy dataset vectors

μ_0, Σ_0 finite clean-data mean/covariance

$\epsilon \sim \mathcal{N}(0, I_d)$ independent of X_0

Check $\mu_k = \alpha_k \mu_0$, $\Sigma_k = \alpha_k^2 \Sigma_0 + \sigma_k^2 I$.

DDPM Eq.4; DL §3.8 · Ho, Jain & Abbeel (2020) · Goodfellow et al. (2016)

EXERCISE

Forward diffusion

Does this terminal schedule match the prior?

Can this law be N(0,1)? Check moments.

$$\mathbb{E}[X_K] = \alpha_K \mathbb{E}[X_0], \quad \mathrm{Var}(X_K) = \alpha_K^2 \,\mathrm{Var}(X_0) + \sigma_K^2$$
$$\alpha_K = 0.8,\ \sigma_K = 0.6,\ \mathbb{E}[X_0] = 5,\ \mathrm{Var}(X_0) = 1$$

X_0, X_K clean/noisy scalar data

$N(0,1)$ proposed generation prior

DDPM §4; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Forward diffusion

Does this terminal schedule match the prior?

Solution 1 / 1

Use a necessary moment check

The added standard noise is independent of clean data.

---

1. $\mathbb{E}[X_K] = 0.8 \times 5 = 4.$
2. $\mathrm{Var}(X_K) = 0.8^2(1) + 0.6^2 = 1.$
3. A standard normal has mean zero. Matching its variance does not repair the mean mismatch.

DDPM §4; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Forward diffusion

Does this terminal schedule match the prior?

Can this law be N(0,1)? Check moments.

$$\mathbb{E}[X_K] = \alpha_K \mathbb{E}[X_0], \quad \mathrm{Var}(X_K) = \alpha_K^2 \,\mathrm{Var}(X_0) + \sigma_K^2$$
$$\alpha_K = 0.8,\ \sigma_K = 0.6,\ \mathbb{E}[X_0] = 5,\ \mathrm{Var}(X_0) = 1$$

X_0, X_K clean/noisy scalar data

$N(0,1)$ proposed generation prior

> **Check** Variance 1 alone does not establish N(0,1).

DDPM §4; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

The score

Compute an anisotropic score

Compute s(x). Is its direction parallel to −x?

$$\mu = \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \Sigma = \begin{bmatrix} 4 & 0 \\ 0 & 1 \end{bmatrix}, x = \begin{bmatrix} 2 \\ 1 \end{bmatrix}$$

Σ covariance, not standard deviations

$s(x) = -\Sigma^{-1}(x - \mu)$ score to find

DL §3.9.3; course exercise · Goodfellow et al. (2016)

SOLUTION

The score

Compute an anisotropic score

Solution 1 / 1

Apply the precision matrix

The inverse covariance is the precision matrix.

1. $\Sigma^{-1} = \operatorname{diag}(1/4, 1)$.
2. $s(x) = -\operatorname{diag}(1/4, 1)(2, 1)^T = (-1/2, -1)^T$.
3. The narrower second direction receives stronger correction per unit displacement.

DL §3.9.3; course exercise · Goodfellow et al. (2016)

RESULT

The score

Compute an anisotropic score

Compute s(x). Is its direction parallel to −x?

$$\mu = \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \Sigma = \begin{bmatrix} 4 & 0 \\ 0 & 1 \end{bmatrix}, x = \begin{bmatrix} 2 \\ 1 \end{bmatrix}$$

Σ covariance, not standard deviations

$s(x) = -\Sigma^{-1}(x - \mu)$ score to find

> **Check** $s(x) = (-0.5, -1)^T$.

DL §3.9.3; course exercise · Goodfellow et al. (2016)

EXERCISE

The score

What does a stationary point tell us?

Find s(0). Is x=0 a mode? Explain.

$$p(x) = \tfrac{1}{2}\mathcal{N}(x; -2, 1) + \tfrac{1}{2}\mathcal{N}(x; 2, 1)$$

x scalar state

$s_j(x) = -(x - \mu_j)$ component score for variance 1

DL §3.9.6; course exercise · Goodfellow et al. (2016)

SOLUTION

The score

What does a stationary point tell us?

Solution 1 / 1

Opposing component directions cancel

At $x = 0$, symmetry makes both responsibilities $1/2$.

1. $s_1(0) = -(0 + 2) = -2$, $s_2(0) = -(0 - 2) = 2$.
2. $s(0) = \frac{1}{2}(-2) + \frac{1}{2}(2) = 0$.
3. Each Gaussian has $p_j''(0) = (2^2 - 1)p_j(0)$, so $p''(0) = 3\mathcal{N}(0; 2, 1) > 0$.

DL §3.9.6; course exercise · Goodfellow et al. (2016)

RESULT

The score

What does a stationary point tell us?

Find s(0). Is x=0 a mode? Explain.

$$p(x) = \tfrac{1}{2}\mathcal{N}(x; -2, 1) + \tfrac{1}{2}\mathcal{N}(x; 2, 1)$$

x scalar state

$s_j(x) = -(x - \mu_j)$ component score for variance 1

> **Check** At x=0, score 0 does not imply a mode.

DL §3.9.6; course exercise · Goodfellow et al. (2016)

EXERCISE

The score

Transfer: doubling standard deviation

Compare standard deviations 1 and 2. Compute both scores.

$$\mu = 1, \quad x = 3, \quad s(x) = -(x - \mu)/v$$

- v variance
- $\sqrt{v}$ standard deviation

DL §3.9.3; course exercise · Goodfellow et al. (2016)

SOLUTION

The score

Transfer: doubling standard deviation

Solution 1 / 1

Convert spread into variance

The displacement $x - \mu = 2$ in both models.

1. First: $v = 1^2 = 1$, so $s(3) = -2$.
2. Second: $v = 2^2 = 4$, so $s(3) = -2/4 = -0.5$.
3. The wider log density changes less sharply at the same displacement.

DL §3.9.3; course exercise · Goodfellow et al. (2016)

RESULT

The score

Transfer: doubling standard deviation

Compare standard deviations 1 and 2. Compute both scores.

$$\mu = 1, \quad x = 3, \quad s(x) = -(x - \mu)/v$$

v variance

$\sqrt{v}$ standard deviation

> **Check** Doubling standard deviation divides the score by four.

DL §3.9.3; course exercise · Goodfellow et al. (2016)

EXERCISE

Learning to denoise

Noise prediction gives a score estimate

Explain the minus sign and the factor 1/σ_k.

$$s_k(x) = -\frac{\mathbb{E}[\epsilon \mid x_k = x, k]}{\sigma_k} \approx -\frac{\epsilon_\theta(x, k)}{\sigma_k}$$

- s_k marginal noisy-data score
- $\sigma_k > 0$ noise standard deviation

Vincent (2011) §4.2, Eqs.4.3–4.5; DDPM §3.2 · Ho, Jain & Abbeel (2020) · Vincent (2011)

SOLUTION

Learning to denoise

Noise prediction gives a score estimate

Solution 1 / 2

Join regression to the score identity

At fixed k, $\sigma_k > 0$ is constant.

---

1. $\nabla \log q_k = -\epsilon / \sigma_k$.
2. $s_k = \mathbb{E}[\nabla \log q_k \mid x_k] = -\mathbb{E}[\epsilon \mid x_k] / \sigma_k$.
3. The MSE optimum is $\epsilon_\theta^* = \mathbb{E}[\epsilon \mid x_k]$.

Vincent (2011) §4.2, Eqs.4.3–4.5; DDPM §3.2 · Ho, Jain & Abbeel (2020) · Vincent (2011)

SOLUTION

Learning to denoise

Noise prediction gives a score estimate

Solution 2 / 2

Noise regression is a form of denoising score matching

Fix k; set $s_\theta = -\epsilon_\theta/\sigma_k$, $c = \nabla_x \log q_k = -\epsilon/\sigma_k$.

1. $\mathbb{E}\|\epsilon_\theta - \epsilon\|^2 = \sigma_k^2 \mathbb{E}\|s_\theta - c\|^2$.
2. $\mathbb{E}\|s_\theta - c\|^2 = \mathbb{E}\|s_\theta - s_k\|^2 + C_k$.
3. Denoising score matching fits the conditional score target. C_k is its irreducible conditional variance, independent of theta.

Vincent (2011) §4.2, Eqs.4.3–4.5; DDPM §3.2 · Ho, Jain & Abbeel (2020) · Vincent (2011)

RESULT

Learning to denoise

Noise prediction gives a score estimate

Explain the minus sign and the factor 1/σ_k.

$$s_k(x) = -\frac{\mathbb{E}[\epsilon \mid x_k = x, k]}{\sigma_k} \approx -\frac{\epsilon_\theta(x, k)}{\sigma_k}$$

s_k marginal noisy-data score

$\sigma_k > 0$ noise standard deviation

> **Check** $s_\theta = -\epsilon_\theta / \sigma_k$.

Vincent (2011) §4.2, Eqs.4.3–4.5; DDPM §3.2 · Ho, Jain & Abbeel (2020) · Vincent (2011)

EXERCISE

Learning to denoise

What can a zero noise prediction mean?

Find the noise for each clean hypothesis, then its mean.

$$X_0 \in \{-1, 1\}, \quad \alpha = \sigma = 1/\sqrt{2}, \quad X_k = 0$$

X_0 clean values −1,+1, each probability 1/2

$X_k = \alpha X_0 + \sigma\epsilon$ Gaussian ε independent of X_0; condition via its density

DDPM Eq.14; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Learning to denoise

What can a zero noise prediction mean?

Solution 1 / 1

Two explanations of one input

The symmetric likelihoods give equal posterior weights.

1. If $X_0 = 1$, then $0 = (1 + \epsilon)/\sqrt{2}$, so $\epsilon = -1$.
2. If $X_0 = -1$, the required noise is $\epsilon = 1$.
3. $\mathbb{E}[\epsilon \mid X_k = 0] = (-1 + 1)/2 = 0$.

DDPM Eq.14; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Learning to denoise

What can a zero noise prediction mean?

Find the noise for each clean hypothesis, then its mean.

$$X_0 \in \{-1, 1\}, \quad \alpha = \sigma = 1/\sqrt{2}, \quad X_k = 0$$

X_0 clean values $-1, +1$, each probability 1/2

$X_k = \alpha X_0 + \sigma \epsilon$ Gaussian ε independent of X_0; condition via its density

> **Check** Zero conditional mean can average nonzero noises.

DDPM Eq.14; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

Learning to denoise

How does predictor error reach the clean estimate?

Find $\Delta\hat{x}_0$. Compare $\alpha=0.8$ and $\alpha=0.1$, with $\sigma^2=1-\alpha^2$.

$$\hat{x}_0 = \frac{x - \sigma\hat{\epsilon}}{\alpha}, \quad \hat{\epsilon} = \epsilon^* + \delta$$

- ϵ^* optimal mean-noise predictor
- δ prediction error; alpha > 0

DDPM Eq.11; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Learning to denoise

How does predictor error reach the clean estimate?

Solution 1 / 1

Subtract the two estimates

Both estimates use the same x, α and σ.

1. $\Delta\hat{x}_0 = [x - \sigma(\epsilon^* + \delta)]/\alpha - [x - \sigma\epsilon^*]/\alpha.$
2. $\Delta\hat{x}_0 = -(\sigma/\alpha)\delta.$
3. Error magnitude is multiplied by σ/α: 0.75 at $\alpha = 0.8$, and $\sqrt{0.99}/0.1 \approx 9.95$ at $\alpha = 0.1$.

DDPM Eq.11; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Learning to denoise

How does predictor error reach the clean estimate?

Find $\Delta\hat{x}_0$. Compare $\alpha=0.8$ and $\alpha=0.1$, with $\sigma^2=1-\alpha^2$.

$$\hat{x}_0 = \frac{x - \sigma\hat{\epsilon}}{\alpha}, \quad \hat{\epsilon} = \epsilon^* + \delta$$

- ϵ^* optimal mean-noise predictor
- δ prediction error; alpha > 0

> **Check** $\Delta\hat{x}_0 = -(\sigma/\alpha)\delta$.

DDPM Eq.11; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

Learning to denoise

Checkpoint: trace an input to a score

Data → known corruption → noise regression → score
Which quantity is sampled, observed, and learned?

DDPM Algorithm 1; Vincent (2011) §4.2, Eqs.4.3–4.5 · Ho, Jain & Abbeel (2020) · Vincent (2011)

SOLUTION

Learning to denoise

Checkpoint: trace an input to a score

Solution 1 / 1

Connect the four objects

At one training level, α and σ are fixed.

---

1. $x_0 \sim p_0$, $\epsilon \sim \mathcal{N}(0, I)$, then $x = \alpha x_0 + \sigma\epsilon$.
2. Input (x, k); target ϵ; population optimum $\mathbb{E}[\epsilon \mid x, k]$.
3. $s_k(x) = -\mathbb{E}[\epsilon \mid x, k]/\sigma$.

DDPM Algorithm 1; Vincent (2011) §4.2, Eqs.4.3–4.5 · Ho, Jain & Abbeel (2020) · Vincent (2011)

RESULT

Learning to denoise

Checkpoint: trace an input to a score

Data → known corruption → noise regression → score
Which quantity is sampled, observed, and learned?

> **Check** Training learns a conditional mean noise field.

DDPM Algorithm 1; Vincent (2011) §4.2, Eqs.4.3–4.5 · Ho, Jain & Abbeel (2020) · Vincent (2011)

EXERCISE

Reverse sampling

A reverse draw uses a standard deviation

Compute one draw and the variance across repeated draws.

$$x_{k-1} = \mu_\theta + \sqrt{\tilde{\beta}_k}\, z, \quad z \sim \mathcal{N}(0, I)$$

$\mu_\theta = 1.025$ reverse mean from the previous example

$\tilde{\beta}_k = 0.24609375,\ z = -1$ derived posterior variance; fresh draw

DDPM Algorithm 2; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Reverse sampling

A reverse draw uses a standard deviation

Solution 1 / 1

Continue the same forward schedule

$\beta_k = 0.36$, $a_k = 0.64$, $\sigma_k = 0.8$; hence $\bar{a}_k = 0.36$.

1. $\bar{a}_{k-1} = .36/.64 = .5625.$
2. $\tilde{\beta}_k = .36(1 - .5625)/.64 = .24609375.$
3. $\sqrt{\tilde{\beta}_k} \approx .4960784$; $x_{k-1} = 1.025 - .4960784 = .5289216.$
4. Across fresh draws, $\mathrm{Var}(x_{k-1} \mid x_k) = .24609375$ in this Gaussian model.

DDPM Algorithm 2; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Reverse sampling

A reverse draw uses a standard deviation

Compute one draw and the variance across repeated draws.

$$x_{k-1} = \mu_\theta + \sqrt{\tilde{\beta}_k}\, z, \qquad z \sim \mathcal{N}(0, I)$$

$\mu_\theta = 1.025$ reverse mean from the previous example

$\tilde{\beta}_k = 0.24609375,\ z = -1$ derived posterior variance; fresh draw

Check $x_{k-1} = 1.025 - \sqrt{0.24609375} \approx 0.5289.$

DDPM Algorithm 2; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

Reverse sampling

Does a mean predictor force identical samples?

Same observation and trained weights.
Different initial Gaussian draws.
Must the final samples be identical?

DDPM Algorithm 2; course exercise · Ho, Jain & Abbeel (2020)

SOLUTION

Reverse sampling

Does a mean predictor force identical samples?

Solution 1 / 1

Follow the whole random process

The network is deterministic at a fixed input and level.

1. X_K is random, so $\mu_\theta(X_K, K)$ can vary.
2. For stochastic reverse steps, fresh z_k adds variation.
3. A conditional mean at each state does not equal the unconditional mean of every final sample.

DDPM Algorithm 2; course exercise · Ho, Jain & Abbeel (2020)

RESULT

Reverse sampling

Does a mean predictor force identical samples?

Same observation and trained weights.
Different initial Gaussian draws.
Must the final samples be identical?

> **Check** A conditional mean field is not one fixed output.

DDPM Algorithm 2; course exercise · Ho, Jain & Abbeel (2020)

EXERCISE

Reverse sampling

Transfer: check deterministic sampling at the endpoint

Compute the deterministic clean-endpoint output. Can different initial noise draws still produce different outputs?

$$x_k = 0.9, \quad \alpha_k = 0.8, \quad \sigma_k = 0.6, \quad \hat{\epsilon} = 0.5$$

$\alpha_0 = 1, \sigma_0 = 0$ clean endpoint

x_0^{out} deterministic output to find

DDIM Eq.12; course exercise · Song, Meng & Ermon (2021)

SOLUTION

Reverse sampling

Transfer: check deterministic sampling at the endpoint

Solution 1 / 1

Set the destination to the clean endpoint

At level zero, signal coefficient is one and noise coefficient is zero.

---

1. $\hat{x}_0 = (0.9 - 0.3)/0.8 = 0.75.$
2. $x_0^{\text{out}} = 1\hat{x}_0 + 0\hat{\epsilon} = 0.75.$
3. The initial random state can still differ across generation runs; no fresh endpoint noise is added.

DDIM Eq.12; course exercise · Song, Meng & Ermon (2021)

RESULT

Reverse sampling

Transfer: check deterministic sampling at the endpoint

Compute the deterministic clean-endpoint output. Can different initial noise draws still produce different outputs?

$$x_k = 0.9, \quad \alpha_k = 0.8, \quad \sigma_k = 0.6, \quad \hat{\epsilon} = 0.5$$

$\alpha_0 = 1, \sigma_0 = 0$ clean endpoint

x_0^{out} deterministic output to find

> **Check** $x_0^{\text{out}} = (0.9 - 0.6(0.5))/0.8 = 0.75.$

DDIM Eq.12; course exercise · Song, Meng & Ermon (2021)

EXERCISE

Reverse sampling

A step budget trades computation for approximation

Assumed cost: 8 ms per network evaluation.
Compare 20 evaluations with 5.
Which claims require an experiment?

Diffusion Policy §3.4; course exercise · Chi et al. (2023/2024)

SOLUTION

Reverse sampling

A step budget trades computation for approximation

Solution 1 / 1

Separate timing arithmetic from quality evidence

The hypothetical cost is 8 ms per sequential network evaluation.

1. 20 evaluations: 20 × 8 = 160 ms. Five evaluations: 5 × 8 = 40 ms.
2. Fixed overhead and hardware details were omitted, so these are model-only estimates.
3. Equal task success does not follow from the timing calculation.

Diffusion Policy §3.4; course exercise · Chi et al. (2023/2024)

RESULT

Reverse sampling

A step budget trades computation for approximation

Assumed cost: 8 ms per network evaluation.
Compare 20 evaluations with 5.
Which claims require an experiment?

> **Check** Model time: 160 ms vs 40 ms; quality must be measured.

Diffusion Policy §3.4; course exercise · Chi et al. (2023/2024)

EXERCISE

Conditioning

Transfer: calculate and interpret guidance

Compute guided noise and score for each w.

$$\hat{\epsilon}_g = \hat{\epsilon}_u + w(\hat{\epsilon}_c - \hat{\epsilon}_u), \qquad s_g = -\hat{\epsilon}_g / \sigma_k$$

$\hat{\epsilon}_u = 0.2,\ \hat{\epsilon}_c = -0.1$ null-context / conditional noise

$\sigma_k = 0.5$ shared noise standard deviation

$w = 0, 1, 2$ guidance scales to compare

Classifier-Free Guidance §3.2; course exercise · Ho & Salimans (2022)

SOLUTION

Conditioning

Transfer: calculate and interpret guidance

Solution 1 / 1

Compute the difference and apply the scale

Conditional minus unconditional predicted noise is -0.3.

1. $w = 0$: $\hat{\epsilon}_g = 0.2$, so $s_g = -0.4$.
2. $w = 1$: $\hat{\epsilon}_g = -0.1$, so $s_g = 0.2$.
3. $w = 2$: $\hat{\epsilon}_g = -0.4$, so $s_g = 0.8$; this extrapolates.

Classifier-Free Guidance §3.2; course exercise · Ho & Salimans (2022)

RESULT

Conditioning

Transfer: calculate and interpret guidance

Compute guided noise and score for each w.

$$\hat{\epsilon}_g = \hat{\epsilon}_u + w(\hat{\epsilon}_c - \hat{\epsilon}_u), \qquad s_g = -\hat{\epsilon}_g / \sigma_k$$

$\hat{\epsilon}_u = 0.2,\ \hat{\epsilon}_c = -0.1$	null-context / conditional noise
$\sigma_k = 0.5$	shared noise standard deviation
$w = 0, 1, 2$	guidance scales to compare

> **Check** w=1 gives the ordinary conditional prediction.

Classifier-Free Guidance §3.2; course exercise · Ho & Salimans (2022)

EXERCISE

Diffusion Policy

Three horizons serve different purposes

Count observations, predicted scalars, and executed steps.

$$H_o = 2, \quad H_p = 4, \quad H_a = 2, \quad d_a = 2$$

- H_o observations supplied
- H_p actions predicted
- H_a actions executed before replanning

Diffusion Policy §2.3; course exercise · Chi et al. (2023/2024)

SOLUTION

Diffusion Policy

Three horizons serve different purposes

Solution 1 / 1

Read each horizon in its own clock

Each of four predicted actions has two components.

1. Observation input: two recent observations.
2. Prediction: $4 \times 2 = 8$ scalar components.
3. Execution: apply the first two actions, then obtain new observations and replan.

Diffusion Policy §2.3; course exercise · Chi et al. (2023/2024)

RESULT

Diffusion Policy

Three horizons serve different purposes

Count observations, predicted scalars, and executed steps.

$$H_o = 2, \quad H_p = 4, \quad H_a = 2, \quad d_a = 2$$

- H_o observations supplied
- H_p actions predicted
- H_a actions executed before replanning

> **Check** 2 observations; 8 predicted scalars; execute 2 steps.

Diffusion Policy §2.3; course exercise · Chi et al. (2023/2024)

EXERCISE

Diffusion Policy

A receding horizon closes the feedback loop

Receding-horizon execution predicts a sequence, applies a prefix and replans from fresh observations.
What happens to the unused suffix?

Diffusion Policy §2.3 · Chi et al. (2023/2024)

SOLUTION

Diffusion Policy

A receding horizon closes the feedback loop

Solution 1 / 1

Close the feedback loop

The learned parameters remain fixed during deployment.

1. Collect the current observation context, then denoise an initialized action chunk.
2. Execute its first H_a actions using the robot controller.
3. Refresh the context and generate a new chunk; the unexecuted suffix is not a commitment.

Diffusion Policy §2.3 · Chi et al. (2023/2024)

RESULT

Diffusion Policy

A receding horizon closes the feedback loop

Receding-horizon execution predicts a sequence, applies a prefix and replans from fresh observations.
What happens to the unused suffix?

> **Check** Replan using fresh observations; do not blindly replay the old suffix.

Diffusion Policy §2.3 · Chi et al. (2023/2024)

EXERCISE

Diffusion Policy

Transfer: change execution without changing the sampler

Targets: 0.6 m, then 0.3 m. Compare H_a=1 and H_a=2. An obstacle moves after the first action: which policy can refresh its second target?

Diffusion Policy §2.3; course exercise · Chi et al. (2023/2024)

SOLUTION

Diffusion Policy

Transfer: change execution without changing the sampler

Solution 1 / 1

Separate generation from execution

The clean predicted chunk and sampler are unchanged.

1. $H_a = 1$: execute 0.6 m target, observe, then regenerate the next target.
2. $H_a = 2$: execute both planned targets before the policy replans.
3. The first policy can incorporate the new observation earlier; neither horizon alone guarantees safety.

Diffusion Policy §2.3; course exercise · Chi et al. (2023/2024)

RESULT

Diffusion Policy

Transfer: change execution without changing the sampler

Targets: 0.6 m, then 0.3 m. Compare H_a=1 and H_a=2. An obstacle moves after the first action: which policy can refresh its second target?

> **Check** Shorter execution horizon refreshes policy feedback sooner.

Diffusion Policy §2.3; course exercise · Chi et al. (2023/2024)

EXERCISE

Diffusion Policy

A low denoising loss is not a deployment certificate

Training metric: noise-prediction error.
Deployment question: does the closed-loop task succeed?
Give two missing checks.

Diffusion Policy §§5,9; course exercise · Chi et al. (2023/2024)

SOLUTION

Diffusion Policy

A low denoising loss is not a deployment certificate

Solution 1 / 1

Trace the gap to the physical task

Noise loss is a surrogate measured on a specified data distribution.

1. New observations can lie outside that distribution; evaluate held-out environments.
2. Wrong units, action alignment, controller tracking or latency can break an otherwise correct denoiser.
3. Measure repeated closed-loop task success and variability across trials; plausible samples alone do not enforce every physical constraint.

Diffusion Policy §§5,9; course exercise · Chi et al. (2023/2024)

RESULT

Diffusion Policy

A low denoising loss is not a deployment certificate

Training metric: noise-prediction error.
Deployment question: does the closed-loop task succeed?
Give two missing checks.

> **Check** Validate the entire observation-to-action loop.

Diffusion Policy §§5,9; course exercise · Chi et al. (2023/2024)