

CS3230

Tutorial 7

1. Consider the following undirected graph.

$G = (V, E)$, where the set of vertices is $\{1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12\}$, and the edges and their weights are given as follows:

$wt(1, 2) = 3$, $wt(1, 5) = 2$, $wt(1, 4) = 10$, $wt(2, 3) = 4$, $wt(2, 5) = 9$, $wt(3, 5) = 6$,
 $wt(3, 6) = 5$, $wt(4, 5) = 4$, $wt(4, 7) = 4$, $wt(5, 6) = 3$, $wt(5, 7) = 6$, $wt(5, 8) = 2$,
 $wt(5, 9) = 6$, $wt(6, 9) = 6$, $wt(7, 8) = 8$, $wt(7, 10) = 3$, $wt(8, 9) = 8$, $wt(8, 10) = 3$,
 $wt(8, 11) = 5$, $wt(8, 12) = 7$, $wt(9, 12) = 4$, $wt(10, 11) = 5$, $wt(11, 12) = 2$

- (a) Use Prim's algorithm to find a minimal spanning tree for the graph. Start with node 1.
- (b) Use Kruskal's algorithm to find a minimal spanning tree for the graph.

For each of above show your working by giving how the array D and set Rem are modified in each round/loop of the algorithm.

2. Does Dijkstra's algorithm work if the weights can be negative?
Either give an argument that it works, or give a counterexample that it does not work.
3. Consider the following divide and conquer algorithm for finding a minimal spanning tree.
 - (a) Divide the set of vertices into two halves.
Note: It is assumed that the division into two halves might be arbitrary.
 - (b) Find the minimal spanning tree for each half.
 - (c) Find the minimal weight edge which has two endpoints in two different halves above.
 - (d) Use the edge found in (c) above to connect the two spanning trees found in (b) above.

Is the above algorithm correct? If so, give an argument for it. If not, give a counterexample.

4. Prove or disprove:
 - (a) Suppose the graph contains only one edge of minimal weight. Then show that every minimal spanning tree must contain that edge.
 - (b) Suppose a graph may contain several edges of minimal weight. Then does the minimal spanning tree contain all the edges of minimal weight?

5. Suppose we are given n sorted lists.

Suppose the only further operations allowed to us is to merge two lists (which may be among the above lists or obtained in turn by merging some of the lists).

Suppose further that merging two lists of size k and ℓ requires time $k + \ell$.

Give an algorithm to determine the order in which the n lists (having m_1, m_2, \dots, m_n numbers respectively), should be merged so that the merging operations take the least amount of time.

Note that the aim above is to minimize the merging time of lists (and not the time taken by your algorithm).

6. Suppose we modify the continuous knapsack problem done in class to the discrete version as follows:

Either take all of item i or none of item i (that is, we cannot take only a part of item i as done for the continuous knapsack problem done in class).

Appropriately modify the greedy algorithm for continuous knapsack problem to the discrete knapsack problem.

Is the modified greedy algorithm still optimal? If so, give an argument. If not, give a counterexample.