

Illuminant and Gamma Comprehensive Normalisation in log RGB Space

Pattern Recognition Letter, Volume 24, Issue 11, July 2003
Graham Finlayson and Ruixia Xu

School of Electrical Engineering and Computer
Science Kyungpook National University



Abstract

- ◆ A non-iterative comprehensive normalization
 - Using logarithms of RGB images
 - Considering lighting geometry and illuminant color
 - Leading to invariance with two simple projection operators in log color space
 - The efficacy of new normalization procedures



Introduction

- ◆ Approaching methods to deal with illumination dependencies
 - Color constancy algorithms
 - approximating surface reflectance
 - Finding some correlate of surface reflectance that we know
 - Being insufficient to render color a stable enough cue for object recognition

– Color invariant approach

- Finding functions of proximate image pixels which cancel out lighting dependencies
- Removing the intensity from an RGB response vector
- Removing lighting geometry
 - Chromaticity function and the grey-world normalization
 - Insufficient

◆ Comprehensive normalization




Fig.1. Flowchart of CN

◆ Non-iterative comprehensive normalization




Fig. 2. Flowchart of NCN



Background

- ◆ Assumption that imaging device is linear
 - With respect to the incident light

$$\begin{pmatrix} R_i \\ G_i \\ B_i \end{pmatrix} \rightarrow \begin{pmatrix} \rho_i R_i \\ \rho_i G_i \\ \rho_i B_i \end{pmatrix} \quad (1)$$

where ρ_i : A simple scalar
i: Indication of each pixel

– Lambert law

- The power of the light striking a surface is proportional to the scalar $\underline{n} \cdot \underline{e}$

where \underline{n} : Surface normal
 \underline{e} : Lighting direction

- ◆ The mathematical model of the RGB value
 - A change in illumination

$$\begin{pmatrix} R_i \\ G_i \\ B_i \end{pmatrix} \rightarrow \begin{pmatrix} a & 0 & 0 \\ 0 & b & 0 \\ 0 & 0 & c \end{pmatrix} \begin{pmatrix} R_i \\ G_i \\ B_i \end{pmatrix} \quad (2)$$

- Non-linearity (Power function transformation)

$$\begin{pmatrix} R_i \\ G_i \\ B_i \end{pmatrix} \rightarrow \begin{pmatrix} R_i^\gamma \\ G_i^\gamma \\ B_i^\gamma \end{pmatrix} \quad (3)$$

- Combining Eqs. (1)-(3)

$$\begin{pmatrix} R_i \\ G_i \\ B_i \end{pmatrix} \rightarrow \begin{pmatrix} [a \rho_i R_i]^\gamma \\ [b \rho_i G_i]^\gamma \\ [c \rho_i B_i]^\gamma \end{pmatrix} \quad (4)$$

- Simplifying Eq. (4)

$$\begin{pmatrix} R_i \\ G_i \\ B_i \end{pmatrix} \rightarrow \begin{pmatrix} a' \rho_i' R_i^\gamma \\ b' \rho_i' G_i^\gamma \\ c' \rho_i' B_i^\gamma \end{pmatrix} \quad (5)$$

◆ Chromaticity normalization

$$\begin{aligned}r_i &= \frac{\rho_i R_i}{\rho_i R_i + \rho_i G_i + \rho_i B_i}, \\g_i &= \frac{\rho_i G_i}{\rho_i R_i + \rho_i G_i + \rho_i B_i}, \\b_i &= \frac{\rho_i B_i}{\rho_i R_i + \rho_i G_i + \rho_i B_i}\end{aligned}\tag{6}$$

where r , g and b : The new co-ordinates
and independent of ρ_i

– Denoted this procedure $C()$

◆ Grey-world normalization

$$\mu(R) = \frac{\sum_{i=1}^N R_i}{N} \quad (7)$$

$$\mu(R)' = \frac{\sum_{i=1}^N aR_i}{N} = a\mu(R) \quad (8)$$

$$R'_i = \frac{aR_i}{a\mu(R)}, \quad G'_i = \frac{bG_i}{b\mu(G)}, \quad B'_i = \frac{cB_i}{c\mu(B)} \quad (9)$$

where N : The number of pixels in the image

– Denoted this procedure G()

◆ Comprehensive normalization

- Applying successively and repeatedly until the resulting image converges to a fixed point

- Initialization

$$I_0 = I$$

- Iteration step

$$I_{i+1} = G(C (I_i)) \quad (10)$$

- Termination condition

$$I_{i+1} = I_i$$

- Denoted this procedure $CN()$



Non-iterative comprehensive normalization in log-space

◆ Taking logarithms from Eq. (5)

$$\begin{bmatrix} \log(R_i) \\ \log(G_i) \\ \log(B_i) \end{bmatrix} \rightarrow \begin{bmatrix} a'' + \rho_i'' + \gamma \log(R_i) \\ b'' + \rho_i'' + \gamma \log(G_i) \\ c'' + \rho_i'' + \gamma \log(B_i) \end{bmatrix} \quad (11)$$

$$\begin{pmatrix} R_i' \\ G_i' \\ B_i' \end{pmatrix} \rightarrow \begin{pmatrix} a'' \\ b'' \\ c'' \end{pmatrix} + \rho_i'' \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix} + \begin{pmatrix} \gamma R_i' \\ \gamma G_i' \\ \gamma B_i' \end{pmatrix} \quad (12)$$

where $a'' = \log a'$, $b'' = \log b'$, $c'' = \log c'$, $\rho_i'' = \log \rho_i'$

◆ Projection matrix Pr

$$Pr = U^t (U U^t)^{-1} U = \begin{pmatrix} \frac{1}{3} & \frac{1}{3} & \frac{1}{3} \\ \frac{1}{3} & \frac{1}{3} & \frac{1}{3} \\ \frac{1}{3} & \frac{1}{3} & \frac{1}{3} \end{pmatrix} \quad (13)$$

$$Pr^\perp = I - Pr = \begin{pmatrix} \frac{2}{3} & -\frac{1}{3} & -\frac{1}{3} \\ -\frac{1}{3} & \frac{2}{3} & -\frac{1}{3} \\ -\frac{1}{3} & -\frac{1}{3} & \frac{2}{3} \end{pmatrix} \quad (14)$$

where $U = (1, 1, 1)^t$

- ◆ Projection of a log RGB onto the orthogonal space
 - Multiplying by Pr^\perp

$$\begin{pmatrix} \frac{2}{3} & -\frac{1}{3} & -\frac{1}{3} \\ -\frac{1}{3} & \frac{2}{3} & -\frac{1}{3} \\ -\frac{1}{3} & -\frac{1}{3} & \frac{2}{3} \end{pmatrix} \begin{pmatrix} R'_i \\ G'_i \\ B'_i \end{pmatrix} = \begin{pmatrix} \frac{2R'_i}{3} - \frac{G'_i}{3} - \frac{B'_i}{3} \\ \frac{2G'_i}{3} - \frac{R'_i}{3} - \frac{B'_i}{3} \\ \frac{2B'_i}{3} - \frac{R'_i}{3} - \frac{G'_i}{3} \end{pmatrix} = \begin{pmatrix} R'_i - \frac{R'_i + G'_i + B'_i}{3} \\ G'_i - \frac{R'_i + G'_i + B'_i}{3} \\ B'_i - \frac{R'_i + G'_i + B'_i}{3} \end{pmatrix} \quad (15)$$

- Removing dependency on lighting geometry by subtracting the mean log response at a pixel (a “brightness” correlate) from each pixel

– Multiplying by Pc^\perp

$$\begin{pmatrix} a'' + \gamma R_1' \\ a'' + \gamma R_2' \\ \vdots \\ a'' + \gamma R_N' \end{pmatrix} \rightarrow \begin{pmatrix} \gamma R_1' \\ \gamma R_2' \\ \vdots \\ \gamma R_N' \end{pmatrix} + a'' \begin{pmatrix} 1 \\ 1 \\ \vdots \\ 1 \end{pmatrix} \quad (16)$$

$$Pc = \begin{pmatrix} \frac{1}{N} & \frac{1}{N} & \dots & \frac{1}{N} \\ \frac{1}{N} & \frac{1}{N} & \dots & \frac{1}{N} \\ \vdots & \vdots & \ddots & \vdots \\ \frac{1}{N} & \frac{1}{N} & \dots & \frac{1}{N} \end{pmatrix} \quad (17)$$

$$P_c^\perp = I - P_c$$

$$= \begin{pmatrix} \frac{N-1}{N} & -\frac{1}{N} & \dots & -\frac{1}{N} \\ -\frac{1}{N} & \frac{N-1}{N} & \dots & -\frac{1}{N} \\ \vdots & \vdots & \ddots & \vdots \\ -\frac{1}{N} & -\frac{1}{N} & \dots & \frac{N-1}{N} \end{pmatrix} \quad (18)$$

- Operating on the vector of all log red (or green, or blue) responses
- Removing the effect of illuminant color

◆ Explicit equation for the application

- The lighting geometry and light color normalization

$$\gamma Y = (I - P_c)Y\gamma(I - P_r) \quad (19)$$

- Projection theory

$$(I - P_c)(I - P_c) = (I - P_c)$$

$$(I - P_r)(I - P_r) = (I - P_r) : \text{Idempotent}$$

$$\begin{aligned} \gamma Y &= (I - P_c)(I - P_c)Y\gamma(I - P_r)(I - P_r) \\ &= (I - P_c)Y\gamma(I - P_r) \end{aligned} \quad (20)$$

- Removing shading or light color completely
- $Y\gamma$: N pixel image as an N x 3 matrix of log RGBs

◆ Gamma normalization

- Second order statistic

$$\sigma^2(\gamma Y) = \frac{\text{trace}((\gamma Y)^t (\gamma Y))}{3N} \quad (21)$$

where $\text{trace}()$: The sum of the diagonal elements of a matrix

- Dividing by the standard deviation

$$\frac{\gamma Y}{\sigma(\gamma Y)} = \frac{\gamma Y}{\gamma \sigma(Y)} = \frac{Y}{\sigma(Y)} \quad (22)$$



Object recognition experiments

- ◆ Image database under one illuminant
 - Each image represents an object
 - The choice reference dataset had little effect on the indexing results
 - We try to match the query to the database images with color histogram
 - If the closest database histogram to the query is the correct answer

- **Table 1.** Indexing performance of Lee and Berwick dataset
(rank are % of the dataset)

Methods	Average percentile	Rank 1	Rank 2	Rank > 2	Worst rank
Nothing	69.84	33.33	33.33	33.33	8 out of 8
Grey-world	98.41	88.89	11.11	0	2 out of 8

- **Table 2.** Indexing performance of Swain's dataset
(rank are % of the dataset)

Methods	Average percentile	Rank 1	Rank 2	Rank > 2	Worst rank
Nothing	98.54	93.33	3.33	3.33	9 out of 66
Grey-world	98.77	83.33	13.33	3.34	21 out of 66
Comprehensive	98.46	86.67	3.33	10	9 out of 66
Log gamma	98.05	56.67	26.67	16.66	17 out of 66

- **Table 3.** Indexing performance of Simon Fraser dataset
(rank are % of the dataset)

Methods	Average percentile	Rank 1	Rank 2	Rank > 2	Worst rank
Nothing	73.08	30.77	15.38	53.85	13 out of 13
Grey-world	98.08	84.62	11.54	3.84	4 out of 13
Comprehensive	98.08	84.62	11.54	3.84	4 out of 13
Log gamma	97.76	84.62	7.69	7.69	4 out of 13

- **Table 4.** Indexing performance of composite dataset
(rank are % of the dataset)

Methods	Average percentile	Rank 1	Rank 2	Rank > 2	Worst rank
Nothing	93.92	58.46	6.15	35.38	65 out of 87
Grey-world	92.11	56.92	9.23	33.85	72 out of 87
Comprehensive	99.71				
Log gamma	98.60	84.62	4.62	10.76	19 out of 87

- **Table 5.** Indexing performance of Large Simon Fraser dataset
(rank are % of the dataset)

Methods	Average percentile	Rank 1	Rank 2	Rank > 2	Worst rank
Nothing	73.50	28	12	60	20 out of 20
Grey-world	94.21	72.50	10.5	17	20 out of 20
Comprehensive	98.84	91.00	3.5	5.5	16 out of 20
Log gamma	97.61	84.50	6	9.5	10 out of 20

– Performance of each of the three normalization methods




Fig. 3. This figure shows performance of log gamma, non-iterative and comprehensive normalization on the design dataset. The x-axis corresponds to the proportion of query images for which average match percentile (y-axis) is investigated. The query set is sorted according to how well the images conform to a diagonal-gamma model.



Discussion

- ◆ Non-iterative comprehensive normalization
 - Removing image dependence on lighting geometry and illumination at the same time
 - ◆ Gamma normalization
 - Extending the first to additionally cancel the effect of power functions which are typically applied to captured images
 - Obtaining with non-linearity
- **Being valid in most practical situations**