

QUIC
Internet-Draft
Intended status: Standards Track
Expires: April 6, 2019

C. Krasic
Netflix
M. Bishop
Akamai Technologies
A. Frindell, Ed.
Facebook
October 03, 2018

QPACK: Header Compression for HTTP over QUIC
draft-ietf-quic-qpack-03

Abstract

This specification defines QPACK, a compression format for efficiently representing HTTP header fields, to be used in HTTP/QUIC. This is a variation of HPACK header compression that seeks to reduce head-of-line blocking.

Note to Readers

Discussion of this draft takes place on the QUIC working group mailing list (quic@ietf.org), which is archived at https://mailarchive.ietf.org/arch/search/?email_list=quic [1].

Working Group information can be found at <https://github.com/quicwg> [2]; source code and issues list for this draft can be found at <https://github.com/quicwg/base-drafts/labels/-qpack> [3].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 6, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
2. Header Tables	4
2.1. Static Table	4
2.2. Dynamic Table	4
2.2.1. Maximum Table Size	5
2.2.2. Calculating Table Size	6
2.2.3. Absolute Indexing	6
2.2.4. Relative Indexing	6
2.2.5. Post-Base Indexing	7
2.3. Avoiding Head-of-Line Blocking in HTTP/QUIC	8
2.3.1. State Synchronization	9
3. Conventions and Definitions	10
3.1. Notational Conventions	10
4. Configuration	10
5. Wire Format	11
5.1. Primitives	11
5.1.1. Prefixed Integers	11
5.1.2. String Literals	11
5.2. QPACK Encoder Stream	12
5.2.1. Insert With Name Reference	12
5.2.2. Insert Without Name Reference	13
5.2.3. Duplicate	13
5.2.4. Dynamic Table Size Update	14
5.3. QPACK Decoder Stream	14
5.3.1. Table State Synchronize	14
5.3.2. Header Acknowledgement	15
5.3.3. Stream Cancellation	16
5.4. Request and Push Streams	17
5.4.1. Header Data Prefix	17
5.4.2. Instructions	18
6. Error Handling	21

7.	Encoding Strategies	22
7.1.	Single Pass Encoding	22
7.2.	Preventing Eviction Races	22
7.3.	Reference Tracking	22
7.3.1.	Blocked Dynamic Table Insertions	22
7.3.2.	Blocked Decoding	23
7.4.	Speculative table updates	23
7.5.	Sample One Pass Encoding Algorithm	24
8.	Security Considerations	26
9.	IANA Considerations	26
9.1.	Settings Registration	26
9.2.	Stream Type Registration	26
9.3.	Error Code Registration	26
10.	References	27
10.1.	Normative References	27
10.2.	Informative References	28
10.3.	URIs	28
Appendix A.	Static Table	28
Appendix B.	Change Log	33
B.1.	Since draft-ietf-quic-qpack-02	33
B.2.	Since draft-ietf-quic-qpack-01	33
B.3.	Since draft-ietf-quic-qpack-00	33
B.4.	Since draft-ietf-quic-qcram-00	34
	Acknowledgments	34
	Authors' Addresses	34

1. Introduction

The QUIC transport protocol was designed from the outset to support HTTP semantics, and its design subsumes many of the features of HTTP/2. HTTP/2 uses HPACK ([RFC7541]) for header compression, but QUIC's stream multiplexing comes into some conflict with HPACK. A key goal of the design of QUIC is to improve stream multiplexing relative to HTTP/2 by reducing head-of-line blocking. If HPACK were used for HTTP/QUIC, it would induce head-of-line blocking due to built-in assumptions of a total ordering across frames on all streams.

QUIC is described in [QUIC-TRANSPORT]. The HTTP/QUIC mapping is described in [QUIC-HTTP]. For a full description of HTTP/2, see [RFC7540]. The description of HPACK is [RFC7541].

QPACK reuses core concepts from HPACK, but is redesigned to allow correctness in the presence of out-of-order delivery, with flexibility for implementations to balance between resilience against head-of-line blocking and optimal compression ratio. The design goals are to closely approach the compression ratio of HPACK with

substantially less head-of-line blocking under the same loss conditions.

QPACK preserves the ordering of header fields within each header list. An encoder **MUST** emit header field representations in the order they appear in the input header list. A decoder **MUST** emit header fields in the order their representations appear in the input header block.

2. Header Tables

Like HPACK, QPACK uses two tables for associating header fields to indices. The static table (see [Section 2.1](#)) is predefined and contains common header fields (some of them with an empty value). The dynamic table (see [Section 2.2](#)) is built up over the course of the connection and can be used by the encoder to index header fields repeated in the encoded header lists.

Unlike in HPACK, entries in the QPACK static and dynamic tables are addressed separately. The following sections describe how entries in each table are addressed.

2.1. Static Table

The static table consists of a predefined static list of header fields, each of which has a fixed index over time. Its entries are defined in [Appendix A](#).

A decoder that encounters an invalid static table index on a request stream or push stream **MUST** treat this as a stream error of type "HTTP_QPACK_DECOMPRESSION_FAILED". If this index is received on the encoder stream, this **MUST** be treated as a connection error of type "HTTP_QPACK_ENCODER_STREAM_ERROR".

2.2. Dynamic Table

The dynamic table consists of a list of header fields maintained in first-in, first-out order. The dynamic table is initially empty. Entries are added by instructions on the encoder stream (see [Section 5.2](#)).

The maximum size of the dynamic table can be modified by the encoder, subject to a decoder-controlled limit (see [Section 4](#) and [Section 5.2.4](#)). The initial maximum size is determined by the corresponding setting when HTTP requests or responses are first permitted to be sent. For clients using 0-RTT data in HTTP/QUIC, the table size is the remembered value of the setting, even if the server later specifies a larger maximum in its SETTINGS frame. For HTTP/

QUIC servers and HTTP/QUIC clients when 0-RTT is not attempted or is rejected, the initial maximum table size is the value of the setting in the peer's SETTINGS frame.

Before a new entry is added to the dynamic table, entries are evicted from the end of the dynamic table until the size of the dynamic table is less than or equal to (maximum size - new entry size) or until the table is empty. The encoder **MUST NOT** evict a dynamic table entry unless it has first been acknowledged by the decoder.

If the size of the new entry is less than or equal to the maximum size, that entry is added to the table. It is an error to attempt to add an entry that is larger than the maximum size; this **MUST** be treated as a connection error of type "HTTP_QPACK_ENCODER_STREAM_ERROR".

A new entry can reference an entry in the dynamic table that will be evicted when adding this new entry into the dynamic table. Implementations are cautioned to avoid deleting the referenced name if the referenced entry is evicted from the dynamic table prior to inserting the new entry.

The dynamic table can contain duplicate entries (i.e., entries with the same name and same value). Therefore, duplicate entries **MUST NOT** be treated as an error by a decoder.

2.2.1. Maximum Table Size

The encoder decides how to update the dynamic table and as such can control how much memory is used by the dynamic table. To limit the memory requirements of the decoder, the dynamic table size is strictly bounded.

The decoder determines the maximum size that the encoder is permitted to use for the dynamic table. In HTTP/QUIC, this value is determined by the SETTINGS_HEADER_TABLE_SIZE setting (see [Section 4](#)).

An encoder can choose to use less capacity than this maximum size (see [Section 5.2.4](#)), but the chosen size **MUST** stay lower than or equal to the maximum set by the decoder. Whenever the maximum size for the dynamic table is reduced, entries are evicted from the end of the dynamic table until the size of the dynamic table is less than or equal to the maximum size.

This mechanism can be used to completely clear entries from the dynamic table by setting a maximum size of 0, which can subsequently be restored.

2.2.2. Calculating Table Size

The size of the dynamic table is the sum of the size of its entries.

The size of an entry is the sum of its name's length in octets (as defined in [Section 5.1.2](#)), its value's length in octets, and 32.

The size of an entry is calculated using the length of its name and value without any Huffman encoding applied.

"MaxEntries" is the maximum number of entries that the dynamic table can have. The smallest entry has empty name and value strings and has the size of 32. The MaxEntries is calculated as

$$\text{MaxEntries} = \text{floor}(\text{MaxTableSize} / 32)$$

MaxTableSize is the maximum size of the dynamic table as specified by the decoder (see [Section 2.2.1](#)).


2.2.3. Absolute Indexing

Each entry possesses both an absolute index which is fixed for the lifetime of that entry and a relative index which changes over time based on the context of the reference. The first entry inserted has an absolute index of "1"; indices increase sequentially with each insertion.

2.2.4. Relative Indexing

The relative index begins at zero and increases in the opposite direction from the absolute index. Determining which entry has a relative index of "0" depends on the context of the reference.

On the encoder stream, a relative index of "0" always refers to the most recently inserted value in the dynamic table. Note that this means the entry referenced by a given relative index will change while interpreting instructions on the encoder stream.




n = count of entries inserted

d = count of entries dropped

Example Dynamic Table Indexing - Control Stream

Because frames from request streams can be delivered out of order with instructions on the encoder stream, relative indices are relative to the Base Index at the beginning of the header block (see [Section 5.4.1](#)). The Base Index is an absolute index. When interpreting the rest of the frame, the entry identified by Base Index has a relative index of zero. The relative indices of entries do not change while interpreting headers on a request or push stream.




n = count of entries inserted

d = count of entries dropped

Example Dynamic Table Indexing - Relative Index on Request Stream

2.2.5. Post-Base Indexing

A header block on the request stream can reference entries added after the entry identified by the Base Index. This allows an encoder to process a header block in a single pass and include references to entries added while processing this (or other) header blocks. Newly added entries are referenced using Post-Base instructions. Indices for Post-Base instructions increase in the same direction as absolute indices, but the zero value is one higher than the Base Index.



n = count of entries inserted

d = count of entries dropped

Example Dynamic Table Indexing - Post-Base Index on Request Stream

If the decoder encounters a reference on a request or push stream to a dynamic table entry which has already been dropped or which has an absolute index greater than the declared Largest Reference (see [Section 5.4.1](#)), it MUST treat this as a stream error of type "HTTP_QPACK_DECOMPRESSION_FAILED".

If the decoder encounters a reference on the encoder stream to a dynamic table entry which has already been dropped, it MUST treat this as a connection error of type "HTTP_QPACK_ENCODER_STREAM_ERROR".

2.3. Avoiding Head-of-Line Blocking in HTTP/QUIC

Because QUIC does not guarantee order between data on different streams, a header block might reference an entry in the dynamic table that has not yet been received.

Each header block contains a Largest Reference which identifies the table state necessary for decoding. If the greatest absolute index in the dynamic table is less than the value of the Largest Reference, the stream is considered "blocked." While blocked, header field data should remain in the blocked stream's flow control window. When the Largest Reference is zero, the frame contains no references to the dynamic table and can always be processed immediately. A stream becomes unblocked when the greatest absolute index in the dynamic table becomes greater than or equal to the Largest Reference for all header blocks the decoder has started reading from the stream. If a decoder encounters a header block where the actual largest reference is not equal to the Largest Reference declared in the prefix, it MAY treat this as a stream error of type HTTP_QPACK_DECOMPRESSION_FAILED.

A decoder can permit the possibility of blocked streams by setting SETTINGS_QPACK_BLOCKED_STREAMS to a non-zero value (see [Section 4](#)). This setting specifies an upper bound on the number of streams which can be blocked.

An encoder can decide whether to risk having a stream become blocked. If permitted by the value of `SETTINGS_QPACK_BLOCKED_STREAMS`, compression efficiency can be improved by referencing dynamic table entries that are still in transit, but if there is loss or reordering the stream can become blocked at the decoder. An encoder avoids the risk of blocking by only referencing dynamic table entries which have been acknowledged, but this means using literals. Since literals make the header block larger, this can result in the encoder becoming blocked on congestion or flow control limits.

An encoder **MUST** limit the number of streams which could become blocked to the value of `SETTINGS_QPACK_BLOCKED_STREAMS` at all times. Note that the decoder might not actually become blocked on every stream which risks becoming blocked. If the decoder encounters more blocked streams than it promised to support, it **MUST** treat this as a stream error of type `HTTP_QPACK_DECOMPRESSION_FAILED`.

2.3.1. State Synchronization

The decoder stream ([Section 5.3](#)) signals key events at the decoder that permit the encoder to track the decoder's state. These events are:

- o Complete processing of a header block
- o Abandonment of a stream which might have remaining header blocks
- o Receipt of new dynamic table entries

Regardless of whether a header block contained blocking references, the knowledge that it has been processed permits the encoder to evict entries to which no unacknowledged references remain; see [Section 7.3.1](#). When a stream is reset or abandoned, the indication that these header blocks will never be processed serves a similar function; see [Section 5.3.3](#).

For the encoder to identify which dynamic table entries can be safely used without a stream becoming blocked, the encoder tracks the absolute index of the decoder's Largest Known Received entry.

When blocking references are permitted, the encoder uses acknowledgement of header blocks to identify the Largest Known Received index, as described in [Section 5.3.2](#).

To acknowledge dynamic table entries which are not referenced by header blocks, for example because the encoder or the decoder have chosen not to risk blocked streams, the decoder sends a Table State Synchronize instruction (see [Section 5.3.1](#)).

3. Conventions and Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14 \[RFC2119\] \[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

Definitions of terms that are used in this document:

Header field: A name-value pair sent as part of an HTTP message.

Header list: The ordered collection of header fields associated with an HTTP message. A header list can contain multiple header fields with the same name. It can also contain duplicate header fields.

Header block: The compressed representation of a header list.

Encoder: An implementation which transforms a header list into a header block.

Decoder: An implementation which transforms a header block into a header list.

QPACK is a name, not an acronym.

3.1. Notational Conventions

Diagrams use the format described in [Section 3.1 of \[RFC2360\]](#), with the following additional conventions:

x (A) Indicates that x is A bits long

x (A+) Indicates that x uses the prefixed integer encoding defined in [Section 5.1 of \[RFC7541\]](#), beginning with an A-bit prefix.

x ... Indicates that x is variable-length and extends to the end of the region.

4. Configuration

QPACK defines two settings which are included in the HTTP/QUIC SETTINGS frame.

SETTINGS_HEADER_TABLE_SIZE (0x1): An integer with a maximum value of $2^{30} - 1$. The default value is 4,096 bytes. See [Section 2.2](#) for usage.

SETTINGS_QPACK_BLOCKED_STREAMS (0x7): An integer with a maximum value of $2^{16} - 1$. The default value is 100. See [Section 2.3](#).

5. Wire Format

QPACK instructions occur in three locations, each of which uses a separate instruction space:

- o The encoder stream is a unidirectional stream of type "0x48" (ASCII 'H') which carries table updates from encoder to decoder. Instructions on this stream modify the dynamic table state without generating output to any particular request.
- o The decoder stream is a unidirectional stream of type "0x68" (ASCII 'h') which carries acknowledgements of table modifications and header processing from decoder to encoder.
- o Finally, the contents of HEADERS and PUSH_PROMISE frames on request streams and push streams reference the QPACK table state.

There MUST be exactly one of each unidirectional stream type in each direction. Receipt of a second instance of either stream type MUST be treated as a connection error of HTTP_WRONG_STREAM_COUNT. Closure of either unidirectional stream MUST be treated as a connection error of type HTTP_CLOSED_CRITICAL_STREAM.

This section describes the instructions which are possible on each stream type.

All table updates occur on the encoder stream. Request streams and push streams only carry header blocks that do not modify the state of the table.

5.1. Primitives

5.1.1. Prefixed Integers

The prefixed integer from [Section 5.1 of \[RFC7541\]](#) is used heavily throughout this document. The format from [\[RFC7541\]](#) is used unmodified. QPACK implementations MUST be able to decode integers up to 62 bits long.

5.1.2. String Literals

The string literal defined by [Section 5.2 of \[RFC7541\]](#) is also used throughout. This string format includes optional Huffman encoding.

HPACK defines string literals to begin on a byte boundary. They begin with a single flag (indicating whether the string is Huffman-coded), followed by the Length encoded as a 7-bit prefix integer, and finally Length octets of data. When Huffman encoding is enabled, the Huffman table from [Appendix B of \[RFC7541\]](#) is used without modification.

This document expands the definition of string literals and permits them to begin other than on a byte boundary. An "N-bit prefix string literal" begins with the same Huffman flag, followed by the length encoded as an (N-1)-bit prefix integer. The remainder of the string literal is unmodified.

A string literal without a prefix length noted is an 8-bit prefix string literal and follows the definitions in [\[RFC7541\]](#) without modification.

5.2. QPACK Encoder Stream

Table updates can add a table entry, possibly using existing entries to avoid transmitting redundant information. The name can be transmitted as a reference to an existing entry in the static or the dynamic table or as a string literal. For entries which already exist in the dynamic table, the full entry can also be used by reference, creating a duplicate entry.

The contents of the encoder stream are an unframed sequence of the following instructions.

5.2.1. Insert With Name Reference

An addition to the header table where the header field name matches the header field name of an entry stored in the static table or the dynamic table starts with the '1' one-bit pattern. The "S" bit indicates whether the reference is to the static (S=1) or dynamic (S=0) table. The 6-bit prefix integer (see [Section 5.1 of \[RFC7541\]](#)) that follows is used to locate the table entry for the header name. When S=1, the number represents the static table index; when S=0, the number is the relative index of the entry in the dynamic table.

The header name reference is followed by the header field value represented as a string literal (see [Section 5.2 of \[RFC7541\]](#)).

0	1	2	3	4	5	6	7
1	S	Name Index (6+)					
H	Value Length (7+)						
Value String (Length octets)							

Insert Header Field -- Indexed Name

5.2.2. Insert Without Name Reference

An addition to the header table where both the header field name and the header field value are represented as string literals (see [Section 5.1](#)) starts with the '01' two-bit pattern.

The name is represented as a 6-bit prefix string literal, while the value is represented as an 8-bit prefix string literal.

0	1	2	3	4	5	6	7
0	1	H	Name Length (5+)				
Name String (Length octets)							
H	Value Length (7+)						
Value String (Length octets)							

Insert Header Field -- New Name

5.2.3. Duplicate

Duplication of an existing entry in the dynamic table starts with the '000' three-bit pattern. The relative index of the existing entry is represented as an integer with a 5-bit prefix.

0	1	2	3	4	5	6	7
0	0	0	Index (5+)				

Figure 1: Duplicate

The existing entry is re-inserted into the dynamic table without resending either the name or the value. This is useful to mitigate

the eviction of older entries which are frequently referenced, both to avoid the need to resend the header and to avoid the entry in the table blocking the ability to insert new headers.

5.2.4. Dynamic Table Size Update

An encoder informs the decoder of a change to the size of the dynamic table using an instruction which begins with the '001' three-bit pattern. The new maximum table size is represented as an integer with a 5-bit prefix (see [Section 5.1 of \[RFC7541\]](#)).




Figure 2: Maximum Dynamic Table Size Change

The new maximum size MUST be lower than or equal to the limit determined by the protocol using QPACK. A value that exceeds this limit MUST be treated as a connection error of type "HTTP_QPACK_ENCODER_STREAM_ERROR". In HTTP/QUIC, this limit is the value of the `SETTINGS_HEADER_TABLE_SIZE` parameter (see [Section 4](#)) received from the decoder.

Reducing the maximum size of the dynamic table can cause entries to be evicted (see [Section 4.3 of \[RFC7541\]](#)). This MUST NOT cause the eviction of entries with outstanding references (see [Section 7.3](#)). Changing the size of the dynamic table is not acknowledged as this instruction does not insert an entry.

5.3. QPACK Decoder Stream

The decoder stream carries information used to ensure consistency of the dynamic table. Information is sent from the QPACK decoder to the QPACK encoder; that is, the server informs the client about the processing of the client's header blocks and table updates, and the client informs the server about the processing of the server's header blocks and table updates.

The contents of the decoder stream are an unframed sequence of the following instructions.

5.3.1. Table State Synchronize

The Table State Synchronize instruction begins with the '00' two-bit pattern. The instruction specifies the total number of dynamic table inserts and duplications since the last Table State Synchronize or

Header Acknowledgement that increased the Largest Known Received dynamic table entry. This is encoded as a 6-bit prefix integer. The encoder uses this value to determine which table entries might cause a stream to become blocked, as described in [Section 2.3.1](#).




Figure 3: Table State Synchronize

An encoder that receives an Insert Count equal to zero or one that increases Largest Known Received beyond what the encoder has sent MUST treat this as a connection error of type "HTTP_QPACK_DECODER_STREAM_ERROR".

A decoder chooses when to emit Table State Synchronize instructions. Emitting a Table State Synchronize after adding each new dynamic table entry will provide the most timely feedback to the encoder, but could be redundant with other decoder feedback. By delaying a Table State Synchronize, a decoder might be able to coalesce multiple Table State Synchronize instructions, or replace them entirely with Header Acknowledgements. However, delaying too long may lead to compression inefficiencies if the encoder waits for an entry to be acknowledged before using it.

5.3.2. Header Acknowledgement

After processing a header block whose declared Largest Reference is not zero, the decoder emits a Header Acknowledgement instruction on the decoder stream. The instruction begins with the '1' one-bit pattern and includes the request stream's stream ID, encoded as a 7-bit prefix integer. It is used by the peer's QPACK encoder to know when it is safe to evict an entry.




Figure 4: Header Acknowledgement

The same Stream ID can be identified multiple times, as multiple header blocks can be sent on a single stream in the case of intermediate responses, trailers, and pushed requests. Since header frames on each stream are received and processed in order, this gives

the encoder precise feedback on which header blocks within a stream have been fully processed.

If an encoder receives a Header Acknowledgement instruction referring to a stream on which every header block with a non-zero Largest Reference has already been acknowledged, that **MUST** be treated as a connection error of type "HTTP_QPACK_DECODER_STREAM_ERROR".

When blocking references are permitted, the encoder uses acknowledgement of header blocks to update the Largest Known Received index. If a header block was potentially blocking, the acknowledgement implies that the decoder has received all dynamic table state necessary to process the header block. If the Largest Reference of an acknowledged header block was greater than the encoder's current Largest Known Received index, the block's Largest Reference becomes the new Largest Known Received.

5.3.3. Stream Cancellation

A stream that is reset might have multiple outstanding header blocks with dynamic table references. A decoder that receives a stream reset before the end of a stream generates a Stream Cancellation instruction on the decoder stream. Similarly, a decoder that abandons reading of a stream needs to signal this using the Stream Cancellation instruction. This signals to the encoder that all references to the dynamic table on that stream are no longer outstanding. A decoder with a maximum dynamic table size equal to zero **MAY** omit sending Stream Cancellations, because the encoder cannot have any dynamic table references.

An encoder cannot infer from this instruction that any updates to the dynamic table have been received.

The instruction begins with the '01' two-bit pattern. The instruction includes the stream ID of the affected stream - a request or push stream - encoded as a 6-bit prefix integer.




Figure 5: Stream Cancellation

5.4. Request and Push Streams

HEADERS and PUSH_PROMISE frames on request and push streams reference the dynamic table in a particular state without modifying it. Frames on these streams emit the headers for an HTTP request or response.

5.4.1. Header Data Prefix

Header data is prefixed with two integers, "Largest Reference" and "Base Index".




Figure 6: Frame Payload

"Largest Reference" identifies the largest absolute dynamic index referenced in the block. Blocking decoders use the Largest Reference to determine when it is safe to process the rest of the block. If Largest Reference is greater than zero, the encoder transforms it as follows before encoding:

$$\text{LargestReference} = \text{LargestReference} \bmod 2 * \text{MaxEntries} + 1$$

The decoder reconstructs the Largest Reference using the following algorithm:

```

if LargestReference > 0:
    LargestReference -= 1
    CurrentWrapped = TableLargestAbsoluteIndex mod 2*MaxEntries

    if CurrentWrapped >= LargestReference + MaxEntries:
        # Largest Reference wrapped around 1 extra time
        LargestReference += 2*MaxEntries
    else if CurrentWrapped + MaxEntries < LargestReference:
        # Decoder wrapped around 1 extra time
        CurrentWrapped += 2*MaxEntries

    LargestReference +=
        (TableLargestAbsoluteIndex - CurrentWrapped)

```

TableLargestAbsoluteIndex is the Absolute Index of the most recently inserted item in the decoder's dynamic table. This encoding limits the length of the prefix on long-lived connections.

"Base Index" is used to resolve references in the dynamic table as described in [Section 2.2.4](#).

To save space, Base Index is encoded relative to Largest Reference using a one-bit sign and the "Delta Base Index" value. A sign bit of 0 indicates that the Base Index has an absolute index that is greater than or equal to the Largest Reference; the value of Delta Base Index is added to the Largest Reference to determine the absolute value of the Base Index. A sign bit of 1 indicates that the Base Index is less than the Largest Reference. That is:

```
if sign == 0:
    baseIndex = largestReference + deltaBaseIndex
else:
    baseIndex = largestReference - deltaBaseIndex
```

A single-pass encoder is expected to determine the absolute value of Base Index before encoding a header block. If the encoder inserted entries in the dynamic table while encoding the header block, Largest Reference will be greater than Base Index, so the encoded difference is negative and the sign bit is set to 1. If the header block did not reference the most recent entry in the table and did not insert any new entries, Base Index will be greater than the Largest Reference, so the delta will be positive and the sign bit is set to 0.

An encoder that produces table updates before encoding a header block might set Largest Reference and Base Index to the same value. When Largest Reference and Base Index are equal, the Delta Base Index is encoded with a zero sign bit. A sign bit set to 1 when the Delta Base Index is 0 MUST be treated as a decoder error.

A header block that does not reference the dynamic table can use any value for Base Index; setting both Largest Reference and Base Index to zero is the most efficient encoding.

[5.4.2. Instructions](#)

[5.4.2.1. Indexed Header Field](#)

An indexed header field representation identifies an entry in either the static table or the dynamic table and causes that header field to be added to the decoded header list, as described in [Section 3.2 of \[RFC7541\]](#).

0	1	2	3	4	5	6	7
1	S	Index (6+)					

Indexed Header Field

If the entry is in the static table, or in the dynamic table with an absolute index less than or equal to Base Index, this representation starts with the '1' 1-bit pattern, followed by the "S" bit indicating whether the reference is into the static (S=1) or dynamic (S=0) table. Finally, the relative index of the matching header field is represented as an integer with a 6-bit prefix (see [Section 5.1 of \[RFC7541\]](#)).

5.4.2.2. Indexed Header Field With Post-Base Index

If the entry is in the dynamic table with an absolute index greater than Base Index, the representation starts with the '0001' 4-bit pattern, followed by the post-base index (see [Section 2.2.5](#)) of the matching header field, represented as an integer with a 4-bit prefix (see [Section 5.1 of \[RFC7541\]](#)).

0	1	2	3	4	5	6	7
0	0	0	1	Index (4+)			

Indexed Header Field with Post-Base Index

5.4.2.3. Literal Header Field With Name Reference

A literal header field with a name reference represents a header where the header field name matches the header field name of an entry stored in the static table or the dynamic table.

If the entry is in the static table, or in the dynamic table with an absolute index less than or equal to Base Index, this representation starts with the '01' two-bit pattern. If the entry is in the dynamic table with an absolute index greater than Base Index, the representation starts with the '0000' four-bit pattern.

The following bit, 'N', indicates whether an intermediary is permitted to add this header to the dynamic header table on subsequent hops. When the 'N' bit is set, the encoded header **MUST** always be encoded with a literal representation. In particular, when a peer sends a header field that it received represented as a literal header field with the 'N' bit set, it **MUST** use a literal

representation to forward this header field. This bit is intended for protecting header field values that are not to be put at risk by compressing them (see [Section 7.1 of \[RFC7541\]](#) for more details).

0	1	2	3	4	5	6	7
+-----+-----+-----+-----+-----+-----+-----+-----+							
0	1	N	S	Name Index (4+)			
+-----+-----+-----+-----+-----+-----+-----+-----+							
H	Value Length (7+)						
+-----+-----+-----+-----+-----+-----+-----+-----+							
Value String (Length octets)							
+-----+-----+-----+-----+-----+-----+-----+-----+							

Literal Header Field With Name Reference

For entries in the static table or in the dynamic table with an absolute index less than or equal to Base Index, the header field name is represented using the relative index of that entry, which is represented as an integer with a 4-bit prefix (see [Section 5.1 of \[RFC7541\]](#)). The "S" bit indicates whether the reference is to the static (S=1) or dynamic (S=0) table.

5.4.2.4. Literal Header Field With Post-Base Name Reference

For entries in the dynamic table with an absolute index greater than Base Index, the header field name is represented using the post-base index of that entry (see [Section 2.2.5](#)) encoded as an integer with a 3-bit prefix.

0	1	2	3	4	5	6	7
+-----+-----+-----+-----+-----+-----+-----+-----+							
0	0	0	0	N	NameIdx(3+)		
+-----+-----+-----+-----+-----+-----+-----+-----+							
H	Value Length (7+)						
+-----+-----+-----+-----+-----+-----+-----+-----+							
Value String (Length octets)							
+-----+-----+-----+-----+-----+-----+-----+-----+							

Literal Header Field With Post-Base Name Reference

5.4.2.5. Literal Header Field Without Name Reference

An addition to the header table where both the header field name and the header field value are represented as string literals (see [Section 5.1](#)) starts with the '001' three-bit pattern.

The fourth bit, 'N', indicates whether an intermediary is permitted to add this header to the dynamic header table on subsequent hops.

When the 'N' bit is set, the encoded header MUST always be encoded with a literal representation. In particular, when a peer sends a header field that it received represented as a literal header field with the 'N' bit set, it MUST use a literal representation to forward this header field. This bit is intended for protecting header field values that are not to be put at risk by compressing them (see [Section 7.1 of \[RFC7541\]](#) for more details).

The name is represented as a 4-bit prefix string literal, while the value is represented as an 8-bit prefix string literal.

```

      0   1   2   3   4   5   6   7
+---+---+---+---+---+---+---+---+
| 0 | 0 | 1 | N | H | NameLen(3+) |
+---+---+---+---+---+---+---+
| Name String (Length octets) |
+---+---+---+---+---+---+---+
| H | Value Length (7+) |
+---+---+---+---+---+---+---+
| Value String (Length octets) |
+---+---+---+---+---+---+---+

```

Literal Header Field Without Name Reference

6. Error Handling

The following error codes are defined for HTTP/QUIC to indicate failures of QPACK which prevent the stream or connection from continuing:

HTTP_QPACK_DECOMPRESSION_FAILED (TBD): The decoder failed to interpret an instruction on a request or push stream and is not able to continue decoding that header block.

HTTP_QPACK_ENCODER_STREAM_ERROR (TBD):

The decoder failed to interpret an instruction on the encoder stream. HTTP_QPACK_DECODER_STREAM_ERROR (TBD):

The encoder failed to interpret an instruction on the decoder stream.

Upon encountering an error, an implementation MAY elect to treat it as a connection error even if this document prescribes that it MUST be treated as a stream error.

7. Encoding Strategies

7.1. Single Pass Encoding

An encoder making a single pass over a list of headers must choose Base Index before knowing Largest Reference. When trying to reference a header inserted to the table after encoding has begun, the entry is encoded with different instructions that tell the decoder to use an absolute index greater than the Base Index.

7.2. Preventing Eviction Races

Due to out-of-order arrival, QPACK's eviction algorithm requires changes (relative to HPACK) to avoid the possibility that an indexed representation is decoded after the referenced entry has already been evicted. QPACK employs a two-phase eviction algorithm, in which the encoder will not evict entries that have outstanding (unacknowledged) references.

7.3. Reference Tracking

An encoder MUST ensure that a header block which references a dynamic table entry is not received by the decoder after the referenced entry has already been evicted. An encoder also respects the limit set by the decoder on the number of streams that are allowed to become blocked. Even if the decoder is willing to tolerate blocked streams, the encoder might choose to avoid them in certain cases.

In order to enable this, the encoder will need to track outstanding (unacknowledged) header blocks and table updates using feedback received from the decoder.

7.3.1. Blocked Dynamic Table Insertions

An encoder MUST NOT insert an entry into the dynamic table (or duplicate an existing entry) if doing so would evict an entry with unacknowledged references. For header blocks that might rely on the newly added entry, the encoder can use a literal representation and maybe insert the entry later.

To ensure that the encoder is not prevented from adding new entries, the encoder can avoid referencing entries that will be evicted soonest. Rather than reference such an entry, the encoder SHOULD emit a Duplicate instruction (see [Section 5.2.3](#)), and reference the duplicate instead.

Determining which entries are too close to eviction to reference is an encoder preference. One heuristic is to target a fixed amount of

available space in the dynamic table: either unused space or space that can be reclaimed by evicting unreferenced entries. To achieve this, the encoder can maintain a draining index, which is the smallest absolute index in the dynamic table that it will emit a reference for. As new entries are inserted, the encoder increases the draining index to maintain the section of the table that it will not reference. Draining entries - entries with an absolute index lower than the draining index - will not accumulate new references. The number of unacknowledged references to draining entries will eventually become zero, making the entry available for eviction.




Figure 7: Draining Dynamic Table Entries

7.3.2. Blocked Decoding

For header blocks encoded in non-blocking mode, the encoder needs to forego indexed representations that refer to table updates which have not yet been acknowledged (see [Section 5.3](#)). Since all table updates are processed in sequence on the control stream, an index into the dynamic table is sufficient to track which entries have been acknowledged.

To track blocked streams, the necessary Base Index value for each stream can be used. Whenever the decoder processes a table update, it can begin decoding any blocked streams that now have their dependencies satisfied.

7.4. Speculative table updates

Implementations can `_speculatively_` send instructions on the encoder stream which are not needed for any current HTTP request or response. Such headers could be used strategically to improve performance. For instance, the encoder might decide to `_refresh_` by sending Duplicate representations for popular header fields ([Section 5.2.3](#)), ensuring they have small indices and hence minimal size on the wire.

7.5. Sample One Pass Encoding Algorithm

Pseudo-code for single pass encoding, excluding handling of duplicates, non-blocking mode, and reference tracking.


```
baseIndex = dynamicTable.baseIndex
largestReference = 0
for header in headers:
    staticIdx = staticTable.getIndex(header)
    if staticIdx:
        encodeIndexReference(streamBuffer, staticIdx)
        continue

    dynamicIdx = dynamicTable.getIndex(header)
    if !dynamicIdx:
        # No matching entry. Either insert+index or encode literal
        nameIdx = getNameIndex(header)
        if shouldIndex(header) and dynamicTable.canIndex(header):
            encodeLiteralWithIncrementalIndex(controlBuffer, nameIdx,
                                              header)

            dynamicTable.add(header)
            dynamicIdx = dynamicTable.baseIndex

        if !dynamicIdx:
            # Couldn't index it, literal
            if nameIdx <= staticTable.size:
                encodeLiteral(streamBuffer, nameIndex, header)
            else:
                # encode literal, possibly with nameIdx above baseIndex
                encodeDynamicLiteral(streamBuffer, nameIndex, baseIndex,
                                    header)
                largestReference = max(largestReference,
                                      dynamicTable.toAbsolute(nameIdx))
        else:
            # Dynamic index reference
            assert(dynamicIdx)
            largestReference = max(largestReference, dynamicIdx)
            # Encode dynamicIdx, possibly with dynamicIdx above baseIndex
            encodeDynamicIndexReference(streamBuffer, dynamicIdx,
                                       baseIndex)

# encode the prefix
encodeInteger(prefixBuffer, 0x00, largestReference, 8)
if baseIndex >= largestReference:
    encodeInteger(prefixBuffer, 0, baseIndex - largestReference, 7)
else:
    encodeInteger(prefixBuffer, 0x80,
                  largestReference - baseIndex, 7)

return controlBuffer, prefixBuffer + streamBuffer
```

8. Security Considerations

TBD.

9. IANA Considerations

9.1. Settings Registration

This document creates two new settings in the "HTTP/QUIC Settings" registry established in [QUIC-HTTP].

The entries in the following table are registered by this document.

Setting Name	Code	Specification
HEADER_TABLE_SIZE	0x1	Section 4
QPACK_BLOCKED_STREAMS	0x7	Section 4

9.2. Stream Type Registration

This document creates two new settings in the "HTTP/QUIC Stream Type" registry established in [QUIC-HTTP].

The entries in the following table are registered by this document.

Stream Type	Code	Specification	Sender
QPACK Encoder Stream	0x48	Section 5	Both
QPACK Decoder Stream	0x68	Section 5	Both

9.3. Error Code Registration

This document establishes the following new error codes in the "HTTP/QUIC Error Code" registry established in [QUIC-HTTP].

Name	Code	Description	Specification
HTTP_QPACK_DECOMPRESSION_FAILED	TBD	Decompression of a header block failed	Section 6
HTTP_QPACK_ENCODER_STREAM_ERROR	TBD	Error on the encoder stream	Section 6
HTTP_QPACK_DECODER_STREAM_ERROR	TBD	Error on the decoder stream	Section 6

10. References

10.1. Normative References

[QUIC-HTTP]

Bishop, M., Ed., "Hypertext Transfer Protocol (HTTP) over QUIC", [draft-ietf-quic-http-15](#) (work in progress), October 2018.

[QUIC-TRANSPORT]

Iyengar, J., Ed. and M. Thomson, Ed., "QUIC: A UDP-Based Multiplexed and Secure Transport", [draft-ietf-quic-transport-14](#) (work in progress), October 2018.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC7541] Peon, R. and H. Ruellan, "HPACK: Header Compression for HTTP/2", [RFC 7541](#), DOI 10.17487/RFC7541, May 2015, <<https://www.rfc-editor.org/info/rfc7541>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

10.2. Informative References

- [RFC2360] Scott, G., "Guide for Internet Standards Writers", [BCP 22](#), [RFC 2360](#), DOI 10.17487/RFC2360, June 1998, <<https://www.rfc-editor.org/info/rfc2360>>.
- [RFC7540] Belshe, M., Peon, R., and M. Thomson, Ed., "Hypertext Transfer Protocol Version 2 (HTTP/2)", [RFC 7540](#), DOI 10.17487/RFC7540, May 2015, <<https://www.rfc-editor.org/info/rfc7540>>.

10.3. URIs

- [1] https://mailarchive.ietf.org/arch/search/?email_list=quic
- [2] <https://github.com/quicwg>
- [3] <https://github.com/quicwg/base-drafts/labels/-qpack>

Appendix A. Static Table

Index	Name	Value
0	:authority	
1	:path	/
2	age	0
3	content-disposition	
4	content-length	0
5	cookie	
6	date	
7	etag	
8	if-modified-since	
9	if-none-match	
10	last-modified	
11	link	

12	location	
13	referer	
14	set-cookie	
15	:method	CONNECT
16	:method	DELETE
17	:method	GET
18	:method	HEAD
19	:method	OPTIONS
20	:method	POST
21	:method	PUT
22	:scheme	http
23	:scheme	https
24	:status	103
25	:status	200
26	:status	304
27	:status	404
28	:status	503
29	accept	*/*
30	accept	application/dns-message
31	accept-encoding	gzip, deflate, br
32	accept-ranges	bytes
33	access-control-allow-headers	cache-control
34	access-control-allow-headers	content-type

35	access-control-allow-origin	*
36	cache-control	max-age=0
37	cache-control	max-age=2592000
38	cache-control	max-age=604800
39	cache-control	no-cache
40	cache-control	no-store
41	cache-control	public, max-age=31536000
42	content-encoding	br
43	content-encoding	gzip
44	content-type	application/dns-message
45	content-type	application/javascript
46	content-type	application/json
47	content-type	application/x-www-form-urlencoded
48	content-type	image/gif
49	content-type	image/jpeg
50	content-type	image/png
51	content-type	text/css
52	content-type	text/html; charset=utf-8
53	content-type	text/plain
54	content-type	text/plain; charset=utf-8
55	range	bytes=0-
56	strict-transport-security	max-age=31536000
57	strict-transport-security	max-age=31536000; includesubdomains

58	strict-transport-security	max-age=31536000; includesubdomains; preload
59	vary	accept-encoding
60	vary	origin
61	x-content-type-options	nosniff
62	x-xss-protection	1; mode=block
63	:status	100
64	:status	204
65	:status	206
66	:status	302
67	:status	400
68	:status	403
69	:status	421
70	:status	425
71	:status	500
72	accept-language	
73	access-control-allow-credentials	FALSE
74	access-control-allow-credentials	TRUE
75	access-control-allow-headers	*
76	access-control-allow-methods	get
77	access-control-allow-methods	get, post, options
78	access-control-allow-	options

	methods	
79	access-control-expose-headers	content-length
80	access-control-request-headers	content-type
81	access-control-request-method	get
82	access-control-request-method	post
83	alt-svc	clear
84	authorization	
85	content-security-policy	script-src 'none'; object-src 'none'; base-uri 'none'
86	early-data	1
87	expect-ct	
88	forwarded	
89	if-range	
90	origin	
91	purpose	prefetch
92	server	
93	timing-allow-origin	*
94	upgrade-insecure-requests	1
95	user-agent	
96	x-forwarded-for	
97	x-frame-options	deny
98	x-frame-options	sameorigin

Appendix B. Change Log

RFC Editor's Note: Please remove this section prior to publication of a final version of this document.

B.1. Since [draft-ietf-quic-qpack-02](#)

- o Largest Reference encoded modulo MaxEntries (#1763)
- o New Static Table (#1355)
- o Table Size Update with Insert Count=0 is a connection error (#1762)
- o Stream Cancellations are optional when SETTINGS_HEADER_TABLE_SIZE=0 (#1761)
- o Implementations must handle 62 bit integers (#1760)
- o Different error types for each QPACK stream, other changes to error handling (#1726)
- o Preserve header field order (#1725)
- o Initial table size is the maximum permitted when table is first usable (#1642)

B.2. Since [draft-ietf-quic-qpack-01](#)

- o Only header blocks that reference the dynamic table are acknowledged (#1603, #1605)

B.3. Since [draft-ietf-quic-qpack-00](#)

- o Renumbered instructions for consistency (#1471, #1472)
- o Decoder is allowed to validate largest reference (#1404, #1469)
- o Header block acknowledgments also acknowledge the associated largest reference (#1370, #1400)
- o Added an acknowledgment for unread streams (#1371, #1400)
- o Removed framing from encoder stream (#1361, #1467)
- o Control streams use typed unidirectional streams rather than fixed stream IDs (#910, #1359)

B.4. Since [draft-ietf-quic-qcram-00](#)

- o Separate instruction sets for table updates and header blocks (#1235, #1142, #1141)
- o Reworked indexing scheme (#1176, #1145, #1136, #1130, #1125, #1314)
- o Added mechanisms that support one-pass encoding (#1138, #1320)
- o Added a setting to control the number of blocked decoders (#238, #1140, #1143)
- o Moved table updates and acknowledgments to dedicated streams (#1121, #1122, #1238)

Acknowledgments

This draft draws heavily on the text of [[RFC7541](#)]. The indirect input of those authors is gratefully acknowledged, as well as ideas from:

- o Ryan Hamilton
- o Patrick McManus
- o Kazuho Oku
- o Biren Roy
- o Ian Swett
- o Dmitri Tikhonov

Buck's contribution was supported by Google during his employment there.

A substantial portion of Mike's contribution was supported by Microsoft during his employment there.

Authors' Addresses

Charles 'Buck' Krasic
Netflix

Email: ckrasic@netflix.com

Mike Bishop
Akamai Technologies

Email: mbishop@evequefou.be

Alan Frindell (editor)
Facebook

Email: afrind@fb.com