



自定义登录成功处理器

源码分析

使用`successForwardUrl()`时表示成功后转发请求到地址。内部是通过 `successHandler()` 方法进行控制成功后交给哪个类进行处理

```
public FormLoginConfigurer<H> successForwardUrl(String forwardUrl) {  
    this.successHandler(new ForwardAuthenticationSuccessHandler(forwardUrl));  
    return this;  
}
```

`ForwardAuthenticationSuccessHandler`内部就是最简单的请求转发。由于是请求转发，当遇到需要跳转到站外或在前后端分离的项目中就无法使用了。

```
public class ForwardAuthenticationSuccessHandler implements AuthenticationSuccessHandler {  
    private final String forwardUrl;  
  
    public ForwardAuthenticationSuccessHandler(String forwardUrl) {  
        Assert.isTrue(UrlUtils.isValidRedirectUrl(forwardUrl), () -> {  
            return "" + forwardUrl + " is not a valid forward URL";  
        });  
        this.forwardUrl = forwardUrl;  
    }  
  
    public void onAuthenticationSuccess(HttpServletRequest request, HttpServletResponse response, Authentication authentication) throws IOException, ServletException {  
        request.getRequestDispatcher(this.forwardUrl).forward(request, response);  
    }  
}
```

当需要控制登录成功后去做一些事情时，可以进行自定义认证成功控制器。

代码实现

自定义类

新建类 `com.xxxx.handler.MyAuthenticationSuccessHandler` 编写如下：

```
package com.xxxx.springsecuritydemo.handler;  
  
import org.springframework.security.core.Authentication;  
import org.springframework.security.core.userdetails.User;  
import org.springframework.security.web.authentication.AuthenticationSuccessHandler;  
  
import javax.servlet.ServletException;  
import javax.servlet.http.HttpServletRequest;  
import javax.servlet.http.HttpServletResponse;  
import java.io.IOException;  
  
/**  
 * @author zhoubin  
 * @since 1.0.0  
 */  
public class MyAuthenticationSuccessHandler implements AuthenticationSuccessHandler {  
  
    private String url;
```



```
public MyAuthenticationSuccessHandler(String url) {
    this.url = url;
}

@Override
public void onAuthenticationSuccess(HttpServletRequest request, HttpServletResponse
response, Authentication authentication) throws IOException, ServletException {
    //Principal 主体, 存放了登录用户的信息
    User user = (User) authentication.getPrincipal();
    System.out.println(user.getUsername());
    //输出null
    System.out.println(user.getPassword());
    System.out.println(user.getAuthorities());
    response.sendRedirect(url);
}
}
```

修改配置项

使用 successHandler()方法设置成功后交给哪个对象进行处理

```
//表单提交
http.formLogin()
    //自定义登录页面
    .loginPage("/login.html")
    //当发现/login时认为是登录, 必须和表单提交的地址一样。去执行UserServiceImpl
    .loginProcessingUrl("/login")
    //登录成功后跳转页面, POST请求
    // .successForwardUrl("/toMain")
    //和successForwardUrl不能共存
    .successHandler(new MyAuthenticationSuccessHandler("http://www.baidu.com"))
    //登录失败后跳转页面, POST请求
    .failureForwardUrl("/toError")
    .usernameParameter("myusername")
    .passwordParameter("mypassword");
```