

## **CHAPTER 9: Morphological image processing**

- Language of mathematical morphology: set theory
- Sets ≡ objects in an image
- Binary images: sets  $\in Z^2$
- Gray-scale images: sets  $\in Z^3$

## 9.1 Preliminaries

- Let A be a set in  $Z^2$ . If  $a=(a_1,a_2)$  is an element of A, then we write  $a\in A$
- Subset, union, intersection:


$$A \subseteq B$$
,  $C = A \bigcup B$ ,  $D = A \bigcap B$ 

- Disjoint or mutually exclusive:  $A \cap B = \emptyset$
- Complement:  $A^c = \{w | w \notin A\}$
- Difference:  $A B = \{w | w \in A, w \notin B\} = A \cap B^c$



- Reflection:  $\hat{B} = \{w|w = -b, \text{ for } b \in B\}$
- Translation of set A by point  $z=(z_1,z_2)$ :  $(A)_z=\{c|c=a+z, \text{ for } a\in A\}$

(Ed 2)




a b c

by z.

**FIGURE 9.1**(a) A set, (b) its reflection, and


(c) its translation

(Ed 3)





• Reflection and translation are employed to formulate operations based on structuring elements (SEs): small sets (subimages) used to probe an image for properties of interest



**FIGURE 9.3** (a) A set (each shaded square is a member of the set). (b) A structuring element. (c) The set padded with background elements to form a rectangular array and provide a background border. (d) Structuring element as a rectangular array. (e) Set processed by the structuring element.



#### 9.2 Erosion and dilation

These operations are fundamental to morphological processing


#### 9.2.1 Erosion

With A and B sets in  $\mathbb{Z}^2$ , the erosion of A by B, is defined as

$$A \ominus B = \{z | (B)_z \subseteq A\}$$

or alternatively


 $A\ominus B=\left\{z|(B)_z\bigcap A^c=\emptyset\right\}$ 



### • Convolution process



## Example 9.1



a b c d

FIGURE 9.5 Using erosion to remove image components. (a) A  $486 \times 486$  binary image of a wirebond mask. (b)-(d) Image eroded using square structuring elements of sizes  $11 \times 11, 15 \times 15,$ and  $45 \times 45$ , respectively. The elements of the SEs were all 1s.




#### 9.2.2 Dilation

With A and B sets in  $\mathbb{Z}^2$ , the dilation of A by B, is defined as

$$A \oplus B = \left\{ z | (\hat{B})_z \bigcap A \neq \emptyset \right\}$$

or alternatively

$$A \oplus B = \left\{ z | \left[ (\hat{B})_z \bigcap A \right] \subseteq A \right\}$$



d/8

 $\hat{B} = B$ 

(b) Square structuring element (the dot denotes the origin). (c) Dilation of A by B, shown shaded. (d) Elongated structuring element. (e) Dilation of A using this element. The dotted border in (c) and (e) is the boundary of set A, shown only for reference d/2 $A \oplus B$ d d/8

a b c d e FIGURE 9.6 (a) Set A.



### Example 9.2

Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.

Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.

a		С
	b	

#### FIGURE 9.7

- (a) Sample text of poor resolution with broken characters (see magnified view).
- (b) Structuring element.
- (c) Dilation of (a) by (b). Broken segments were joined.

0	1	0
1	1	1
0	1	0



### 9.2.3 Duality

Dilation and erosion are duals of each other with respect to set complementation and reflection, that is

$$\left| (A \ominus B)^c = A^c \oplus \hat{B} \right| \tag{*}$$

and

$$\left| (A \oplus B)^c = A^c \ominus \hat{B} \right|$$

# Proof of (\*):

$$(A \ominus B)^{c} = \{z | (B)_{z} \subseteq A\}^{c}$$

$$= \{z | (B)_{z} \cap A^{c} = \emptyset\}^{c}$$

$$= \{z | (B)_{z} \cap A^{c} \neq \emptyset\}$$

$$= A^{c} \oplus \hat{B}$$



### 9.3 Opening and closing

#### **USES**

**Opening: Smoothes the contour of an object** 

Breaks narrow isthmuses ("bridges")

**Eliminates thin protrusions** 

**Closing: Smoothes sections of contours** 

Fuses narrow breaks and long thin gulfs

Eliminates small holes in contours

Fills gaps in contours

#### **Definitions**

The opening of set A by structuring element B:


$$A \circ B = (A \ominus B) \oplus B$$

The closing of set A by structuring element B:

$$A \bullet B = (A \oplus B) \ominus B$$



### Illustration of opening...



a b c d


**FIGURE 9.8** (a) Structuring element B "rolling" along the inner boundary of A (the dot indicates the origin of B). (b) Structuring element. (c) The heavy line is the outer boundary of the opening. (d) Complete opening (shaded). We did not shade A in (a) for clarity.

# Alternative definition for opening:

$$A \circ B = \bigcup \{(B)_z | (B)_z \subseteq A\}$$



#### Illustration of closing...



**FIGURE 9.9** (a) Structuring element B "rolling" on the outer boundary of set A. (b) The heavy line is the outer boundary of the closing. (c) Complete closing (shaded). We did not shade A in (a) for clarity.

### Alternative definition for closing:

A point w is an element of  $A \bullet B$  if and only if  $(B)_z \cap A \neq \emptyset$  for any translate of  $(B)_z$  that contains w

Opening and closing are also duals of each other with respect to set complementation and reflection, that is

$$(A \bullet B)^c = A^c \circ \hat{B}$$
 (Verify)




### The opening operation satisfies the following properties:

(i)  $A \circ B \subseteq A$  (ii) If  $C \subseteq D$ , then  $C \circ B \subseteq D \circ B$  (iii)  $(A \circ B) \circ B = A \circ B$ 

#### The closing operation satisfies the following properties:

(i)  $A \subseteq A \bullet B$  (ii) If  $C \subseteq D$ , then  $C \bullet B \subseteq D \bullet B$  (iii)  $(A \bullet B) \bullet B = A \bullet B$ 

### Example 9.3





## Example 9.4:

