Course Title: [Sound Mixing]
GiveAway#1
Instructor: [John Ko]

Standards and Best Practices: Sound Mixing: EQ Guide

Type of Input	Frequencies of Interest	Troubleshooting
Speech	Mid range is irritating Harmonics(1k, 500, 250, 125)	Enable HPF Raise gain till loud and clear Feedback: sweep freqs, cut gain of bad freq Sibilance: lower high freqs Plosives: check mic placement
Vocals	Low mid range is key but problematic 150-300hz 500hz – nasally Clarity – boost mid highs(1k-5k) Breathy – boost highs(5k-10k)	Enable HPF
Keyboards	Mid range – set EQ to boost, sweep, then cut bad freq Usually 250hz Can be muddy(80z)	
Acoustic Guitar	Mid range – set EQ to boost, sweep, then cut muddy freq Usually 900hz/1k Add sparkle(12k)	Disable HPF
Electric guitar	Warm up – boost mids(250-300hz) Clarity – boost(3k) Distortion – boost(5k-8k) Airiness – boost(12k)	EQ affects main mix a lot because of our style of music
Bass Guitar	Muddiness(250hz) Low end – boost(40-80hz) Clarity – boost highs(3k)	Pass through bass amp
Drums – High Hat	Lower lows(125hz-) Lower 3k/4k – piercing Boost highs(12k) Lower midrange - muddy	Enable HPF Mics need phantom power
Drums - Toms	Lower 250hz Sweep midrange(500hz+) Boost lows(40-80hz) Boost highs for attack(12k)	
Drums - Snare	Low/mid gives warmth(250hz) Boost high(10k) Cut/attack – boost(3k/4k)	Enable HPF Mic placement: 45 deg for top/bottom
Drums - Kick	Lower 250hz Sweep and cut midrange 500hz+ Boost low(40-80hz) Boost high(4k or 10k)	Disable HPF Mic placement