```
client 2 writes, Nagle on          p50   41.00  p99   41.16 ms
client 2 writes, TCP_NODELAY       p50    0.07  p99    0.11 ms
```

*A companion to the Testing Field Guide*

# Java *performance* deep dives

TCP_NODELAY and delayed ACKs, connections and timeouts, pools and Little's Law, measuring latency, the JIT, GC pauses, virtual threads, containers, the memory model and Kafka — each explained from the specification or the source code, and each measured. Every number in this book is read from a log written in CI.

| 11 | 20 | 30 | 1 |
|---|---|---|---|
| chapters | experiments | logs | runner, named |

INSIDE

# Contents

**How it was measured** — the runner, the experiments, the rules 03

01 **Nagle, delayed ACK and TCP_NODELAY**
The mechanism, packet by packet 04
Measured; who sets TCP_NODELAY 05

02 **Connections**
A connection's life 06
Measured: reuse and close 07

03 **Timeouts**
Phases and defaults 08
Measured: three broken peers 09

04 **Pools and Little's Law**
Little's Law 10
Measured: database and CPU pools 11

05 **Measuring latency**
Open and closed loops 12
Measured: the same server, three ways 13

06 **JIT and benchmarks**
Warm-up 14
Dead code and constant folding, with JMH 15

07 **GC pauses**
Pauses and the G1 cycle 16
Measured: the tail 17

08 **Virtual threads**
Measured: blocking and pinning 18

09 **Containers and CPUs**
What the JVM sees 19
Sized from the CPU count; throttling 20

10 **The Java Memory Model**
What another thread may see 21
Visibility and lost updates 22

11 **Kafka**
Producer batching: linger.ms and batch.size 23
Consumer fetching, partitions, max.poll.interval.ms 24

**Sources** — every specification, source file and document cited 25
**Index A–Z** 26

Facts as of October 2026, for JDK 21 unless a page says otherwise. Every entry, page reference and footer link is clickable.

COLOUR LANGUAGE

Network · queues and measurement · the JVM · the platform

READ WITH

**Testing Java applications — Field Guide** (Testing-Field-Guide.pdf, same repository). Its performance chapter introduces several of these topics in a page each; this book is the long version.

ON EVERY PAGE

The mechanism, from the specification or the source. The experiment's code, as it ran. The real output. What to do about it. The sources, at the foot.

BEFORE YOU START

# How it was measured

Each page explains a mechanism and then measures it. Explanations cite a specification, the source code of the version discussed, or the vendor's documentation; measurements come from programs in this repository, run in CI.

### Sources for explanations

The specification (RFC 9293 for TCP, the Java Language Specification for the memory model, JEPs for JDK features), the **source code of the version discussed** — OpenJDK 21, Linux 6.17, the libraries — or the vendor's documentation. Each page lists what it used at its foot; the full list is at the back.

### Measurements

Each chapter has a small program in `deepdive/`. The `deepdive` CI job runs all of them on every push (`deepdive/run.sh`) and publishes the logs to the `ci-logs-deepdive` branch. This book is built from those logs: every measured number on a page is read from them at build time.

## The machine

| | |
|---|---|
| **Runner** | GitHub Actions, `ubuntu-latest` |
| **CPU** | 4 CPUs · AMD EPYC 7763 64-Core Processor |
| **Kernel** | Linux 6.17.0-1022-azure, `CONFIG_HZ=1000` |
| **JDK** | OpenJDK 21.0.12.1 (Temurin) |
| `ip_local_port_range` | 32768 60999 |
| `tcp_tw_reuse` | 2 |
| `tcp_syn_retries` | 6 |
| `tcp_pingpong_thresh` | 1 |
| `tcp_fin_timeout` | 60 |

From `machine.txt`, written by the same run.

## The experiments

| CH. | PROGRAM | LOG |
|---|---|---|
| **1** | tcp/Nagle.java + tcpdump | nagle.txt, nagle-trace.txt |
| **2** | tcp/Connections.java | connections.txt |
| **3** | tcp/Timeouts.java, SynRetries.java + iptables | timeouts.txt, syn*.txt |
| **4** | pool/PoolSize.java, CpuPool.java | pool.txt, cpupool.txt |
| **5** | latency/CoordinatedOmission.java | co.txt |
| **6** | jit/WarmUp.java, DeadCodeBench.java (JMH) | warmup*.txt, jmh.txt, jit-flags.txt |
| **7** | gc/GcLatency.java, G1 and ZGC | gc-*.txt, gc-*.log |
| **8** | vt/VirtualThreads.java | vt.txt |
| **9** | box/Resources.java, Throttle.java in Docker | containers.txt, throttle.txt |
| **10** | jmm/StaleFlag.java + 4 jcstress tests | staleflag.txt, jcstress.log |
| **11** | kafka/KafkaLatency.java, one broker in Docker | kafka-*.txt |

## One number, traced

| STEP | EVIDENCE |
|---|---|
| **The claim (chapter 1)** | Two small writes with Nagle on: median **41.00 ms** per request |
| **The log line** | `client 2 writes, Nagle on p50 41.00` — `nagle.txt`, written by `Nagle.java` in CI |
| **The packets** | `nagle-trace.txt`: the server's ACK of the first 50-byte half left 40.51 ms after it; the second half was held until then — tcpdump on loopback |
| **Why 40 ms** | Linux `include/net/tcp.h`: `TCP_DELACK_MIN = HZ/25`; with `CONFIG_HZ=1000` that is 40 ms |
| **Why it waits at all** | RFC 9293 §3.7.4 (Nagle: hold small segments while data is unacknowledged) and §3.8.6.3 (delayed ACK) |

- **The text follows the data.** Where a sentence interprets a result — "slower", "removed by the JIT", "not caused by a GC pause" — it is computed from the log, and changes if the result changes.
- **Conclusions are checked.** `guide/claims_deep.py` re-reads the logs and fails the build if a conclusion this book states no longer holds.
- **One machine.** The numbers are from one CI runner and depend on its CPU, kernel and JDK. To rerun on another machine: `bash deepdive/run.sh` (Linux, JDK 21, Maven, Docker; `sudo` for tcpdump and iptables).
- **Versions matter.** Statements are for JDK 21 and the library versions named; where a later JDK changed the behaviour (JEP 474, 490, 491) the page says so.

01 · NAGLE AND DELAYED ACK

# Nagle's algorithm and delayed ACK

TCP has two mechanisms that reduce the number of small packets. The **sender** holds back a small segment while earlier data is unacknowledged (Nagle). The **receiver** holds back its ACK, hoping to piggyback it on a reply (delayed ACK). In a request/response exchange where one message goes out in two `write()` calls, each waits for the other — until a timer fires.

### Nagle's algorithm — the sender

> "If there is unacknowledged data (i.e., SND.NXT > SND.UNA), then the sending TCP endpoint buffers all user data (regardless of the PSH bit) until the outstanding data has been acknowledged or until the TCP endpoint can send a full-sized segment." — RFC 9293 §3.7.4


TCP **SHOULD** implement it (SHLD-7); there **MUST** be a way to disable it per connection (MUST-17). In Java that is `TCP_NODELAY`, off by default on a `java.net.Socket`.

### Delayed ACK — the receiver

> "A TCP endpoint SHOULD implement a delayed ACK (SHLD-18) ... the delay MUST be less than 0.5 seconds (MUST-40)." An ACK SHOULD go out for at least every second full-sized segment. — RFC 9293 §3.8.6.3

Linux starts each connection in **quick-ACK** mode and leaves it once the connection looks like request/response ("ping-pong"): a reply sent within the ACK timeout of receiving data counts. From then on, a lone segment waits for the timer.

## The stall, captured




| LINUX | VALUE | MEANING | WHERE |
|---|---|---|---|
| `TCP_DELACK_MIN` | HZ/25 jiffies = **40 ms** | shortest delayed-ACK timer | include/net/tcp.h |
| `TCP_DELACK_MAX` | HZ/5 jiffies = **200 ms** | longest delayed-ACK timer | include/net/tcp.h |
| `TCP_MAX_QUICKACKS` | **16** | ACKs sent at once in quick-ACK mode | include/net/tcp.h |
| `tcp_pingpong_thresh` | **1** on the runner | replies before a connection counts as request/response | ip-sysctl.rst |
| `CONFIG_HZ` | **1000** on the runner | timer tick: 1 ms | /boot/config |

The capture shows the second request on the connection. The server's ACK left **40.5 ms** after the first half of the request; `TCP_DELACK_MIN` is 40 ms on this kernel.

The **first** request did not wait: its ACK came back in 0.015 ms, while the new connection was still in quick-ACK mode. After one request and its reply, Linux treats the connection as ping-pong and starts delaying ACKs.

SOURCES RFC 9293 (2022) §3.7.4, §3.8.6.3 · RFC 896 (Nagle, 1984) · Linux include/net/tcp.h, net/ipv4/tcp_input.c, tcp_output.c (tcp_event_data_sent: pingpong) · Documentation/networking/ip-sysctl.rst · OpenJDK 21 StandardSocketOptions.TCP_NODELAY · capture: tcpdump on loopback, GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

01 · NAGLE AND DELAYED ACK

# Measured: one or two writes per message, 7 setups

One connection on loopback, 200 request/response round trips of 100 bytes each way. The only differences: whether a message is written in one `write()` or two (like headers, then body), on which side, and which socket option is set.

Nagle.java — the client side

```java
static long[] exchange(Socket socket, int writes, int rounds)
    throws Exception {
  OutputStream out = socket.getOutputStream();
  InputStream in = socket.getInputStream();
  long[] rtt = new long[rounds];
  for (int i = 0; i < rounds; i++) {
    long t0 = System.nanoTime();
    write(out, writes);
    in.readNBytes(100);
    rtt[i] = System.nanoTime() - t0;
  }
  return rtt;
}

/** 100 bytes in one write, or 50 + 50 like headers + body. */
static void write(OutputStream out, int writes)
    throws Exception {
  if (writes == 1) {
    out.write(new byte[100]);
  } else {
    out.write(new byte[50]);
    out.write(new byte[50]);
  }
  out.flush();
}
```

| SETUP | P50 MS | P99 MS | MAX MS | OVER 30 MS |
|---|---|---|---|---|
| **client 2 writes, Nagle on** | 41.00 | 41.16 | 41.27 | 199 of 200 |
| **client 2 writes, TCP_NODELAY** | 0.07 | 0.11 | 0.41 | 0 of 200 |
| **client 1 write, Nagle on** | 0.05 | 0.09 | 0.25 | 0 of 200 |
| **server 2 writes, Nagle on** | 41.00 | 41.10 | 43.75 | 199 of 200 |
| **server 2 writes, TCP_NODELAY** | 0.07 | 0.10 | 0.11 | 0 of 200 |
| **client 2 writes, QUICKACK once** | 41.00 | 41.11 | 41.13 | 199 of 200 |
| **client 2 writes, QUICKACK per read** | 0.06 | 0.10 | 0.24 | 0 of 200 |

Real output · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

## TCP_NODELAY defaults in common libraries

| LIBRARY | TCP_NODELAY | EVIDENCE IN ITS SOURCE |
|---|---|---|
| **JDK `HttpClient`** | on | `PlainHttpConnection`: `setOption(TCP_NODELAY, true)` |
| **JDK `HttpServer`** | **off** | only with `-Dsun.net.httpserver.nodelay=true` (`ServerConfig`) |
| **`java.net.Socket`** | **off** | `StandardSocketOptions.TCP_NODELAY`: default `FALSE` |
| **Tomcat** | on | `SocketProperties.tcpNoDelay = TRUE` |
| **Jetty 12** | on | `ServerConnector._acceptedTcpNoDelay = true` |
| **Netty 4.1** | on | `DefaultSocketChannelConfig`: on unless Android |
| **PostgreSQL JDBC** | on | `PGProperty.TCP_NO_DELAY`: default `"true"` |
| **Lettuce (Redis)** | on | `SocketOptions.DEFAULT_SO_NO_DELAY = true` |
| **Kafka client** | on | `Selector`: `socket.setTcpNoDelay(true)` |


- **Two writes per message + Nagle = one timer per message.** Every round trip took about 41 ms; every fix brought p99 under 0.1 ms.
- **Write each message once.** Build it in a buffer (or wrap the stream in a `BufferedOutputStream`) and flush once: Nagle never has a second small segment to hold.
- **Or set `TCP_NODELAY`** on request/response connections — on the side that writes twice. Most servers and the JDK client already do; the JDK's own `HttpServer` does not.
- **The receiver can help:** `jdk.net.ExtendedSocketOptions.TCP_QUICKACK` (Linux, JDK 10+) asks for an immediate ACK — but it is not sticky. Set once, nothing changed; set before every read, the stall was gone.
- **Symptom:** a p50 just above 40 ms on Linux while the CPUs are idle. The main guide's load test of the JDK `HttpServer` showed the same stall.

SOURCES OpenJDK 21: jdk/internal/net/http/PlainHttpConnection.java, sun/net/httpserver/ServerConfig.java, ServerImpl.java, java/net/StandardSocketOptions.java, jdk/net/ExtendedSocketOptions.java (TCP_QUICKACK, since 10) · Tomcat main: SocketProperties.java · Jetty 12.0: ServerConnector.java · Netty 4.1: DefaultSocketChannelConfig.java · pgjdbc: PGProperty.java · Lettuce: SocketOptions.java · Kafka: clients/.../network/Selector.java · results: deepdive/logs/nagle.txt

02 · CONNECTIONS

# Connection set-up, reuse and close

Before the first byte of a request, TCP spends a round trip on the handshake. After the last byte, the side that closes **first** keeps the connection in TIME_WAIT, holding its port. Both costs are paid once per connection, however many requests it carries.




### TIME_WAIT

> "When a connection is closed actively, it MUST linger in the TIME-WAIT state for a time 2xMSL (Maximum Segment Lifetime) (MUST-13)." "For this specification the MSL is taken to be 2 minutes." — RFC 9293 §3.6.1, §3.4.2

Sequence numbers stay "busy" until MSL seconds have passed (§3.4.3): the wait keeps old segments from being taken for a new connection's. Linux does not wait 4 minutes but a fixed **60 s** ( `TCP_TIMEWAIT_LEN` ). `tcp_fin_timeout` is something else — how long an orphaned connection may sit in FIN_WAIT_2.

### Ephemeral ports run out

A connection is identified by four values: source address and port, destination address and port. To one destination, a client can only vary its own port. The runner's range is `32768-60999` : **28,232** ports. Each closed connection keeps its port for 60 s, so one client address can open at most about **471 new connections per second** to one server address and port, for as long as that lasts — unless TIME_WAIT reuse applies.

### Reuse is not on everywhere

`tcp_tw_reuse` lets a new outgoing connection take a port still in TIME_WAIT when that is safe. Its default is **2: loopback traffic only** — the runner has `2` . With the default, a client connecting to `localhost` can reuse ports in TIME_WAIT; a client connecting to another host cannot.

## TCP states shown by `ss`

| STATE | MEANS | A LARGE COUNT INDICATES |
|---|---|---|
| `SYN-SENT` | connect() sent a SYN, no answer yet | the server is unreachable or dropping packets — see the next chapter |
| `ESTABLISHED` | open, data can flow both ways | the number of open connections; compare with pool sizes |
| `FIN-WAIT-2` | we closed; the peer has not closed its side yet | the peer is not closing its sockets |
| `CLOSE-WAIT` | the peer closed; our application has not called close() | **a socket leak in our code** |
| `TIME-WAIT` | we closed first; waiting before the port can be reused | many short-lived connections closed by this side |

SOURCES RFC 9293 §3.3.2, §3.4.2, §3.4.3, §3.6.1 · Linux include/net/tcp.h (TCP_TIMEWAIT_LEN) · Documentation/networking/ip-sysctl.rst (ip_local_port_range, tcp_tw_reuse, tcp_fin_timeout) · capture and sysctl values: GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

02 · CONNECTIONS

# Measured: kept-alive and per-request connections

2,000 request/response exchanges on loopback: over one kept-alive connection, then over a new connection each time, closed four different ways. Afterwards the program counts sockets by state in the kernel's own tables, `/proc/net/tcp` and `tcp6`.

| HOW | MS / REQUEST | VS KEPT-ALIVE | TIME_WAIT CLIENT / SERVER | CLOSE_WAIT CLIENT / SERVER | FIN_WAIT2 CLIENT / SERVER |
|---|---|---|---|---|---|
| **one kept-alive connection** | 65.6 | 1.0× | – | – | – |
| **new connection, client closes first** | 270.3 | 4.1× | **2000** / 0 | 0 / 0 | 0 / 0 |
| **new connection, server closes first** | 243.1 | 3.7× | 0 / **2000** | 0 / 0 | 0 / 0 |
| **new connection, client closes with `SO_LINGER(0)`** | 263.4 | 4.0× | 0 / 0 | 0 / 0 | 0 / 0 |
| **new connection, server never closes (a leak)** | 225.9 | 3.4× | 0 / 0 | 0 / **2000** | **2000** / 0 |

Real output · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

Connections.java — a new connection per request

```java
static void perRequest(Close how) throws Exception {
  try (var server = new ServerSocket(0, 512, LO)) {
    int port = server.getLocalPort();
    Thread.ofPlatform().daemon()
        .start(() -> oneEach(server, how));
    long t0 = System.nanoTime();
    for (int i = 0; i < N; i++) {
      try (var s = new Socket(LO, port)) {
        s.setTcpNoDelay(true);
        if (how == Close.CLIENT_RESET) {
          s.setSoLinger(true, 0);       // close() sends RST
        }
        s.getOutputStream().write(new byte[100]);
        var in = s.getInputStream();
        in.readNBytes(100);
        if (how == Close.SERVER_FIRST) {
          in.read();          // wait for the server's FIN
        }
      }
    }
    Thread.sleep(200);
    report("new connection, " + how.name().toLowerCase()
        .replace('_', ' '), t0, port);
  }
}
```

- **A new connection per request cost 4.1× as much as a kept-alive one**, on loopback. Across a network each new connection also adds the handshake's round trip.
- **TIME_WAIT was on the side that closed first**: 2,000 sockets on that side, none on the other.
- **`SO_LINGER(0)` left no TIME_WAIT.** With a zero linger time, Linux `tcp_close()` calls `tcp_disconnect()`, which sends a reset (RST) instead of a FIN; unsent data is discarded.
- **A server that never closed** left 2,000 sockets in CLOSE_WAIT, and the clients' ends in FIN_WAIT2 — the state `tcp_fin_timeout` limits for orphaned sockets. CLOSE_WAIT means the application has not called `close()`.
- **The JDK `HttpClient` keeps idle connections for 30 s** (`jdk.httpclient.keepalive.timeout`) and reuses them; a new client per request opens a new connection per request.

- **Count sockets by state** during a test with `ss -tan state time-wait` (or `close-wait`), or from `/proc/net/tcp` as the program on the right does.

counting sockets by state


```java
static long count(String state, int port, boolean local)
    throws Exception {
  String hex = String.format(":%04X", port);
  long n = 0;
  for (String table : new String[] {"tcp", "tcp6"}) {
    Path p = Path.of("/proc/net/" + table);
    if (!Files.exists(p)) {
      continue;                  // no IPv6 on this machine
    }
    n += Files.readAllLines(p).stream()
        .skip(1).map(l -> l.trim().split("\\s+"))
        .filter(f -> f[3].equals(state))
        .filter(f -> (local ? f[1] : f[2]).endsWith(hex))
        .count();
  }
  return n;
}
```

SOURCES OpenJDK 21 java.net.http module-info.java (jdk.httpclient.keepalive.timeout, default 30) · Linux ip-sysctl.rst · results: deepdive/logs/connections.txt

03 · TIMEOUTS

# What each timeout covers

An HTTP call has phases: connect, send, wait for the status line and headers, read the body. Each timeout setting bounds one phase; a phase without one waits indefinitely. The table gives the bound for each phase from the JDK 21 Javadoc and source; the next page measures them.




| PHASE | BOUNDED BY | IF UNSET |
|---|---|---|
| **TCP connect (handshake)** | `HttpClient.Builder.connectTimeout` ; `Socket.connect(addr, ms)` | the kernel's SYN retries |
| **request sent, waiting for the status line and headers** | `HttpRequest.Builder.timeout` (counts from the start, connect included) | forever |
| **reading the body** | nothing in `HttpClient` ; `Socket.setSoTimeout` bounds each `read()` , not the total | forever |
| **the whole call** | only what you add around it — e.g. `future.get(timeout)` | forever |

### What the request timeout covers

> "If the response is not received within the specified timeout then an HttpTimeoutException is thrown … The effect of not setting a timeout is the same as setting an infinite Duration, i.e. block forever." — `HttpRequest.Builder.timeout`

"The response" means the status line and headers: in JDK 21 the timer is cancelled when `exch.responseAsync()` completes ( `MultiExchange` , step "5. handle errors and cancel any timer set"). A body that arrives slowly is not covered.

## Defaults: what you get when you set nothing

| CLIENT | CONNECT | WAITING FOR DATA | SOURCE |
|---|---|---|---|
| **JDK `HttpClient`** | none | none ("block forever") | `HttpClient.Builder` , `HttpRequest.Builder` Javadoc |
| `HttpURLConnection` | 0 = infinite | 0 = infinite | `URLConnection` : "A timeout of zero is interpreted as an infinite timeout" |
| `java.net.Socket` | kernel's SYN retries | 0 = infinite, per `read()` | `Socket.setSoTimeout` Javadoc |
| **PostgreSQL JDBC** | `connectTimeout` 10 s | `socketTimeout` 0 = none | `PGProperty` |
| **HikariCP** | `connectionTimeout` 30 s — waiting for a pool connection | — | `HikariConfig` |
| **Lettuce (Redis)** | 10 s | command timeout 60 s | `SocketOptions` , `RedisURI.DEFAULT_TIMEOUT` |
| **Kafka producer** | — | `request.timeout.ms` 30 s | `ProducerConfig` |

SOURCES OpenJDK 21: java/net/http/HttpRequest.java, HttpClient.java (Javadoc) · jdk/internal/net/http/MultiExchange.java, ResponseTimerEvent.java · java/net/Socket.java, URLConnection.java (Javadoc) · pgjdbc PGProperty.java · HikariCP HikariConfig.java · Lettuce SocketOptions.java, RedisURI.java · Kafka ProducerConfig.java

03 · TIMEOUTS

# Measured: three unresponsive servers

Three local peers misbehave in different phases. The harness gives up after 5 s — the overall deadline the HTTP client does not provide. Packets to `192.0.2.1` (an address reserved for documentation, RFC 5737) are dropped with `iptables`, so the handshake never completes.

Timeouts.java — one call, two optional timeouts

```
static void call(String name, String hostPort,
    Duration connect, Duration request) throws Exception {
  var client = HttpClient.newBuilder();
  if (connect ≠ null) {
    client.connectTimeout(connect);
  }
  var req = HttpRequest.newBuilder(
      URI.create("http://" + hostPort + "/"));
  if (request ≠ null) {
    req.timeout(request);
  }
  long t0 = System.nanoTime();
  String result;
  try {
    var r = client.build().sendAsync(req.build(),
        BodyHandlers.ofString())
        .get(GIVE_UP_S, TimeUnit.SECONDS);
    result = "returned " + r.statusCode() + ", body "
        + r.body().length() + " bytes";
  } catch (TimeoutException e) {
    result = "still waiting after " + GIVE_UP_S + " s";
  } catch (Exception e) {
    result = e.getCause().getClass().getSimpleName();
  }
  print(name, t0, result);
}
```

| PEER | SETTING | WAITED | RESULT |
|---|---|---|---|
| **silent: never answers** | no timeouts | 5.3 s | still waiting after 5 s |
| **silent: never answers** | connectTimeout 1 s | 5.0 s | still waiting after 5 s |
| **silent: never answers** | request timeout 2 s | 2.0 s | `HttpTimeoutException` |
| **trickle: headers at once, body 1 byte / 0.5 s** | request timeout 2 s | 5.0 s | still waiting after 5 s |
| **dropped: packets dropped (no handshake)** | no timeouts | 5.0 s | still waiting after 5 s |
| **dropped: packets dropped (no handshake)** | request timeout 2 s | 2.0 s | `HttpConnectTimeoutException` |
| **dropped: packets dropped (no handshake)** | connectTimeout 1 s | 1.0 s | `HttpConnectTimeoutException` |
| **trickle: headers at once, body 1 byte / 0.5 s** | Socket soTimeout 1 s | 6.0 s | returned 70 bytes, no error |

Real output · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

## No timeout at all: the kernel decides

real output · connect() with no timeout

```
java.net.ConnectException: Connection timed out after 135.5 s
```

The kernel's SYN retransmission count, read from `ss` every second: 0 at 1 s · 1 at 2 s · 2 at 3 s · 3 at 4 s · 4 at 5 s · 5 at 6 s · 6 at 8 s · 7 at 12 s · 0 at 18 s · 1 at 19 s · 2 at 20 s · 3 at 21 s · 4 at 22 s · 5 at 23 s · 0 at 25 s · 6 at 26 s · 7 at 29 s · 8 at 32 s · 9 at 36 s · 10 at 68 s. With `tcp_syn_retries = 6` the kernel gave up after **136 s**.

### Connect timeouts

> "If the connection cannot be established within the given duration, then HttpClient::send throws an HttpConnectTimeoutException … If a new connection does not need to be established … this timeout duration has no effect."
> — `HttpClient.Builder.connectTimeout`

The request timer fires during connect too: `ResponseTimerEvent` throws `HttpConnectTimeoutException` when the connection is not yet connected, else `HttpTimeoutException`.

- **The trickling body beat the 2 s request timeout**: still waiting at 5 s. A raw socket with a 1 s read timeout read it all in 6 s without an error — every byte came within 1 s.
- **A connect timeout alone does not help** against a server that accepts and stays silent: still waiting at 5 s.
- **Set both, and a deadline:** `connectTimeout` for the handshake, `timeout` for the headers, and a bound on the whole call around it ( `future.get(…)` ) — in this run, the only bound that ended the trickling call.

SOURCES RFC 5737 (documentation addresses) · Linux ip-sysctl.rst (tcp_syn_retries) · results: deepdive/logs/timeouts.txt, syn.txt, syn-ss.txt

04 · POOLS AND LITTLE'S LAW

# Little's Law and pool size

Every pool is a queue in front of a resource. Little's Law ties the three numbers you can measure together, for any stable system, whatever the pattern of arrivals: **L = λ·W** — the average number of requests inside equals the rate they leave times the average time each spends inside.

### Three consequences

**1. A pool caps throughput:** with C connections each busy for S seconds, at most C/S requests per second leave. Our database (4 slots, ~10.2 ms per query as measured) tops out near 394 per second.

**2. Past the cap, more callers only add waiting:** 64 callers in a system that serves 394/s means W = 64 / 394 ≈ 162 ms each, however the queue is arranged.

**3. A bigger pool moves the queue** from the pool into the database: measured on the next page as time spent waiting inside the database.

### How big, then?

> "connections = ((core_count * 2) + effective_spindle_count)" — a starting point from the PostgreSQL project, quoted by HikariCP's "About Pool Sizing"

It is a starting value. The next page measures throughput and latency as the pool size changes, for a pool in front of a database and for a pool of CPU-bound threads.

## The experiment




PoolSize.java — one caller's loop

```
callers[i] = Thread.ofVirtual().start(() → {
  while (System.nanoTime() < end) {
    long t0 = System.nanoTime();
    inSystem.incrementAndGet();
    pool.acquireUninterruptibly();
    long t1 = System.nanoTime();
    db.acquireUninterruptibly();   // the database's queue
    dbWait.add(System.nanoTime() - t1);
    sleep(QUERY_MS);
    db.release();
    pool.release();
    inSystem.decrementAndGet();
    long t2 = System.nanoTime();
    done.add(new Done(t2 - start, t2 - t0));
  }
});
```

## Using it: three questions, answered from the measured numbers

| QUESTION | LITTLE'S LAW | WITH THIS CHAPTER'S DATABASE |
|---|---|---|
| **How many connections are busy at a target rate?** | L = λ · S (S = time a query holds a connection) | 197 queries/s × 10.2 ms = **2.0** connections busy on average — a pool of 4 has headroom |
| **What would a smaller pool deliver?** | $\lambda_{max}$ = C / S | C = 1: **99/s**, C = 2: **197/s** predicted; measured 98/s and 197/s |
| **How long will callers wait once it is saturated?** | W = L / $\lambda_{max}$ | 64 callers / 394/s = **162 ms**; measured mean with pool 4: 162.8 ms |

S is derived from the saturated rows only (4 slots ÷ 394 queries/s); the smaller pools are then a prediction, checked against their own rows. The law needs averages over a stable period; it says nothing about the tail — p99 needs the distribution (chapter 5).

SOURCES J. D. C. Little, "A Proof for the Queuing Formula: L = λW", Operations Research 9(3), 1961 · HikariCP wiki, "About Pool Sizing" · deepdive/src/.../pool/PoolSize.java

04 · POOLS AND LITTLE'S LAW


# Measured: database pool and CPU pool sizes


Each row ran for 3 s with 64 callers. λ, W and L were measured independently over the steady window 0.5–2.5 s: λ from completions, W from each request's time in the system, L by counting callers inside every millisecond.

| POOL | QUERIES/S (λ) | MEAN MS (W) | P99 MS | WAIT IN DB | L | λ·W |
|---|---|---|---|---|---|---|
| **1** | 98 | 648.2 | 656.5 | 0.0 ms | 64.0 | 63.2 |
| **2** | 197 | 325.9 | 326.7 | 0.0 ms | 64.0 | 64.0 |
| **4** | 392 | 162.8 | 163.2 | 0.0 ms | 64.0 | 63.8 |
| **8** | 394 | 162.5 | 164.0 | 10.1 ms | 64.0 | 64.0 |
| **16** | 394 | 162.4 | 162.8 | 30.3 ms | 64.0 | 64.0 |
| **64** | 394 | 162.6 | 163.0 | 148.6 ms | 64.0 | 64.1 |

Real output · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

- **Little's Law held in every row:** λ·W was within 1.2% of the measured L.
- **Throughput stopped at the database:** from pool size 4 up, 392–394 queries/s.
- **Bigger pools moved the queue into the database:** the wait inside it grew from 0 to 149 ms per query while the total time stayed the same.
- **Too small a pool** is visible the same way: at 1 and 2 connections the database sat idle while callers queued.








## The same question with a real resource: 4 CPU cores

| THREADS | TOTAL MS | TASKS/S | TASK P50 MS | TASK P99 MS |
|---|---|---|---|---|
| **1** | 2030 | 197 | 5.0 | 5.3 |
| **4** | 621 | 644 | 6.1 | 10.9 |
| **16** | 618 | 647 | 24.0 | 41.1 |
| **64** | 626 | 639 | 60.0 | 94.1 |

400 tasks of about 5 ms of arithmetic each · real output · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

- **Throughput is capped by cores:** 197 tasks/s on 1 thread, 644 on 4, 639 on 64 — no gain past the core count.
- **Each task got slower** as threads were added: p50 5.0 ms alone, 60.0 ms with 64 threads, because the cores were shared. A timeout set from a single-thread test would fail under load.
- **For I/O-bound work** the right size is set by the resource behind it (the database's slots), for CPU-bound work by the cores. Measure both throughput and per-task latency when you change it.








SOURCES results: deepdive/logs/pool.txt, cpupool.txt · deepdive/src/.../pool/PoolSize.java, CpuPool.java

05 · MEASURING LATENCY

# Coordinated omission

Most load tests send a request, wait for the answer, then send the next. When the server stalls, the test stalls with it — and stops sending the requests that real users would have kept sending. Those requests are never measured. This is **coordinated omission**, the term used in the wrk2 README and the HdrHistogram Javadoc: the tester slows down with the system it measures, and omits the requests that would have seen the stall.




(schematic: one box per request; the real run has 5,000)

### Two ways to get the truth

**Measure from the due time.** Keep a schedule — an *open* workload — and count each request's latency from when it should have been sent. wrk2 "measures response latency from the time the transmission *should* have occurred".

**Or correct afterwards.** HdrHistogram's `recordValueWithExpectedInterval` adds, for a value longer than the expected interval, "an additional series of decreasingly-smaller … value records" — the requests that would have queued behind it.

### Open and closed models in load tools

> "In a closed model, the execution time of each iteration dictates the number of iterations executed … In the open model, on the other hand, VUs arrive independently of iteration completion." — k6 documentation

k6: `constant-arrival-rate`, `ramping-arrival-rate` (open). Gatling: `constantUsersPerSec`, `rampUsersPerSec` (open) versus `constantConcurrentUsers` (closed). To reproduce users who arrive independently of each other's responses, use an open model.

### The arithmetic of this chapter's experiment

The program (constants read from `CoordinatedOmission.java`) sends one request every 2 ms for 10 s — 5,000 due — and the server stalls once, for 1000 ms. **Open loop:** 500 requests fall due during the stall, 10% of all; they wait from about 1000 ms down to 0, so everything from about p90 up is stall. **Closed loop:** the client waits with the server, so only one request sees the stall — 1 of 4,501 samples, 0.02%: it can only appear at p99.99 or the maximum. Chapter 5's second page shows exactly that.

## Percentiles, read correctly

Stats.java — the percentile every experiment here uses

```
/** Nearest-rank percentile, in milliseconds. */
public double ms(double percentile) {
  int rank =
      (int) Math.ceil(percentile / 100 * values.length);
  return values[Math.max(rank, 1) - 1] / 1e6;
}
```

**p99 of 5,000 samples is the 4,950th smallest** — the 50 slowest are above it. Nearest-rank never interpolates: the value reported was really measured.

| REQUESTS PER PAGE VIEW | CHANCE ONE OF THEM IS SLOWER THAN P99 |
|---|---|
| **1** | 1% |
| **10** | 10% |
| **50** | 39% |
| **100** | 63% |
| **200** | 87% |

The table is arithmetic, not a measurement: $1 - 0.99^n$. A page that makes 100 backend calls shows a p99 delay to most of its users — so for the calls behind a page, p99.9 and the maximum are the numbers that describe the user's experience.

SOURCES HdrHistogram AbstractHistogram.recordValueWithExpectedInterval (Javadoc) · wrk2 README (github.com/giltene/wrk2) · k6 docs, "Open and closed models" · Gatling docs, "Injection"


05 · MEASURING LATENCY

# Measured: closed loop, corrected, open loop

A service that answers in 1 ms, except once: from second 2 to second 3 of a 10-second run it stalls. The intended rate is one request every 2 ms (500 per second). The same stall, measured three ways:

| MEASUREMENT | SAMPLES | P50 MS | P90 MS | P99 MS | P99.9 MS | P99.99 MS | MAX MS |
|---|---|---|---|---|---|---|---|
| **closed loop — what most tests report** | 4501 | 1.07 | 1.07 | **1.09** | 1.11 | 1000.13 | 1000.13 |
| **closed loop, HdrHistogram-style correction** | 5000 | 1.07 | 1.40 | 900.13 | 992.13 | 1000.13 | 1000.13 |
| **open loop, latency from the due time** | 5000 | 1.07 | 534.49 | **954.14** | 996.54 | 1000.14 | 1000.14 |

Real output · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1




open loop: latency from the due time

```
/** Requests are due every 2 ms; latency from due time. */
static long[] openLoop() throws Exception {
  int total = (int) (RUN_NS / INTERVAL);
  long[] out = new long[total];
  start = System.nanoTime();
  for (int i = 0; i < total; i++) {
    long due = start + i * INTERVAL;
    while (System.nanoTime() < due) {
      Thread.onSpinWait();
    }
    serve();
    out[i] = System.nanoTime() - due;
  }
  return out;
}
```

the correction, as HdrHistogram does it

```
/**
 * HdrHistogram's recordValueWithExpectedInterval: for a value
 * longer than the interval, also record the requests that
 * would have been sent meanwhile: value - k·interval.
 */
static long[] corrected(long[] values) {
  long[] out = new long[values.length * 2];
  int n = 0;
  for (long v : values) {
    out = grow(out, n);
    out[n++] = v;
    for (long m = v - INTERVAL; m ≥ INTERVAL;
        m -= INTERVAL) {
      out = grow(out, n);
      out[n++] = m;
    }
  }
  return Arrays.copyOf(out, n);
}
```

- **The naive p99 was 1.09 ms**. Measured from the due times, p99 was **954.14 ms**: one request in ten was due during the stall, and more waited while the backlog drained.
- **The naive run recorded 4501 samples, not 5,000**: the missing 499 are the requests the client did not send while it waited. The max was right; the percentiles below it were not.
- **The correction recovered most of it** (p99 900.13 ms) from the closed-loop data alone, because the expected interval was known.
- **Report max and high percentiles, with the sample count.** A drop in the count during a test is a stall the percentiles cannot show.
- **Generate load on a schedule** (open model) and measure from the due time; if your tool cannot, correct with the known interval.
- **Percentiles cannot be averaged** across machines or intervals: merge the recorded values (or histograms), then read the percentile.


SOURCES results: deepdive/logs/co.txt · deepdive/src/.../latency/CoordinatedOmission.java · G. Tene, “How NOT to Measure Latency” (conference talk)

06 · JIT AND BENCHMARKS

# Tiered compilation and warm-up

HotSpot starts every method in the interpreter, counts calls and loop iterations, and compiles the hot ones — first quickly with C1, collecting a profile, then again with C2 using that profile. Measurements taken before the final version is installed include slower code: in the run below, the first two batches.

| LEVEL | CODE | USED FOR |
|---|---|---|
| **0** | interpreter | runs bytecode; profiles the method |
| **1** | C1, full optimisation, no profiling | trivial methods |
| **2** | C1 with invocation and back-edge counters | when C2 is busy |
| **3** | C1 with full profiling | the usual first compiled form |
| **4** | C2, profile-guided optimisation | the fast steady state |




On the runner's JVM: `Tier3InvocationThreshold` = 200, `Tier4InvocationThreshold` = 5000, `Tier4BackEdgeThreshold` = 40000, `CICompilerCount` = 3 — from `-XX:+PrintFlagsFinal`. They are not exact call counts: `compilationPolicy.hpp` compares the counters with each threshold multiplied by a scale factor that depends on the compile queues.

WarmUp.java — 30 batches of 100 calls

```
for (int batch = 1; batch ⩽ 30; batch++) {
  long t0 = System.nanoTime();
  for (int i = 0; i < 100; i++) {
    sink = sumOfSquares(DATA);
  }
  double us = (System.nanoTime() - t0) / 1e3 / 100;
  if (batch ⩽ 5 || batch % 5 == 0) {
    System.out.printf("%5d %10.2f%n", batch, us);
  }
}
```

-XX:+PrintCompilation · real output (ms · id · % OSR · level)

```
34   11 %     3       deep.jit.WarmUp::sumOfSquares @ 11 (42
bytes)
34   12       3       deep.jit.WarmUp::sumOfSquares (42
bytes)
35   13 %     4       deep.jit.WarmUp::sumOfSquares @ 11 (42
bytes)
43   11 %     3       deep.jit.WarmUp::sumOfSquares @ 11 (42
bytes)   made not entrant
72  127       4       deep.jit.WarmUp::sumOfSquares (42
bytes)
  2    75    12       3       deep.jit.WarmUp::sumOfSquares
(42 bytes)   made not entrant
```

## Reading a PrintCompilation line

| COLUMN | MEANING |
|---|---|
| **1** | milliseconds since the JVM started |
| **2** | compile id — the same id for every event of one compilation |
| **3** | flags: `%` on-stack replacement · `s` synchronized · `!` has exception handlers · `b` blocking compile · `n` native wrapper |
| **4** | tier, 0–4 (table above) |
| **5** | the method; `@ 11` after an OSR compile is the bytecode index of the loop it enters at; then the bytecode size |
| **…** | `made not entrant`: the method's entry is patched so new calls no longer enter this code (`nmethod::make_not_entrant`). In the output above it follows the level 4 versions. |

- **Interpreter only:** about 287 µs per call. **Compiled:** about 2.4 µs — 118× faster, the same code.
- **The first batches** ran at 40–43 µs while compilation was under way.
- **Exclude the warm-up from a measurement**, or report it separately: keep measuring until the values stop changing. JMH runs warm-up iterations (`-wi`) before measured ones and forks a fresh JVM (`-f`).
- **In a load test, plot latency over time** rather than one percentile for the whole run, so the warm-up is visible.

SOURCES OpenJDK 21 hotspot/share/compiler/compilationPolicy.hpp (the five levels), compileTask.cpp (the print format), code/nmethod.cpp (make_not_entrant) · -XX:+PrintCompilation, -XX:+PrintFlagsFinal on the runner · results: deepdive/logs/warmup*.txt, jit-flags.txt

06 · JIT AND BENCHMARKS

# Dead-code elimination and constant folding, measured with JMH

The JIT may remove code whose result is never used (dead-code elimination) and compute expressions on constants ahead of time (constant folding). A hand-written timing loop cannot tell; JMH can — compare with an empty baseline and hand results back.

DeadCodeBench.java (1/2)

```java
@State(Scope.Thread)
@BenchmarkMode(Mode.AverageTime)
@OutputTimeUnit(TimeUnit.NANOSECONDS)
public class DeadCodeBench {
  static final double CONSTANT = Math.PI;
  static final int[] FIXED = new int[1_000];
  double x = Math.PI;
  int[] data = new int[1_000];

  @Benchmark
  public void baseline() {
    // nothing: the cost of the harness itself
  }

  @Benchmark
  public void discarded() {
    Math.log(x);                    // result unused: dead code
  }

  @Benchmark
  public double returned() {
    return Math.log(x);           // JMH consumes the result
  }

  @Benchmark
  public void blackhole(Blackhole bh) {
    bh.consume(Math.log(x));
  }

  @Benchmark
  public double constant() {
    return Math.log(CONSTANT);    // foldable at compile time?
  }
```

DeadCodeBench.java (2/2)

```java
  @Benchmark
  public void sumDiscarded() {
    long s = 0;
    for (int v : data) {
      s += v;                       // the sum is never used
    }
  }

  @Benchmark
  public long sumReturned() {
    long s = 0;
    for (int v : data) {
      s += v;
    }
    return s;
  }

  @Benchmark
  public void mulDiscarded() {
    double r = x * x + 1;           // never used
  }

  @Benchmark
  public double mulReturned() {
    return x * x + 1;
  }

  @Benchmark
  public double mulConstant() {
    return CONSTANT * CONSTANT + 1;  // static final: foldable
  }
}
```

| BENCHMARK | NS/OP | ERROR (99.9%) | MINUS BASELINE |
|---|---|---|---|
| `baseline` | 0.376 | ± 0.029 | +0.000 |
| `blackhole` | 7.094 | ± 0.020 | +6.718 |
| `constant` | 7.014 | ± 0.025 | +6.638 |
| `discarded` | 7.100 | ± 0.032 | +6.724 |
| `mulConstant` | 0.627 | ± 0.011 | +0.251 |
| `mulDiscarded` | 0.371 | ± 0.004 | -0.005 |
| `mulReturned` | 0.633 | ± 0.025 | +0.257 |
| `returned` | 7.090 | ± 0.025 | +6.714 |
| `sumDiscarded` | 0.711 | ± 0.009 | +0.335 |
| `sumReturned` | 107.664 | ± 8.521 | +107.288 |

JMH 1.37 · 1 fork, 3 warm-up and 5 measured iterations of 1 s · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

- **The empty baseline costs 0.38 ns**: the harness itself. Anything at that level did no work.
- **Math.log, result unused**: 7.10 ns; returned 7.09 ns; into a Blackhole 7.09 ns — **not** removed: the unused call still ran.
- **Math.log of a static final constant**: 7.01 ns — **not** folded here: it cost the same as the call on a field.
- **A pure loop summing 1,000 ints**: 0.71 ns unused, 107.66 ns returned — the JIT **removed** the whole loop.
- `x * x + 1`: 0.37 ns unused, 0.63 ns returned, 0.63 ns on constants — the JIT **removed** the arithmetic.

- **Never trust a benchmark you have not seen fail:** add a baseline and a variant that should be eliminated.
- **Return results or use a Blackhole**, read inputs from `@State` fields, and let JMH fork a fresh JVM ( `-f` ).

SOURCES JMH 1.37 (org.openjdk.jmh): Blackhole, @State, -f/-wi/-i options · results: deepdive/logs/jmh.txt, jmh-full.txt

07 · GC PAUSES AND TAIL LATENCY


# GC pauses: G1 and generational ZGC

A garbage collector has to find live objects and make room. Some of that work needs every application thread stopped — a **pause**. G1, the default on a server-class machine, copies live objects during its young and mixed pauses. ZGC copies them concurrently; Oracle's JDK 21 GC tuning guide states "max pause times under a millisecond … Pause times are independent of heap size".

### The collectors, as of JDK 21–24

**G1**: default when the JVM sees at least 2 CPUs and about 1792 MB (chapter 9). Young and mixed collections copy live objects during pauses; marking of the old generation runs concurrently.

**Generational ZGC**: JEP 439, JDK 21, enabled with `-XX:+UseZGC -XX:+ZGenerational`; the default ZGC mode from JDK 23 (JEP 474); the only mode from JDK 24 (JEP 490). The tuning guide: "at the cost of some throughput".




## A G1 cycle, as it happened in the measured window

| PAUSE | COUNT | LONGEST MS | EVACUATION FAILED | WHAT IT DOES (JDK 21 G1 TUNING GUIDE) |
|---|---|---|---|---|
| **Young (Normal)** | 6 | 11.703 | 1 | copies live young objects; promotes survivors to old |
| **Young (Concurrent Start)** | 2 | 10.733 | 1 | a young collection that also starts concurrent marking |
| **Remark** | 1 | 0.740 | – | finishes marking, processes references, frees empty regions |
| **Cleanup** | 1 | 0.317 | – | decides whether mixed collections follow |
| **Young (Prepare Mixed)** | 1 | 9.786 | – | the last young-only collection before mixed ones |
| **Young (Mixed)** | 3 | 17.204 | 2 | young regions plus some old regions, copied |
| **Full** | 1 | 49.864 | – | fallback: compacts the whole heap in place, all threads stopped |

**Evacuation failure** (4 of these pauses): G1 could not find free regions to copy live objects into. The tuning guide: G1 then hopes marking and mixed collections catch up; "if this assumption doesn't hold, then G1 will eventually schedule a Full GC" — which is what happened here: one full, in-place compaction of the heap (1023M→405M).

## The workload

GcLatency.java — one operation due every 50 µs

```
for (int i = 0; i < total; i++) {
  long due = start + i * INTERVAL_NS;
  while (System.nanoTime() < due) {
    Thread.onSpinWait();
  }
  live[random.nextInt(LIVE)] = new byte[1024];
  sink = new byte[8 * 1024];
  latency[i] = System.nanoTime() - due;
}
```

A live set of 400,000 × 1 KB arrays (≈ 400 MB in a 1 GB heap) that keeps changing — every operation replaces one, so old objects keep dying — plus 8 KB of garbage per operation. One operation is due every 50 µs for 15 s; latency counts from the due time, the open-loop measurement from chapter 5. Pauses come from each JVM's own log (`-Xlog:gc,gc+phases`), from the moment measuring started.

SOURCES JEP 439 (JDK 21), JEP 474 (JDK 23), JEP 490 (JDK 24) · Java SE 21 HotSpot GC Tuning Guide: "Garbage-First (G1) Garbage Collector", "Available Collectors" · OpenJDK 21 gcConfig.cpp, os.cpp (default selection) · run: GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1, -Xms1g -Xmx1g

07 · GC PAUSES AND TAIL LATENCY

# Measured: latency and pauses under one workload

| COLLECTOR | OPERATIONS | P50 MS | P99 MS | P99.9 MS | MAX MS | PAUSES | LONGEST PAUSE MS | PAUSE TOTAL MS |
|---|---|---|---|---|---|---|---|---|
| **G1** | 300,000 | 0.001 | 1.191 | 36.867 | 51.556 | 15 | 49.864 | 159.5 |
| **ZGC** | 300,000 | 0.001 | 0.006 | 0.054 | 2.396 | 22 | 0.015 | 0.2 |

Real output and GC logs · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

- **The median was the same** (0.001 ms against 0.001 ms): most operations never meet a pause.
- **The tail was not:** G1's p99.9 was 36.9 ms and its worst operation waited 51.6 ms; with ZGC p99.9 was 0.054 ms and the worst 2.4 ms.
- **The GC logs agree:** G1's longest pause was 49.9 ms; ZGC paused 22 times, the longest 0.015 ms. ZGC's worst operation (2.4 ms) was therefore not caused by a GC pause; the GC log does not show what delayed it.
- **Measure throughput as well as latency:** the tuning guide describes ZGC's low pauses as coming "at the cost of some throughput".
- **Log GC during load tests** (`-Xlog:gc`, as here) and compare pause times with the slow requests' times.
- **Size the heap on purpose** (`-Xmx` or `MaxRAMPercentage`): the default is 25% of the memory the JVM sees, which in a container is the container's limit.

### Why p99 sits on the pauses

In an open loop, every operation that falls due during a pause waits for it. G1 was paused for 159.5 ms of the 15 s window: about 3,189 operations (one per 50 µs) were due while the application was stopped — 1.06% of all operations. Anything above that share is inside the tail: p99 is the slowest 1%, p99.9 the slowest 0.1%.

ZGC was paused for 0.22 ms in total — about 4 operations, 0.0015%: too few to reach p99.9.

| FULL GC PHASE | MS |
|---|---|
| **Mark live objects** | 14.894 |
| **Prepare compaction** | 4.996 |
| **Adjust pointers** | 6.021 |
| **Compact heap** | 21.584 |
| **Reset Metadata** | 0.783 |
| **pause** | **49.864** |

The full collection marked and compacted the whole heap while every application thread waited. Without it, G1's longest pause was 17.2 ms.

## Every pause in the measured window

G1: 15 pauses

```
  8.667 ms  Young (Normal)
  3.642 ms  Young (Normal)
  5.907 ms  Young (Normal)
 10.576 ms  Young (Normal)
 11.703 ms  Young (Normal)
 10.733 ms  Young (Concurrent Start)
  0.740 ms  Remark
  0.317 ms  Cleanup
  9.786 ms  Young (Prepare Mixed)
 17.204 ms  Young (Mixed)
 16.647 ms  Young (Mixed)
  9.290 ms  Young (Mixed)
  2.843 ms  Young (Concurrent Start)
  1.538 ms  Young (Normal)
 49.864 ms  Full
```

| ZGC: 22 PAUSES | COUNT | LONGEST MS |
|---|---|---|
| **Mark Start · minor** | 4 | 0.012 |
| **Mark End · minor** | 4 | 0.012 |
| **Relocate Start · minor** | 4 | 0.008 |
| **Mark Start · major, young** | 2 | 0.015 |
| **Mark End · major, young** | 2 | 0.012 |
| **Relocate Start · major, young** | 2 | 0.007 |
| **Mark End · major, old** | 2 | 0.013 |
| **Relocate Start · major, old** | 2 | 0.008 |

In this log, cycles tagged `y:` have only young-generation pauses; cycles tagged `Y:` also have `O:` (old) pauses and start with `Mark Start (Major)`. ZGC's driver runs minor collections of the young generation and major collections of both (JDK 21 `zDriver.cpp`).

SOURCES Java SE 21 HotSpot GC Tuning Guide (G1 cycle, evacuation failure) · OpenJDK 21 gc/z/zDriver.cpp (minor and major collections) · results: deepdive/logs/gc-G1.txt, gc-G1.log, gc-ZGC.txt, gc-ZGC.log

08 · VIRTUAL THREADS

# Virtual threads, carriers and pinning

A virtual thread (JEP 444, final in JDK 21) is a Java thread that is not tied to an OS thread. It runs *mounted* on a carrier — a platform thread of a small pool — and when it blocks on a socket, a sleep or a `java.util.concurrent` lock, it *unmounts* and the carrier runs another one.

### Carriers

The scheduler is a `ForkJoinPool` whose parallelism is `availableProcessors()` unless `jdk.virtualThreadScheduler.parallelism` says otherwise (JDK 21 `VirtualThread.java`). The runner had 4.

### Pinning (JDK 21–23)

Blocking inside `synchronized` keeps the virtual thread **pinned**: it cannot unmount, so it holds its carrier while it waits. JEP 491 (JDK 24) lets virtual threads unmount inside `synchronized`; the `jdk.tracePinnedThreads` property used here was removed with it.

VirtualThreads.java — the same wait, two locks

```
static void blockInSynchronized() {
  Object lock = new Object();             // one lock per task
  synchronized (lock) {
    sleep(100);                           // pins the carrier
  }
}

static void blockInLock() {
  var lock = new ReentrantLock();
  lock.lock();
  try {
    sleep(100);                           // unmounts
  } finally {
    lock.unlock();
  }
}
```

| RUN | WALL TIME |
|---|---|
| **10,000 tasks, 200 platform threads** | 5.03 s |
| **10,000 tasks, virtual thread each** | 0.18 s |
| **100 tasks, synchronized + sleep** | 2.50 s |
| **100 tasks, ReentrantLock + sleep** | 0.10 s |

Real output · JDK 21 · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

-Djdk.tracePinnedThreads=short · real output

```
VirtualThread[#10227]/runnable@ForkJoinPool-1-worker-3
reason:MONITOR

deep.vt.VirtualThreads.blockInSynchronized(VirtualThreads.ja
va:51) ⟸ monitors:1
VirtualThread[#10234]/runnable@ForkJoinPool-1-worker-3
reason:MONITOR
```

- **10,000 blocking tasks:** 5.03 s on 200 platform threads (10,000 / 200 × 0.1 s = 5 s), 0.18 s with a virtual thread each.
- **Pinned:** 100 tasks holding a monitor while sleeping took 2.50 s = 100 / 4 carriers × 0.1 s. With `ReentrantLock`: 0.10 s.
- **On JDK 21–23, replace `synchronized` around blocking calls** with `java.util.concurrent` locks, or upgrade: JDK 24 removes this kind of pinning.
- **CPU-bound work is still limited by the cores:** the carriers number `availableProcessors()` (4 here), as in chapter 4's CPU pool.

## What a blocking call does to the carrier, JDK 21

| THE VIRTUAL THREAD BLOCKS IN… | CARRIER | EVIDENCE |
|---|---|---|
| **`Thread.sleep`, `LockSupport.park`, `java.util.concurrent` locks and queues, socket I/O** | **released** — the virtual thread unmounts | measured: 0.10 s above; sockets: `NioSocketImpl.park` → `Poller.poll` |
| **`Object.wait()`, file I/O such as `FileInputStream.read`** | held, but **compensated**: the pool adds a carrier for the duration | JDK 21 `Object.wait` and `FileInputStream.read` call `Blocker.begin()` → `ForkJoinPool` compensated block |
| **any of the above inside `synchronized`** | **pinned**, not compensated: the carrier waits too | measured above: 2.50 s = 100 / 4 × 0.1 s; `VirtualThread.parkOnCarrierThread` |
| **a native method or foreign function on the stack** | **pinned** | `Continuation.Pinned.NATIVE` |

**Compensation has a ceiling:** `jdk.virtualThreadScheduler.maxPoolSize`, by default the larger of the parallelism and 256 (JDK 21 `VirtualThread.createDefaultScheduler`).

**Finding pins in production:** the JFR event `jdk.VirtualThreadPinned` is on in the default JFR settings, with a 20 ms threshold and a stack trace (JDK 21 `default.jfc`).

SOURCES JEP 444 (JDK 21), JEP 491 (JDK 24) · OpenJDK 21 java/lang/VirtualThread.java, Object.java, io/FileInputStream.java, jdk/internal/misc/Blocker.java, jdk/internal/vm/Continuation.java, sun/nio/ch/NioSocketImpl.java · jdk.jfr default.jfc · results: deepdive/logs/vt.txt

09 · CONTAINERS AND CPUS

# How the JVM reads cgroup limits

A container's limits are cgroup settings: a CPU **quota** per period (`cpu.max`) and a memory limit (`memory.max`). With `UseContainerSupport`, true by default in JDK 21 (`globals_linux.hpp`), the JVM reads both at start-up and sizes itself from them — the number of CPUs it reports, the heap, the garbage collector, and every thread pool sized from `availableProcessors()`.

### CPUs from the quota

`--cpus=N` writes `cpu.max` as *quota period*. HotSpot divides quota by period and **rounds up**, capped at the host's CPUs (JDK 21 `cgroupUtil_linux.cpp`: `ceilf(quota / period)`). `-XX:ActiveProcessorCount` overrides the result.

### Heap from the memory limit

Without `-Xmx`, the maximum heap is `MaxRAMPercentage` of the memory the JVM sees — **25** by default (`gc_globals.hpp`). `MinRAMPercentage` (50) is used instead only when memory is so small that half of it is below the default `MaxHeapSize` (`arguments.cpp`).

### The collector from both

G1 is chosen only on a "server-class machine": at least **2** active processors and at least **2 GB − 256 MB** of memory (`os.cpp` `is_server_class_machine`, with an extra check for hyper-threaded packages). Otherwise **Serial** — one thread, stop-the-world (`gcConfig.cpp`).

## Measured: the same JVM, different limits

| DOCKER RUN … | CPU.MAX | MEMORY.MAX | CPUS | MAX HEAP | HEAP / LIMIT | COMMON POOL | GC |
|---|---|---|---|---|---|---|---|
| `no limits` | max/100000 | max | **4** | 3,998 MB | – | 3 | **G1** |
| `--cpus=2 --memory=2g` | 200000/100000 | 2,048 MB | **2** | 512 MB | 25.0% | 1 | **G1** |
| `--cpus=1 --memory=1g` | 100000/100000 | 1,024 MB | **1** | 247 MB | 24.1% | 1 | **Serial** |
| `--cpus=0.5 --memory=512m` | 50000/100000 | 512 MB | **1** | 123 MB | 24.0% | 1 | **Serial** |
| `--cpus=1 --memory=1g -XX:ActiveProcessorCount=4` | 100000/100000 | 1,024 MB | **4** | 247 MB | 24.1% | 3 | **Serial** |
| `--cpus=1 --memory=1g -XX:MaxRAMPercentage=75` | 100000/100000 | 1,024 MB | **1** | 742 MB | 72.5% | 1 | **Serial** |

eclipse-temurin:21-jdk on GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1 · the program prints `/sys/fs/cgroup` and what the JVM decided · GC names: Copy + MarkSweepCompact is Serial

Resources.java

```
public static void main(String[] args) throws Exception {
  var rt = Runtime.getRuntime();
  String gcs = ManagementFactory.getGarbageCollectorMXBeans()
      .stream().map(b -> b.getName())
      .collect(Collectors.joining(", "));
  System.out.printf("cgroup cpu.max %-14s memory.max %-11s"
      + " | CPUs %d  max heap %4d MB  commonPool %d  GC %s%n",
      cgroup("cpu.max"), cgroup("memory.max"),
      rt.availableProcessors(), rt.maxMemory() / (1 << 20),
      ForkJoinPool.getCommonPoolParallelism(), gcs);
}
```

- **--cpus=0.5** is reported as **1** CPU: 0.5 rounded up. The JVM cannot express half a CPU; the kernel enforces it by throttling.
- **2 CPUs and 2 GB** crossed the server-class line: **G1**, heap 512 MB. **1 CPU and 1 GB** did not: **Serial**.
- **ActiveProcessorCount=4** made the JVM report 4 CPUs (common pool 3) — and it still chose **Serial**: 1 GB is below the memory line.
- **MaxRAMPercentage=75** raised the heap from 247 MB to 742 MB in the same 1 GB container.

### A quota is time, not cores

`--cpus=0.5` lets the container run for half of each scheduling period, then stops it until the next one. The JVM still reports 1 CPU and runs one GC thread. A multi-threaded burst can use the whole quota early in the period and then wait — throttling, visible in `cpu.stat` as `nr_throttled` and `throttled_usec`.

SOURCES OpenJDK 21: os/linux/cgroupUtil_linux.cpp, os/linux/globals_linux.hpp, runtime/os.cpp, gc/shared/gcConfig.cpp, gc/shared/gc_globals.hpp, runtime/arguments.cpp · results: deepdive/logs/containers.txt

09 · CONTAINERS AND CPUS

# Defaults sized from the CPU count; CPU throttling

These defaults are computed from `availableProcessors()`, which reported 1 for both `--cpus=1` and `--cpus=0.5` in the runs on the previous page.

| SIZED FROM THE CPU COUNT | DEFAULT | SOURCE | MEASURED (HOST / 2 / 1 CPU) |
|---|---|---|---|
| **`ForkJoinPool.commonPool()` — parallel streams, `CompletableFuture.*Async`** | CPUs − 1, at least 1 | JDK 21 `ForkJoinPool.java` | 3 / 1 / 1 |
| **virtual-thread carriers** | CPUs | JDK 21 `VirtualThread.java` | chapter 8 |
| **G1/Parallel GC worker threads ( `ParallelGCThreads` )** | CPUs up to 8, then 8 + 5/8 of the rest | JDK 21 `workerPolicy.cpp` | – |
| **Netty event-loop threads** | 2 × CPUs | Netty 4.1 `MultithreadEventLoopGroup` | – |
| **the garbage collector itself** | Serial below 2 CPUs or 1792 MB | `os.cpp` , `gcConfig.cpp` | Serial at 1 CPU |

### The heap is not the whole process

`memory.max` is a "memory usage hard limit" for the whole cgroup; if usage reaches it and cannot be reduced, "the OOM killer is invoked" (cgroup-v2.rst). The JVM uses memory outside the heap too: Native Memory Tracking reports it under Class, Thread Stack, Code, GC, Compiler, Internal, Other and more (JDK 21 `allocation.hpp` ). Raising `MaxRAMPercentage` to 75 (measured above: 742 MB of 1,024 MB) leaves the rest for that memory; measure it with `-XX:NativeMemoryTracking=summary` and `jcmd <pid> VM.native_memory` .

- **Run performance tests with the production limits** — the same `--cpus` and `--memory` . A laptop or an unlimited runner chooses a different collector, a different heap and different pool sizes.
- **Print what the JVM decided:** `-Xlog:gc` prints the collector at start-up ("Using G1" in chapter 7's log); `-XX:+PrintFlagsFinal` marks values the JVM chose itself `{ergonomic}` .
- **Give a JVM service at least 2 CPUs and 2 GB**, or choose the collector yourself ( `-XX:+UseG1GC` ) — otherwise a small pod gets Serial.
- **Set the heap on purpose** — `-Xmx` , or `MaxRAMPercentage` for a heap that follows the limit.

## Measured: throttling

| DOCKER RUN … | BUSY THREADS | LATE P50 MS | LATE P99 MS | LATE MAX MS | PERIODS | THROTTLED PERIODS |
|---|---|---|---|---|---|---|
| `no limit` | 0 | 0.1 | 0.1 | **0.3** | – | – |
| `--cpus=0.5` | 0 | 0.1 | 0.1 | **0.2** | 29 | 0 |
| `no limit` | 3 | 0.1 | 0.1 | **0.5** | – | – |
| `--cpus=2` | 3 | 0.1 | 34.2 | **35.6** | 44 | 44 |
| `--cpus=0.5` | 3 | 0.1 | 75.1 | **89.9** | 38 | 38 |

Throttle.java: busy threads use the quota while a timer thread sleeps 5 ms, 600 times, and records how late it wakes; periods and throttling from the container's `cpu.stat` · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

- **--cpus=0.5 with 3 busy threads:** 38 of 38 periods throttled, and a 5 ms sleep woke up to **90 ms** late — against 0.5 ms with no limit.
- **Why the timer thread was late:** the busy threads used the period's quota, and `cpu.max` allows the cgroup "up to $MAX in each $PERIOD" (cgroup-v2.rst), so the timer thread could not run until the next period began.

SOURCES OpenJDK 21: java/util/concurrent/ForkJoinPool.java, java/lang/VirtualThread.java, gc/shared/workerPolicy.cpp, memory/allocation.hpp and services/nmtDCmd.hpp (Native Memory Tracking) · Netty 4.1 MultithreadEventLoopGroup.java · Linux 6.17 Documentation/admin-guide/cgroup-v2.rst (cpu.max, cpu.stat, memory.max) · results: deepdive/logs/containers.txt, throttle.txt

10 · THE JAVA MEMORY MODEL

# Data races, happens-before and store buffering

Without synchronisation, Java promises much less than the source code suggests. The compiler and the CPU may reorder and cache memory accesses as long as a single thread cannot tell. The Java Memory Model (JLS chapter 17) says exactly when another thread is guaranteed to see a write — and that guarantee is the *happens-before* order.

### Data race (JLS §17.4.5)

Two accesses to the same variable **conflict** if at least one is a write. A program has a **data race** when two conflicting accesses are not ordered by happens-before.

**The guarantee** (§17.4.3): "If a program has no data races, then all executions of the program will appear to be sequentially consistent." With a race, the JMM allows results no interleaving of the source lines can produce.

### Happens-before, JLS §17.4.5 (quoted)

- An unlock on a monitor *happens-before* every subsequent lock on that monitor.
- A write to a `volatile` field *happens-before* every subsequent read of that field.
- A call to `start()` on a thread *happens-before* any actions in the started thread.
- All actions in a thread *happen-before* any other thread successfully returns from a `join()` on that thread.

Plus program order within a thread, and transitivity. The `java.util.concurrent` package documentation ("Memory Consistency Properties") extends them to concurrent collections, executors, futures, locks and synchronizers.

## Measured with jcstress: store buffering

StoreBufferingTest.java (outcomes declared with @Outcome)

```
@State
public class StoreBufferingTest {
  int x;
  int y;

  @Actor
  public void first(II_Result r) {
    x = 1;
    r.r1 = y;
  }

  @Actor
  public void second(II_Result r) {
    y = 1;
    r.r2 = x;
  }
}
```

**Plain fields** — every interleaving of the four lines gives at least one 1. Yet:

| RESULT | SAMPLES | SHARE | EXPECTED | MEANING |
|---|---|---|---|---|
| `0, 0` | 393,230,568 | 29.23% | Interesting | both read before either write was visible |
| `0, 1` | 477,617,586 | 35.50% | Acceptable | some interleaving of the four steps |
| `1, 0` | 474,466,654 | 35.27% | Acceptable | some interleaving of the four steps |
| `1, 1` | 21,020 | <0.01% | Acceptable | some interleaving of the four steps |

**The same with `volatile int x, y`** — `0, 0` declared forbidden:

| RESULT | SAMPLES | SHARE | EXPECTED | MEANING |
|---|---|---|---|---|
| `0, 0` | 0 | 0.00% | Forbidden | both read before either write was visible |
| `0, 1` | 433,330,372 | 49.01% | Acceptable | some interleaving of the four steps |
| `1, 0` | 425,637,138 | 48.14% | Acceptable | some interleaving of the four steps |
| `1, 1` | 25,271,358 | 2.86% | Acceptable | some interleaving of the four steps |

- **393,230,568 of 1,345,335,828 plain runs (29.23%) ended 0, 0**: both threads read before either write was visible. No interleaving of the source allows that; the JMM does, because the program has a data race.
- **With volatile: 0 of 884,238,868**. Volatile reads and writes are synchronisation actions, totally ordered (§17.4.4), so one write must come first and the other thread's read must see it.
- **The result does not say whether the compiler or the CPU reordered the accesses.** The log shows jcstress ran the actors interpreted, with C1 and with C2, and with C2's stress options ( `-XX:+StressLCM` , `-XX:+StressGCM` ...); the JMM allows 0, 0 for this racy program in every case.
- **The machine:** 4 CPUs (AMD EPYC 7763 64-Core Processor); jcstress pins each actor thread to its own CPU.

SOURCES JLS SE 21 §17.4.2–17.4.5 · jcstress 0.16 (org.openjdk.jcstress) · OpenJDK 21 java/util/concurrent/package-info.java · results: ci-logs-ops logs/jcstress.log

10 · THE JAVA MEMORY MODEL

# Visibility and lost updates

Happens-before is also about *whether* a write is seen at all. A thread spinning on a plain field has no happens-before edge with the thread that sets it, and JLS §17.3 allows the loop to keep a value it read once: “The compiler is free to read the field `this.done` just once, and reuse the cached value in each execution of the loop.”

StaleFlag.java — the loop runs 1 s, then the flag is set

```
static String stops(boolean useVolatile) throws Exception {
  Thread spinner = new Thread(() -> {
    if (useVolatile) {
      while (!marked) {
        // spin
      }
    } else {
      while (!plain) {
        // spin
      }
    }
  });
  spinner.setDaemon(true);
  spinner.start();
  Thread.sleep(1_000);      // let the JIT compile the loop
  if (useVolatile) {
    marked = true;
  } else {
    plain = true;
  }
  spinner.join(3_000);
  return spinner.isAlive()
      ? "still spinning 3 s after the flag was set"
      : "stopped";
}
```

real output · 5 runs in CI

```
plain field:    still spinning 3 s after the flag was set
volatile field: stopped
plain field:    still spinning 3 s after the flag was set
volatile field: stopped
plain field:    still spinning 3 s after the flag was set
volatile field: stopped
plain field:    still spinning 3 s after the flag was set
volatile field: stopped
plain field:    still spinning 3 s after the flag was set
volatile field: stopped
```

- **Plain field: 5 of 5 runs** still spinning 3 s after the flag was set, as §17.3 allows.
- **Volatile: 5 of 5** stopped. A write to a volatile field happens-before every subsequent read of that field (§17.4.5).

## The same question, asked by jcstress

SpinTest.java — Mode.Termination

```
@JCStressTest(Mode.Termination)
@Outcome(id = "TERMINATED", expect = ACCEPTABLE,
    desc = "saw it")
@Outcome(id = "STALE", expect = ACCEPTABLE_INTERESTING,
    desc = "spins forever")
@State
public class SpinTest {
  boolean ready;

  @Actor
  public void spin() {
    while (!ready) {
      // wait
    }
  }

  @Signal
  public void signal() {
    ready = true;
  }
}
```

| RESULT | SAMPLES | SHARE | EXPECTED | MEANING |
|---|---|---|---|---|
| `STALE` | 2 | 0.12% | Interesting | spins forever |
| `TERMINATED` | 1,682 | 99.88% | Acceptable | saw it |

With `volatile boolean ready`: `STALE` 0 of 3,279, declared forbidden.

- **Only 2 of 1,684 runs (0.12%) got stuck.** StaleFlag, which let the loop run for 1 s before setting the flag, got stuck in every run.
- **Lost updates**, from the guide’s own counter tests: `count++` on a plain field lost an update in 18.66% of 1,785,768,468 runs; `AtomicInteger` in 0 of 842,674,708.

- **Share mutable state through something that creates the edge:** `volatile`, an `Atomic*`, a lock, a concurrent collection, a future’s result, `Thread.start` / `join`.
- **Publish immutable objects through final fields** (JLS §17.5): a correctly constructed object’s final fields are seen initialised by every thread.
- **The bad outcomes were rare in jcstress** (0.12% stuck spins, 18.66% lost updates): a test that runs the code once will usually pass. jcstress runs it millions of times across compilation modes.

SOURCES JLS SE 21 §17.3, §17.4, §17.5 · jcstress 0.16: Mode.Termination, @Signal · results: deepdive/logs/staleflag.txt; ci-logs-ops logs/jcstress.log

11 · KAFKA

# Producer batching: linger.ms and batch.size

A Kafka producer does not send each record on its own. It appends records to a batch per partition and sends a batch when it is full or when it has waited `linger.ms`. The Kafka 4.3.1 client's documentation for `linger.ms` compares this to chapter 1:

### `linger.ms`, from `ProducerConfig.java`

> "This can be thought of as analogous to Nagle's algorithm in TCP. … once we get `batch.size` worth of records for a partition it will be sent immediately regardless of this setting … The default changed from 0 to 5 in Apache Kafka 4.0 as the efficiency gains from larger batches typically result in similar or lower producer latency despite the increased linger."

| SETTING | DEFAULT (4.3.1) | MEANING |
|---|---|---|
| `linger.ms` | 5 | how long a batch may wait for more records |
| `batch.size` | 16384 bytes | a batch this full is sent at once |
| `acks` | all | the leader waits for the in-sync replicas |
| `enable.idempotence` | true | "exactly one copy of each message is written" |
| `fetch.min.bytes` | 1 | the broker answers a fetch as soon as 1 byte is available |
| `fetch.max.wait.ms` | 500 | or after this long, if less data is available |
| `max.poll.records` | 500 | most records returned by one `poll()` |
| `max.poll.interval.ms` | 300000 | longest gap between `poll()` calls |

Defaults from the `define(…)` calls in `ProducerConfig.java` and `ConsumerConfig.java` at tag 4.3.1. `acks` is not measured here: with one broker the leader is the only in-sync replica, so `acks=all` and `acks=1` wait for the same write.

## Measured: the same producer at two rates and three linger times

| RATE | LINGER.MS | P50 MS | P99 MS | MAX MS | REQUESTS | RECORDS / REQUEST |
|---|---|---|---|---|---|---|
| **20/s** | 0 | 3.67 | 6.59 | 10.20 | 106 | 1.0 |
| **20/s** | 5 | 7.10 | 9.82 | 10.06 | 105 | 1.0 |
| **20/s** | 50 | 4.37 | 53.93 | 54.37 | 55 | 2.0 |
| **2,000/s** | 0 | 1.97 | 17.67 | 38.12 | 7,061 | 1.4 |
| **2,000/s** | 5 | 3.32 | 7.38 | 11.19 | 961 | 10.5 |
| **2,000/s** | 50 | 26.00 | 50.49 | 51.94 | 105 | 99.0 |

KafkaLatency.java · 5 s per row, 100-byte records, one partition · latency from each record's due time to its acknowledgement · requests and records per request from the producer's own metrics (`request-total`, `records-per-request-avg`) · broker 4.3.1 in Docker · GitHub Actions · Linux 6.17.0-1022-azure · 4 CPUs · JDK 21.0.12.1

- **At 2,000 records/s**, `linger.ms=0` sent 7,061 requests (1.4 records each) and had a p99 of 17.7 ms. `linger.ms=5` sent 961 requests (10.5 records each) with a p99 of 7.4 ms — fewer requests and a lower tail, as the source's note on the 4.0 default change says.
- **At 2,000 records/s with `linger.ms=50`**: 99 records per request and a p50 of 26.0 ms — records waited for the batch.
- **At 20 records/s** (one every 50 ms) `linger.ms=50` put 2 records in each request: p50 4.4 ms, p90 53.1 ms. The first record of each pair waited for the linger; with `linger.ms=0` the p90 was 4.5 ms.

KafkaLatency.java — records sent on a schedule

```
for (int i = 0; i < n; i++) {
  long due = start + i * interval;
  while (System.nanoTime() < due) {
    Thread.onSpinWait();
  }
  final int k = i;
  prod.send(new ProducerRecord<>(t, new byte[100]),
      (md, e) -> {
        lat[k] = System.nanoTime() - due;
        done.countDown();
      });
}
```

SOURCES Apache Kafka 4.3.1: clients/.../producer/ProducerConfig.java (linger.ms, batch.size, acks, enable.idempotence) · results: deepdive/logs/kafka-producer.txt, kafka-broker.txt

11 · KAFKA

# Consumer fetching, partitions and max.poll.interval.ms

### `fetch.min.bytes` and `fetch.max.wait.ms`

> "If insufficient data is available the request will wait for that much data to accumulate before answering the request." `fetch.max.wait.ms` : "The maximum amount of time the server will block before answering the fetch request" when there is not enough data for `fetch.min.bytes` . — `ConsumerConfig.java`

## Measured: one record every 100 ms

| CONSUMER | P50 MS | P90 MS | P99 MS | MAX MS |
|---|---|---|---|---|
| **fetch.min.bytes 1 (default)** | 3.8 | 4.2 | 56.8 | 56.8 |
| **fetch.min.bytes 1000000, max.wait 500** | 210.2 | 412.1 | 416.9 | 416.9 |

- **With the default `fetch.min.bytes=1`** the broker answered as soon as a record arrived: p50 3.8 ms from send to `poll()` .
- **With `fetch.min.bytes=1000000`** one record never filled a fetch, so the broker held each fetch until `fetch.max.wait.ms` : p50 210 ms, max 417 ms. A record that arrived early in a waiting fetch waited longest.

## Measured: 4 consumers, 2 partitions

| CONSUMER | PARTITIONS ASSIGNED |
|---|---|
| **c0** | 1 |
| **c1** | 1 |
| **c2** | 0 |
| **c3** | 0 |

The `KafkaConsumer` Javadoc: the group divides the partitions "so that each partition is assigned to exactly one consumer in the group". Here 2 of the 4 consumers had nothing to read.

## Measured: processing longer than `max.poll.interval.ms`

real output

```
max.poll.interval.ms 3000: polled 1 record, processing for 6 s
commitSync: CommitFailedException: Offset commit cannot be
completed since the consumer is not part of an active group for
auto partition assignment; it is likely that the consumer was
kicked out of the group.
```

The client documentation: "If poll() is not called before expiration of this timeout, then the consumer is considered failed and the group will rebalance in order to reassign the partitions to another member." The 6 s of processing exceeded the 3 s set here; the commit was then refused. The default is 300,000 ms.

KafkaLatency.java — slow processing

```
static void pollInterval() throws Exception {
  String t = topic(1);
  try (var prod = producer(0)) {
    prod.send(new ProducerRecord<>(t, new byte[100])).get();
  }
  try (var cons = consumer(Map.of("group.id", "slow-" + t,
      "auto.offset.reset", "earliest",
      "enable.auto.commit", false,
      "max.poll.interval.ms", 3000))) {
    cons.subscribe(Set.of(t));
    int got = 0;
    while (got == 0) {
      got = cons.poll(Duration.ofSeconds(1)).count();
    }
    System.out.println("max.poll.interval.ms 3000: polled "
        + got + " record, processing for 6 s");
    Thread.sleep(6_000);                    // "processing"
    try {
      cons.commitSync();
      System.out.println("commitSync: committed");
    } catch (Exception e) {
      System.out.println("commitSync: "
          + e.getClass().getSimpleName() + ": "
          + e.getMessage().lines().findFirst().orElse(""));
    }
  }
}
```

- **End-to-end latency includes the consumer's fetch wait.** Raising `fetch.min.bytes` trades latency for fewer fetch responses; the wait is bounded by `fetch.max.wait.ms` .
- **The number of partitions caps the number of consumers that do work** in one group.
- **Keep the time to process one `poll()` 's records below `max.poll.interval.ms`** , by processing faster or lowering `max.poll.records` (default 500); otherwise the consumer leaves the group and its commit fails.

SOURCES Apache Kafka 4.3.1: clients/.../consumer/ConsumerConfig.java, KafkaConsumer.java (Javadoc), CommonClientConfigs.java (MAX_POLL_INTERVAL_MS_DOC) · results: deepdive/logs/kafka-fetch.txt, kafka-partitions.txt, kafka-pollinterval.txt

BACK MATTER

# Sources

Everything this book relies on for how things work. Measured results come from the logs listed last.

## Standards and specifications

- RFC 9293 — Transmission Control Protocol (2022): Nagle (§3.7.4), delayed ACK (§3.8.6.3), TIME-WAIT and MSL (§3.4.2–3.4.3), states (§3.3.2)
- RFC 896 — J. Nagle, Congestion Control in IP/TCP Internetworks (1984)
- RFC 5737 — IPv4 address blocks reserved for documentation (192.0.2.0/24)
- JLS SE 21, chapter 17 — threads and locks; the memory model (§17.3–17.5)
- JEP 439 Generational ZGC · JEP 444 Virtual threads · JEP 474 ZGC generational by default · JEP 490 non-generational ZGC removed · JEP 491 synchronized without pinning

## Linux 6.17 source and documentation

- include/net/tcp.h — TCP_DELACK_MIN/MAX, TCP_MAX_QUICKACKS, TCP_TIMEWAIT_LEN
- net/ipv4/tcp_input.c (quick ACKs, pingpong mode) · net/ipv4/tcp_output.c (tcp_event_data_sent) · net/ipv4/tcp.c (zero-linger close)
- Documentation/networking/ip-sysctl.rst — tcp_pingpong_thresh, tcp_tw_reuse, tcp_fin_timeout, tcp_syn_retries, ip_local_port_range
- Documentation/admin-guide/cgroup-v2.rst — cpu.max, cpu.stat, memory.max

## OpenJDK 21 source

- java.net.http: PlainHttpConnection, MultiExchange, ResponseTimerEvent, module-info (keep-alive 30 s)
- java.base: StandardSocketOptions, Socket, URLConnection, VirtualThread, Object, FileInputStream, Blocker, ForkJoinPool, java.util.concurrent package-info, Continuation, NioSocketImpl
- jdk.httpserver ServerConfig · jdk.net ExtendedSocketOptions · jdk.jfr default.jfc
- HotSpot: compilationPolicy.hpp, compileTask.cpp, os.cpp, gcConfig.cpp, gc_globals.hpp, arguments.cpp, workerPolicy.cpp, cgroupUtil_linux.cpp, globals_linux.hpp, nmethod.cpp, zDriver.cpp, allocation.hpp, nmtDCmd.hpp

## Documentation

- Java SE 21 HotSpot GC Tuning Guide — the G1 cycle, evacuation failure, full GC; "Available Collectors"
- HttpClient.Builder and HttpRequest.Builder Javadoc — connect and request timeouts
- HikariCP wiki, "About Pool Sizing" · J. D. C. Little, "A Proof for the Queuing Formula: L = λW", Operations Research 9(3), 1961

## Apache Kafka 4.3.1 client source

- ProducerConfig, ConsumerConfig, KafkaConsumer, CommonClientConfigs — defaults and documentation of every setting the chapter uses

## Libraries (source, default branch or named version)

- Tomcat SocketProperties · Jetty 12.0 ServerConnector · Netty 4.1 DefaultSocketChannelConfig, MultithreadEventLoopGroup
- pgjdbc PGProperty · HikariCP HikariConfig · Lettuce SocketOptions, RedisURI · Kafka Selector, ProducerConfig

## Tools

- JMH 1.37 · jcstress 0.16 · HdrHistogram (recordValueWithExpectedInterval) · wrk2 · k6, open and closed models · Gatling, injection profiles

## The evidence in this repository

- Experiments: `deepdive/src/main/java/deep/` and `concurrency/src/main/java/shop/` (jcstress) · runner script `deepdive/run.sh`
- Logs: branch `ci-logs-deepdive` (`logs/`) and `ci-logs-ops` (`logs/jcstress.log`), rewritten on every push to main

FIND ANYTHING

# Index A–Z


**A**

acks 23
ActiveProcessorCount 19
availableProcessors() 19, 20

**B**

batch.size 23
Blackhole 15

**C**

Carrier threads 18
cgroups 19, 20
CLOSE_WAIT 06, 07
CommitFailedException 24
Connect timeout 08, 09
Constant folding 15
Consumer groups and partitions 24
Coordinated omission 12, 13
CPU throttling 19, 20
CPU-bound pools 11
--cpus / cpu.max 19, 20

**D**

Data race 21
Dead-code elimination 15
Delayed ACK 04, 05
Deoptimisation 14

**E**

enable.idempotence 23
Ephemeral ports 06
Evacuation failure 16, 17

**F**

fetch.min.bytes / fetch.max.wait.ms 24
FIN_WAIT2 06, 07
Final fields 22
ForkJoinPool.commonPool 20
Full GC 16, 17

**G**

G1 16, 17
GC logging 16, 17

**H**

Happens-before 21, 22
HdrHistogram 12
HikariCP 10, 08

**J**

Java Memory Model 21, 22
jcstress 21, 22
jdk.VirtualThreadPinned (JFR) 18
JIT tiers (C1, C2) 14
JMH 15

**K**

Kafka producer batching 23
Keep-alive (HTTP) 06, 07

**L**

linger.ms 23
Little's Law 10, 11
Lost update 22

**M**

max.poll.interval.ms 24
MaxRAMPercentage 19, 20

**N**

Nagle's algorithm 04, 05
Native memory 20

**O**

On-stack replacement 14
Open vs closed loop 12, 13

**P**

Percentiles 12, 13
Pingpong mode (Linux) 04
Pinning 18
Pool sizing 10, 11
PrintCompilation 14

**R**

Rebalance (Kafka) 24
ReentrantLock 18
Request timeout (HttpClient) 08, 09

**S**

Serial GC 19
Server-class machine 19, 16
SO_LINGER / RST 07
SO_TIMEOUT / read timeout 08, 09
Store buffering 21
SYN retries 09
synchronized 18, 21

**T**

Tail latency 17, 13
TCP_NODELAY 04, 05
TCP_QUICKACK 04, 05
tcp_tw_reuse 06
tcpdump 04, 06
Three-way handshake 06
TIME_WAIT 06, 07
Timeout defaults 08

**V**

Virtual threads 18
Visibility 22
volatile 21, 22

**W**

Warm-up 14
wrk2 / k6 / Gatling 12

**Z**

ZGC (generational) 16, 17


## Three ways in

### A request is slow

Nagle **p.04**, connection reuse **p.07**, pools **p.10**, GC pauses **p.17**, CPU throttling **p.20**.

### A request hangs

Timeouts and their defaults **p.08**, the three broken peers **p.09**, pinned virtual threads **p.18**, a loop that never sees a flag **p.22**.

### The numbers look wrong

Coordinated omission **p.12**, warm-up **p.14**, JMH and dead code **p.15**, production limits in tests **p.19**.