



OSLC Systems Modeling Language Version 2.0. Part 1: Specification

Project Specification Draft 01 25 April 2024

This stage:

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-spec.html> (Authoritative)
<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-spec.pdf>

Previous stage:

N/A

Latest stage:

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-spec.html> (Authoritative)
<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-spec.pdf>

Latest version:

<https://open-services.net/spec/sysml/latest>

Latest editor's draft:

<https://open-services.net/spec/sysml/latest-draft>

Open Project:

[OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#)

Project Chairs:

Jim Amsden (jamsden@us.ibm.com), [IBM](#)
Andrii Berezhovskyi (andriib@kth.se), [KTH](#)

Editor:

Jim Amsden (jamsden@us.ibm.com), [IBM](#)

Additional components:

This specification is one component of a Work Product that also includes:

- OSLC SysML Version 2.0. Part 1: Specification (*this document*). [sysml-spec.html](#)
- OSLC SysML Version 2.0. Part 2: Vocabulary. [sysml-vocab.html](#)
- OSLC SysML Version 2.0. Part 3: Constraints. [sysml-shapes.html](#)
- OSLC SysML Version 2.0. Part 4: Machine Readable Vocabulary Terms. [sysml-vocab.ttl](#)
- OSLC SysML Version 2.0. Part 5: Machine Readable Constraints. [sysml-shapes.ttl](#)

Related work:

This specification is related to:

- *OMG Systems Modeling Language*. <https://www.omg.org/spec/SysML/>
- *Systems Modeling Application Programming Interface (API) and Services*. <https://www.omg.org/spec/SystemsModelingAPI/1.0/Beta1/PDF>

RDF Namespaces:

<http://open-services.net/ns/sysmlv2#>

Abstract:

This specification defines the OSLC SysML domain, a RESTful web services interface for the SysML v2 resources and relationships between those and related resources such as product change requests, activities, tasks, requirements or test cases. To support these scenarios, this specification defines a set of HTTP-based RESTful interfaces in terms of HTTP methods: GET, POST, PUT and DELETE, as well as HTTP response codes, content type handling and resource formats.

Status:

This document was last revised or approved by the [OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#) on the above date. The level of approval is also listed above. Check the “Latest stage” location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Open Project are listed at <https://open-services.net/about/>.

Comments on this work can be provided by opening issues in the project repository or by sending email to the project’s public comment list oslc-op@lists.oasis-open-projects.org.

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this specification the following citation format should be used:

[OSLC-SYSML-2.0-Part1]

OSLC Systems Modeling Language Version 2.0. Part 1: Specification. Edited by Jim Amsden. 25 April 2024. OASIS Project Specification Draft 01. <https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-spec.html>. Latest stage: <https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-spec.html>.

Notices

Copyright © OASIS Open 2024. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This specification is published under the [Attribution 4.0 International \(CC BY 4.0\)](#). Portions of this specification are also provided under the [Apache License 2.0](#).

All contributions made to this project have been made under the [OASIS Contributor License Agreement \(CLA\)](#).

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the [Open Projects IPR Statements page](#).

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Open Project or OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Project Specification or OASIS Standard, to notify the OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Open Project that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Open Project Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.

Table of Contents

- 1. [Introduction](#)
 - 1.1 [Terminology](#)
 - 1.2 [References](#)
 - 1.2.1 [Normative references](#)
 - 1.2.2 [Informative references](#)
 - 1.3 [Typographical Conventions and Use of RFC Terms](#)
- 2. [Base Requirements](#)
 - 2.1 [Base Compliance](#)
 - 2.2 [Specification Versioning](#)
 - 2.3 [Namespaces](#)
 - 2.4 [Resource Formats](#)
 - 2.5 [Resource Operations](#)
 - 2.6 [Authentication](#)
 - 2.7 [Error Responses](#)
 - 2.8 [Pagination](#)
 - 2.9 [Requesting and Updating Properties](#)
 - 2.9.1 [Requesting a Subset of Properties](#)
 - 2.9.2 [Updating a Subset of Properties](#)
 - 2.9.3 [Updating Multi-Valued Properties](#)
- 3. [Vocabulary Terms and Constraints](#)
- 4. [Vocabulary Subsets](#)
- 5. [SysML Server Capabilities](#)
 - 5.1 [Resource Shapes](#)
 - 5.2 [Service Provider Resources](#)
 - 5.3 [Creation Factories](#)
 - 5.4 [Query Capabilities](#)
 - 5.5 [Delegated Uls](#)
- 6. [Conformance](#)
- Appendix A. [Acknowledgements](#)

1. Introduction

This section is non-normative.

Object Management group (<https://www.omg.org>) defines the OMG Systems Modeling Language Version 2.0 commonly referred to as SysML v2 [SysML]. From OMG: "SysML is a general-purpose modeling language for modeling systems that is intended to facilitate a model-based systems engineering (MBSE) approach to engineer systems. It provides the capability to create and visualize models that represent many different aspects of a system. This includes representing the requirements, structure, and behavior of the system, and the specification of analysis cases and verification cases used to analyze and verify the system. The language is intended to support multiple systems engineering methods and practices. The specific methods and practices may impose additional constraints on how the language is used."

SysML v2 plays a key role in Model-Based Systems and Software Engineering which is a major part of lifecycle management by defining a representation of the resources whose lifecycles are to be managed. It is therefore highly desirable to be able to integrate and link SysML resources with OSLC resources such as Requirements, Change Requests, Architecture Resources and test cases. This is accomplished by two OSLC-OP initiatives:

- Contributing an OSLC PIM to PSM mapping to the OMG Systems Modeling API and Services specification [SYSTEMSMODELINGAPI] and
- This OASIS specification, which defines the OSLC RDF representation of SysML v2 models, and is used by [SYSTEMSMODELINGAPI].

This specification defines the RESTful web services interface for the SysML OSLC domain that is used in the PIM to PSM mapping. This domain addresses the management of Model-Based Systems Engineering (MBSE) artifacts such as models, and relationships with other resources such as requirements, testing resources and change requests, as well as relationships between reusable SysML model elements in a supply chain. To support these scenarios, this specification defines a set of HTTP-based RESTful interfaces in terms of HTTP methods: GET, POST, PUT and DELETE, HTTP response codes, content type handling and resource formats.

The intent of this specification is to define the capabilities needed to support integration scenarios used in typical MBSE methods using SysML v2, and to enable linking SysML model artifacts with other OSLC lifecycle artifacts. This is accomplished by generating the OSLC SysML v2 vocabulary terms and constraints from the [SysML Abstract Syntax \(XMI\)](#), and having `http://open-services.net/ns/kerml#Element` subclass `http://open-services.net/ns/am#Resource` [OSLCAM].

This specification is a [OSLCCore3] compliant specification, and as such most of its content are references to [OSLCCore3].

1.1 Terminology

SysML Client

An implementation of the OSLC SysML specifications as a client. OSLC SysML Clients consume services provided by SysML servers.

SysML Server

A server implementing the OSLC SysML domain specifications. OSLC SysML clients consume services provided by SysML Servers. The use of the terms Client and Server are intended to distinguish typical consumers and providers of OSLC resources in a distributed environment based on REST. A particular application component could be a client for some OSLC domain services and a server for the same or another domain.

1.2 References

1.2.1 Normative references

[OSLCAM]

Jim Amsden; Andrii Berezovskyi. *OSLC Architecture Management Version 3.0. Part 1: Specification*. OASIS. OASIS Standard. URL: <https://docs.oasis-open-projects.org/oslc-op/am/v3.0/os/architecture-management-spec.html>

[OSLCCore2]

Dave Johnson; S. Speicher. *OSLC Core Specification 2.0*. <https://open-services.net/>. Finalized. URL: <https://archive.open-services.net/bin/view/Main/OslcCoreSpecification>

[OSLCCore3]

Jim Amsden; S. Speicher. *OSLC Core Version 3.0. Part 1: Overview*. OASIS. OASIS Standard. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/oslc-core.html>

[OSLCPreview]

OSLC Core Version 3.0. Part 3: Resource Preview0. OASIS. OASIS Standard. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/resource-preview.html>

[OSLCShapes]

Arthur Ryman; Jim Amsden. *OSLC Core Version 3.0. Part 6: Resource Shape*. OASIS. OASIS Standard. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/resource-shape.html>

[RFC2119]

S. Bradner. *Key words for use in RFCs to Indicate Requirement Levels*. IETF, March 1997. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc2119>

[RFC8174]

B. Leiba. *Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words*. IETF, May 2017. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc8174>

[SysML]

OMG ADTF. *OMG Systems Modeling Language Version 2.0*. OMG. Beta1. URL: <https://www.omg.org/spec/SysML/>

1.2.2 Informative references

[LDPPatch]

Linked Data Patch Format. <http://www.w3.org/>. Working Group Note. URL: <http://www.w3.org/TR/ldpatch/>

[SYSTEMSMODELINGAPI]

OMG ADTF. *Systems Modeling API and Services*. OMG. 1.0 Beta. URL: <https://www.omg.org/spec/SystemsModelingAPI/1.0/Beta1/About-SystemsModelingAPI>

1.3 Typographical Conventions and Use of RFC Terms

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words "**MUST**", "**MUST NOT**", "**REQUIRED**", "**SHALL**", "**SHALL NOT**", "**SHOULD**", "**SHOULD NOT**", "**RECOMMENDED**", "**NOT RECOMMENDED**", "**MAY**", and "**OPTIONAL**" in this specification are to be interpreted as described in [BCP 14](#) [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. Base Requirements

The following sub-sections define the mandatory and optional requirements for an OSLC SysML (OSLC SysML) server.

2.1 Base Compliance

This specification is based on [OSLCCore3]. OSLC SysML servers **MUST** be compliant with both the core specification, **MUST** follow all the mandatory requirements in the normative sections of this specification, and **SHOULD** follow all the guidelines and recommendations in both these specifications. [sml-1]

An OSLC SysML server **MUST** implement the domain vocabulary defined in [OSLC SysML Version 2.1. Part 2: Vocabulary](#) [sml-2]

The following table summarizes the requirements from OSLC Core Specification as well as some additional requirements specific to the SysML domain. Note that this specification further restricts some of the requirements from the OSLC Core Specification. See the previous sections in this specification or the OSLC Core Specification to get further details on each of these requirements.

Requirement	Meaning
Absolute URIs	SysML Servers MUST use absolute URIs for all references to resources by properties [sml-3]
Unknown properties and content	SysML Servers MAY ignore unknown content and SysML clients MUST preserve unknown content. SysML Servers MAY discard such properties and continue the POST or PUT operation without warning to the client. [sml-4]
Resource Operations	SysML Servers MUST support resource operations via standard HTTP operations [sml-5]
Update and Delete	SysML Servers SHOULD support resource modifications with standard HTTP PUT and DELETE methods. SysML Servers MAY limit modifications [sml-6]
HTTP If-Match use	SysML Servers supporting update and delete of resources MUST support the standard HTTP If-Match header in PUT and DELETE for concurrency protection of resources. [sml-7]
Resource Paging	SysML Servers MAY provide paging for resources but only when specifically requested by clients [sml-8]
Partial Resource Representations	SysML Servers MAY support requests for a subset of a resource's properties via the osc.properties URL parameter retrieval via HTTP GET [sml-9]
Partial Update	SysML Servers MAY support partial update of resources via the osc.properties URL parameter retrieval via HTTP PUT and or using [LDPPatch]. [sml-10]
Discovery	SysML Servers MAY provide a Service Provider Catalog, MUST provide a Service Provider resource, and MAY provide other forms of discovery described in [OSLCCore3]. [sml-11]
Creation Factories	SysML Servers MAY provide creation factories for resource formats that it supports. SysML Servers MAY support creation factories for OSLC SysML defined resources formatted as application/rdf+xml. SysML Servers MAY support creation factories for other formats, and indicate such creation factories with a non-default identifier in the osc:usage property of the creation factory definition in the service provider document [sml-12]

Requirement	Meaning
Query Capabilities	SysML Servers MUST provide query capabilities on <code>oslc_am:Resource</code> resources to enable clients to query for resources. SysML Servers SHOULD support a query interface for <code>oslc_am:LinkType</code> resources that support a GET for all LinkType resources. Such a GET does not require any simple query syntax parameters. SysML Servers MAY support the full query syntax for LinkType resources. [sml-13]
Query Syntax	OSLC query capabilities MUST support the OSLC Core Query Syntax [sml-14]
Delegated Dialogs	SysML Services SHOULD offer selection delegated dialogs and MAY offer creation delegated dialogs specified via service provider resource [sml-15]
Resource Preview	SysML Services SHOULD offer resource previews for resources that may be referenced by other resources [sml-16]
Authentication	SysML Services SHOULD follow the recommendations for Authentication specified in [OSLCCore3] [sml-17]
Error Responses	SysML Servers SHOULD provide error responses using OSLC Core defined error formats [sml-18]
RDF/XML Representations	SysML Servers MUST support RDF/XML representations for OSLC Defined Resources [sml-19]
XML Representations	SysML Servers MUST support XML representations that conform to the OSLC Core Guidelines for XML [sml-20]
JSON Representations	SysML Servers MAY support JSON representations; those which do MUST conform to the OSLC Core Guidelines for JSON [sml-21]
HTML Representations	SysML Servers MAY provide HTML representations for GET requests [sml-22]

2.2 Specification Versioning

This specification follows the specification version guidelines given in [OSLCCore3].

2.3 Namespaces

In addition to the namespace URLs and namespace prefixes `oslc`, `rdf`, `dcterms` and `foaf` defined in [OSLCCore3], OSLC SysML defines the namespace URI of `http://open-services.net/ns/sysmlv2#` with a preferred namespace prefix of `oslc_am`.

2.4 Resource Formats

In addition to the requirements for resource representations in [OSLCCore3], this section outlines further refinements and restrictions.

For HTTP GET/PUT/POST requests on all OSLC SysML and OSLC Core defined resource types,

- SysML Servers **MUST** support RDF/XML representations with media-type `application/rdf+xml`. SysML Clients **SHOULD** be prepared to deal with any valid RDF/XML document. [sml-23]
- SysML Servers **MUST** support XML representations with media-type `application/xml`. The XML representations **MUST** follow the guidelines outlined in the [OSLC Core Representations Guidance](#) to maintain compatibility with [OSLCCore2]. [sml-24]
- SysML Servers **MAY** support JSON representations with media-type `application/json`. The JSON representations **MUST** follow the guidelines outlined in the [OSLC Core Representations Guidance](#) to maintain compatibility with [OSLCCore2]. [sml-25]

2.5 Resource Operations

For compatibility with OSLC 2.0, OSLC SysML Servers **MAY** accept the OSLC Core Version header (OSLC-Core-Version: 2.0) in any HTTP request as specified in [OSLCCore3], and return an OSLC SysML 2.0 representation (including the OSLC-Core-Version: 2.0 header). If the OSLC Core Version header is absent on a request, or has some undefined value, the OSLC SysML Server **MUST** return an SysML 2.0 representation. [sml-26]

OSLC SysML Servers **MUST** support HTTP GET requests on SysML Resources, with an Accept header of `application/rdf+xml`, and return the RDF/XML representation of the resource. [sml-27]

OSLC SysML Servers **SHOULD** support HTTP GET requests on SysML Resources, with an Accept header of an HTML type (`application/html`, `application/xhtml`), and return either an HTML/XHTML representation of the resource or redirect the client to another URL that can (i.e. 302 Redirect). [sml-28]

OSLC SysML Servers **SHOULD** support HTTP GET requests for user interface (UI) preview of SysML Resources as defined by [OSLCPreview]. [sml-29]

OSLC SysML Servers **SHOULD** support resource modifications on SysML Resources with standard HTTP PUT and DELETE methods. SysML Servers **MAY** limit modifications in any way they want. For example a service provider may limit updates to resources to simple link properties of link types already defined in the provider. Modification methods **MUST** use the If-Match header for concurrency management. Providers **MAY** discard such properties and continue a PUT operation without warning to the client. [sml-30]

OSLC SysML Servers **SHOULD** support resource modifications on LinkType Resources (LTR) with standard HTTP PUT and DELETE methods. SysML Servers **MAY** limit modifications in any way they want. For example a service provider may not support additional properties. Modification methods **SHOULD** use the If-Match header for concurrency management. [sml-31]

2.6 Authentication

See [OSLCCore3], OSLC SysML puts no additional constraints on authentication.

2.7 Error Responses

See [OSLCCore3], OSLC SysML puts no additional constraints on error responses

2.8 Pagination

OSLC SysML Servers **SHOULD** support pagination of query results and **MAY** support pagination of a single resource's properties as defined by [OSLCCore3]. [sml-32]

2.9 Requesting and Updating Properties

2.9.1 Requesting a Subset of Properties

An OSLC SysML server **MAY** support the `oslc.properties` URL query parameter on an HTTP GET request on individual resource request or a collection of resources by query. If the `oslc.properties` query parameter is omitted on the request, then all resource properties **MUST** be provided in the response. [sml-33]

2.9.2 Updating a Subset of Properties

An OSLC SysML client **MAY** request that a subset of a resource's properties be updated by identifying those properties to be modified using the `oslc.properties` URL parameter on a HTTP PUT request. [sml-34]

2.9.3 Updating Multi-Valued Properties

An OSLC SysML Server **MAY** support updating a subset of a resource's properties by using the [LDPPatch] `PATCH` method. [sml-35]

For compatibility with [OSLCCore2], an SysML Server **MAY** also support partial update by identifying those properties to be modified using the `oslc.properties` URL parameter on a HTTP PUT request. [sml-36]

If the parameter `oslc.properties` contains a valid resource property on the request that is not provided in the content, the server **MUST** set the resource's property to a null or empty value. If the parameter `oslc.properties` contains an invalid resource property, then a **409 Conflict** **MUST** be returned. [sml-37]

3. Vocabulary Terms and Constraints

[OSLC SysML Resources 2.1](#) Defines the vocabulary terms and constraints for OSLC Change Management resources. These terms and constraints are specified according to [\[OSLC Core3\]](#).

4. Vocabulary Subsets

SysML OSLC servers **MAY** choose to limit the types of SysML resources that can be accessed directly with a URL, or are accessible for resource preview or selection and creation dialogs. This allows servers to simplify the OSLC REST API to those SysML elements that are necessary for their particular purpose. SysML Servers **MUST** allow direct access to at least Element and Relationship. [\[sml-38\]](#)

5. SysML Server Capabilities

5.1 Resource Shapes

OSLC SysML servers **SHOULD** support Resource Shapes as defined in [OSLCShapes]. [sml-39]

5.2 Service Provider Resources

OSLC SysML Servers **MUST** provide a ServiceProvider Resource that can be retrieved at a implementation dependent URI. [sml-40]

OSLC SysML Servers **MUST** provide a ServiceProviderCatalog Resource that can be retrieved at a implementation dependent URI. [sml-41]

OSLC SysML Servers **MUST** provide an `oslc:serviceProvider` property for their defined resources that will be the URI to a ServiceProvider Resource. This does not prevent SysML Servers from providing multiple service provider properties with different values, if the service provider supports multiple OSLC domain specifications, and the resource is applicable to multiple domains. [sml-42]

OSLC SysML Servers **MUST** supply a value of `http://open-services.net/ns/am#` for the property `oslc:domain` on either `oslc:ServiceProvider` or `oslc:ServiceProviderCatalog` resources. [sml-43]

5.3 Creation Factories

OSLC SysML Servers **MAY** support CreationFactories as defined by [OSLCCore3]. [sml-44]

OSLC SysML Servers **MAY** discard properties it does not recognize and continue the POST operation without warning to the client. The returned resource will contain the accepted properties (and server generated properties like the `dcterms:identifier`) so clients will be able to confirm if required what was accepted. [sml-45]

If OSLC SysML Servers support the creation of resources from the OSLC defined `oslc_am:Resource` format, there **MUST** be at least one CreationFactory entry in the Services definition, and its `oslc:usage` property **MUST** be set to `http://open-services.net/ns/core#default`. The `oslc:resourceType` **MUST** be set to `http://open-services.net/ns/am#Resource`. [sml-46]

If OSLC SysML Servers support the creation of resources from a resource other than `oslc_am:Resource`, there **MUST** be a separate creation services definition whose `oslc:usage` property **MUST NOT** be set to `http://open-services.net/ns/core#default`. [sml-47]

5.4 Query Capabilities

OSLC SysML Servers **SHOULD** support the Query Capabilities as defined by [OSLCCore3] for both `oslc_am:Resource` and `oslc_am:LinkType` resources. [sml-48]

If the service provider supports query capability for `oslc_am:Resource` resources, it **MUST** support the following query parameters: [sml-49]

- `oslc.where`
- `oslc.searchTerms`

OSLC SysML Servers **SHOULD** support query capability for `oslc_am:LinkType` resources. If supported then SysML Servers **MUST** support a simple GET without any query parameters that returns all link type resources. SysML Servers **SHOULD** support the full OSLC query syntax. [sml-50]

5.5 Delegated UIs

OSLC SysML Servers **SHOULD** support the selection of resources by delegated selection dialogs as defined by [OSLCCore3]. [sml-51]

OSLC SysML Servers **MAY** support the creation of resources by delegated creation dialogs as defined by [OSLCCore3]. [sml-52]

In **oslc:Dialog** elements, the two optional child elements; **oslc:hintWidth** and **oslc:hintHeight** specify the suggested size of the dialog or frame to render the HTML content in. Expected size values are defined by [CSS length units](#). [sml-53]

6. Conformance

Implementations of this specification need to satisfy the following conformance clauses.

Clause Number	Requirement
sml-1	This specification is based on [OSLCCore3] . OSLC SysML servers MUST be compliant with both the core specification, MUST follow all the mandatory requirements in the normative sections of this specification, and SHOULD follow all the guidelines and recommendations in both these specifications.
sml-2	An OSLC SysML server MUST implement the domain vocabulary defined in OSLC SysML Version 2.1. Part 2: Vocabulary
sml-3	SysML Servers MUST use absolute URIs for all references to resources by properties
sml-4	SysML Servers MAY ignore unknown content and SysML clients MUST preserve unknown content. SysML Servers MAY discard such properties and continue the POST or PUT operation without warning to the client.
sml-5	SysML Servers MUST support resource operations via standard HTTP operations
sml-6	SysML Servers SHOULD support resource modifications with standard HTTP PUT and DELETE methods. SysML Servers MAY limit modifications
sml-7	SysML Servers supporting update and delete of resources MUST support the standard HTTP If-Match header in PUT and DELETE for concurrency protection of resources.
sml-8	SysML Servers MAY provide paging for resources but only when specifically requested by clients
sml-9	SysML Servers MAY support requests for a subset of a resource's properties via the osc.properties URL parameter retrieval via HTTP GET
sml-10	SysML Servers MAY support partial update of resources via the osc.properties URL parameter retrieval via HTTP PUT and or using [LDPPatch] .
sml-11	SysML Servers MAY provide a Service Provider Catalog, MUST provide a Service Provider resource, and MAY provide other forms of discovery described in [OSLCCore3] .
sml-12	SysML Servers MAY provide creation factories for resource formats that it supports. SysML Servers MAY support creation factories for OSLC SysML defined resources formatted as application/rdf+xml. SysML Servers MAY support creation factories for other formats, and indicate such creation factories with a non-default identifier in the osc:usage property of the creation factory definition in the service provider document
sml-13	SysML Servers MUST provide query capabilities on osc_am:Resource resources to enable clients to query for resources. SysML Servers SHOULD support a query interface for osc_am:LinkType resources that support a GET for all LinkType resources. Such a GET does not require any simple query syntax parameters. SysML Servers MAY support the full query syntax for LinkType resources.
sml-14	OSLC query capabilities MUST support the OSLC Core Query Syntax
sml-15	SysML Services SHOULD offer selection delegated dialogs and MAY offer creation delegated dialogs specified via service provider resource
sml-16	SysML Services SHOULD offer resource previews for resources that may be referenced by other resources
sml-17	SysML Services SHOULD follow the recommendations for Authentication specified in [OSLCCore3]
sml-18	SysML Servers SHOULD provide error responses using OSLC Core defined error formats
sml-19	SysML Servers MUST support RDF/XML representations for OSLC Defined Resources
sml-20	SysML Servers MUST support XML representations that conform to the OSLC Core Guidelines for XML
sml-21	SysML Servers MAY support JSON representations; those which do MUST conform to the OSLC Core Guidelines for JSON
sml-22	SysML Servers MAY provide HTML representations for GET requests

Clause Number	Requirement
sml-23	SysML Servers MUST support RDF/XML representations with media-type application/rdf+xml . SysML Clients SHOULD be prepared to deal with any valid RDF/XML document.
sml-24	SysML Servers MUST support XML representations with media-type application/xml . The XML representations MUST follow the guidelines outlined in the OSLC Core Representations Guidance to maintain compatibility with [OSLCCore2] .
sml-25	SysML Servers MAY support JSON representations with media-type application/json . The JSON representations MUST follow the guidelines outlined in the OSLC Core Representations Guidance to maintain compatibility with [OSLCCore2] .
sml-26	For compatibility with OSLC 2.0, OSLC SysML Servers MAY accept the OSLC Core Version header (OSLC-Core-Version: 2.0) in any HTTP request as specified in [OSLCCore3] , and return an OSLC SysML 2.0 representation (including the OSLC-Core-Version: 2.0 header). If the OSLC Core Version header is absent on a request, or has some undefined value, the OSLC SysML Server MUST return an SysML 2.0 representation.
sml-27	OSLC SysML Servers MUST support HTTP GET requests on SysML Resources, with an Accept header of application/rdf+xml , and return the RDF/XML representation of the resource.
sml-28	OSLC SysML Servers SHOULD support HTTP GET requests on SysML Resources, with an Accept header of an HTML type (application/html , application/xhtml), and return either an HTML/XHTML representation of the resource or redirect the client to another URL that can (i.e. 302 Redirect).
sml-29	OSLC SysML Servers SHOULD support HTTP GET requests for user interface (UI) preview of SysML Resources as defined by [OSLCPreview] .
sml-30	OSLC SysML Servers SHOULD support resource modifications on SysML Resources with standard HTTP PUT and DELETE methods. SysML Servers MAY limit modifications in any way they want. For example a service provider may limit updates to resources to simple link properties of link types already defined in the provider. Modification methods MUST use the If-Match header for concurrency management. Providers MAY discard such properties and continue a PUT operation without warning to the client.
sml-31	OSLC SysML Servers SHOULD support resource modifications on LinkType Resources (LTR) with standard HTTP PUT and DELETE methods. SysML Servers MAY limit modifications in any way they want. For example a service provider may not support additional properties. Modification methods SHOULD use the If-Match header for concurrency management.
sml-32	OSLC SysML Servers SHOULD support pagination of query results and MAY support pagination of a single resource's properties as defined by [OSLCCore3] .
sml-33	An OSLC SysML server MAY support the oslc.properties URL query parameter on an HTTP GET request on individual resource request or a collection of resources by query. If the oslc.properties query parameter is omitted on the request, then all resource properties MUST be provided in the response.
sml-34	An OSLC SysML client MAY request that a subset of a resource's properties be updated by identifying those properties to be modified using the oslc.properties URL parameter on a HTTP PUT request.
sml-35	An OSLC SysML Server MAY support updating a subset of a resource's properties by using the [LDPPatch] PATCH method.
sml-36	For compatibility with [OSLCCore2] , an SysML Server MAY also support partial update by identifying those properties to be modified using the oslc.properties URL parameter on a HTTP PUT request.
sml-37	If the parameter oslc.properties contains a valid resource property on the request that is not provided in the content, the server MUST set the resource's property to a null or empty value. If the parameter oslc.properties contains an invalid resource property, then a 409 Conflict MUST be returned.
sml-38	SysML OSLC servers MAY choose to limit the types of SysML resources that can be accessed directly with a URL, or are accessible for resource preview or selection and creation dialogs. This allows servers to simplify the OSLC REST API to those SysML elements that are necessary for their particular purpose. SysML Servers MUST allow direct access to at least Element and Relationship.
sml-39	OSLC SysML servers SHOULD support Resource Shapes as defined in [OSLCShapes] .
sml-40	OSLC SysML Servers MUST provide a ServiceProvider Resource that can be retrieved at a implementation dependent URI.

Clause Number	Requirement
sml-41	OSLC SysML Servers MUST provide a ServiceProviderCatalog Resource that can be retrieved at a implementation dependent URI.
sml-42	OSLC SysML Servers MUST provide an <code>oslc:serviceProvider</code> property for their defined resources that will be the URI to a ServiceProvider Resource. This does not prevent SysML Servers from providing multiple service provider properties with different values, if the service provider supports multiple OSLC domain specifications, and the resource is applicable to multiple domains.
sml-43	OSLC SysML Servers MUST supply a value of <code>http://open-services.net/ns/am#</code> for the property <code>oslc:domain</code> on either <code>oslc:ServiceProvider</code> or <code>oslc:ServiceProviderCatalog</code> resources.
sml-44	OSLC SysML Servers MAY support CreationFactories as defined by [OSLCCore3].
sml-45	OSLC SysML Servers MAY discard properties it does not recognize and continue the POST operation without warning to the client. The returned resource will contain the accepted properties (and server generated properties like the <code>dcterms:identifier</code>) so clients will be able to confirm if required what was accepted.
sml-46	If OSLC SysML Servers support the creation of resources from the OSLC defined <code>oslc_am:Resource</code> format, there MUST be at least one Creation Factory entry in the Services definition, and its <code>oslc:usage</code> property MUST be set to <code>http://open-services.net/ns/core#default</code> . The <code>oslc:resourceType</code> MUST be set to <code>http://open-services.net/ns/am#Resource</code> .
sml-47	If OSLC SysML Servers support the creation of resources from a resource other than <code>oslc_am:Resource</code> , there MUST be a separate creation services definition whose <code>oslc:usage</code> property MUST NOT be set to <code>http://open-services.net/ns/core#default</code> .
sml-48	OSLC SysML Servers SHOULD support the Query Capabilities as defined by [OSLCCore3] for both <code>oslc_am:Resource</code> and <code>oslc_am:LinkType</code> resources.
sml-49	If the service provider supports query capability for <code>oslc_am:Resource</code> resources, it MUST support the following query parameters:
sml-50	OSLC SysML Servers SHOULD support query capability for <code>oslc_am:LinkType</code> resources. If supported then SysML Servers MUST support a simple GET without any query parameters that returns all link type resources. SysML Servers SHOULD support the full OSLC query syntax.
sml-51	OSLC SysML Servers SHOULD support the selection of resources by delegated selection dialogs as defined by [OSLCCore3].
sml-52	OSLC SysML Servers MAY support the creation of resources by delegated creation dialogs as defined by [OSLCCore3].
sml-53	In <code>oslc:Dialog</code> elements, the two optional child elements; <code>oslc:hintWidth</code> and <code>oslc:hintHeight</code> specify the suggested size of the dialog or frame to render the HTML content in. Expected size values are defined by CSS length units .

Appendix A. Acknowledgements

This section is non-normative.

The following individuals have participated in the creation of this specification and are gratefully acknowledged:

Participants:

James Amsden, IBM (Editor)
Jad El-khoury, KTH



OSLC Systems Modeling Language Version 2.0. Part 2: Vocabulary

Project Specification Draft 01 25 April 2024

This stage:

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-vocab.html> (Authoritative)
<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-vocab.pdf>

Previous stage:

N/A

Latest stage:

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-vocab.html> (Authoritative)
<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-vocab.pdf>

Latest version:

<https://open-services.net/spec/sysml/latest>

Latest editor's draft:

<https://open-services.net/spec/sysml/latest-draft>

Open Project:

[OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#)

Project Chairs:

Jim Amsden (jamsden@us.ibm.com), [IBM](#)

Jad El-khoury (jad@kth.se), [KTH Royal Institute of Technology](#)

Editor:

Jim Amsden (jamsden@us.ibm.com), [IBM](#)

Additional components:

This specification is one component of a Work Product that also includes:

- OSLC SysML Version 2.0. Part 1: Specification. [sysml-spec.html](#)
- OSLC SysML Version 2.0. Part 2: Vocabulary (this document). [sysml-vocab.html](#)
- OSLC SysML Version 2.0. Part 3: Constraints. [sysml-shapes.html](#)
- OSLC SysML Version 2.0. Part 4: Machine Readable Vocabulary Terms. [sysml-vocab.ttl](#)
- OSLC SysML Version 2.0. Part 5: Machine Readable Constraints. [sysml-shapes.ttl](#)

Related work:

This specification is related to:

- *OMG Systems Modeling Language*. <https://www.omg.org/spec/SysML/>
- *Systems Modeling Application Programming Interface (API) and Services*. <https://www.omg.org/spec/SystemsModelingAPI/1.0/Beta1/PDF>

RDF Namespaces:

<http://open-services.net/ns/sysmlv2#>

Abstract:

This specification defines the OSLC vocabulary terms for [OSLC Systems Modeling Language Version 2.0. Part 1: Specification](#), and OSLC representation of the OMG Systems Modeling Language v2.

Status:

This document was last revised or approved by the [OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#) on the above date. The level of approval is also listed above. Check the “Latest stage” location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Open Project are listed at <https://open-services.net/about/>.

Comments on this work can be provided by opening issues in the project repository or by sending email to the project's public comment list oslc-op@lists.oasis-open-projects.org.

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this specification the following citation format should be used:

[OSLC-SYSML-2.0-Part2]

OSLC Systems Modeling Language Version 2.0. Part 2: Vocabulary. Edited by Jim Amsden. 25 April 2024. OASIS Project Specification Draft 01. <https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-vocab.html>. Latest stage: <https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-vocab.html>.

Notices

Copyright © OASIS Open 2024. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This specification is published under the [Attribution 4.0 International \(CC BY 4.0\)](#). Portions of this specification are also provided under the [Apache License 2.0](#).

All contributions made to this project have been made under the [OASIS Contributor License Agreement \(CLA\)](#).

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the [Open Projects IPR Statements page](#).

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Open Project or OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Project Specification or OASIS Standard, to notify the OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Open Project that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Open Project Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.

Table of Contents

- 1. [Introduction](#)
 - 1.1 [Terminology](#)
 - 1.2 [References](#)
 - 1.2.1 [Normative references](#)
 - 1.2.2 [Informative references](#)
 - 1.3 [Typographical Conventions and Use of RFC Terms](#)
- 2. [SysML v2 Vocabulary Terms](#)
 - 2.1 [Vocabulary Details](#)
 - 2.1.1 [Classes in this namespace \(179\)](#)
 - 2.1.2 [Properties in this namespace \(412\)](#)
 - 2.1.3 [Resources \(Individuals\) in this namespace \(19\)](#)
- 3. [Conformance](#)

1. Introduction

This section is non-normative.

This specification defines vocabulary terms for OSLC Systems Modeling Language Version 2.0 [SysML] resources. The intent is to define resources needed to support common integration scenarios that utilize OMG Systems Modeling Language v2. The resource formats are intended to define RDF resources that enable model elements in typical Model-Based Systems Engineering methods using SysML v2 to integrate with other OSLC resources including Requirements, Architecture Management Resources, Change Requests, Test case, etc.

1.1 Terminology

This section is non-normative.

Terminology is based on OSLC Core Overview [OSLCCore3], W3C Linked Data Platform [LDP], W3C's Architecture of the World Wide Web [WEBARCH], Hyper-text Transfer Protocol [HTTP11]. Terminology for this specification is defined in part 1 of the multi-part specification.

1.2 References

1.2.1 Normative references

[HTTP11]

R. Fielding, Ed.; J. Reschke, Ed.. [Hypertext Transfer Protocol \(HTTP/1.1\): Message Syntax and Routing](#). IETF, June 2014. Proposed Standard. URL: <https://httpwg.org/specs/rfc7230.html>

[LDP]

Steve Speicher; John Arwe; Ashok Malhotra. [Linked Data Platform 1.0](#). W3C, 26 February 2015. W3C Recommendation. URL: <https://www.w3.org/TR/ldp/>

[OSLCCore3]

Jim Amsden; S. Speicher. [OSLC Core Version 3.0. Part 1: Overview](#). OASIS. Project Specification Draft. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/oslc-core.html>

[RFC2119]

S. Bradner. [Key words for use in RFCs to Indicate Requirement Levels](#). IETF, March 1997. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc2119>

[RFC8174]

B. Leiba. [Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words](#). IETF, May 2017. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc8174>

[SysML]

OMG ADTF. [OMG Systems Modeling Language Version 2.0](#). OMG. Beta1. URL: <https://www.omg.org/spec/SysML/>

1.2.2 Informative references

[WEBARCH]

Ian Jacobs; Norman Walsh. [Architecture of the World Wide Web, Volume One](#). W3C, 15 December 2004. W3C

Recommendation. URL: <https://www.w3.org/TR/webarch/>

1.3 Typographical Conventions and Use of RFC Terms

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words "**MUST**", "**MUST NOT**", "**REQUIRED**", "**SHALL**", "**SHALL NOT**", "**SHOULD**", "**SHOULD NOT**", "**RECOMMENDED**", "**NOT RECOMMENDED**", "**MAY**", and "**OPTIONAL**" in this specification are to be interpreted as described in [BCP 14](#) [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

In addition to the namespace URIs and namespace prefixes **oslc**, **rdf**, **dcterms** and **foaf** defined in the [OSLC Core specification](#), OSLC SysML v2 defines the namespace URI of <http://open-services.net/ns/sysmlv2#> with a namespace prefix of **oslc_sysmlv2**

This specification also uses these namespace prefix definitions:

- **oslc** : <http://open-services.net/ns/core#> [OSLCCore3]

2. SysML v2 Vocabulary Terms

Property value types that are not defined in the following sections, are defined in [OSLCCore3].

OSLC SysML v2 defines a set of properties for OMG SysML v2 resources. However, service implementations are free to extend this set of properties. Clients **MUST** preserve properties it does not recognize when updating resources. OSLC SysML v2 Servers **MAY** ignore properties that it does not recognize. Additional properties may come from existing vocabularies (ie. Dublin Core, OWL). When additional properties do not come from a known vocabulary, it is recommended that they exist in their own unique namespace, and providers **SHOULD NOT** reuse namespaces defined in these specifications. [sml-1]

All RDF/XML resources that include links with annotations **MUST** begin with an outer `<rdf:RDF>` element. This outer XML element is required to support the ability to include annotations on 'link' properties with additional `<rdf:Description>` elements [reifying statements](#) about the link. [sml-2]

Service implementations and clients **MUST** be prepared to accept any form of valid RDF/XML. For example the following two resource forms are equivalent. [sml-3]

EXAMPLE 1

```
<rdf:RDF
  xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:oslc="http://open-services.net/ns/core#"
  xmlns:oslc_sysmlv2="http://open-services.net/ns/sysmlv2#"
  xmlns:dcterms="http://purl.org/dc/terms/">

  <oslc_sysmlv2:PartDef rdf:about="https://example.com/resources/res1">
    <dcterms:title>Service Interface</dcterms:title>
    <dcterms:identifier>res1</dcterms:identifier>
    <oslc:serviceProvider rdf:resource="http://open-services.net/ns/sysmlv2#" />
  </oslc_sysmlv2:PartDef>
</rdf:RDF>
```

is equivalent to

```
<rdf:RDF
  xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:oslc="http://open-services.net/ns/core#"
  xmlns:dcterms="http://purl.org/dc/terms/">

  <rdf:Description rdf:about="https://example.com/resources/res1">
    <dcterms:title>Service Interface</dcterms:title>
    <dcterms:identifier>res1</dcterms:identifier>
    <rdf:type rdf:resource="http://open-services.net/ns/sysmlv2#PartDef" />
    <oslc:serviceProvider rdf:resource="http://open-services.net/ns/sysmlv2#" />
  </rdf:Description>
</rdf:RDF>
```

This specification defines a number of specific, commonly occurring vocabulary terms (OWL classes), properties and values. Servers may define additional classes and provide additional properties as needed.

2.1 Vocabulary Details

The namespace URI for this vocabulary is: <http://open-services.net/ns/sysmlv2#>

All vocabulary URIs defined in the OSLC SysML v2 namespace.

2.1.1 Classes in this namespace (179)

[AcceptActionUsage](#), [ActionDefinition](#), [ActionUsage](#), [ActorMembership](#), [AllocationDefinition](#), [AllocationUsage](#), [AnalysisCaseDefinition](#), [AnalysisCaseUsage](#), [AnnotatingElement](#), [Annotation](#), [AssertConstraintUsage](#), [AssignmentActionUsage](#), [Association](#), [AssociationStructure](#), [AttributeDefinition](#), [AttributeUsage](#), [Behavior](#), [BindingConnector](#), [BindingConnectorAsUsage](#), [BooleanExpression](#), [CalculationDefinition](#), [CalculationUsage](#), [CaseDefinition](#), [CaseUsage](#), [Class](#), [Classifier](#), [CollectExpression](#), [Comment](#), [ConcernDefinition](#), [ConcernUsage](#), [ConjugatedPortDefinition](#), [ConjugatedPortTyping](#), [Conjugation](#), [ConnectionDefinition](#), [ConnectionUsage](#), [Connector](#), [ConnectorAsUsage](#), [ConstraintDefinition](#), [ConstraintUsage](#), [ControlNode](#), [DataType](#), [DecisionNode](#), [Definition](#), [Dependency](#), [Differencing](#), [Disjoining](#), [Documentation](#), [Element](#), [ElementFilterMembership](#), [EndFeatureMembership](#), [EnumerationDefinition](#), [EnumerationUsage](#), [EventOccurrenceUsage](#), [ExhibitStateUsage](#), [Expose](#), [Expression](#), [Feature](#), [FeatureChainExpression](#), [FeatureChaining](#), [FeatureDirectionKind](#), [FeatureInverting](#), [FeatureMembership](#), [FeatureReferenceExpression](#), [FeatureTyping](#), [FeatureValue](#), [Featuring](#), [FlowConnectionDefinition](#), [FlowConnectionUsage](#), [ForkNode](#), [ForLoopActionUsage](#), [FramedConcernMembership](#), [Function](#), [IfActionUsage](#), [Import](#), [IncludeUseCaseUsage](#), [Interaction](#), [InterfaceDefinition](#), [InterfaceUsage](#), [Intersecting](#), [Invariant](#), [InvocationExpression](#), [ItemDefinition](#), [ItemFeature](#), [ItemFlow](#), [ItemFlowEnd](#), [ItemUsage](#), [JoinNode](#), [LibraryPackage](#), [LifeClass](#), [LiteralBoolean](#), [LiteralExpression](#), [LiteralInfinity](#), [LiteralInteger](#), [LiteralRational](#), [LiteralString](#), [LoopActionUsage](#), [Membership](#), [MembershipExpose](#), [MembershipImport](#), [MergeNode](#), [Metaclass](#), [MetadataAccessExpression](#), [MetadataDefinition](#), [MetadataFeature](#), [MetadataUsage](#), [Multiplicity](#), [MultiplicityRange](#), [Namespace](#), [NamespaceExpose](#), [NamespaceImport](#), [NullExpression](#), [ObjectiveMembership](#), [OccurrenceDefinition](#), [OccurrenceUsage](#), [OperatorExpression](#), [OwningMembership](#), [Package](#), [ParameterMembership](#), [PartDefinition](#), [PartUsage](#), [PerformActionUsage](#), [PortConjugation](#), [PortDefinition](#), [PortionKind](#), [PortUsage](#), [Predicate](#), [Redefinition](#), [ReferenceSubsetting](#), [ReferenceUsage](#), [Relationship](#), [RenderingDefinition](#), [RenderingUsage](#), [RequirementConstraintKind](#), [RequirementConstraintMembership](#), [RequirementDefinition](#), [RequirementUsage](#), [RequirementVerificationMembership](#), [ResultExpressionMembership](#), [ReturnParameterMembership](#), [SatisfyRequirementUsage](#), [SelectExpression](#), [SendActionUsage](#), [Specialization](#), [StakeholderMembership](#), [StateDefinition](#), [StateSubactionKind](#), [StateSubactionMembership](#), [StateUsage](#), [Step](#), [Structure](#), [Subclassification](#), [SubjectMembership](#), [Subsetting](#), [Succession](#), [SuccessionAsUsage](#), [SuccessionFlowConnectionUsage](#), [SuccessionItemFlow](#), [TextualRepresentation](#), [TransitionFeatureKind](#), [TransitionFeatureMembership](#), [TransitionUsage](#), [TriggerInvocationExpression](#), [TriggerKind](#), [Type](#), [TypeFeaturing](#), [Unioning](#), [Usage](#), [UseCaseDefinition](#), [UseCaseUsage](#), [VariantMembership](#), [VerificationCaseDefinition](#), [VerificationCaseUsage](#), [ViewDefinition](#), [ViewpointDefinition](#), [ViewpointUsage](#), [ViewRenderingMembership](#), [ViewUsage](#), [VisibilityKind](#), [WhileLoopActionUsage](#)

AcceptActionUsage

<http://open-services.net/ns/sysmlv2#AcceptActionUsage>

AcceptActionUsage is an RDFS class.

An *AcceptActionUsage* is an *ActionUsage* that specifies the acceptance of an incoming *Transfer* from the *Occurrence* given by the result of its *receiverArgument* Expression. (If no *receiverArgument* is provided, the default is the this context of the *AcceptActionUsage*.) The payload of the accepted *Transfer* is output on its *payloadParameter*. Which *Transfers* may be accepted is determined by conformance to the typing and (potentially) binding of the *payloadParameter*.

ActionDefinition

<http://open-services.net/ns/sysmlv2#ActionDefinition>

ActionDefinition is an RDFS class.

An *ActionDefinition* is a *Definition* that is also a *Behavior* that defines an *Action* performed by a system or part of a system.

ActionUsage

<http://open-services.net/ns/sysmlv2#ActionUsage>

ActionUsage is an RDFS class.

An *ActionUsage* is a *Usage* that is also a *Step*, and, so, is typed by a *Behavior*. Nominally, if the type is an *ActionDefinition*, an *ActionUsage* is a *Usage* of that *ActionDefinition* within a system. However, other kinds of kernel *Behaviors* are also allowed, to permit use of *Behaviors* from the Kernel Model Libraries.

ActorMembership

<http://open-services.net/ns/sysmlv2#ActorMembership>

ActorMembership is an RDFS class.

An ActorMembership is a ParameterMembership that identifies a PartUsage as an actor parameter, which specifies a role played by an external entity in interaction with the owningType of the ActorMembership.

AllocationDefinition

<http://open-services.net/ns/sysmlv2#AllocationDefinition>

AllocationDefinition is an RDFS class.

An AllocationDefinition is a ConnectionDefinition that specifies that some or all of the responsibility to realize the intent of the source is allocated to the target instances. Such allocations define mappings across the various structures and hierarchies of a system model, perhaps as a precursor to more rigorous specifications and implementations. An AllocationDefinition can itself be refined using nested allocations that give a finer-grained decomposition of the containing allocation mapping.

AllocationUsage

<http://open-services.net/ns/sysmlv2#AllocationUsage>

AllocationUsage is an RDFS class.

An AllocationUsage is a usage of an AllocationDefinition asserting the allocation of the source feature to the target feature.

AnalysisCaseDefinition

<http://open-services.net/ns/sysmlv2#AnalysisCaseDefinition>

AnalysisCaseDefinition is an RDFS class.

An AnalysisCaseDefinition is a CaseDefinition for the case of carrying out an analysis.

AnalysisCaseUsage

<http://open-services.net/ns/sysmlv2#AnalysisCaseUsage>

AnalysisCaseUsage is an RDFS class.

An AnalysisCaseUsage is a Usage of an AnalysisCaseDefinition.

AnnotatingElement

<http://open-services.net/ns/sysmlv2#AnnotatingElement>

AnnotatingElement is an RDFS class.

An AnnotatingElement is an Element that provides additional description of or metadata on some other Element. An AnnotatingElement is either attached to its annotatedElements by Annotation Relationships, or it implicitly annotates its owningNamespace.

Annotation

<http://open-services.net/ns/sysmlv2#Annotation>

Annotation is an RDFS class.

An Annotation is a Relationship between an AnnotatingElement and the Element that is annotated by that AnnotatingElement.

AssertConstraintUsage

<http://open-services.net/ns/sysmlv2#AssertConstraintUsage>

AssertConstraintUsage is an RDFS class.

An AssertConstraintUsage is a ConstraintUsage that is also an Invariant and, so, is asserted to be true (by default). Unless it is the AssertConstraintUsage itself, the asserted ConstraintUsage is related to the AssertConstraintUsage by a ReferenceSubsetting Relationship.

AssignmentActionUsage

<http://open-services.net/ns/sysmlv2#AssignmentActionUsage>

AssignmentActionUsage is an RDFS class.

An AssignmentActionUsage is an ActionUsage that is defined, directly or indirectly, by the ActionDefinition AssignmentAction from the Systems Model Library. It specifies that the value of the referent Feature, relative to the target given by the result of the targetArgument Expression, should be set to the result of the valueExpression.

Association

<http://open-services.net/ns/sysmlv2#Association>

Association is an RDFS class.

An Association is a Relationship and a Classifier to enable classification of links between things (in the universe). The co-domains (types) of the associationEnd Features are the relatedTypes, as co-domain and participants (linked things) of an Association identify each other.

AssociationStructure

<http://open-services.net/ns/sysmlv2#AssociationStructure>

AssociationStructure is an RDFS class.

An AssociationStructure is an Association that is also a Structure, classifying link objects that are both links and objects. As objects, link objects can be created and destroyed, and their non-end Features can change over time. However, the values of the end Features of a link object are fixed and cannot change over its lifetime.

AttributeDefinition

<http://open-services.net/ns/sysmlv2#AttributeDefinition>

AttributeDefinition is an RDFS class.

An AttributeDefinition is a Definition and a DataType of information about a quality or characteristic of a system or part of a system that has no independent identity other than its value. All features of an AttributeDefinition must be referential (non-composite).

AttributeUsage

<http://open-services.net/ns/sysmlv2#AttributeUsage>

AttributeUsage is an RDFS class.

An **AttributeUsage** is a **Usage** whose type is a **DataType**. Nominally, if the type is an **AttributeDefinition**, an **AttributeUsage** is a usage of a **AttributeDefinition** to represent the value of some system quality or characteristic. However, other kinds of kernel **DataTypes** are also allowed, to permit use of **DataTypes** from the Kernel Model Libraries. An **AttributeUsage** itself as well as all its nested features must be referential (non-composite).

Behavior

<http://open-services.net/ns/sysmlv2#Behavior>

Behavior is an RDFS class.

A **Behavior** coordinates occurrences of other **Behaviors**, as well as changes in objects. **Behaviors** can be decomposed into **Steps** and be characterized by parameters.

BindingConnector

<http://open-services.net/ns/sysmlv2#BindingConnector>

BindingConnector is an RDFS class.

A **BindingConnector** is a binary **Connector** that requires its related **Features** to identify the same things (have the same values).

BindingConnectorAsUsage

<http://open-services.net/ns/sysmlv2#BindingConnectorAsUsage>

BindingConnectorAsUsage is an RDFS class.

A **BindingConnectorAsUsage** is both a **BindingConnector** and a **ConnectorAsUsage**.

BooleanExpression

<http://open-services.net/ns/sysmlv2#BooleanExpression>

BooleanExpression is an RDFS class.

A **BooleanExpression** is a Boolean-valued **Expression** whose type is a **Predicate**. It represents a logical condition resulting from the evaluation of the **Predicate**.

CalculationDefinition

<http://open-services.net/ns/sysmlv2#CalculationDefinition>

CalculationDefinition is an RDFS class.

A **CalculationDefinition** is an **ActionDefinition** that also defines a **Function** producing a result.

CalculationUsage

<http://open-services.net/ns/sysmlv2#CalculationUsage>

CalculationUsage is an RDFS class.

A **CalculationUsage** is an **ActionUsage** that is also an **Expression**, and, so, is typed by a **Function**. Nominally, if the type is a **CalculationDefinition**, a **CalculationUsage** is a **Usage** of that **CalculationDefinition** within a system. However, other kinds of kernel **Functions** are also allowed, to permit use of **Functions** from the Kernel Model Libraries.

CaseDefinition

<http://open-services.net/ns/sysmlv2#CaseDefinition>

CaseDefinition is an RDFS class.

A *CaseDefinition* is a *CalculationDefinition* for a process, often involving collecting evidence or data, relative to a subject, possibly involving the collaboration of one or more other actors, producing a result that meets an objective.

CaseUsage

<http://open-services.net/ns/sysmlv2#CaseUsage>

CaseUsage is an RDFS class.

A *CaseUsage* is a *Usage* of a *CaseDefinition*.

Class

<http://open-services.net/ns/sysmlv2#Class>

Class is an RDFS class.

A *Class* is a *Classifier* of things (in the universe) that can be distinguished without regard to how they are related to other things (via *Features*). This means multiple things classified by the same *Class* can be distinguished, even when they are related other things in exactly the same way.

Classifier

<http://open-services.net/ns/sysmlv2#Classifier>

Classifier is an RDFS class.

A *Classifier* is a *Type* that classifies:.

CollectExpression

<http://open-services.net/ns/sysmlv2#CollectExpression>

CollectExpression is an RDFS class.

A *CollectExpression* is an *OperatorExpression* whose operator is "collect", which resolves to the Function *ControlFunctions::collect* from the Kernel Functions Library.

Comment

<http://open-services.net/ns/sysmlv2#Comment>

Comment is an RDFS class.

A *Comment* is an *AnnotatingElement* whose body in some way describes its *annotatedElements*.

ConcernDefinition

<http://open-services.net/ns/sysmlv2#ConcernDefinition>

ConcernDefinition is an RDFS class.

A *ConcernDefinition* is a *RequirementDefinition* that one or more stakeholders may be interested in having addressed. These stakeholders are identified by the *ownedStakeholders* of the *ConcernDefinition*.

ConcernUsage

<http://open-services.net/ns/sysmlv2#ConcernUsage>

ConcernUsage is an RDFS class.

A ConcernUsage is a Usage of a ConcernDefinition.

ConjugatedPortDefinition

<http://open-services.net/ns/sysmlv2#ConjugatedPortDefinition>

ConjugatedPortDefinition is an RDFS class.

A ConjugatedPortDefinition is a PortDefinition that is a PortDefinition of its original PortDefinition. That is, a ConjugatedPortDefinition inherits all the features of the original PortDefinition, but input flows of the original PortDefinition become outputs on the ConjugatedPortDefinition and output flows of the original PortDefinition become inputs on the ConjugatedPortDefinition. Every PortDefinition (that is not itself a ConjugatedPortDefinition) has exactly one corresponding ConjugatedPortDefinition, whose effective name is the name of the originalPortDefinition, with the character ~ prepended.

ConjugatedPortTyping

<http://open-services.net/ns/sysmlv2#ConjugatedPortTyping>

ConjugatedPortTyping is an RDFS class.

A ConjugatedPortTyping is a FeatureTyping whose type is a ConjugatedPortDefinition. (This relationship is intended to be an abstract-syntax marker for a special surface notation for conjugated typing of ports.).

Conjugation

<http://open-services.net/ns/sysmlv2#Conjugation>

Conjugation is an RDFS class.

Conjugation is a Relationship between two types in which the conjugatedType inherits all the Features of the originalType, but with all input and output Features reversed. That is, any Features with a direction in relative to the originalType are considered to have an effective direction of out relative to the conjugatedType and, similarly, Features with direction out in the originalType are considered to have an effective direction of in in the conjugatedType. Features with direction inout, or with no direction, in the originalType, are inherited without change.

ConnectionDefinition

<http://open-services.net/ns/sysmlv2#ConnectionDefinition>

ConnectionDefinition is an RDFS class.

A ConnectionDefinition is a PartDefinition that is also an AssociationStructure. The end Features of a ConnectionDefinition must be Usages.

ConnectionUsage

<http://open-services.net/ns/sysmlv2#ConnectionUsage>

ConnectionUsage is an RDFS class.

A ConnectionUsage is a ConnectorAsUsage that is also a PartUsage. Nominally, if its type is a ConnectionDefinition, then a ConnectionUsage is a Usage of that ConnectionDefinition, representing a connection between parts of a system. However, other kinds of kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model

Libraries.

Connector

<http://open-services.net/ns/sysmlv2#Connector>

Connector is an RDFS class.

A Connector is a usage of Associations, with links restricted according to instances of the Type in which they are used (domain of the Connector). The associations of the Connector restrict what kinds of things might be linked. The Connector further restricts these links to be between values of Features on instances of its domain.

ConnectorAsUsage

<http://open-services.net/ns/sysmlv2#ConnectorAsUsage>

ConnectorAsUsage is an RDFS class.

A ConnectorAsUsage is both a Connector and a Usage. ConnectorAsUsage cannot itself be instantiated in a SysML model, but it is the base class for the concrete classes BindingConnectorAsUsage, SuccessionAsUsage and ConnectionUsage.

ConstraintDefinition

<http://open-services.net/ns/sysmlv2#ConstraintDefinition>

ConstraintDefinition is an RDFS class.

A ConstraintDefinition is an OccurrenceDefinition that is also a Predicate that defines a constraint that may be asserted to hold on a system or part of a system.

ConstraintUsage

<http://open-services.net/ns/sysmlv2#ConstraintUsage>

ConstraintUsage is an RDFS class.

A ConstraintUsage is an OccurrenceUsage that is also a BooleanExpression, and, so, is typed by a Predicate. Nominally, if the type is a ConstraintDefinition, a ConstraintUsage is a Usage of that ConstraintDefinition. However, other kinds of kernel Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.

ControlNode

<http://open-services.net/ns/sysmlv2#ControlNode>

ControlNode is an RDFS class.

A ControlNode is an ActionUsage that does not have any inherent behavior but provides constraints on incoming and outgoing Successions that are used to control other Actions. A ControlNode must be a composite owned usage of an ActionDefinition or ActionUsage.

DataType

<http://open-services.net/ns/sysmlv2#DataType>

DataType is an RDFS class.

A DataType is a Classifier of things (in the universe) that can only be distinguished by how they are related to other things (via Features). This means multiple things classified by the same DataType.

DecisionNode

<http://open-services.net/ns/sysmlv2#DecisionNode>

DecisionNode is an RDFS class.

A *DecisionNode* is a *ControlNode* that makes a selection from its outgoing Successions.

Definition

<http://open-services.net/ns/sysmlv2#Definition>

Definition is an RDFS class.

A *Definition* is a *Classifier* of *Usages*. The actual kinds of *Definition* that may appear in a model are given by the subclasses of *Definition* (possibly as extended with user-defined *SemanticMetadata*).

Dependency

<http://open-services.net/ns/sysmlv2#Dependency>

Dependency is an RDFS class.

A *Dependency* is a *Relationship* that indicates that one or more client *Elements* require one more supplier *Elements* for their complete specification. In general, this means that a change to one of the supplier *Elements* may necessitate a change to, or re-specification of, the client *Elements*.

Differencing

<http://open-services.net/ns/sysmlv2#Differencing>

Differencing is an RDFS class.

Differencing is a *Relationship* that makes its *differencingType* one of the *differencingTypes* of its *typeDifferenced*.

Disjoining

<http://open-services.net/ns/sysmlv2#Disjoining>

Disjoining is an RDFS class.

A *Disjoining* is a *Relationship* between *Types* asserted to have interpretations that are not shared (disjoint) between them, identified as *typeDisjoined* and *disjoiningType*. For example, a *Classifier* for mammals is disjoint from a *Classifier* for minerals, and a *Feature* for people's parents is disjoint from a *Feature* for their children.

Documentation

<http://open-services.net/ns/sysmlv2#Documentation>

Documentation is an RDFS class.

Documentation is a *Comment* that specifically documents a *documentedElement*, which must be its owner.

Element

<http://open-services.net/ns/sysmlv2#Element>

Element is an RDFS class.

An Element is a constituent of a model that is uniquely identified relative to all other Elements. It can have Relationships with other Elements. Some of these Relationships might imply ownership of other Elements, which means that if an Element is deleted from a model, then so are all the Elements that it owns.

ElementFilterMembership

<http://open-services.net/ns/sysmlv2#ElementFilterMembership>

ElementFilterMembership is an RDFS class.

ElementFilterMembership is a Membership between a Namespace and a model-level evaluable Boolean-valued Expression, asserting that imported members of the Namespace should be filtered using the condition Expression. A general Namespace does not define any specific filtering behavior, but such behavior may be defined for various specialized kinds of Namespaces.

EndFeatureMembership

<http://open-services.net/ns/sysmlv2#EndFeatureMembership>

EndFeatureMembership is an RDFS class.

EndFeatureMembership is a FeatureMembership that requires its memberFeature be owned and have isEnd = true.

EnumerationDefinition

<http://open-services.net/ns/sysmlv2#EnumerationDefinition>

EnumerationDefinition is an RDFS class.

An EnumerationDefinition is an AttributeDefinition all of whose instances are given by an explicit list of enumeratedValues. This is realized by requiring that the EnumerationDefinition have isVariation = true, with the enumeratedValues being its variants.

EnumerationUsage

<http://open-services.net/ns/sysmlv2#EnumerationUsage>

EnumerationUsage is an RDFS class.

An EnumerationUsage is an AttributeUsage whose attributeDefinition is an EnumerationDefinition.

EventOccurrenceUsage

<http://open-services.net/ns/sysmlv2#EventOccurrenceUsage>

EventOccurrenceUsage is an RDFS class.

An EventOccurrenceUsage is an OccurrenceUsage that represents another OccurrenceUsage occurring as a suboccurrence of the containing occurrence of the EventOccurrenceUsage. Unless it is the EventOccurrenceUsage itself, the referenced OccurrenceUsage is related to the EventOccurrenceUsage by a ReferenceSubsetting Relationship.

ExhibitStateUsage

<http://open-services.net/ns/sysmlv2#ExhibitStateUsage>

ExhibitStateUsage is an RDFS class.

An ExhibitStateUsage is a StateUsage that represents the exhibiting of a StateUsage. Unless it is the StateUsage itself, the StateUsage to be exhibited is related to the ExhibitStateUsage by a ReferenceSubsetting Relationship. An ExhibitStateUsage

is also a `PerformActionUsage`, with its `exhibitedState` as the `performedAction`.

Expose

<http://open-services.net/ns/sysmlv2#Expose>

Expose is an RDFS class.

An *Expose* is an *Import of Memberships* into a *ViewUsage* that provide the *Elements* to be included in a view. Visibility is always ignored for an *Expose* (i.e., `isImportAll` = true).

Expression

<http://open-services.net/ns/sysmlv2#Expression>

Expression is an RDFS class.

An *Expression* is a *Step* that is typed by a *Function*. An *Expression* that also has a *Function* as its *featuringType* is a computational step within that *Function*. An *Expression* always has a single result parameter, which redefines the result parameter of its defining function. This allows *Expressions* to be interconnected in tree structures, in which inputs to each *Expression* in the tree are determined as the results of other *Expression* in the tree.

Feature

<http://open-services.net/ns/sysmlv2#Feature>

Feature is an RDFS class.

A *Feature* is a *Type* that classifies relations between multiple things (in the universe). The domain of the relation is the intersection of the *featuringTypes* of the *Feature*. (The domain of a *Feature* with no *featuringTypes* is implicitly the most general *Type* `Base::Anything` from the Kernel Semantic Library.) The co-domain of the relation is the intersection of the types of the *Feature*.

FeatureChainExpression

<http://open-services.net/ns/sysmlv2#FeatureChainExpression>

FeatureChainExpression is an RDFS class.

A *FeatureChainExpression* is an *OperatorExpression* whose operator is ".", which resolves to the *Function* `ControlFunctions::'` from the Kernel Functions Library. It evaluates to the result of chaining the result *Feature* of its single argument *Expression* with its *targetFeature*.

FeatureChaining

<http://open-services.net/ns/sysmlv2#FeatureChaining>

FeatureChaining is an RDFS class.

FeatureChaining is a *Relationship* that makes its target *Feature* one of the *chainingFeatures* of its owning *Feature*.

FeatureDirectionKind

<http://open-services.net/ns/sysmlv2#FeatureDirectionKind>

FeatureDirectionKind is an RDFS class.

FeatureDirectionKind enumerates the possible kinds of direction that a *Feature* may be given as a member of a *Type*.

FeatureInverting

<http://open-services.net/ns/sysmlv2#FeatureInverting>

FeatureInverting is an RDFS class.

A *FeatureInverting* is a Relationship between Features asserting that their interpretations (sequences) are the reverse of each other, identified as *featureInverted* and *invertingFeature*. For example, a Feature identifying each person's parents is the inverse of a Feature identifying each person's children. A person identified as a parent of another will identify that other as one of their children.

FeatureMembership

<http://open-services.net/ns/sysmlv2#FeatureMembership>

FeatureMembership is an RDFS class.

A *FeatureMembership* is an *OwningMembership* between a Feature in an *owningType* that is also a *Featuring* Relationship between the Feature and the Type, in which the *featuringType* is the source and the *featureOfType* is the target. A *FeatureMembership* is always owned by its *owningType*, which is the *featuringType* for the *FeatureMembership* considered as a *Featuring*.

FeatureReferenceExpression

<http://open-services.net/ns/sysmlv2#FeatureReferenceExpression>

FeatureReferenceExpression is an RDFS class.

A *FeatureReferenceExpression* is an Expression whose result is bound to a referent Feature.

FeatureTyping

<http://open-services.net/ns/sysmlv2#FeatureTyping>

FeatureTyping is an RDFS class.

FeatureTyping is Specialization in which the specific Type is a Feature. This means the set of instances of the (specific) *typedFeature* is a subset of the set of instances of the (general) type. In the simplest case, the type is a Classifier, whereupon the *typedFeature* has values that are instances of the Classifier.

FeatureValue

<http://open-services.net/ns/sysmlv2#FeatureValue>

FeatureValue is an RDFS class.

A *FeatureValue* is a Membership that identifies a particular member Expression that provides the value of the Feature that owns the *FeatureValue*. The value is specified as either a bound value or an initial value, and as either a concrete or default value. A Feature can have at most one *FeatureValue*.

Featuring

<http://open-services.net/ns/sysmlv2#Featuring>

Featuring is an RDFS class.

Featuring is a Relationship between a Type and a Feature that is featured by that Type. It asserts that every instance in the domain of the feature must be classified by the type.

FlowConnectionDefinition

<http://open-services.net/ns/sysmlv2#FlowConnectionDefinition>

FlowConnectionDefinition is an RDFS class.

A FlowConnectionDefinition is a ConnectionDefinition and ActionDefinition that is also an Interaction representing flows between Usages.

FlowConnectionUsage

<http://open-services.net/ns/sysmlv2#FlowConnectionUsage>

FlowConnectionUsage is an RDFS class.

A FlowConnectionUsage is a ConnectionUsage that is also an ItemFlow.

ForkNode

<http://open-services.net/ns/sysmlv2#ForkNode>

ForkNode is an RDFS class.

A ForkNode is a ControlNode that must be followed by successor Actions as given by all its outgoing Successions.

ForLoopActionUsage

<http://open-services.net/ns/sysmlv2#ForLoopActionUsage>

ForLoopActionUsage is an RDFS class.

A ForLoopActionUsage is a LoopActionUsage that specifies that its bodyAction ActionUsage should be performed once for each value, in order, from the sequence of values obtained as the result of the seqArgument Expression, with the loopVariable set to the value for each iteration.

FramedConcernMembership

<http://open-services.net/ns/sysmlv2#FramedConcernMembership>

FramedConcernMembership is an RDFS class.

A FramedConcernMembership is a RequirementConstraintMembership for a framed ConcernUsage of a RequirementDefinition or RequirementUsage.

Function

<http://open-services.net/ns/sysmlv2#Function>

Function is an RDFS class.

A Function is a Behavior that has an out parameter that is identified as its result. A Function represents the performance of a calculation that produces the values of its result parameter. This calculation may be decomposed into Expressions that are steps of the Function.

IfActionUsage

<http://open-services.net/ns/sysmlv2#IfActionUsage>

IfActionUsage is an RDFS class.

An **IfActionUsage** is an **ActionUsage** that specifies that the **thenAction** **ActionUsage** should be performed if the result of the **ifArgument** Expression is true. It may also optionally specify an **elseAction** **ActionUsage** that is performed if the result of the **ifArgument** is false.

Import

<http://open-services.net/ns/sysmlv2#Import>

Import is an RDFS class.

An **Import** is an **Relationship** between its **importOwningNamespace** and either a **Membership** (for a **MembershipImport**) or another **Namespace** (for a **NamespaceImport**), which determines a set of **Memberships** that become **importedMemberships** of the **importOwningNamespace**. If **isImportAll** = false (the default), then only public **Memberships** are considered "visible". If **isImportAll** = true, then all **Memberships** are considered "visible", regardless of their declared visibility. If **isRecursive** = true, then visible **Memberships** are also recursively imported from owned sub-Namespaces.

IncludeUseCaseUsage

<http://open-services.net/ns/sysmlv2#IncludeUseCaseUsage>

IncludeUseCaseUsage is an RDFS class.

An **IncludeUseCaseUsage** is a **UseCaseUsage** that represents the inclusion of a **UseCaseUsage** by a **UseCaseDefinition** or **UseCaseUsage**. Unless it is the **IncludeUseCaseUsage** itself, the **UseCaseUsage** to be included is related to the **includedUseCase** by a **ReferenceSubsetting** **Relationship**. An **IncludeUseCaseUsage** is also a **PerformActionUsage**, with its **useCaseIncluded** as the **performedAction**.

Interaction

<http://open-services.net/ns/sysmlv2#Interaction>

Interaction is an RDFS class.

An **Interaction** is a **Behavior** that is also an **Association**, providing a context for multiple objects that have behaviors that impact one another.

InterfaceDefinition

<http://open-services.net/ns/sysmlv2#InterfaceDefinition>

InterfaceDefinition is an RDFS class.

An **InterfaceDefinition** is a **ConnectionDefinition** all of whose ends are **PortUsages**, defining an interface between elements that interact through such ports.

InterfaceUsage

<http://open-services.net/ns/sysmlv2#InterfaceUsage>

InterfaceUsage is an RDFS class.

An **InterfaceUsage** is a **Usage** of an **InterfaceDefinition** to represent an interface connecting parts of a system through specific ports.

Intersecting

<http://open-services.net/ns/sysmlv2#Intersecting>

Intersecting is an RDFS class.

Intersecting is a Relationship that makes its intersectingType one of the intersectingTypes of its typeIntersected.

Invariant

<http://open-services.net/ns/sysmlv2#Invariant>

Invariant is an RDFS class.

An Invariant is a BooleanExpression that is asserted to have a specific Boolean result value. If isNegated = false, then the result is asserted to be true. If isNegated = true, then the result is asserted to be false.

InvocationExpression

<http://open-services.net/ns/sysmlv2#InvocationExpression>

InvocationExpression is an RDFS class.

An InvocationExpression is an Expression each of whose input parameters are bound to the result of an argument Expression.

ItemDefinition

<http://open-services.net/ns/sysmlv2#ItemDefinition>

ItemDefinition is an RDFS class.

An ItemDefinition is an OccurrenceDefinition of the Structure of things that may themselves be systems or parts of systems, but may also be things that are acted on by a system or parts of a system, but which do not necessarily perform actions themselves. This includes items that can be exchanged between parts of a system, such as water or electrical signals.

ItemFeature

<http://open-services.net/ns/sysmlv2#ItemFeature>

ItemFeature is an RDFS class.

An ItemFeature is the ownedFeature of an ItemFlow that identifies the things carried by the kinds of transfers that are instances of the ItemFlow.

ItemFlow

<http://open-services.net/ns/sysmlv2#ItemFlow>

ItemFlow is an RDFS class.

An ItemFlow is a Step that represents the transfer of objects or data values from one Feature to another. ItemFlows can take non-zero time to complete.

ItemFlowEnd

<http://open-services.net/ns/sysmlv2#ItemFlowEnd>

ItemFlowEnd is an RDFS class.

An ItemFlowEnd is a Feature that is one of the connectorEnds giving the source or target of an ItemFlow. For ItemFlows typed by FlowTransfer or its specializations, ItemFlowEnds must have exactly one ownedFeature, which redefines Transfer::source::sourceOutput or Transfer::target::targetInput and redefines the corresponding feature of the relatedElement for its end.

ItemUsage

<http://open-services.net/ns/sysmlv2#ItemUsage>

ItemUsage is an RDFS class.

An *ItemUsage* is a *ItemUsage* whose definition is a *Structure*. Nominally, if the definition is an *ItemDefinition*, an *ItemUsage* is a *ItemUsage* of that *ItemDefinition* within a system. However, other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Model Libraries.

JoinNode

<http://open-services.net/ns/sysmlv2#JoinNode>

JoinNode is an RDFS class.

A *JoinNode* is a *ControlNode* that waits for the completion of all the predecessor Actions given by incoming Successions.

LibraryPackage

<http://open-services.net/ns/sysmlv2#LibraryPackage>

LibraryPackage is an RDFS class.

A *LibraryPackage* is a *Package* that is the container for a model library. A *LibraryPackage* is itself a library Element as are all Elements that are directly or indirectly contained in it.

LifeClass

<http://open-services.net/ns/sysmlv2#LifeClass>

LifeClass is an RDFS class.

A *LifeClass* is a *Class* that specializes both the *Class Occurrences::Life* from the Kernel Semantic Library and a single *OccurrenceDefinition*, and has a multiplicity of 0..1. This constrains the *OccurrenceDefinition* being specialized to have at most one instance that is a complete *Life*.

LiteralBoolean

<http://open-services.net/ns/sysmlv2#LiteralBoolean>

LiteralBoolean is an RDFS class.

LiteralBoolean is a *LiteralExpression* that provides a Boolean value as a result. Its result parameter must have type Boolean.

LiteralExpression

<http://open-services.net/ns/sysmlv2#LiteralExpression>

LiteralExpression is an RDFS class.

A *LiteralExpression* is an *Expression* that provides a basic *DataValue* as a result.

LiteralInfinity

<http://open-services.net/ns/sysmlv2#LiteralInfinity>

LiteralInfinity is an RDFS class.

A **LiteralInfinity** is a **LiteralExpression** that provides the positive infinity value (*). Its result must have the type **Positive**.

LiteralInteger

<http://open-services.net/ns/sysmlv2#LiteralInteger>

LiteralInteger is an RDFS class.

A **LiteralInteger** is a **LiteralExpression** that provides an **Integer** value as a result. Its result parameter must have the type **Integer**.

LiteralRational

<http://open-services.net/ns/sysmlv2#LiteralRational>

LiteralRational is an RDFS class.

A **LiteralRational** is a **LiteralExpression** that provides a **Rational** value as a result. Its result parameter must have the type **Rational**.

LiteralString

<http://open-services.net/ns/sysmlv2#LiteralString>

LiteralString is an RDFS class.

A **LiteralString** is a **LiteralExpression** that provides a **String** value as a result. Its result parameter must have the type **String**.

LoopActionUsage

<http://open-services.net/ns/sysmlv2#LoopActionUsage>

LoopActionUsage is an RDFS class.

A **LoopActionUsage** is an **ActionUsage** that specifies that its **bodyAction** should be performed repeatedly. Its subclasses **WhileLoopActionUsage** and **ForLoopActionUsage** provide different ways to determine how many times the **bodyAction** should be performed.

Membership

<http://open-services.net/ns/sysmlv2#Membership>

Membership is an RDFS class.

A **Membership** is a **Relationship** between a **Namespace** and an **Element** that indicates the **Element** is a member of (i.e., is contained in) the **Namespace**. Any **memberNames** specify how the **memberElement** is identified in the **Namespace** and the **visibility** specifies whether or not the **memberElement** is publicly visible from outside the **Namespace**.

MembershipExpose

<http://open-services.net/ns/sysmlv2#MembershipExpose>

MembershipExpose is an RDFS class.

A **MembershipExpose** is an **Expose** that exposes a specific **importedMembership** and, if **isRecursive** = true, additional **Memberships** recursively.

MembershipImport

<http://open-services.net/ns/sysmlv2#MembershipImport>

MembershipImport is an RDFS class.

A MembershipImport is an Import that imports its importedMembership into the importOwningNamespace. If isRecursive = true and the memberElement of the importedMembership is a Namespace, then the equivalent of a recursive NamespaceImport is also performed on that Namespace.

MergeNode

<http://open-services.net/ns/sysmlv2#MergeNode>

MergeNode is an RDFS class.

A MergeNode is a ControlNode that asserts the merging of its incoming Successions. A MergeNode may have at most one outgoing Successions.

Metaclass

<http://open-services.net/ns/sysmlv2#Metaclass>

Metaclass is an RDFS class.

A Metaclass is a Structure used to type MetadataFeatures.

MetadataAccessExpression

<http://open-services.net/ns/sysmlv2#MetadataAccessExpression>

MetadataAccessExpression is an RDFS class.

A MetadataAccessExpression is an Expression whose result is a sequence of instances of Metaclasses representing all the MetadataFeature annotations of the referencedElement. In addition, the sequence includes an instance of the reflective Metaclass corresponding to the MOF class of the referencedElement, with values for all the abstract syntax properties of the referencedElement.

MetadataDefinition

<http://open-services.net/ns/sysmlv2#MetadataDefinition>

MetadataDefinition is an RDFS class.

A MetadataDefinition is an ItemDefinition that is also a Metaclass.

MetadataFeature

<http://open-services.net/ns/sysmlv2#MetadataFeature>

MetadataFeature is an RDFS class.

A MetadataFeature is a Feature that is an AnnotatingElement used to annotate another Element with metadata. It is typed by a Metaclass. All its ownedFeatures must redefine features of its metaclass and any feature bindings must be model-level evaluable.

MetadataUsage

<http://open-services.net/ns/sysmlv2#MetadataUsage>

MetadataUsage is an RDFS class.

A **MetadataUsage** is a **Usage** and a **MetadataFeature**, used to annotate other **Elements** in a system model with metadata. As a **MetadataFeature**, its type must be a **Metaclass**, which will nominally be a **MetadataDefinition**. However, any kernel **Metaclass** is also allowed, to permit use of **Metaclasses** from the **Kernel Model Libraries**.

Multiplicity

<http://open-services.net/ns/sysmlv2#Multiplicity>

Multiplicity is an RDFS class.

A **Multiplicity** is a **Feature** whose co-domain is a set of natural numbers giving the allowed cardinalities of each **typeWithMultiplicity**. The cardinality of a **Type** is defined as follows, depending on whether the **Type** is a **Classifier** or **Feature**. .

MultiplicityRange

<http://open-services.net/ns/sysmlv2#MultiplicityRange>

MultiplicityRange is an RDFS class.

A **MultiplicityRange** is a **Multiplicity** whose value is defined to be the (inclusive) range of natural numbers given by the result of a **lowerBound** Expression and the result of an **upperBound** Expression. The result of these Expressions shall be of type **Natural**. If the result of the **upperBound** Expression is the unbounded value *****, then the specified range includes all natural numbers greater than or equal to the **lowerBound** value. If no **lowerBound** Expression, then the default is that the lower bound has the same value as the upper bound, except if the **upperBound** evaluates to *****, in which case the default for the lower bound is 0.

Namespace

<http://open-services.net/ns/sysmlv2#Namespace>

Namespace is an RDFS class.

A **Namespace** is an **Element** that contains other **Elements**, known as its members, via **Membership Relationships** with those **Elements**. The members of a **Namespace** may be owned by the **Namespace**, aliased in the **Namespace**, or imported into the **Namespace** via **Import Relationships**.

NamespaceExpose

<http://open-services.net/ns/sysmlv2#NamespaceExpose>

NamespaceExpose is an RDFS class.

A **NamespaceExpose** is an **Expose Relationship** that exposes the **Memberships** of a specific **importedNamespace** and, if **isRecursive** = true, additional **Memberships** recursively.

NamespaceImport

<http://open-services.net/ns/sysmlv2#NamespaceImport>

NamespaceImport is an RDFS class.

A **NamespaceImport** is an **Import** that imports **Memberships** from its **importedNamespace** into the **importOwningNamespace**. If **isRecursive** = false, then only the visible **Memberships** of the **importedNamespace** are imported. If **isRecursive** = true, then, in addition, **Memberships** are recursively imported from any owned **Members** of the **importedNamespace** that are **Namespaces**.

NullExpression

<http://open-services.net/ns/sysmlv2#NullExpression>

NullExpression is an RDFS class.

A *NullExpression* is an *Expression* that results in a null value.

ObjectiveMembership

<http://open-services.net/ns/sysmlv2#ObjectiveMembership>

ObjectiveMembership is an RDFS class.

An *ObjectiveMembership* is a *FeatureMembership* that indicates that its owned *ObjectiveRequirement* is the objective *RequirementUsage* for its owning *Type*, which must be a *CaseDefinition* or *CaseUsage*.

OccurrenceDefinition

<http://open-services.net/ns/sysmlv2#OccurrenceDefinition>

OccurrenceDefinition is an RDFS class.

An *OccurrenceDefinition* is a *Definition* of a *Class* of individuals that have an independent life over time and potentially an extent over space. This includes both structural things and behaviors that act on such structures.

OccurrenceUsage

<http://open-services.net/ns/sysmlv2#OccurrenceUsage>

OccurrenceUsage is an RDFS class.

An *OccurrenceUsage* is a *Usage* whose types are all *Classes*. Nominally, if a type is an *OccurrenceDefinition*, an *OccurrenceUsage* is a *Usage* of that *OccurrenceDefinition* within a system. However, other types of *Kernel Classes* are also allowed, to permit use of *Classes* from the *Kernel Model Libraries*.

OperatorExpression

<http://open-services.net/ns/sysmlv2#OperatorExpression>

OperatorExpression is an RDFS class.

An *OperatorExpression* is an *InvocationExpression* whose function is determined by resolving its operator in the context of one of the standard packages from the *Kernel Function Library*.

OwningMembership

<http://open-services.net/ns/sysmlv2#OwningMembership>

OwningMembership is an RDFS class.

An *OwningMembership* is a *Membership* that owns its *memberElement* as a *ownedRelatedElement*. The *ownedMemberElement* becomes an *ownedMember* of the *membershipOwningNamespace*.

Package

<http://open-services.net/ns/sysmlv2#Package>

Package is an RDFS class.

A *Package* is a *Namespace* used to group *Elements*, without any instance-level semantics. It may have one or more model-level evaluable *filterCondition Expressions* used to filter its imported *Memberships*. Any imported member must meet all of the *filterConditions*.

ParameterMembership

<http://open-services.net/ns/sysmlv2#ParameterMembership>

ParameterMembership is an RDFS class.

A *ParameterMembership* is a *FeatureMembership* that identifies its *memberFeature* as a parameter, which is always owned, and must have a direction. A *ParameterMembership* must be owned by a *Behavior* or a *Step*.

PartDefinition

<http://open-services.net/ns/sysmlv2#PartDefinition>

PartDefinition is an RDFS class.

A *PartDefinition* is an *ItemDefinition* of a Class of systems or parts of systems. Note that all parts may be considered items for certain purposes, but not all items are parts that can perform actions within a system.

PartUsage

<http://open-services.net/ns/sysmlv2#PartUsage>

PartUsage is an RDFS class.

A *PartUsage* is a usage of a *PartDefinition* to represent a system or a part of a system. At least one of the *itemDefinitions* of the *PartUsage* must be a *PartDefinition*.

PerformActionUsage

<http://open-services.net/ns/sysmlv2#PerformActionUsage>

PerformActionUsage is an RDFS class.

A *PerformActionUsage* is an *ActionUsage* that represents the performance of an *ActionUsage*. Unless it is the *PerformActionUsage* itself, the *ActionUsage* to be performed is related to the *PerformActionUsage* by a *ReferenceSubsetting* relationship. A *PerformActionUsage* is also an *EventOccurrenceUsage*, with its *performedAction* as the *eventOccurrence*.

PortConjugation

<http://open-services.net/ns/sysmlv2#PortConjugation>

PortConjugation is an RDFS class.

A *PortConjugation* is a *Conjugation Relationship* between a *PortDefinition* and its corresponding *ConjugatedPortDefinition*. As a result of this Relationship, the *ConjugatedPortDefinition* inherits all the features of the original *PortDefinition*, but input flows of the original *PortDefinition* become outputs on the *ConjugatedPortDefinition* and output flows of the original *PortDefinition* become inputs on the *ConjugatedPortDefinition*.

PortDefinition

<http://open-services.net/ns/sysmlv2#PortDefinition>

PortDefinition is an RDFS class.

A *PortDefinition* defines a point at which external entities can connect to and interact with a system or part of a system. Any ownedUsages of a *PortDefinition*, other than *PortUsages*, must not be composite.

PortionKind

<http://open-services.net/ns/sysmlv2#PortionKind>

PortionKind is an RDFS class.

PortionKind is an enumeration of the specific kinds of Occurrence portions that can be represented by an OccurrenceUsage.

PortUsage

<http://open-services.net/ns/sysmlv2#PortUsage>

PortUsage is an RDFS class.

A PortUsage is a usage of a PortDefinition. A PortUsage itself as well as all its nestedUsages must be referential (non-composite).

Predicate

<http://open-services.net/ns/sysmlv2#Predicate>

Predicate is an RDFS class.

A Predicate is a Function whose result parameter has type Boolean and multiplicity 1..1.

Redefinition

<http://open-services.net/ns/sysmlv2#Redefinition>

Redefinition is an RDFS class.

Redefinition is a kind of Subsetting that requires the redefinedFeature and the redefiningFeature to have the same values (on each instance of the domain of the redefiningFeature). This means any restrictions on the redefiningFeature, such as type or multiplicity, also apply to the redefinedFeature (on each instance of the domain of the redefiningFeature), and vice versa. The redefinedFeature might have values for instances of the domain of the redefiningFeature, but only as instances of the domain of the redefinedFeature that happen to also be instances of the domain of the redefiningFeature. This is supported by the constraints inherited from Subsetting on the domains of the redefiningFeature and redefinedFeature. However, these constraints are narrowed for Redefinition to require the owningTypes of the redefiningFeature and redefinedFeature to be different and the redefinedFeature to not be inherited into the owningNamespace of the redefiningFeature. This enables the redefiningFeature to have the same name as the redefinedFeature, if desired.

ReferenceSubsetting

<http://open-services.net/ns/sysmlv2#ReferenceSubsetting>

ReferenceSubsetting is an RDFS class.

ReferenceSubsetting is a kind of Subsetting in which the referencedFeature is syntactically distinguished from other Features subsetting by the referencingFeature. ReferenceSubsetting has the same semantics as Subsetting, but the referenceFeature may have a special purpose relative to the referencingFeature. For instance, ReferenceSubsetting is used to identify the relatedFeatures of a Connector.

ReferenceUsage

<http://open-services.net/ns/sysmlv2#ReferenceUsage>

ReferenceUsage is an RDFS class.

A ReferenceUsage is a Usage that specifies a non-compositional (isComposite = false) reference to something. The definition of a ReferenceUsage can be any kind of Classifier, with the default being the top-level Classifier Base::Anything from the Kernel Semantic Library. This allows the specification of a generic reference without distinguishing if the thing referenced is an

attribute value, item, action, etc.

Relationship

<http://open-services.net/ns/sysmlv2#Relationship>

Relationship is an RDFS class.

A Relationship is an Element that relates other Element. Some of its relatedElements may be owned, in which case those ownedRelatedElements will be deleted from a model if their owningRelationship is. A Relationship may also be owned by another Element, in which case the ownedRelatedElements of the Relationship are also considered to be transitively owned by the owningRelatedElement of the Relationship.

RenderingDefinition

<http://open-services.net/ns/sysmlv2#RenderingDefinition>

RenderingDefinition is an RDFS class.

A RenderingDefinition is a PartDefinition that defines a specific rendering of the content of a model view (e.g., symbols, style, layout, etc.).

RenderingUsage

<http://open-services.net/ns/sysmlv2#RenderingUsage>

RenderingUsage is an RDFS class.

A RenderingUsage is the usage of a RenderingDefinition to specify the rendering of a specific model view to produce a physical view artifact.

RequirementConstraintKind

<http://open-services.net/ns/sysmlv2#RequirementConstraintKind>

RequirementConstraintKind is an RDFS class.

A RequirementConstraintKind indicates whether a ConstraintUsage is an assumption or a requirement in a RequirementDefinition or RequirementUsage.

RequirementConstraintMembership

<http://open-services.net/ns/sysmlv2#RequirementConstraintMembership>

RequirementConstraintMembership is an RDFS class.

A RequirementConstraintMembership is a FeatureMembership for an assumed or required ConstraintUsage of a RequirementDefinition or RequirementUsage.

RequirementDefinition

<http://open-services.net/ns/sysmlv2#RequirementDefinition>

RequirementDefinition is an RDFS class.

A RequirementDefinition is a ConstraintDefinition that defines a requirement used in the context of a specification as a constraint that a valid solution must satisfy. The specification is relative to a specified subject, possibly in collaboration with one or more external actors.

RequirementUsage

<http://open-services.net/ns/sysmlv2#RequirementUsage>

RequirementUsage is an RDFS class.

A RequirementUsage is a Usage of a RequirementDefinition.

RequirementVerificationMembership

<http://open-services.net/ns/sysmlv2#RequirementVerificationMembership>

RequirementVerificationMembership is an RDFS class.

A RequirementVerificationMembership is a RequirementConstraintMembership used in the objective of a VerificationCase to identify a RequirementUsage that is verified by the VerificationCase.

ResultExpressionMembership

<http://open-services.net/ns/sysmlv2#ResultExpressionMembership>

ResultExpressionMembership is an RDFS class.

A ResultExpressionMembership is a FeatureMembership that indicates that the ownedResultExpression provides the result values for the Function or Expression that owns it. The owning Function or Expression must contain a BindingConnector between the result parameter of the ownedResultExpression and the result parameter of the owning Function or Expression.

ReturnParameterMembership

<http://open-services.net/ns/sysmlv2#ReturnParameterMembership>

ReturnParameterMembership is an RDFS class.

A ReturnParameterMembership is a ParameterMembership that indicates that the ownedMemberParameter is the result parameter of a Function or Expression. The direction of the ownedMemberParameter must be out.

SatisfyRequirementUsage

<http://open-services.net/ns/sysmlv2#SatisfyRequirementUsage>

SatisfyRequirementUsage is an RDFS class.

A SatisfyRequirementUsage is an AssertConstraintUsage that asserts, by default, that a satisfied RequirementUsage is true for a specific satisfyingFeature, or, if isNegated = true, that the RequirementUsage is false. The satisfied RequirementUsage is related to the SatisfyRequirementUsage by a ReferenceSubsetting Relationship.

SelectExpression

<http://open-services.net/ns/sysmlv2#SelectExpression>

SelectExpression is an RDFS class.

A SelectExpression is an OperatorExpression whose operator is "select", which resolves to the Function ControlFunctions::select from the Kernel Functions Library.

SendActionUsage

<http://open-services.net/ns/sysmlv2#SendActionUsage>

SendActionUsage is an RDFS class.

A *SendActionUsage* is an *ActionUsage* that specifies the sending of a payload given by the result of its *payloadArgument* Expression via a *MessageTransfer* whose source is given by the result of the *senderArgument* Expression and whose target is given by the result of the *receiverArgument* Expression. If no *senderArgument* is provided, the default is the this context for the action. If no *receiverArgument* is given, then the receiver is to be determined by, e.g., outgoing Connections from the sender.

Specialization

<http://open-services.net/ns/sysmlv2#Specialization>

Specialization is an RDFS class.

Specialization is a Relationship between two Types that requires all instances of the specific type to also be instances of the general Type (i.e., the set of instances of the specific Type is a subset of those of the general Type, which might be the same set).

StakeholderMembership

<http://open-services.net/ns/sysmlv2#StakeholderMembership>

StakeholderMembership is an RDFS class.

A *StakeholderMembership* is a *ParameterMembership* that identifies a *PartUsage* as a *stakeholderParameter* of a *RequirementDefinition* or *RequirementUsage*, which specifies a role played by an entity with concerns framed by the owning Type.

StateDefinition

<http://open-services.net/ns/sysmlv2#StateDefinition>

StateDefinition is an RDFS class.

A *StateDefinition* is the Definition of the Behavior of a system or part of a system in a certain state condition.

StateSubactionKind

<http://open-services.net/ns/sysmlv2#StateSubactionKind>

StateSubactionKind is an RDFS class.

A *StateSubactionKind* indicates whether the action of a *StateSubactionMembership* is an entry, do or exit action.

StateSubactionMembership

<http://open-services.net/ns/sysmlv2#StateSubactionMembership>

StateSubactionMembership is an RDFS class.

A *StateSubactionMembership* is a *FeatureMembership* for an entry, do or exit *ActionUsage* of a *StateDefinition* or *StateUsage*.

StateUsage

<http://open-services.net/ns/sysmlv2#StateUsage>

StateUsage is an RDFS class.

A *StateUsage* is an *ActionUsage* that is nominally the Usage of a *StateDefinition*. However, other kinds of kernel Behaviors

are also allowed as types, to permit use of Behaviors .

Step

<http://open-services.net/ns/sysmlv2#Step>

Step is an RDFS class.

A Step is a Feature that is typed by one or more Behaviors. Steps may be used by one Behavior to coordinate the performance of other Behaviors, supporting a steady refinement of behavioral descriptions. Steps can be ordered in time and can be connected using ItemFlows to specify things flowing between their parameters.

Structure

<http://open-services.net/ns/sysmlv2#Structure>

Structure is an RDFS class.

A Structure is a Class of objects in the modeled universe that are primarily structural in nature. While such an object is not itself behavioral, it may be involved in and acted on by Behaviors, and it may be the performer of some of them.

Subclassification

<http://open-services.net/ns/sysmlv2#Subclassification>

Subclassification is an RDFS class.

Subclassification is Specialization in which both the specific and general Types are Classifier. This means all instances of the specific Classifier are also instances of the general Classifier.

SubjectMembership

<http://open-services.net/ns/sysmlv2#SubjectMembership>

SubjectMembership is an RDFS class.

A SubjectMembership is a ParameterMembership that indicates that its ownedSubjectParameter is the subject of its owningType. The owningType of a SubjectMembership must be a RequirementDefinition, RequirementUsage, CaseDefinition, or CaseUsage.

Subsetting

<http://open-services.net/ns/sysmlv2#Subsetting>

Subsetting is an RDFS class.

Subsetting is Specialization in which the specific and general Types are Features. This means all values of the subsettingFeature (on instances of its domain, i.e., the intersection of its featuringTypes) are values of the subsettedFeature on instances of its domain. To support this the domain of the subsettingFeature must be the same or specialize (at least indirectly) the domain of the subsettedFeature (via Specialization), and the co-domain (intersection of the types) of the subsettingFeature must specialize the co-domain of the subsettedFeature.

Succession

<http://open-services.net/ns/sysmlv2#Succession>

Succession is an RDFS class.

A Succession is a binary Connector that requires its relatedFeatures to happen separately in time.

SuccessionAsUsage

<http://open-services.net/ns/sysmlv2#SuccessionAsUsage>

SuccessionAsUsage is an RDFS class.

A SuccessionAsUsage is both a ConnectorAsUsage and a Succession.

SuccessionFlowConnectionUsage

<http://open-services.net/ns/sysmlv2#SuccessionFlowConnectionUsage>

SuccessionFlowConnectionUsage is an RDFS class.

A SuccessionFlowConnectionUsage is a FlowConnectionUsage that is also a SuccessionItemFlow.

SuccessionItemFlow

<http://open-services.net/ns/sysmlv2#SuccessionItemFlow>

SuccessionItemFlow is an RDFS class.

A SuccessionItemFlow is an ItemFlow that also provides temporal ordering. It classifies Transfers that cannot start until the source Occurrence has completed and that must complete before the target Occurrence can start.

TextualRepresentation

<http://open-services.net/ns/sysmlv2#TextualRepresentation>

TextualRepresentation is an RDFS class.

A TextualRepresentation is an AnnotatingElement whose body represents the representedElement in a given language. The representedElement must be the owner of the TextualRepresentation. The named language can be a natural language, in which case the body is an informal representation, or an artificial language, in which case the body is expected to be a formal, machine-parsable representation.

TransitionFeatureKind

<http://open-services.net/ns/sysmlv2#TransitionFeatureKind>

TransitionFeatureKind is an RDFS class.

A TransitionActionKind indicates whether the transitionFeature of a TransitionFeatureMembership is a trigger, guard or effect.

TransitionFeatureMembership

<http://open-services.net/ns/sysmlv2#TransitionFeatureMembership>

TransitionFeatureMembership is an RDFS class.

A TransitionFeatureMembership is a FeatureMembership for a trigger, guard or effect of a TransitionUsage, whose transitionFeature is a AcceptActionUsage, Boolean-valued Expression or ActionUsage, depending on its kind. .

TransitionUsage

<http://open-services.net/ns/sysmlv2#TransitionUsage>

TransitionUsage is an RDFS class.

A *TransitionUsage* is an *ActionUsage* representing a triggered transition between *ActionUsages* or *StateUsages*. When triggered by a *triggerAction*, when its *guardExpression* is true, the *TransitionUsage* asserts that its source is exited, then its *effectAction* (if any) is performed, and then its target is entered.

TriggerInvocationExpression

<http://open-services.net/ns/sysmlv2#TriggerInvocationExpression>

TriggerInvocationExpression is an RDFS class.

A *TriggerInvocationExpression* is an *InvocationExpression* that invokes one of the trigger Functions from the Kernel Semantic Library Triggers package, as indicated by its *kind*.

TriggerKind

<http://open-services.net/ns/sysmlv2#TriggerKind>

TriggerKind is an RDFS class.

TriggerKind enumerates the kinds of triggers that can be represented by a *TriggerInvocationExpression*.

Type

<http://open-services.net/ns/sysmlv2#Type>

Type is an RDFS class.

A *Type* is a *Namespace* that is the most general kind of *Element* supporting the semantics of classification. A *Type* may be a *Classifier* or a *Feature*, defining conditions on what is classified by the *Type* (see also the description of *isSufficient*).

TypeFeaturing

<http://open-services.net/ns/sysmlv2#TypeFeaturing>

TypeFeaturing is an RDFS class.

A *TypeFeaturing* is a *Featuring Relationship* in which the *featureOfType* is the source and the *featuringType* is the target.

Unioning

<http://open-services.net/ns/sysmlv2#Unioning>

Unioning is an RDFS class.

Unioning is a *Relationship* that makes its *unioningType* one of the *unioningTypes* of its *typeUnioned*.

Usage

<http://open-services.net/ns/sysmlv2#Usage>

Usage is an RDFS class.

A *Usage* is a usage of a *Definition*. A *Usage* may only be an *ownedFeature* of a *Definition* or another *Usage*.

UseCaseDefinition

<http://open-services.net/ns/sysmlv2#UseCaseDefinition>

UseCaseDefinition is an RDFS class.

A *UseCaseDefinition* is a *CaseDefinition* that specifies a set of actions performed by its subject, in interaction with one or more actors external to the subject. The objective is to yield an observable result that is of value to one or more of the actors.

UseCaseUsage

<http://open-services.net/ns/sysmlv2#UseCaseUsage>

UseCaseUsage is an RDFS class.

A *UseCaseUsage* is a *Usage* of a *UseCaseDefinition*.

VariantMembership

<http://open-services.net/ns/sysmlv2#VariantMembership>

VariantMembership is an RDFS class.

A *VariantMembership* is a *Membership* between a variation point *Definition* or *Usage* and a *Usage* that represents a variant in the context of that variation. The *membershipOwningNamespace* for the *VariantMembership* must be either a *Definition* or a *Usage* with *isVariation* = true.

VerificationCaseDefinition

<http://open-services.net/ns/sysmlv2#VerificationCaseDefinition>

VerificationCaseDefinition is an RDFS class.

A *VerificationCaseDefinition* is a *CaseDefinition* for the purpose of verification of the subject of the case against its requirements.

VerificationCaseUsage

<http://open-services.net/ns/sysmlv2#VerificationCaseUsage>

VerificationCaseUsage is an RDFS class.

A *VerificationCaseUsage* is a *Usage* of a *VerificationCaseDefinition*.

ViewDefinition

<http://open-services.net/ns/sysmlv2#ViewDefinition>

ViewDefinition is an RDFS class.

A *ViewDefinition* is a *PartDefinition* that specifies how a view artifact is constructed to satisfy a viewpoint. It specifies a *viewConditions* to define the model content to be presented and a *viewRendering* to define how the model content is presented.

ViewpointDefinition

<http://open-services.net/ns/sysmlv2#ViewpointDefinition>

ViewpointDefinition is an RDFS class.

A *ViewpointDefinition* is a *RequirementDefinition* that specifies one or more stakeholder concerns that are to be satisfied by

creating a view of a model.

ViewpointUsage

<http://open-services.net/ns/sysmlv2#ViewpointUsage>

ViewpointUsage is an RDFS class.

A ViewpointUsage is a Usage of a ViewpointDefinition.

ViewRenderingMembership

<http://open-services.net/ns/sysmlv2#ViewRenderingMembership>

ViewRenderingMembership is an RDFS class.

A ViewRenderingMembership is a FeatureMembership that identifies the viewRendering of a ViewDefinition or ViewUsage.

ViewUsage

<http://open-services.net/ns/sysmlv2#ViewUsage>

ViewUsage is an RDFS class.

A ViewUsage is a usage of a ViewDefinition to specify the generation of a view of the members of a collection of exposedNamespaces. The ViewUsage can satisfy more viewpoints than its definition, and it can specialize the viewRendering specified by its definition.

VisibilityKind

<http://open-services.net/ns/sysmlv2#VisibilityKind>

VisibilityKind is an RDFS class.

VisibilityKind is an enumeration whose literals specify the visibility of a Membership of an Element in a Namespace outside of that Namespace. Note that "visibility" specifically restricts whether an Element in a Namespace may be referenced by name from outside the Namespace and only otherwise restricts access to an Element as provided by specific constraints in the abstract syntax (e.g., preventing the import or inheritance of private Elements).

WhileLoopActionUsage

<http://open-services.net/ns/sysmlv2#WhileLoopActionUsage>

WhileLoopActionUsage is an RDFS class.

A WhileLoopActionUsage is a LoopActionUsage that specifies that the bodyAction ActionUsage should be performed repeatedly while the result of the whileArgument Expression is true or until the result of the untilArgument Expression (if provided) is true. The whileArgument Expression is evaluated before each (possible) performance of the bodyAction, and the untilArgument Expression is evaluated after each performance of the bodyAction.

2.1.2 Properties in this namespace (412)

[acceptActionUsage_PayloadArgument](#), [acceptActionUsage_PayloadParameter](#), [acceptActionUsage_ReceiverArgument](#), [actionDefinition_Action](#), [actionUsage_ActionDefinition](#), [actorMembership_OwnedActorParameter](#), [allocationDefinition_Allocation](#), [allocationUsage_AllocationDefinition](#), [analysisCaseDefinition_AnalysisAction](#), [analysisCaseDefinition_ResultExpression](#), [analysisCaseUsage_AnalysisAction](#), [analysisCaseUsage_AnalysisCaseDefinition](#), [analysisCaseUsage_ResultExpression](#), [annotatingElement_AnnotatedElement](#), [annotatingElement_Annotation](#), [annotatingElement_OwnedAnnotatingRelationship](#), [annotation_AnnotatedElement](#),

[annotation_AnnotatingElement](#), [annotation_OwningAnnotatedElement](#), [annotation_OwningAnnotatingElement](#),
[assertConstraintUsage_AssertedConstraint](#), [assignmentActionUsage_Referent](#), [assignmentActionUsage_TargetArgument](#),
[assignmentActionUsage_ValueExpression](#), [association_AssociationEnd](#), [association_RelatedType](#),
[association_SourceType](#), [association_TargetType](#), [attributeUsage_AttributeDefinition](#), [behavior_Parameter](#), [behavior_Step](#),
[booleanExpression_Predicate](#), [calculationDefinition_Calculation](#), [calculationUsage_CalculationDefinition](#),
[caseDefinition_ActorParameter](#), [caseDefinition_ObjectiveRequirement](#), [caseDefinition_SubjectParameter](#),
[caseUsage_ActorParameter](#), [caseUsage_CaseDefinition](#), [caseUsage_ObjectiveRequirement](#),
[caseUsage_SubjectParameter](#), [classifier_OwnedSubclassification](#), [comment_Body](#), [comment_Locale](#),
[concernUsage_ConcernDefinition](#), [conjugatedPortDefinition_OriginalPortDefinition](#),
[conjugatedPortDefinition_OwnedPortConjugator](#), [conjugatedPortTyping_ConjugatedPortDefinition](#),
[conjugatedPortTyping_PortDefinition](#), [conjugation_ConjugatedType](#), [conjugation_OriginalType](#), [conjugation_OwningType](#),
[connectionDefinition_ConnectionEnd](#), [connectionUsage_ConnectionDefinition](#), [connector_Association](#),
[connector_ConnectorEnd](#), [connector_RelatedFeature](#), [connector_SourceFeature](#), [connector_TargetFeature](#),
[constraintUsage_ConstraintDefinition](#), [definition_DirectedUsage](#), [definition_IsVariation](#), [definition_OwnedAction](#),
[definition_OwnedAllocation](#), [definition_OwnedAnalysisCase](#), [definition_OwnedAttribute](#), [definition_OwnedCalculation](#),
[definition_OwnedCase](#), [definition_OwnedConcern](#), [definition_OwnedConnection](#), [definition_OwnedConstraint](#),
[definition_OwnedEnumeration](#), [definition_OwnedFlow](#), [definition_OwnedInterface](#), [definition_OwnedItem](#),
[definition_OwnedMetadata](#), [definition_OwnedOccurrence](#), [definition_OwnedPart](#), [definition_OwnedPort](#),
[definition_OwnedReference](#), [definition_OwnedRendering](#), [definition_OwnedRequirement](#), [definition_OwnedState](#),
[definition_OwnedTransition](#), [definition_OwnedUsage](#), [definition_OwnedUseCase](#), [definition_OwnedVerificationCase](#),
[definition_OwnedView](#), [definition_OwnedViewpoint](#), [definition_Usage](#), [definition_Variant](#), [definition_VariantMembership](#),
[dependency_Client](#), [dependency_Supplier](#), [differencing_DifferencingType](#), [differencing_TypeDifferenced](#),
[disjoining_DisjoiningType](#), [disjoining_OwningType](#), [disjoining_TypeDisjoined](#), [documentation_DocumentedElement](#),
[element_AliasIds](#), [element_DeclaredName](#), [element_DeclaredShortName](#), [element_Documentation](#), [element_ElementId](#),
[element_IsImpliedIncluded](#), [element_IsLibraryElement](#), [element_Name](#), [element_OwnedAnnotation](#), [element_OwnedElement](#),
[element_OwnedRelationship](#), [element_Owner](#), [element_OwningMembership](#), [element_OwningNamespace](#),
[element_OwningRelationship](#), [element_QualifiedName](#), [element_ShortName](#), [element_TextualRepresentation](#),
[elementFilterMembership_Condition](#), [enumerationDefinition_EnumeratedValue](#), [enumerationUsage_EnumerationDefinition](#),
[eventOccurrenceUsage_EventOccurrence](#), [exhibitStateUsage_ExhibitedState](#), [expression_Function](#),
[expression_IsModelLevelEvaluable](#), [expression_Result](#), [feature_ChainingFeature](#), [feature_Direction](#),
[feature_EndOwningType](#), [feature_FeaturingType](#), [feature_IsComposite](#), [feature_IsDerived](#), [feature_IsEnd](#),
[feature_IsNonunique](#), [feature_IsOrdered](#), [feature_IsPortion](#), [feature_IsReadOnly](#), [feature_IsUnique](#),
[feature_OwnedFeatureChaining](#), [feature_OwnedFeatureInverting](#), [feature_OwnedRedefinition](#),
[feature_OwnedReferenceSubsetting](#), [feature_OwnedSubsetting](#), [feature_OwnedTypeFeaturing](#), [feature_OwnedTyping](#),
[feature_OwningFeatureMembership](#), [feature_OwningType](#), [feature_Type](#), [featureChainExpression_TargetFeature](#),
[featureChaining_ChainingFeature](#), [featureChaining_FeatureChained](#), [featureInverting_FeatureInverted](#),
[featureInverting_InvertingFeature](#), [featureInverting_OwningFeature](#), [featureMembership_OwnedMemberFeature](#),
[featureMembership_OwningType](#), [featureReferenceExpression_Referent](#), [featureTyping_OwningFeature](#),
[featureTyping_Type](#), [featureTyping_TypedFeature](#), [featureValue_FeatureWithValue](#), [featureValue_IsDefault](#),
[featureValue_IsInitial](#), [featureValue_Value](#), [featuring_Feature](#), [featuring_Type](#),
[flowConnectionUsage_FlowConnectionDefinition](#), [forLoopActionUsage_LoopVariable](#), [forLoopActionUsage_SeqArgument](#),
[framedConcernMembership_OwnedConcern](#), [framedConcernMembership_ReferencedConcern](#), [function_Expression](#),
[function_IsModelLevelEvaluable](#), [function_Result](#), [ifActionUsage_ElseAction](#), [ifActionUsage_IfArgument](#),
[ifActionUsage_ThenAction](#), [import_ImportedElement](#), [import_ImportOwningNamespace](#), [import_IsImportAll](#),
[import_IsRecursive](#), [import_Visibility](#), [includeUseCaseUsage_UseCaseIncluded](#), [interfaceDefinition_InterfaceEnd](#),
[interfaceUsage_InterfaceDefinition](#), [intersecting_IntersectingType](#), [intersecting_TypeIntersected](#), [invariant_IsNegated](#),
[invocationExpression_Argument](#), [invocationExpression_Operand](#), [itemFlow_Interaction](#), [itemFlow_ItemFeature](#),
[itemFlow_ItemFlowEnd](#), [itemFlow_ItemType](#), [itemFlow_SourceOutputFeature](#), [itemFlow_TargetInputFeature](#),
[itemUsage_ItemDefinition](#), [libraryPackage_IsStandard](#), [literalBoolean_Value](#), [literalInteger_Value](#), [literalRational_Value](#),
[literalString_Value](#), [loopActionUsage_BodyAction](#), [membership_MemberElement](#), [membership_MemberElementId](#),
[membership_MemberName](#), [membership_MembershipOwningNamespace](#), [membership_MemberShortName](#),
[membership_Visibility](#), [membershipImport_ImportedMembership](#), [metadataAccessExpression_ReferencedElement](#),
[metadataFeature_Metaclass](#), [metadataUsage_MetadataDefinition](#), [multiplicityRange_Bound](#), [multiplicityRange_LowerBound](#),
[multiplicityRange_UpperBound](#), [namespace_ImportedMembership](#), [namespace_Member](#), [namespace_Membership](#),
[namespace_OwnedImport](#), [namespace_OwnedMember](#), [namespace_OwnedMembership](#),
[namespaceImport_ImportedNamespace](#), [objectiveMembership_OwnedObjectiveRequirement](#),
[occurrenceDefinition_IsIndividual](#), [occurrenceDefinition_LifeClass](#), [occurrenceUsage_IndividualDefinition](#),
[occurrenceUsage_IsIndividual](#), [occurrenceUsage_OccurrenceDefinition](#), [occurrenceUsage_PortionKind](#),

[operatorExpression_Operator](#), [owningMembership_OwnedMemberElement](#), [owningMembership_OwnedMemberElementId](#), [owningMembership_OwnedMemberName](#), [owningMembership_OwnedMemberShortName](#), [package_FilterCondition](#), [parameterMembership_OwnedMemberParameter](#), [partUsage_PartDefinition](#), [performActionUsage_PerformedAction](#), [portConjugation_ConjugatedPortDefinition](#), [portConjugation_OriginalPortDefinition](#), [portDefinition_ConjugatedPortDefinition](#), [portUsage_PortDefinition](#), [redefinition_RedefinedFeature](#), [redefinition_RedefiningFeature](#), [referenceSubsetting_ReferencedFeature](#), [referenceSubsetting_ReferencingFeature](#), [relationship_IsImplied](#), [relationship_OwnedRelatedElement](#), [relationship_OwningRelatedElement](#), [relationship_RelatedElement](#), [relationship_Source](#), [relationship_Target](#), [renderingDefinition_Rendering](#), [renderingUsage_RenderingDefinition](#), [requirementConstraintMembership_Kind](#), [requirementConstraintMembership_OwnedConstraint](#), [requirementConstraintMembership_ReferencedConstraint](#), [requirementDefinition_ActorParameter](#), [requirementDefinition_AssumedConstraint](#), [requirementDefinition_FramedConcern](#), [requirementDefinition_ReqId](#), [requirementDefinition_RequiredConstraint](#), [requirementDefinition_StakeholderParameter](#), [requirementDefinition_SubjectParameter](#), [requirementDefinition_Text](#), [requirementUsage_ActorParameter](#), [requirementUsage_AssumedConstraint](#), [requirementUsage_FramedConcern](#), [requirementUsage_ReqId](#), [requirementUsage_RequiredConstraint](#), [requirementUsage_RequirementDefinition](#), [requirementUsage_StakeholderParameter](#), [requirementUsage_SubjectParameter](#), [requirementUsage_Text](#), [requirementVerificationMembership_OwnedRequirement](#), [requirementVerificationMembership_VerifiedRequirement](#), [resultExpressionMembership_OwnedResultExpression](#), [satisfyRequirementUsage_SatisfiedRequirement](#), [satisfyRequirementUsage_SatisfyingFeature](#), [sendActionUsage_PayloadArgument](#), [sendActionUsage_ReceiverArgument](#), [sendActionUsage_SenderArgument](#), [specialization_General](#), [specialization_OwningType](#), [specialization_Specific](#), [stakeholderMembership_OwnedStakeholderParameter](#), [stateDefinition_DoAction](#), [stateDefinition_EntryAction](#), [stateDefinition_ExitAction](#), [stateDefinition_IsParallel](#), [stateDefinition_State](#), [stateSubactionMembership_Action](#), [stateSubactionMembership_Kind](#), [stateUsage_DoAction](#), [stateUsage_EntryAction](#), [stateUsage_ExitAction](#), [stateUsage_IsParallel](#), [stateUsage_StateDefinition](#), [step_Behavior](#), [step_Parameter](#), [subclassification_OwningClassifier](#), [subclassification_Subclassifier](#), [subclassification_Superclassifier](#), [subjectMembership_OwnedSubjectParameter](#), [subsetting_OwningFeature](#), [subsetting_SubsettedFeature](#), [subsetting_SubsettingFeature](#), [succession_EffectStep](#), [succession_GuardExpression](#), [succession_TransitionStep](#), [succession_TriggerStep](#), [textualRepresentation_Body](#), [textualRepresentation_Language](#), [textualRepresentation_RepresentedElement](#), [transitionFeatureMembership_Kind](#), [transitionFeatureMembership_TransitionFeature](#), [transitionUsage_EffectAction](#), [transitionUsage_GuardExpression](#), [transitionUsage_Source](#), [transitionUsage_Succession](#), [transitionUsage_Target](#), [transitionUsage_TriggerAction](#), [triggerInvocationExpression_Kind](#), [type_DifferencingType](#), [type_DirectedFeature](#), [type_EndFeature](#), [type_Feature](#), [type_FeatureMembership](#), [type_InheritedFeature](#), [type_InheritedMembership](#), [type_Input](#), [type_IntersectionType](#), [type_IsAbstract](#), [type_IsConjugated](#), [type_IsSufficient](#), [type_Multiplicity](#), [type_Output](#), [type_OwnedConjugator](#), [type_OwnedDifferencing](#), [type_OwnedDisjoining](#), [type_OwnedEndFeature](#), [type_OwnedFeature](#), [type_OwnedFeatureMembership](#), [type_OwnedIntersecting](#), [type_OwnedSpecialization](#), [type_OwnedUnioning](#), [type_UnioningType](#), [typeFeaturing_FeatureOfType](#), [typeFeaturing_FeaturingType](#), [typeFeaturing_OwningFeatureOfType](#), [unioning_TypeUnioned](#), [unioning_UnioningType](#), [usage_Definition](#), [usage_DirectedUsage](#), [usage_IsReference](#), [usage_IsVariation](#), [usage_NestedAction](#), [usage_NestedAllocation](#), [usage_NestedAnalysisCase](#), [usage_NestedAttribute](#), [usage_NestedCalculation](#), [usage_NestedCase](#), [usage_NestedConcern](#), [usage_NestedConnection](#), [usage_NestedConstraint](#), [usage_NestedEnumeration](#), [usage_NestedFlow](#), [usage_NestedInterface](#), [usage_NestedItem](#), [usage_NestedMetadata](#), [usage_NestedOccurrence](#), [usage_NestedPart](#), [usage_NestedPort](#), [usage_NestedReference](#), [usage_NestedRendering](#), [usage_NestedRequirement](#), [usage_NestedState](#), [usage_NestedTransition](#), [usage_NestedUsage](#), [usage_NestedUseCase](#), [usage_NestedVerificationCase](#), [usage_NestedView](#), [usage_NestedViewpoint](#), [usage_OwningDefinition](#), [usage_OwningUsage](#), [usage_Usage](#), [usage_Variant](#), [usage_VariantMembership](#), [useCaseDefinition_IncludedUseCase](#), [useCaseUsage_IncludedUseCase](#), [useCaseUsage_UseCaseDefinition](#), [variantMembership_OwnedVariantUsage](#), [verificationCaseDefinition_VerifiedRequirement](#), [verificationCaseUsage_VerificationCaseDefinition](#), [verificationCaseUsage_VerifiedRequirement](#), [viewDefinition_SatisfiedViewpoint](#), [viewDefinition_View](#), [viewDefinition_ViewCondition](#), [viewDefinition_ViewRendering](#), [viewpointDefinition_ViewpointStakeholder](#), [viewpointUsage_ViewpointDefinition](#), [viewpointUsage_ViewpointStakeholder](#), [viewRenderingMembership_OwnedRendering](#), [viewRenderingMembership_ReferencedRendering](#), [viewUsage_ExposedElement](#), [viewUsage_SatisfiedViewpoint](#), [viewUsage_ViewCondition](#), [viewUsage_ViewDefinition](#), [viewUsage_ViewRendering](#), [whileLoopActionUsage_UntilArgument](#), [whileLoopActionUsage_WhileArgument](#)

acceptActionUsage_PayloadArgument

http://open-services.net/ns/sysmlv2#acceptActionUsage_PayloadArgument

acceptActionUsage_PayloadArgument is an RDF property.

An Expression whose result is bound to the payload parameter of this AcceptActionUsage. If provided, the AcceptActionUsage will only accept a Transfer with exactly this payload.

acceptActionUsage_PayloadParameter

http://open-services.net/ns/sysmlv2#acceptActionUsage_PayloadParameter

acceptActionUsage_PayloadParameter is an RDF property.

The nestedReference of this AcceptActionUsage that redefines the payload output parameter of the base AcceptActionUsage AcceptAction from the Systems Model Library.

acceptActionUsage_ReceiverArgument

http://open-services.net/ns/sysmlv2#acceptActionUsage_ReceiverArgument

acceptActionUsage_ReceiverArgument is an RDF property.

An Expression whose result is bound to the receiver input parameter of this AcceptActionUsage.

actionDefinition_Action

http://open-services.net/ns/sysmlv2#actionDefinition_Action

actionDefinition_Action is an RDF property.

The ActionUsages that are steps in this ActionDefinition, which define the actions that specify the behavior of the ActionDefinition.

actionUsage_ActionDefinition

http://open-services.net/ns/sysmlv2#actionUsage_ActionDefinition

actionUsage_ActionDefinition is an RDF property.

The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.

actorMembership_OwnedActorParameter

http://open-services.net/ns/sysmlv2#actorMembership_OwnedActorParameter

actorMembership_OwnedActorParameter is an RDF property.

The PartUsage specifying the actor.

allocationDefinition_Allocation

http://open-services.net/ns/sysmlv2#allocationDefinition_Allocation

allocationDefinition_Allocation is an RDF property.

The AllocationUsages that refine the allocation mapping defined by this AllocationDefinition.

allocationUsage_AllocationDefinition

http://open-services.net/ns/sysmlv2#allocationUsage_AllocationDefinition

allocationUsage_AllocationDefinition is an RDF property.

The AllocationDefinitions that are the types of this AllocationUsage.

analysisCaseDefinition_AnalysisAction

http://open-services.net/ns/sysmlv2#analysisCaseDefinition_AnalysisAction

analysisCaseDefinition_AnalysisAction is an RDF property.

The composite actions of the AnalysisCaseDefinition that are defined as AnalysisActions.

analysisCaseDefinition_ResultExpression

http://open-services.net/ns/sysmlv2#analysisCaseDefinition_ResultExpression

analysisCaseDefinition_ResultExpression is an RDF property.

An Expression used to compute the result of the AnalysisCaseDefinition, owned via a ResultExpressionMembership.

analysisCaseUsage_AnalysisAction

http://open-services.net/ns/sysmlv2#analysisCaseUsage_AnalysisAction

analysisCaseUsage_AnalysisAction is an RDF property.

The composite usages of the AnalysisCaseUsage that are defined as AnalysisActions.

analysisCaseUsage_AnalysisCaseDefinition

http://open-services.net/ns/sysmlv2#analysisCaseUsage_AnalysisCaseDefinition

analysisCaseUsage_AnalysisCaseDefinition is an RDF property.

The AnalysisCaseDefinition that is the definition of this AnalysisCaseUsage.

analysisCaseUsage_ResultExpression

http://open-services.net/ns/sysmlv2#analysisCaseUsage_ResultExpression

analysisCaseUsage_ResultExpression is an RDF property.

An Expression used to compute the result of the AnalysisCaseUsage, owned via a ResultExpressionMembership.

annotatingElement_AnnotatedElement

http://open-services.net/ns/sysmlv2#annotatingElement_AnnotatedElement

annotatingElement_AnnotatedElement is an RDF property.

The Elements that are annotated by this AnnotatingElement. If annotation is not empty, these are the annotatedElements of the annotations. If annotation is empty, then it is the owningNamespace of the AnnotatingElement.

annotatingElement_Annotation

http://open-services.net/ns/sysmlv2#annotatingElement_Annotation

annotatingElement_Annotation is an RDF property.

The Annotations that relate this AnnotatingElement to its annotatedElements.

annotatingElement_OwnedAnnotatingRelationship

http://open-services.net/ns/sysmlv2#annotatingElement_OwnedAnnotatingRelationship

annotatingElement_OwnedAnnotatingRelationship is an RDF property.

The ownedRelationships of this AnnotatingElement that are Annotations, for which this AnnotatingElement is the annotatingElement.

annotation_AnnotatedElement

http://open-services.net/ns/sysmlv2#annotation_AnnotatedElement

annotation_AnnotatedElement is an RDF property.

The Element that is annotated by the annotatingElement of this Annotation.

annotation_AnnotatingElement

http://open-services.net/ns/sysmlv2#annotation_AnnotatingElement

annotation_AnnotatingElement is an RDF property.

The AnnotatingElement that annotates the annotatedElement of this Annotation.

annotation_OwningAnnotatedElement

http://open-services.net/ns/sysmlv2#annotation_OwningAnnotatedElement

annotation_OwningAnnotatedElement is an RDF property.

The annotatedElement of this Annotation, when it is also its owningRelatedElement.

annotation_OwningAnnotatingElement

http://open-services.net/ns/sysmlv2#annotation_OwningAnnotatingElement

annotation_OwningAnnotatingElement is an RDF property.

The annotatingElement of this Annotation, when it is also its owningRelatedElement.

assertConstraintUsage_AssertedConstraint

http://open-services.net/ns/sysmlv2#assertConstraintUsage_AssertedConstraint

assertConstraintUsage_AssertedConstraint is an RDF property.

The ConstraintUsage to be performed by the AssertConstraintUsage. It is the referenceFeature of the ownedReferenceSubsetting for the AssertConstraintUsage, if there is one, and, otherwise, the AssertConstraintUsage itself.

assignmentActionUsage_Referent

http://open-services.net/ns/sysmlv2#assignmentActionUsage_Referent

assignmentActionUsage_Referent is an RDF property.

The Feature whose value is to be set.

assignmentActionUsage_TargetArgument

http://open-services.net/ns/sysmlv2#assignmentActionUsage_TargetArgument

assignmentActionUsage_TargetArgument is an RDF property.

The Expression whose value is an occurrence in the domain of the referent Feature, for which the value of the referent will be set to the result of the valueExpression by this AssignmentActionUsage.

assignmentActionUsage_ValueExpression

http://open-services.net/ns/sysmlv2#assignmentActionUsage_ValueExpression

assignmentActionUsage_ValueExpression is an RDF property.

The Expression whose result is to be assigned to the referent Feature.

association_AssociationEnd

http://open-services.net/ns/sysmlv2#association_AssociationEnd

association_AssociationEnd is an RDF property.

The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds. When it has exactly two, the Association is called a binary Association.

association_RelatedType

http://open-services.net/ns/sysmlv2#association_RelatedType

association_RelatedType is an RDF property.

The types of the associationEnds of the Association, which are the relatedElements of the Association considered as a Relationship.

association_SourceType

http://open-services.net/ns/sysmlv2#association_SourceType

association_SourceType is an RDF property.

The source relatedType for this Association. It is the first relatedType of the Association.

association_TargetType

http://open-services.net/ns/sysmlv2#association_TargetType

association_TargetType is an RDF property.

The target relatedTypes for this Association. This includes all the relatedTypes other than the sourceType.

attributeUsage_AttributeDefinition

http://open-services.net/ns/sysmlv2#attributeUsage_AttributeDefinition

attributeUsage_AttributeDefinition is an RDF property.

The DataTypes that are the types of this AttributeUsage. Nominally, these are AttributeDefinitions, but other kinds of kernel DataTypes are also allowed, to permit use of DataTypes from the Kernel Model Libraries.

behavior_Parameter

http://open-services.net/ns/sysmlv2#behavior_Parameter

behavior_Parameter is an RDF property.

The parameters of this Behavior, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Behavior.

behavior_Step

http://open-services.net/ns/sysmlv2#behavior_Step

behavior_Step is an RDF property.

The Steps that make up this Behavior.

booleanExpression_Predicate

http://open-services.net/ns/sysmlv2#booleanExpression_Predicate

booleanExpression_Predicate is an RDF property.

The Predicate that types this BooleanExpression.

calculationDefinition_Calculation

http://open-services.net/ns/sysmlv2#calculationDefinition_Calculation

calculationDefinition_Calculation is an RDF property.

The actions of this CalculationDefinition that are CalculationUsages.

calculationUsage_CalculationDefinition

http://open-services.net/ns/sysmlv2#calculationUsage_CalculationDefinition

calculationUsage_CalculationDefinition is an RDF property.

The Function that is the type of this CalculationUsage. Nominally, this would be a CalculationDefinition, but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries.

caseDefinition_ActorParameter

http://open-services.net/ns/sysmlv2#caseDefinition_ActorParameter

caseDefinition_ActorParameter is an RDF property.

The parameters of this CaseDefinition that represent actors involved in the case.

caseDefinition_ObjectiveRequirement

http://open-services.net/ns/sysmlv2#caseDefinition_ObjectiveRequirement

caseDefinition_ObjectiveRequirement is an RDF property.

The RequirementUsage representing the objective of this CaseDefinition.

caseDefinition_SubjectParameter

http://open-services.net/ns/sysmlv2#caseDefinition_SubjectParameter

caseDefinition_SubjectParameter is an RDF property.

The parameter of this CaseDefinition that represents its subject.

caseUsage_ActorParameter

http://open-services.net/ns/sysmlv2#caseUsage_ActorParameter

caseUsage_ActorParameter is an RDF property.

The parameters of this CaseUsage that represent actors involved in the case.

caseUsage_CaseDefinition

http://open-services.net/ns/sysmlv2#caseUsage_CaseDefinition

caseUsage_CaseDefinition is an RDF property.

The CaseDefinition that is the type of this CaseUsage.

caseUsage_ObjectiveRequirement

http://open-services.net/ns/sysmlv2#caseUsage_ObjectiveRequirement

caseUsage_ObjectiveRequirement is an RDF property.

The RequirementUsage representing the objective of this CaseUsage.

caseUsage_SubjectParameter

http://open-services.net/ns/sysmlv2#caseUsage_SubjectParameter

caseUsage_SubjectParameter is an RDF property.

The parameter of this CaseUsage that represents its subject.

classifier_OwnedSubclassification

http://open-services.net/ns/sysmlv2#classifier_OwnedSubclassification

classifier_OwnedSubclassification is an RDF property.

The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.

comment_Body

http://open-services.net/ns/sysmlv2#comment_Body

comment_Body is an RDF property.

The annotation text for the Comment.

comment_Locale

http://open-services.net/ns/sysmlv2#comment_Locale

comment_Locale is an RDF property.

Identification of the language of the body text and, optionally, the region and/or encoding. The format shall be a POSIX locale conformant to ISO/IEC 15897, with the format [language[_territory][.codeset][@modifier]].

concernUsage_ConcernDefinition

http://open-services.net/ns/sysmlv2#concernUsage_ConcernDefinition

concernUsage_ConcernDefinition is an RDF property.

The ConcernDefinition that is the single type of this ConcernUsage.

conjugatedPortDefinition_OriginalPortDefinition

http://open-services.net/ns/sysmlv2#conjugatedPortDefinition_OriginalPortDefinition

conjugatedPortDefinition_OriginalPortDefinition is an RDF property.

The original PortDefinition for this ConjugatedPortDefinition, which is the owningNamespace of the ConjugatedPortDefinition.

conjugatedPortDefinition_OwnedPortConjugator

http://open-services.net/ns/sysmlv2#conjugatedPortDefinition_OwnedPortConjugator

conjugatedPortDefinition_OwnedPortConjugator is an RDF property.

The PortConjugation that is the ownedConjugator of this ConjugatedPortDefinition, linking it to its originalPortDefinition.

conjugatedPortTyping_ConjugatedPortDefinition

http://open-services.net/ns/sysmlv2#conjugatedPortTyping_ConjugatedPortDefinition

conjugatedPortTyping_ConjugatedPortDefinition is an RDF property.

The type of this ConjugatedPortTyping considered as a FeatureTyping, which must be a ConjugatedPortDefinition.

conjugatedPortTyping_PortDefinition

http://open-services.net/ns/sysmlv2#conjugatedPortTyping_PortDefinition

conjugatedPortTyping_PortDefinition is an RDF property.

The originalPortDefinition of the conjugatedPortDefinition of this ConjugatedPortTyping.

conjugation_ConjugatedType

http://open-services.net/ns/sysmlv2#conjugation_ConjugatedType

conjugation_ConjugatedType is an RDF property.

The Type that is the result of applying Conjugation to the originalType.

conjugation_OriginalType

http://open-services.net/ns/sysmlv2#conjugation_OriginalType

conjugation_OriginalType is an RDF property.

The Type to be conjugated.

conjugation_OwningType

http://open-services.net/ns/sysmlv2#conjugation_OwningType

conjugation_OwningType is an RDF property.

The conjugatedType of this Conjugation that is also its owningRelatedElement.

connectionDefinition_ConnectionEnd

http://open-services.net/ns/sysmlv2#connectionDefinition_ConnectionEnd

connectionDefinition_ConnectionEnd is an RDF property.

The Usages that define the things related by the ConnectionDefinition.

connectionUsage_ConnectionDefinition

http://open-services.net/ns/sysmlv2#connectionUsage_ConnectionDefinition

connectionUsage_ConnectionDefinition is an RDF property.

The AssociationStructures that are the types of this ConnectionUsage. Nominally, these are , but other kinds of Kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model Libraries.

connector_Association

http://open-services.net/ns/sysmlv2#connector_Association

connector_Association is an RDF property.

The Associations that type the Connector.

connector_ConnectorEnd

http://open-services.net/ns/sysmlv2#connector_ConnectorEnd

connector_ConnectorEnd is an RDF property.

The endFeatures of a Connector, which redefine the endFeatures of the associations of the Connector. The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector.

connector_RelatedFeature

http://open-services.net/ns/sysmlv2#connector_RelatedFeature

connector_RelatedFeature is an RDF property.

The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector.

connector_SourceFeature

http://open-services.net/ns/sysmlv2#connector_SourceFeature

connector_SourceFeature is an RDF property.

The source relatedFeature for this Connector. It is the first relatedFeature.

connector_TargetFeature

http://open-services.net/ns/sysmlv2#connector_TargetFeature

connector_TargetFeature is an RDF property.

The target relatedFeatures for this Connector. This includes all the relatedFeatures other than the sourceFeature.

constraintUsage_ConstraintDefinition

http://open-services.net/ns/sysmlv2#constraintUsage_ConstraintDefinition

constraintUsage_ConstraintDefinition is an RDF property.

The (single) Predicate that is the type of this ConstraintUsage. Nominally, this will be a ConstraintDefinition, but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.

definition_DirectedUsage

http://open-services.net/ns/sysmlv2#definition_DirectedUsage

definition_DirectedUsage is an RDF property.

The usages of this Definition that are directedFeatures.

definition_IsVariation

http://open-services.net/ns/sysmlv2#definition_IsVariation

definition_IsVariation is an RDF property.

Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.

definition_OwnedAction

http://open-services.net/ns/sysmlv2#definition_OwnedAction

definition_OwnedAction is an RDF property.

The ActionUsages that are ownedUsages of this Definition.

definition_OwnedAllocation

http://open-services.net/ns/sysmlv2#definition_OwnedAllocation

definition_OwnedAllocation is an RDF property.

The AllocationUsages that are ownedUsages of this Definition.

definition_OwnedAnalysisCase

http://open-services.net/ns/sysmlv2#definition_OwnedAnalysisCase

definition_OwnedAnalysisCase is an RDF property.

The AnalysisCaseUsages that are ownedUsages of this Definition.

definition_OwnedAttribute

http://open-services.net/ns/sysmlv2#definition_OwnedAttribute

definition_OwnedAttribute is an RDF property.

The AttributeUsages that are ownedUsages of this Definition.

definition_OwnedCalculation

http://open-services.net/ns/sysmlv2#definition_OwnedCalculation

definition_OwnedCalculation is an RDF property.

The CalculationUsages that are ownedUsages of this Definition.

definition_OwnedCase

http://open-services.net/ns/sysmlv2#definition_OwnedCase

definition_OwnedCase is an RDF property.

The code>CaseUsages that are ownedUsages of this Definition.

definition_OwnedConcern

http://open-services.net/ns/sysmlv2#definition_OwnedConcern

definition_OwnedConcern is an RDF property.

The ConcernUsages that are ownedUsages of this Definition.

definition_OwnedConnection

http://open-services.net/ns/sysmlv2#definition_OwnedConnection

definition_OwnedConnection is an RDF property.

The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.

definition_OwnedConstraint

http://open-services.net/ns/sysmlv2#definition_OwnedConstraint

definition_OwnedConstraint is an RDF property.

The ConstraintUsages that are ownedUsages of this Definition.

definition_OwnedEnumeration

http://open-services.net/ns/sysmlv2#definition_OwnedEnumeration

definition_OwnedEnumeration is an RDF property.

The EnumerationUsages that are ownedUsages of this Definition.

definition_OwnedFlow

http://open-services.net/ns/sysmlv2#definition_OwnedFlow

definition_OwnedFlow is an RDF property.

The FlowConnectionUsages that are ownedUsages of this Definition.

definition_OwnedInterface

http://open-services.net/ns/sysmlv2#definition_OwnedInterface

definition_OwnedInterface is an RDF property.

The InterfaceUsages that are ownedUsages of this Definition.

definition_OwnedItem

http://open-services.net/ns/sysmlv2#definition_OwnedItem

definition_OwnedItem is an RDF property.

The ItemUsages that are ownedUsages of this Definition.

definition_OwnedMetadata

http://open-services.net/ns/sysmlv2#definition_OwnedMetadata

definition_OwnedMetadata is an RDF property.

The MetadataUsages that are ownedUsages of this Definition.

definition_OwnedOccurrence

http://open-services.net/ns/sysmlv2#definition_OwnedOccurrence

definition_OwnedOccurrence is an RDF property.

The OccurrenceUsages that are ownedUsages of this Definition.

definition_OwnedPart

http://open-services.net/ns/sysmlv2#definition_OwnedPart

definition_OwnedPart is an RDF property.

The PartUsages that are ownedUsages of this Definition.

definition_OwnedPort

http://open-services.net/ns/sysmlv2#definition_OwnedPort

definition_OwnedPort is an RDF property.

The PortUsages that are ownedUsages of this Definition.

definition_OwnedReference

http://open-services.net/ns/sysmlv2#definition_OwnedReference

definition_OwnedReference is an RDF property.

The ReferenceUsages that are ownedUsages of this Definition.

definition_OwnedRendering

http://open-services.net/ns/sysmlv2#definition_OwnedRendering

definition_OwnedRendering is an RDF property.

The RenderingUsages that are ownedUsages of this Definition.

definition_OwnedRequirement

http://open-services.net/ns/sysmlv2#definition_OwnedRequirement

definition_OwnedRequirement is an RDF property.

The RequirementUsages that are ownedUsages of this Definition.

definition_OwnedState

http://open-services.net/ns/sysmlv2#definition_OwnedState

definition_OwnedState is an RDF property.

The StateUsages that are ownedUsages of this Definition.

definition_OwnedTransition

http://open-services.net/ns/sysmlv2#definition_OwnedTransition

definition_OwnedTransition is an RDF property.

The TransitionUsages that are ownedUsages of this Definition.

definition_OwnedUsage

http://open-services.net/ns/sysmlv2#definition_OwnedUsage

definition_OwnedUsage is an RDF property.

The Usages that are ownedFeatures of this Definition.

definition_OwnedUseCase

http://open-services.net/ns/sysmlv2#definition_OwnedUseCase

definition_OwnedUseCase is an RDF property.

The UseCaseUsages that are ownedUsages of this Definition.

definition_OwnedVerificationCase

http://open-services.net/ns/sysmlv2#definition_OwnedVerificationCase

definition_OwnedVerificationCase is an RDF property.

The VerificationCaseUsages that are ownedUsages of this Definition.

definition_OwnedView

http://open-services.net/ns/sysmlv2#definition_OwnedView

definition_OwnedView is an RDF property.

The ViewUsages that are ownedUsages of this Definition.

definition_OwnedViewpoint

http://open-services.net/ns/sysmlv2#definition_OwnedViewpoint

definition_OwnedViewpoint is an RDF property.

The ViewpointUsages that are ownedUsages of this Definition.

definition_Usage

http://open-services.net/ns/sysmlv2#definition_Usage

definition_Usage is an RDF property.

The Usages that are features of this Definition (not necessarily owned).

definition_Variant

http://open-services.net/ns/sysmlv2#definition_Variant

definition_Variant is an RDF property.

The Usages which represent the variants of this Definition as a variation point Definition, if isVariation = true. If isVariation = false, there must be no variants.

definition_VariantMembership

http://open-services.net/ns/sysmlv2#definition_VariantMembership

definition_VariantMembership is an RDF property.

The ownedMemberships of this Definition that are VariantMemberships. If isVariation = true, then this must be all ownedMemberships of the Definition. If isVariation = false, then variantMembership must be empty.

dependency_Client

http://open-services.net/ns/sysmlv2#dependency_Client

dependency_Client is an RDF property.

The Element or Elements dependent on the supplier Elements.

dependency_Supplier

http://open-services.net/ns/sysmlv2#dependency_Supplier

dependency_Supplier is an RDF property.

The Element or Elements on which the client Elements depend in some respect.

differencing_DifferencingType

http://open-services.net/ns/sysmlv2#differencing_DifferencingType

differencing_DifferencingType is an RDF property.

Type that partly determines interpretations of `typeDifferenced`, as described in `Type::differencingType`.

`differencing_TypeDifferenced`

http://open-services.net/ns/sysmlv2#differencing_TypeDifferenced

differencing_TypeDifferenced is an RDF property.

Type with interpretations partly determined by `differencingType`, as described in `Type::differencingType`.

`disjoining_DisjoiningType`

http://open-services.net/ns/sysmlv2#disjoining_DisjoiningType

disjoining_DisjoiningType is an RDF property.

Type asserted to be disjoint with the `typeDisjoined`.

`disjoining_OwningType`

http://open-services.net/ns/sysmlv2#disjoining_OwningType

disjoining_OwningType is an RDF property.

A `typeDisjoined` that is also an `owningRelatedElement`.

`disjoining_TypeDisjoined`

http://open-services.net/ns/sysmlv2#disjoining_TypeDisjoined

disjoining_TypeDisjoined is an RDF property.

Type asserted to be disjoint with the `disjoiningType`.

`documentation_DocumentedElement`

http://open-services.net/ns/sysmlv2#documentation_DocumentedElement

documentation_DocumentedElement is an RDF property.

The `Element` that is documented by this `Documentation`.

`element_AliasIds`

http://open-services.net/ns/sysmlv2#element_AliasIds

element_AliasIds is an RDF property.

Various alternative identifiers for this `Element`. Generally, these will be set by tools.

`element_DeclaredName`

http://open-services.net/ns/sysmlv2#element_DeclaredName

element_DeclaredName is an RDF property.

The declared name of this `Element`.

element_DeclaredShortName

http://open-services.net/ns/sysmlv2#element_DeclaredShortName

element_DeclaredShortName is an RDF property.

An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

element_Documentation

http://open-services.net/ns/sysmlv2#element_Documentation

element_Documentation is an RDF property.

The Documentation owned by this Element.

element_ElementId

http://open-services.net/ns/sysmlv2#element_ElementId

element_ElementId is an RDF property.

The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

element_IsImpliedIncluded

http://open-services.net/ns/sysmlv2#element_IsImpliedIncluded

element_IsImpliedIncluded is an RDF property.

Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with `isImplied = true`, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.

element_IsLibraryElement

http://open-services.net/ns/sysmlv2#element_IsLibraryElement

element_IsLibraryElement is an RDF property.

Whether this Element is contained in the ownership tree of a library model.

element_Name

http://open-services.net/ns/sysmlv2#element_Name

element_Name is an RDF property.

The name to be used for this Element during name resolution within its owningNamespace. This is derived using the `effectiveName()` operation. By default, it is the same as the `declaredName`, but this is overridden for certain kinds of Elements to compute a name even when the `declaredName` is null.

element_OwnedAnnotation

http://open-services.net/ns/sysmlv2#element_OwnedAnnotation

element_OwnedAnnotation is an RDF property.

The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.

element_OwnedElement

http://open-services.net/ns/sysmlv2#element_OwnedElement

element_OwnedElement is an RDF property.

The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

element_OwnedRelationship

http://open-services.net/ns/sysmlv2#element_OwnedRelationship

element_OwnedRelationship is an RDF property.

The Relationships for which this Element is the owningRelatedElement.

element_Owner

http://open-services.net/ns/sysmlv2#element_Owner

element_Owner is an RDF property.

The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.

element_OwningMembership

http://open-services.net/ns/sysmlv2#element_OwningMembership

element_OwningMembership is an RDF property.

The owningRelationship of this Element, if that Relationship is a Membership.

element_OwningNamespace

http://open-services.net/ns/sysmlv2#element_OwningNamespace

element_OwningNamespace is an RDF property.

The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

element_OwningRelationship

http://open-services.net/ns/sysmlv2#element_OwningRelationship

element_OwningRelationship is an RDF property.

The Relationship for which this Element is an ownedRelatedElement, if any.

element_QualifiedName

http://open-services.net/ns/sysmlv2#element_QualifiedName

element_QualifiedName is an RDF property.

The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.

element_ShortName

http://open-services.net/ns/sysmlv2#element_ShortName

element_ShortName is an RDF property.

The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

element_TextualRepresentation

http://open-services.net/ns/sysmlv2#element_TextualRepresentation

element_TextualRepresentation is an RDF property.

The TextualRepresentations that annotate this Element.

elementFilterMembership_Condition

http://open-services.net/ns/sysmlv2#elementFilterMembership_Condition

elementFilterMembership_Condition is an RDF property.

The model-level evaluable Boolean-valued Expression used to filter the imported members of the membershipOwningNamespace of this ElementFilterMembership.

enumerationDefinition_EnumeratedValue

http://open-services.net/ns/sysmlv2#enumerationDefinition_EnumeratedValue

enumerationDefinition_EnumeratedValue is an RDF property.

EnumerationUsages of this EnumerationDefinition that have distinct, fixed values. Each enumeratedValue specifies one of the allowed instances of the EnumerationDefinition.

enumerationUsage_EnumerationDefinition

http://open-services.net/ns/sysmlv2#enumerationUsage_EnumerationDefinition

enumerationUsage_EnumerationDefinition is an RDF property.

The single EnumerationDefinition that is the type of this EnumerationUsage.

eventOccurrenceUsage_EventOccurrence

http://open-services.net/ns/sysmlv2#eventOccurrenceUsage_EventOccurrence

eventOccurrenceUsage_EventOccurrence is an RDF property.

The OccurrenceUsage referenced as an event by this EventOccurrenceUsage. It is the referenceFeature of the ownedReferenceSubsetting for the EventOccurrenceUsage, if there is one, and, otherwise, the EventOccurrenceUsage itself.

exhibitStateUsage_ExhibitedState

http://open-services.net/ns/sysmlv2#exhibitStateUsage_ExhibitedState

exhibitStateUsage_ExhibitedState is an RDF property.

The StateUsage to be exhibited by the ExhibitStateUsage. It is the performedAction of the ExhibitStateUsage considered as a PerformActionUsage, which must be a StateUsage.

expression_Function

http://open-services.net/ns/sysmlv2#expression_Function

expression_Function is an RDF property.

The Function that types this Expression.

expression_IsModelLevelEvaluable

http://open-services.net/ns/sysmlv2#expression_IsModelLevelEvaluable

expression_IsModelLevelEvaluable is an RDF property.

Whether this Expression meets the constraints necessary to be evaluated at model level, that is, using metadata within the model.

expression_Result

http://open-services.net/ns/sysmlv2#expression_Result

expression_Result is an RDF property.

result.

feature_ChainingFeature

http://open-services.net/ns/sysmlv2#feature_ChainingFeature

feature_ChainingFeature is an RDF property.

The Feature that are chained together to determine the values of this Feature, derived from the chainingFeatures of the ownedFeatureChainings of this Feature, in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature.

feature_Direction

http://open-services.net/ns/sysmlv2#feature_Direction

feature_Direction is an RDF property.

Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).

feature_EndOwningType

http://open-services.net/ns/sysmlv2#feature_EndOwningType

feature_EndOwningType is an RDF property.

The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature.

feature_FeaturingType

http://open-services.net/ns/sysmlv2#feature_FeaturingType

feature_FeaturingType is an RDF property.

Types that feature this Feature, such that any instance in the domain of the Feature must be classified by all of these Types, including at least all the featuringTypes of its typeFeaturings. If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature.

feature_IsComposite

http://open-services.net/ns/sysmlv2#feature_IsComposite

feature_IsComposite is an RDF property.

Whether the Feature is a composite feature of its featuringType. If so, the values of the Feature cannot exist after its featuring instance no longer does.

feature_IsDerived

http://open-services.net/ns/sysmlv2#feature_IsDerived

feature_IsDerived is an RDF property.

Whether the values of this Feature can always be computed from the values of other Features.

feature_IsEnd

http://open-services.net/ns/sysmlv2#feature_IsEnd

feature_IsEnd is an RDF property.

Whether or not the this Feature is an end Feature, requiring a different interpretation of the multiplicity of the Feature.

feature_IsNonunique

http://open-services.net/ns/sysmlv2#feature_IsNonunique

feature_IsNonunique is an RDF property.

isNonunique.

feature_IsOrdered

http://open-services.net/ns/sysmlv2#feature_IsOrdered

feature_IsOrdered is an RDF property.

Whether an order exists for the values of this Feature or not.

feature_IsPortion

http://open-services.net/ns/sysmlv2#feature_IsPortion

feature_IsPortion is an RDF property.

Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

feature_IsReadOnly

http://open-services.net/ns/sysmlv2#feature_IsReadOnly

feature_IsReadOnly is an RDF property.

Whether the values of this Feature can change over the lifetime of an instance of the domain.

feature_IsUnique

http://open-services.net/ns/sysmlv2#feature_IsUnique

feature_IsUnique is an RDF property.

Whether or not values for this Feature must have no duplicates or not.

feature_OwnedFeatureChaining

http://open-services.net/ns/sysmlv2#feature_OwnedFeatureChaining

feature_OwnedFeatureChaining is an RDF property.

The ownedRelationships of this Feature that are FeatureChainings, for which the Feature will be the featureChained.

feature_OwnedFeatureInverting

http://open-services.net/ns/sysmlv2#feature_OwnedFeatureInverting

feature_OwnedFeatureInverting is an RDF property.

The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted.

feature_OwnedRedefinition

http://open-services.net/ns/sysmlv2#feature_OwnedRedefinition

feature_OwnedRedefinition is an RDF property.

The ownedSubsettings of this Feature that are Redefinitions, for which the Feature is the redefiningFeature.

feature_OwnedReferenceSubsetting

http://open-services.net/ns/sysmlv2#feature_OwnedReferenceSubsetting

feature_OwnedReferenceSubsetting is an RDF property.

The one ownedSubsetting of this Feature, if any, that is a ReferenceSubsetting, for which the Feature is the referencingFeature.

feature_OwnedSubsetting

http://open-services.net/ns/sysmlv2#feature_OwnedSubsetting

feature_OwnedSubsetting is an RDF property.

The ownedSpecializations of this Feature that are Subsettings, for which the Feature is the subsettingFeature.

feature_OwnedTypeFeaturing

http://open-services.net/ns/sysmlv2#feature_OwnedTypeFeaturing

feature_OwnedTypeFeaturing is an RDF property.

The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType.

feature_OwnedTyping

http://open-services.net/ns/sysmlv2#feature_OwnedTyping

feature_OwnedTyping is an RDF property.

The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.

feature_OwningFeatureMembership

http://open-services.net/ns/sysmlv2#feature_OwningFeatureMembership

feature_OwningFeatureMembership is an RDF property.

The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.

feature_OwningType

http://open-services.net/ns/sysmlv2#feature_OwningType

feature_OwningType is an RDF property.

The Type that is the owningType of the owningFeatureMembership of this Feature.

feature_Type

http://open-services.net/ns/sysmlv2#feature_Type

feature_Type is an RDF property.

Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.

featureChainExpression_TargetFeature

http://open-services.net/ns/sysmlv2#featureChainExpression_TargetFeature

featureChainExpression_TargetFeature is an RDF property.

The Feature that is accessed by this FeatureChainExpression, which is its first non-parameter member.

featureChaining_ChainingFeature

http://open-services.net/ns/sysmlv2#featureChaining_ChainingFeature

featureChaining_ChainingFeature is an RDF property.

The Feature whose values partly determine values of featureChained, as described in Feature::chainingFeature.

featureChaining_FeatureChained

http://open-services.net/ns/sysmlv2#featureChaining_FeatureChained

featureChaining_FeatureChained is an RDF property.

The Feature whose values are partly determined by values of the chainingFeature, as described in Feature::chainingFeature.

featureInverting_FeatureInverted

http://open-services.net/ns/sysmlv2#featureInverting_FeatureInverted

featureInverting_FeatureInverted is an RDF property.

The Feature that is an inverse of the invertingFeature.

featureInverting_InvertingFeature

http://open-services.net/ns/sysmlv2#featureInverting_InvertingFeature

featureInverting_InvertingFeature is an RDF property.

The Feature that is an inverse of the invertedFeature.

featureInverting_OwningFeature

http://open-services.net/ns/sysmlv2#featureInverting_OwningFeature

featureInverting_OwningFeature is an RDF property.

A featureInverted that is also the owningRelatedElement of this FeatureInverting.

featureMembership_OwnedMemberFeature

http://open-services.net/ns/sysmlv2#featureMembership_OwnedMemberFeature

featureMembership_OwnedMemberFeature is an RDF property.

The Feature that this FeatureMembership relates to its owningType, making it an ownedFeature of the owningType.

featureMembership_OwningType

http://open-services.net/ns/sysmlv2#featureMembership_OwningType

featureMembership_OwningType is an RDF property.

The Type that owns this FeatureMembership.

featureReferenceExpression_Referent

http://open-services.net/ns/sysmlv2#featureReferenceExpression_Referent

featureReferenceExpression_Referent is an RDF property.

The Feature that is referenced by this FeatureReferenceExpression, which is its first non-parameter member.

featureTyping_OwningFeature

http://open-services.net/ns/sysmlv2#featureTyping_OwningFeature

featureTyping_OwningFeature is an RDF property.

A typedFeature that is also the owningRelatedElement of this FeatureTyping.

featureTyping_Type

http://open-services.net/ns/sysmlv2#featureTyping_Type

featureTyping_Type is an RDF property.

The Type that is being applied by this FeatureTyping.

featureTyping_TypedFeature

http://open-services.net/ns/sysmlv2#featureTyping_TypedFeature

featureTyping_TypedFeature is an RDF property.

The Feature that has a type determined by this FeatureTyping.

featureValue_FeatureWithValue

http://open-services.net/ns/sysmlv2#featureValue_FeatureWithValue

featureValue_FeatureWithValue is an RDF property.

The Feature to be provided a value.

featureValue_IsDefault

http://open-services.net/ns/sysmlv2#featureValue_IsDefault

featureValue_IsDefault is an RDF property.

Whether this FeatureValue is a concrete specification of the bound or initial value of the featureWithValue, or just a default value that may be overridden.

featureValue_IsInitial

http://open-services.net/ns/sysmlv2#featureValue_IsInitial

featureValue_IsInitial is an RDF property.

Whether this FeatureValue specifies a bound value or an initial value for the featureWithValue.

featureValue_Value

http://open-services.net/ns/sysmlv2#featureValue_Value

featureValue_Value is an RDF property.

The Expression that provides the value of the featureWithValue as its result.

featuring_Feature

http://open-services.net/ns/sysmlv2#featuring_Feature

featuring_Feature is an RDF property.

The Feature that is featured by the featuringType.

featuring_Type

http://open-services.net/ns/sysmlv2#featuring_Type

featuring_Type is an RDF property.

The Type that features the featureOfType.

flowConnectionUsage_FlowConnectionDefinition

http://open-services.net/ns/sysmlv2#flowConnectionUsage_FlowConnectionDefinition

flowConnectionUsage_FlowConnectionDefinition is an RDF property.

The Interactions that are the types of this FlowConnectionUsage. Nominally, these are FlowConnectionDefinitions, but other kinds of Kernel Interactions are also allowed, to permit use of Interactions from the Kernel Model Libraries.

forLoopActionUsage_LoopVariable

http://open-services.net/ns/sysmlv2#forLoopActionUsage_LoopVariable

forLoopActionUsage_LoopVariable is an RDF property.

The ownedFeature of this ForLoopActionUsage that acts as the loop variable, which is assigned the successive values of the input sequence on each iteration. It is the ownedFeature that redefines ForLoopAction::var.

forLoopActionUsage_SeqArgument

http://open-services.net/ns/sysmlv2#forLoopActionUsage_SeqArgument

forLoopActionUsage_SeqArgument is an RDF property.

The Expression whose result provides the sequence of values to which the loopVariable is set for each iterative performance of the bodyAction. It is the Expression whose result is bound to the seq input parameter of this ForLoopActionUsage.

framedConcernMembership_OwnedConcern

http://open-services.net/ns/sysmlv2#framedConcernMembership_OwnedConcern

framedConcernMembership_OwnedConcern is an RDF property.

The ConcernUsage that is the ownedConstraint of this FramedConcernMembership.

framedConcernMembership_ReferencedConcern

http://open-services.net/ns/sysmlv2#framedConcernMembership_ReferencedConcern

framedConcernMembership_ReferencedConcern is an RDF property.

The ConcernUsage that is referenced through this FramedConcernMembership. It is the referencedConstraint of the FramedConcernMembership considered as a RequirementConstraintMembership, which must be a ConcernUsage.

function_Expression

http://open-services.net/ns/sysmlv2#function_Expression

function_Expression is an RDF property.

The Expressions that are steps in the calculation of the result of this Function.

function_IsModelLevelEvaluable

http://open-services.net/ns/sysmlv2#function_IsModelLevelEvaluable

function_IsModelLevelEvaluable is an RDF property.

Whether this Function can be used as the function of a model-level evaluable InvocationExpression. Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true. For all other Functions it is false.

function_Result

http://open-services.net/ns/sysmlv2#function_Result

function_Result is an RDF property.

The result parameter of the Function, which is owned by the Function via a ReturnParameterMembership.

ifActionUsage_ElseAction

http://open-services.net/ns/sysmlv2#ifActionUsage_ElseAction

ifActionUsage_ElseAction is an RDF property.

The ActionUsage that is to be performed if the result of the ifArgument is false. It is the (optional) third parameter of the IfActionUsage.

ifActionUsage_IfArgument

http://open-services.net/ns/sysmlv2#ifActionUsage_IfArgument

ifActionUsage_IfArgument is an RDF property.

The Expression whose result determines whether the thenAction or (optionally) the elseAction is performed. It is the first parameter of the IfActionUsage.

ifActionUsage_ThenAction

http://open-services.net/ns/sysmlv2#ifActionUsage_ThenAction

ifActionUsage_ThenAction is an RDF property.

The ActionUsage that is to be performed if the result of the ifArgument is true. It is the second parameter of the IfActionUsage.

import_ImportedElement

http://open-services.net/ns/sysmlv2#import_ImportedElement

import_ImportedElement is an RDF property.

The effectively imported Element for this Import. For a MembershipImport, this is the memberElement of the importedMembership. For a NamespaceImport, it is the importedNamespace.

import_ImportOwningNamespace

http://open-services.net/ns/sysmlv2#import_ImportOwningNamespace

import_ImportOwningNamespace is an RDF property.

The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.

import_IsImportAll

http://open-services.net/ns/sysmlv2#import_IsImportAll

import_IsImportAll is an RDF property.

Whether to import memberships without regard to declared visibility.

import_IsRecursive

http://open-services.net/ns/sysmlv2#import_IsRecursive

import_IsRecursive is an RDF property.

Whether to recursively import Memberships from visible, owned sub-Namespaces.

import_Visibility

http://open-services.net/ns/sysmlv2#import_Visibility

import_Visibility is an RDF property.

The visibility level of the imported members from this Import relative to the importOwningNamespace.

includeUseCaseUsage_UseCaseIncluded

http://open-services.net/ns/sysmlv2#includeUseCaseUsage_UseCaseIncluded

includeUseCaseUsage_UseCaseIncluded is an RDF property.

The UseCaseUsage to be included by this IncludeUseCaseUsage. It is the performedAction of the IncludeUseCaseUsage considered as a PerformActionUsage, which must be a UseCaseUsage.

interfaceDefinition_InterfaceEnd

http://open-services.net/ns/sysmlv2#interfaceDefinition_InterfaceEnd

interfaceDefinition_InterfaceEnd is an RDF property.

The PortUsages that are the connectionEnds of this InterfaceDefinition. .

interfaceUsage_InterfaceDefinition

http://open-services.net/ns/sysmlv2#interfaceUsage_InterfaceDefinition

interfaceUsage_InterfaceDefinition is an RDF property.

The InterfaceDefinitions that type this InterfaceUsage.

intersecting_IntersectingType

http://open-services.net/ns/sysmlv2#intersecting_IntersectingType

intersecting_IntersectingType is an RDF property.

Type that partly determines interpretations of typeIntersected, as described in Type::intersectingType.

intersecting_TypeIntersected

http://open-services.net/ns/sysmlv2#intersecting_TypeIntersected

intersecting_TypeIntersected is an RDF property.

Type with interpretations partly determined by *intersectingType*, as described in *Type::intersectingType*.

invariant_IsNegated

http://open-services.net/ns/sysmlv2#invariant_IsNegated

invariant_IsNegated is an RDF property.

Whether this Invariant is asserted to be false rather than true.

invocationExpression_Argument

http://open-services.net/ns/sysmlv2#invocationExpression_Argument

invocationExpression_Argument is an RDF property.

The value Expressions of the FeatureValues of the owned input parameters of the *InvocationExpression*.

invocationExpression_Operand

http://open-services.net/ns/sysmlv2#invocationExpression_Operand

invocationExpression_Operand is an RDF property.

operand.

itemFlow_Interaction

http://open-services.net/ns/sysmlv2#itemFlow_Interaction

itemFlow_Interaction is an RDF property.

The Interactions that type this *ItemFlow*. Interactions are both Associations and Behaviors, which can type Connectors and Steps, respectively.

itemFlow_ItemFeature

http://open-services.net/ns/sysmlv2#itemFlow_ItemFeature

itemFlow_ItemFeature is an RDF property.

The ownedFeature of the *ItemFlow* that is an *ItemFeature* (if any).

itemFlow_ItemFlowEnd

http://open-services.net/ns/sysmlv2#itemFlow_ItemFlowEnd

itemFlow_ItemFlowEnd is an RDF property.

The connectorEnds of this *ItemFlow* that are *ItemFlowEnds*.

itemFlow_ItemType

http://open-services.net/ns/sysmlv2#itemFlow_ItemType

itemFlow_ItemType is an RDF property.

The type of values transferred, which is the type of the itemFeature of the ItemFlow.

itemFlow_SourceOutputFeature

http://open-services.net/ns/sysmlv2#itemFlow_SourceOutputFeature

itemFlow_SourceOutputFeature is an RDF property.

The Feature that provides the items carried by the ItemFlow. It must be an owned output of the source of the ItemFlow.

itemFlow_TargetInputFeature

http://open-services.net/ns/sysmlv2#itemFlow_TargetInputFeature

itemFlow_TargetInputFeature is an RDF property.

The Feature that receives the values carried by the ItemFlow. It must be an owned output of the target participant of the ItemFlow.

itemUsage_ItemDefinition

http://open-services.net/ns/sysmlv2#itemUsage_ItemDefinition

itemUsage_ItemDefinition is an RDF property.

The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.

libraryPackage_IsStandard

http://open-services.net/ns/sysmlv2#libraryPackage_IsStandard

libraryPackage_IsStandard is an RDF property.

Whether this LibraryPackage contains a standard library model. This should only be set to true for LibraryPackages in the standard Kernel Model Libraries or in normative model libraries for a language built on KerML.

literalBoolean_Value

http://open-services.net/ns/sysmlv2#literalBoolean_Value

literalBoolean_Value is an RDF property.

The Boolean value that is the result of evaluating this LiteralBoolean.

literalInteger_Value

http://open-services.net/ns/sysmlv2#literalInteger_Value

literalInteger_Value is an RDF property.

The Integer value that is the result of evaluating this LiteralInteger.

literalRational_Value

http://open-services.net/ns/sysmlv2#literalRational_Value

literalRational_Value is an RDF property.

The value whose rational approximation is the result of evaluating this LiteralRational.

literalString_Value

http://open-services.net/ns/sysmlv2#literalString_Value

literalString_Value is an RDF property.

The String value that is the result of evaluating this LiteralString.

loopActionUsage_BodyAction

http://open-services.net/ns/sysmlv2#loopActionUsage_BodyAction

loopActionUsage_BodyAction is an RDF property.

The ActionUsage to be performed repeatedly by the LoopActionUsage. It is the second parameter of the LoopActionUsage.

membership_MemberElement

http://open-services.net/ns/sysmlv2#membership_MemberElement

membership_MemberElement is an RDF property.

The Element that becomes a member of the membershipOwningNamespace due to this Membership.

membership_MemberElementId

http://open-services.net/ns/sysmlv2#membership_MemberElementId

membership_MemberElementId is an RDF property.

The elementId of the memberElement.

membership_MemberName

http://open-services.net/ns/sysmlv2#membership_MemberName

membership_MemberName is an RDF property.

The name of the memberElement relative to the membershipOwningNamespace.

membership_MembershipOwningNamespace

http://open-services.net/ns/sysmlv2#membership_MembershipOwningNamespace

membership_MembershipOwningNamespace is an RDF property.

The Namespace of which the memberElement becomes a member due to this Membership.

membership_MemberShortName

http://open-services.net/ns/sysmlv2#membership_MemberShortName

membership_MemberShortName is an RDF property.

The short name of the memberElement relative to the membershipOwningNamespace.

membership_Visibility

http://open-services.net/ns/sysmlv2#membership_Visibility

membership_Visibility is an RDF property.

Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace.

membershipImport_ImportedMembership

http://open-services.net/ns/sysmlv2#membershipImport_ImportedMembership

membershipImport_ImportedMembership is an RDF property.

The Membership to be imported.

metadataAccessExpression_ReferencedElement

http://open-services.net/ns/sysmlv2#metadataAccessExpression_ReferencedElement

metadataAccessExpression_ReferencedElement is an RDF property.

The Element whose metadata is being accessed.

metadataFeature_Metaclass

http://open-services.net/ns/sysmlv2#metadataFeature_Metaclass

metadataFeature_Metaclass is an RDF property.

The type of this MetadataFeature, which must be a Metaclass.

metadataUsage_MetadataDefinition

http://open-services.net/ns/sysmlv2#metadataUsage_MetadataDefinition

metadataUsage_MetadataDefinition is an RDF property.

The MetadataDefinition that is the definition of this MetadataUsage.

multiplicityRange_Bound

http://open-services.net/ns/sysmlv2#multiplicityRange_Bound

multiplicityRange_Bound is an RDF property.

The owned Expressions of the MultiplicityRange whose results provide its bounds. These must be the only ownedMembers of the MultiplicityRange.

multiplicityRange_LowerBound

http://open-services.net/ns/sysmlv2#multiplicityRange_LowerBound

multiplicityRange_LowerBound is an RDF property.

The Expression whose result provides the lower bound of the MultiplicityRange. If no lowerBound Expression is given, then the lower bound shall have the same value as the upper bound, unless the upper bound is unbounded (*), in which case the lower bound shall be 0.

multiplicityRange_UpperBound

http://open-services.net/ns/sysmlv2#multiplicityRange_UpperBound

multiplicityRange_UpperBound is an RDF property.

The Expression whose result is the upper bound of the MultiplicityRange.

namespace_ImportedMembership

http://open-services.net/ns/sysmlv2#namespace_ImportedMembership

namespace_ImportedMembership is an RDF property.

The Memberships in this Namespace that result from the ownedImports of this Namespace.

namespace_Member

http://open-services.net/ns/sysmlv2#namespace_Member

namespace_Member is an RDF property.

The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.

namespace_Membership

http://open-services.net/ns/sysmlv2#namespace_Membership

namespace_Membership is an RDF property.

All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.

namespace_OwnedImport

http://open-services.net/ns/sysmlv2#namespace_OwnedImport

namespace_OwnedImport is an RDF property.

The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.

namespace_OwnedMember

http://open-services.net/ns/sysmlv2#namespace_OwnedMember

namespace_OwnedMember is an RDF property.

The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the .

namespace_OwnedMembership

http://open-services.net/ns/sysmlv2#namespace_OwnedMembership

namespace_OwnedMembership is an RDF property.

The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.

namespaceImport_ImportedNamespace

http://open-services.net/ns/sysmlv2#namespaceImport_ImportedNamespace

namespaceImport_ImportedNamespace is an RDF property.

The Namespace whose visible Memberships are imported by this NamespaceImport.

objectiveMembership_OwnedObjectiveRequirement

http://open-services.net/ns/sysmlv2#objectiveMembership_OwnedObjectiveRequirement

objectiveMembership_OwnedObjectiveRequirement is an RDF property.

The RequirementUsage that is the ownedMemberFeature of this RequirementUsage.

occurrenceDefinition_IsIndividual

http://open-services.net/ns/sysmlv2#occurrenceDefinition_IsIndividual

occurrenceDefinition_IsIndividual is an RDF property.

Whether this OccurrenceDefinition is constrained to represent single individual.

occurrenceDefinition_LifeClass

http://open-services.net/ns/sysmlv2#occurrenceDefinition_LifeClass

occurrenceDefinition_LifeClass is an RDF property.

If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition, restricting it to represent an individual.

occurrenceUsage_IndividualDefinition

http://open-services.net/ns/sysmlv2#occurrenceUsage_IndividualDefinition

occurrenceUsage_IndividualDefinition is an RDF property.

The at most one occurrenceDefinition that has isIndividual = true.

occurrenceUsage_IsIndividual

http://open-services.net/ns/sysmlv2#occurrenceUsage_IsIndividual

occurrenceUsage_IsIndividual is an RDF property.

Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition.

occurrenceUsage_OccurrenceDefinition

http://open-services.net/ns/sysmlv2#occurrenceUsage_OccurrenceDefinition

occurrenceUsage_OccurrenceDefinition is an RDF property.

The Classes that are the types of this OccurrenceUsage. Nominally, these are OccurrenceDefinitions, but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.

occurrenceUsage_PortionKind

http://open-services.net/ns/sysmlv2#occurrenceUsage_PortionKind

occurrenceUsage_PortionKind is an RDF property.

The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage, if it is so restricted.

operatorExpression_Operator

http://open-services.net/ns/sysmlv2#operatorExpression_Operator

operatorExpression_Operator is an RDF property.

An operator symbol that names a corresponding Function from one of the standard packages from the Kernel Function Library .

owningMembership_OwnedMemberElement

http://open-services.net/ns/sysmlv2#owningMembership_OwnedMemberElement

owningMembership_OwnedMemberElement is an RDF property.

The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership.

owningMembership_OwnedMemberElementId

http://open-services.net/ns/sysmlv2#owningMembership_OwnedMemberElementId

owningMembership_OwnedMemberElementId is an RDF property.

The elementId of the ownedMemberElement.

owningMembership_OwnedMemberName

http://open-services.net/ns/sysmlv2#owningMembership_OwnedMemberName

owningMembership_OwnedMemberName is an RDF property.

The name of the ownedMemberElement.

owningMembership_OwnedMemberShortName

http://open-services.net/ns/sysmlv2#owningMembership_OwnedMemberShortName

owningMembership_OwnedMemberShortName is an RDF property.

The shortName of the ownedMemberElement.

package_FilterCondition

http://open-services.net/ns/sysmlv2#package_FilterCondition

package_FilterCondition is an RDF property.

The model-level evaluable Boolean-valued Expression used to filter the members of this Package, which are owned by the Package are via ElementFilterMemberships.

parameterMembership_OwnedMemberParameter

http://open-services.net/ns/sysmlv2#parameterMembership_OwnedMemberParameter

parameterMembership_OwnedMemberParameter is an RDF property.

The Feature that is identified as a parameter by this ParameterMembership.

partUsage_PartDefinition

http://open-services.net/ns/sysmlv2#partUsage_PartDefinition

partUsage_PartDefinition is an RDF property.

The itemDefinitions of this PartUsage that are PartDefinitions.

performActionUsage_PerformedAction

http://open-services.net/ns/sysmlv2#performActionUsage_PerformedAction

performActionUsage_PerformedAction is an RDF property.

The ActionUsage to be performed by this PerformedActionUsage. It is the eventOccurrence of the PerformActionUsage considered as an EventOccurrenceUsage, which must be an ActionUsage.

portConjugation_ConjugatedPortDefinition

http://open-services.net/ns/sysmlv2#portConjugation_ConjugatedPortDefinition

portConjugation_ConjugatedPortDefinition is an RDF property.

The ConjugatedPortDefinition that is conjugate to the originalPortDefinition.

portConjugation_OriginalPortDefinition

http://open-services.net/ns/sysmlv2#portConjugation_OriginalPortDefinition

portConjugation_OriginalPortDefinition is an RDF property.

The PortDefinition being conjugated.

portDefinition_ConjugatedPortDefinition

http://open-services.net/ns/sysmlv2#portDefinition_ConjugatedPortDefinition

portDefinition_ConjugatedPortDefinition is an RDF property.

The that is conjugate to this PortDefinition.

portUsage_PortDefinition

http://open-services.net/ns/sysmlv2#portUsage_PortDefinition

portUsage_PortDefinition is an RDF property.

The occurrenceDefinitions of this PortUsage, which must all be PortDefinitions.

redefinition_RedefinedFeature

http://open-services.net/ns/sysmlv2#redefinition_RedefinedFeature

redefinition_RedefinedFeature is an RDF property.

The Feature that is redefined by the redefiningFeature of this Redefinition.

redefinition_RedefiningFeature

http://open-services.net/ns/sysmlv2#redefinition_RedefiningFeature

redefinition_RedefiningFeature is an RDF property.

The Feature that is redefining the redefinedFeature of this Redefinition.

referenceSubsetting_ReferencedFeature

http://open-services.net/ns/sysmlv2#referenceSubsetting_ReferencedFeature

referenceSubsetting_ReferencedFeature is an RDF property.

The Feature that is referenced by the referencingFeature of this ReferenceSubsetting.

referenceSubsetting_ReferencingFeature

http://open-services.net/ns/sysmlv2#referenceSubsetting_ReferencingFeature

referenceSubsetting_ReferencingFeature is an RDF property.

The Feature that owns this ReferenceSubsetting relationship, which is also its subsettingFeature.

relationship_IsImplied

http://open-services.net/ns/sysmlv2#relationship_IsImplied

relationship_IsImplied is an RDF property.

Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.

relationship_OwnedRelatedElement

http://open-services.net/ns/sysmlv2#relationship_OwnedRelatedElement

relationship_OwnedRelatedElement is an RDF property.

The relatedElements of this Relationship that are owned by the Relationship.

relationship_OwningRelatedElement

http://open-services.net/ns/sysmlv2#relationship_OwningRelatedElement

relationship_OwningRelatedElement is an RDF property.

The relatedElement of this Relationship that owns the Relationship, if any.

relationship_RelatedElement

http://open-services.net/ns/sysmlv2#relationship_RelatedElement

relationship_RelatedElement is an RDF property.

The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.

relationship_Source

http://open-services.net/ns/sysmlv2#relationship_Source

relationship_Source is an RDF property.

The relatedElements from which this Relationship is considered to be directed.

relationship_Target

http://open-services.net/ns/sysmlv2#relationship_Target

relationship_Target is an RDF property.

The relatedElements to which this Relationship is considered to be directed.

renderingDefinition_Rendering

http://open-services.net/ns/sysmlv2#renderingDefinition_Rendering

renderingDefinition_Rendering is an RDF property.

The usages of a RenderingDefinition that are RenderingUsages.

renderingUsage_RenderingDefinition

http://open-services.net/ns/sysmlv2#renderingUsage_RenderingDefinition

renderingUsage_RenderingDefinition is an RDF property.

The RenderingDefinition that is the definition of this RenderingUsage.

requirementConstraintMembership_Kind

http://open-services.net/ns/sysmlv2#requirementConstraintMembership_Kind

requirementConstraintMembership_Kind is an RDF property.

Whether the RequirementConstraintMembership is for an assumed or required ConstraintUsage.

requirementConstraintMembership_OwnedConstraint

http://open-services.net/ns/sysmlv2#requirementConstraintMembership_OwnedConstraint

requirementConstraintMembership_OwnedConstraint is an RDF property.

The ConstraintUsage that is the ownedMemberFeature of this RequirementConstraintMembership.

requirementConstraintMembership_ReferencedConstraint

http://open-services.net/ns/sysmlv2#requirementConstraintMembership_ReferencedConstraint

requirementConstraintMembership_ReferencedConstraint is an RDF property.

The ConstraintUsage that is referenced through this RequirementConstraintMembership. It is the referencedFeature of the ownedReferenceSubsetting of the ownedConstraint, if there is one, and, otherwise, the ownedConstraint itself.

requirementDefinition_ActorParameter

http://open-services.net/ns/sysmlv2#requirementDefinition_ActorParameter

requirementDefinition_ActorParameter is an RDF property.

The parameters of this RequirementDefinition that represent actors involved in the requirement.

requirementDefinition_AssumedConstraint

http://open-services.net/ns/sysmlv2#requirementDefinition_AssumedConstraint

requirementDefinition_AssumedConstraint is an RDF property.

The owned ConstraintUsages that represent assumptions of this RequirementDefinition, which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = assumption.

requirementDefinition_FramedConcern

http://open-services.net/ns/sysmlv2#requirementDefinition_FramedConcern

requirementDefinition_FramedConcern is an RDF property.

The ConcernUsages framed by this RequirementDefinition, which are the ownedConcerns of all FramedConcernMemberships of the RequirementDefinition.

requirementDefinition_ReqlId

http://open-services.net/ns/sysmlv2#requirementDefinition_ReqlId

requirementDefinition_ReqlId is an RDF property.

An optional modeler-specified identifier for this RequirementDefinition (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementDefinition.

requirementDefinition_RequiredConstraint

http://open-services.net/ns/sysmlv2#requirementDefinition_RequiredConstraint

requirementDefinition_RequiredConstraint is an RDF property.

The owned ConstraintUsages that represent requirements of this RequirementDefinition, derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = requirement.

requirementDefinition_StakeholderParameter

http://open-services.net/ns/sysmlv2#requirementDefinition_StakeholderParameter

requirementDefinition_StakeholderParameter is an RDF property.

The parameters of this RequirementDefinition that represent stakeholders for th requirement.

requirementDefinition_SubjectParameter

http://open-services.net/ns/sysmlv2#requirementDefinition_SubjectParameter

requirementDefinition_SubjectParameter is an RDF property.

The parameter of this RequirementDefinition that represents its subject.

requirementDefinition_Text

http://open-services.net/ns/sysmlv2#requirementDefinition_Text

requirementDefinition_Text is an RDF property.

An optional textual statement of the requirement represented by this RequirementDefinition, derived from the bodies of the documentation of the RequirementDefinition.

requirementUsage_ActorParameter

http://open-services.net/ns/sysmlv2#requirementUsage_ActorParameter

requirementUsage_ActorParameter is an RDF property.

The parameters of this RequirementUsage that represent actors involved in the requirement.

requirementUsage_AssumedConstraint

http://open-services.net/ns/sysmlv2#requirementUsage_AssumedConstraint

requirementUsage_AssumedConstraint is an RDF property.

The owned ConstraintUsages that represent assumptions of this RequirementUsage, derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = assumption.

requirementUsage_FramedConcern

http://open-services.net/ns/sysmlv2#requirementUsage_FramedConcern

requirementUsage_FramedConcern is an RDF property.

The ConcernUsages framed by this RequirementUsage, which are the ownedConcerns of all FramedConcernMemberships of the RequirementUsage.

requirementUsage_ReqlId

http://open-services.net/ns/sysmlv2#requirementUsage_ReqlId

requirementUsage_ReqlId is an RDF property.

An optional modeler-specified identifier for this RequirementUsage (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementUsage.

requirementUsage_RequiredConstraint

http://open-services.net/ns/sysmlv2#requirementUsage_RequiredConstraint

requirementUsage_RequiredConstraint is an RDF property.

The owned ConstraintUsages that represent requirements of this RequirementUsage, which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = requirement.

requirementUsage_RequirementDefinition

http://open-services.net/ns/sysmlv2#requirementUsage_RequirementDefinition

requirementUsage_RequirementDefinition is an RDF property.

The RequirementDefinition that is the single definition of this RequirementUsage.

requirementUsage_StakeholderParameter

http://open-services.net/ns/sysmlv2#requirementUsage_StakeholderParameter

requirementUsage_StakeholderParameter is an RDF property.

The parameters of this RequirementUsage that represent stakeholders for the requirement.

requirementUsage_SubjectParameter

http://open-services.net/ns/sysmlv2#requirementUsage_SubjectParameter

requirementUsage_SubjectParameter is an RDF property.

The parameter of this RequirementUsage that represents its subject.

requirementUsage_Text

http://open-services.net/ns/sysmlv2#requirementUsage_Text

requirementUsage_Text is an RDF property.

An optional textual statement of the requirement represented by this RequirementUsage, derived from the bodies of the documentation of the RequirementUsage.

requirementVerificationMembership_OwnedRequirement

http://open-services.net/ns/sysmlv2#requirementVerificationMembership_OwnedRequirement

requirementVerificationMembership_OwnedRequirement is an RDF property.

The owned RequirementUsage that acts as the ownedConstraint for this RequirementVerificationMembership. This will either be the verifiedRequirement, or it will subset the verifiedRequirement.

requirementVerificationMembership_VerifiedRequirement

http://open-services.net/ns/sysmlv2#requirementVerificationMembership_VerifiedRequirement

requirementVerificationMembership_VerifiedRequirement is an RDF property.

The RequirementUsage that is identified as being verified. It is the referencedConstraint of the RequirementVerificationMembership considered as a RequirementConstraintMembership, which must be a RequirementUsage.

resultExpressionMembership_OwnedResultExpression

http://open-services.net/ns/sysmlv2#resultExpressionMembership_OwnedResultExpression

resultExpressionMembership_OwnedResultExpression is an RDF property.

The Expression that provides the result for the owner of the ResultExpressionMembership.

satisfyRequirementUsage_SatisfiedRequirement

http://open-services.net/ns/sysmlv2#satisfyRequirementUsage_SatisfiedRequirement

satisfyRequirementUsage_SatisfiedRequirement is an RDF property.

The RequirementUsage that is satisfied by the satisfyingSubject of this SatisfyRequirementUsage. It is the assertedConstraint of the SatisfyRequirementUsage considered as an AssertConstraintUsage, which must be a RequirementUsage.

satisfyRequirementUsage_SatisfyingFeature

http://open-services.net/ns/sysmlv2#satisfyRequirementUsage_SatisfyingFeature

satisfyRequirementUsage_SatisfyingFeature is an RDF property.

The Feature that represents the actual subject that is asserted to satisfy the satisfiedRequirement. The satisfyingFeature is bound to the subjectParameter of the SatisfyRequirementUsage.

sendActionUsage_PayloadArgument

http://open-services.net/ns/sysmlv2#sendActionUsage_PayloadArgument

sendActionUsage_PayloadArgument is an RDF property.

An Expression whose result is bound to the payload input parameter of this SendActionUsage.

sendActionUsage_ReceiverArgument

http://open-services.net/ns/sysmlv2#sendActionUsage_ReceiverArgument

sendActionUsage_ReceiverArgument is an RDF property.

An Expression whose result is bound to the receiver input parameter of this SendActionUsage.

sendActionUsage_SenderArgument

http://open-services.net/ns/sysmlv2#sendActionUsage_SenderArgument

sendActionUsage_SenderArgument is an RDF property.

An Expression whose result is bound to the sender input parameter of this SendActionUsage.

specialization_General

http://open-services.net/ns/sysmlv2#specialization_General

specialization_General is an RDF property.

A Type with a superset of all instances of the specific Type, which might be the same set.

specialization_OwningType

http://open-services.net/ns/sysmlv2#specialization_OwningType

specialization_OwningType is an RDF property.

The Type that is the specific Type of this Specialization and owns it as its owningRelatedElement.

specialization_Specific

http://open-services.net/ns/sysmlv2#specialization_Specific

specialization_Specific is an RDF property.

A Type with a subset of all instances of the general Type, which might be the same set.

stakeholderMembership_OwnedStakeholderParameter

http://open-services.net/ns/sysmlv2#stakeholderMembership_OwnedStakeholderParameter

stakeholderMembership_OwnedStakeholderParameter is an RDF property.

The PartUsage specifying the stakeholder.

stateDefinition_DoAction

http://open-services.net/ns/sysmlv2#stateDefinition_DoAction

stateDefinition_DoAction is an RDF property.

The ActionUsage of this StateDefinition to be performed while in the state defined by the StateDefinition. It is the owned ActionUsage related to the StateDefinition by a StateSubactionMembership with kind = do.

stateDefinition_EntryAction

http://open-services.net/ns/sysmlv2#stateDefinition_EntryAction

stateDefinition_EntryAction is an RDF property.

The ActionUsage of this StateDefinition to be performed on entry to the state defined by the StateDefinition. It is the owned ActionUsage related to the StateDefinition by a StateSubactionMembership with kind = entry.

stateDefinition_ExitAction

http://open-services.net/ns/sysmlv2#stateDefinition_ExitAction

stateDefinition_ExitAction is an RDF property.

The ActionUsage of this StateDefinition to be performed on exit to the state defined by the StateDefinition. It is the owned ActionUsage related to the StateDefinition by a StateSubactionMembership with kind = exit.

stateDefinition_IsParallel

http://open-services.net/ns/sysmlv2#stateDefinition_IsParallel

stateDefinition_IsParallel is an RDF property.

Whether the ownedStates of this StateDefinition are to all be performed in parallel. If true, none of the ownedActions (which includes ownedStates) may have any incoming or outgoing Transitions. If false, only one ownedState may be performed at a time.

stateDefinition_State

http://open-services.net/ns/sysmlv2#stateDefinition_State

stateDefinition_State is an RDF property.

The StateUsages, which are actions in the StateDefinition, that specify the discrete states in the behavior defined by the StateDefinition.

stateSubactionMembership_Action

http://open-services.net/ns/sysmlv2#stateSubactionMembership_Action

stateSubactionMembership_Action is an RDF property.

The ActionUsage that is the ownedMemberFeature of this StateSubactionMembership.

stateSubactionMembership_Kind

http://open-services.net/ns/sysmlv2#stateSubactionMembership_Kind

stateSubactionMembership_Kind is an RDF property.

Whether this StateSubactionMembership is for an entry, do or exit ActionUsage.

stateUsage_DoAction

http://open-services.net/ns/sysmlv2#stateUsage_DoAction

stateUsage_DoAction is an RDF property.

The ActionUsage of this StateUsage to be performed while in the state defined by the StateDefinition. It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = do.

stateUsage_EntryAction

http://open-services.net/ns/sysmlv2#stateUsage_EntryAction

stateUsage_EntryAction is an RDF property.

The ActionUsage of this StateUsage to be performed on entry to the state defined by the StateDefinition. It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = entry.

stateUsage_ExitAction

http://open-services.net/ns/sysmlv2#stateUsage_ExitAction

stateUsage_ExitAction is an RDF property.

The ActionUsage of this StateUsage to be performed on exit to the state defined by the StateDefinition. It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = exit.

stateUsage_IsParallel

http://open-services.net/ns/sysmlv2#stateUsage_IsParallel

stateUsage_IsParallel is an RDF property.

Whether the nestedStates of this StateUsage are to all be performed in parallel. If true, none of the nestedActions (which include nestedStates) may have any incoming or outgoing Transitions. If false, only one nestedState may be performed at a time.

stateUsage_StateDefinition

http://open-services.net/ns/sysmlv2#stateUsage_StateDefinition

stateUsage_StateDefinition is an RDF property.

The Behaviors that are the types of this StateUsage. Nominally, these would be StateDefinitions, but kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.

step_Behavior

http://open-services.net/ns/sysmlv2#step_Behavior

step_Behavior is an RDF property.

The Behaviors that type this Step.

step_Parameter

http://open-services.net/ns/sysmlv2#step_Parameter

step_Parameter is an RDF property.

The parameters of this Step, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Step.

subclassification_OwningClassifier

http://open-services.net/ns/sysmlv2#subclassification_OwningClassifier

subclassification_OwningClassifier is an RDF property.

The Classifier that owns this Subclassification relationship, which must also be its subclassifier.

subclassification_Subclassifier

http://open-services.net/ns/sysmlv2#subclassification_Subclassifier

subclassification_Subclassifier is an RDF property.

The more specific Classifier in this Subclassification.

subclassification_Superclassifier

http://open-services.net/ns/sysmlv2#subclassification_Superclassifier

subclassification_Superclassifier is an RDF property.

The more general Classifier in this Subclassification.

subjectMembership_OwnedSubjectParameter

http://open-services.net/ns/sysmlv2#subjectMembership_OwnedSubjectParameter

subjectMembership_OwnedSubjectParameter is an RDF property.

The UsageownedMemberParameter of this SubjectMembership.

subsetting_OwningFeature

http://open-services.net/ns/sysmlv2#subsetting_OwningFeature

subsetting_OwningFeature is an RDF property.

A subsettingFeature that is also the owningRelatedElement of this Subsetting.

subsetting_SubsettedFeature

http://open-services.net/ns/sysmlv2#subsetting_SubsettedFeature

subsetting_SubsettedFeature is an RDF property.

The Feature that is subsetted by the subsettingFeature of this Subsetting.

subsetting_SubsettingFeature

http://open-services.net/ns/sysmlv2#subsetting_SubsettingFeature

subsetting_SubsettingFeature is an RDF property.

The Feature that is a subset of the subsettingFeature of this Subsetting.

succession_EffectStep

http://open-services.net/ns/sysmlv2#succession_EffectStep

succession_EffectStep is an RDF property.

Steps that represent occurrences that are side effects of the transitionStep occurring.

succession_GuardExpression

http://open-services.net/ns/sysmlv2#succession_GuardExpression

succession_GuardExpression is an RDF property.

Expressions that must evaluate to true before the transitionStep can occur.

succession_TransitionStep

http://open-services.net/ns/sysmlv2#succession_TransitionStep

succession_TransitionStep is an RDF property.

A Step that is typed by the Behavior TransitionPerformances::TransitionPerformance (from the Kernel Semantic Library) that has this Succession as its transitionLink.

succession_TriggerStep

http://open-services.net/ns/sysmlv2#succession_TriggerStep

succession_TriggerStep is an RDF property.

Steps that map incoming events to the timing of occurrences of the transitionStep. The values of triggerStep subset the list of acceptable events to be received by a Behavior or the object that performs it.

textualRepresentation_Body

http://open-services.net/ns/sysmlv2#textualRepresentation_Body

textualRepresentation_Body is an RDF property.

The textual representation of the representedElement in the given language.

textualRepresentation_Language

http://open-services.net/ns/sysmlv2#textualRepresentation_Language

textualRepresentation_Language is an RDF property.

The natural or artificial language in which the body text is written.

textualRepresentation_RepresentedElement

http://open-services.net/ns/sysmlv2#textualRepresentation_RepresentedElement

textualRepresentation_RepresentedElement is an RDF property.

The Element that is represented by this TextualRepresentation.

transitionFeatureMembership_Kind

http://open-services.net/ns/sysmlv2#transitionFeatureMembership_Kind

transitionFeatureMembership_Kind is an RDF property.

Whether this TransitionFeatureMembership is for a trigger, guard or effect.

transitionFeatureMembership_TransitionFeature

http://open-services.net/ns/sysmlv2#transitionFeatureMembership_TransitionFeature

transitionFeatureMembership_TransitionFeature is an RDF property.

The Step that is the ownedMemberFeature of this TransitionFeatureMembership.

transitionUsage_EffectAction

http://open-services.net/ns/sysmlv2#transitionUsage_EffectAction

transitionUsage_EffectAction is an RDF property.

The ActionUsages that define the effects of this TransitionUsage, which are the ownedFeatures of the TransitionUsage related to it by TransitionFeatureMemberships with kind = effect, which must all be ActionUsages.

transitionUsage_GuardExpression

http://open-services.net/ns/sysmlv2#transitionUsage_GuardExpression

transitionUsage_GuardExpression is an RDF property.

The Expressions that define the guards of this TransitionUsage, which are the ownedFeatures of the TransitionUsage related to it by TransitionFeatureMemberships with kind = guard, which must all be Expressions.

transitionUsage_Source

http://open-services.net/ns/sysmlv2#transitionUsage_Source

transitionUsage_Source is an RDF property.

The source ActionUsage of this TransitionUsage, which becomes the source of the succession for the TransitionUsage.

transitionUsage_Succession

http://open-services.net/ns/sysmlv2#transitionUsage_Succession

transitionUsage_Succession is an RDF property.

The Succession that is the ownedFeature of this TransitionUsage, which, if the TransitionUsage is triggered, asserts the temporal ordering of the source and target.

transitionUsage_Target

http://open-services.net/ns/sysmlv2#transitionUsage_Target

transitionUsage_Target is an RDF property.

The target ActionUsage of this TransitionUsage, which is the targetFeature of the succession for the TransitionUsage.

transitionUsage_TriggerAction

http://open-services.net/ns/sysmlv2#transitionUsage_TriggerAction

transitionUsage_TriggerAction is an RDF property.

The AcceptActionUsages that define the triggers of this TransitionUsage, which are the ownedFeatures of the TransitionUsage related to it by TransitionFeatureMemberships with kind = trigger, which must all be AcceptActionUsages.

triggerInvocationExpression_Kind

http://open-services.net/ns/sysmlv2#triggerInvocationExpression_Kind

triggerInvocationExpression_Kind is an RDF property.

Indicates which of the Functions from the Triggers model in the Kernel Semantic Library is to be invoked by this TriggerInvocationExpression.

type_DifferencingType

http://open-services.net/ns/sysmlv2#type_DifferencingType

type_DifferencingType is an RDF property.

The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types, but not including those of the remaining Types. For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

type_DirectedFeature

http://open-services.net/ns/sysmlv2#type_DirectedFeature

type_DirectedFeature is an RDF property.

The features of this Type that have a non-null direction.

type_EndFeature

http://open-services.net/ns/sysmlv2#type_EndFeature

type_EndFeature is an RDF property.

All features of this Type with isEnd = true.

type_Feature

http://open-services.net/ns/sysmlv2#type_Feature

type_Feature is an RDF property.

The ownedMemberFeatures of the featureMemberships of this Type.

type_FeatureMembership

http://open-services.net/ns/sysmlv2#type_FeatureMembership

type_FeatureMembership is an RDF property.

The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).

type_InheritedFeature

http://open-services.net/ns/sysmlv2#type_InheritedFeature

type_InheritedFeature is an RDF property.

All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.

type_InheritedMembership

http://open-services.net/ns/sysmlv2#type_InheritedMembership

type_InheritedMembership is an RDF property.

All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.

type_Input

http://open-services.net/ns/sysmlv2#type_Input

type_Input is an RDF property.

All features related to this Type by FeatureMemberships that have direction in or inout.

type_IntersectingType

http://open-services.net/ns/sysmlv2#type_IntersectingType

type_IntersectingType is an RDF property.

The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes, which are the Types derived from the intersectingType of the ownedIntersectings of this Type. For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

type_IsAbstract

http://open-services.net/ns/sysmlv2#type_IsAbstract

type_IsAbstract is an RDF property.

Indicates whether instances of this Type must also be instances of at least one of its specialized Types.

type_IsConjugated

http://open-services.net/ns/sysmlv2#type_IsConjugated

type_IsConjugated is an RDF property.

Indicates whether this Type has an ownedConjugator.

type_IsSufficient

http://open-services.net/ns/sysmlv2#type_IsSufficient

type_IsSufficient is an RDF property.

Whether all things that meet the classification conditions of this Type must be classified by the Type.

type_Multiplicity

http://open-services.net/ns/sysmlv2#type_Multiplicity

type_Multiplicity is an RDF property.

An ownedMember of this Type that is a Multiplicity, which constraints the cardinality of the Type. If there is no such ownedMember, then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

type_Output

http://open-services.net/ns/sysmlv2#type_Output

type_Output is an RDF property.

All features related to this Type by FeatureMemberships that have direction out or inout.

type_OwnedConjugator

http://open-services.net/ns/sysmlv2#type_OwnedConjugator

type_OwnedConjugator is an RDF property.

A Conjugation owned by this Type for which the Type is the originalType.

type_OwnedDifferencing

http://open-services.net/ns/sysmlv2#type_OwnedDifferencing

type_OwnedDifferencing is an RDF property.

The ownedRelationships of this Type that are Differencings, having this Type as their typeDifferenced.

type_OwnedDisjoining

http://open-services.net/ns/sysmlv2#type_OwnedDisjoining

type_OwnedDisjoining is an RDF property.

The ownedRelationships of this Type that are Disjoinings, for which the Type is the typeDisjoined Type.

type_OwnedEndFeature

http://open-services.net/ns/sysmlv2#type_OwnedEndFeature

type_OwnedEndFeature is an RDF property.

All endFeatures of this Type that are ownedFeatures.

type_OwnedFeature

http://open-services.net/ns/sysmlv2#type_OwnedFeature

type_OwnedFeature is an RDF property.

The ownedMemberFeatures of the ownedFeatureMemberships of this Type.

type_OwnedFeatureMembership

http://open-services.net/ns/sysmlv2#type_OwnedFeatureMembership

type_OwnedFeatureMembership is an RDF property.

The ownedMemberships of this Type that are FeatureMemberships, for which the Type is the owningType. Each such FeatureMembership identifies an ownedFeature of the Type.

type_OwnedIntersecting

http://open-services.net/ns/sysmlv2#type_OwnedIntersecting

type_OwnedIntersecting is an RDF property.

The ownedRelationships of this Type that are Intersectings, have the Type as their typeIntersected.

type_OwnedSpecialization

http://open-services.net/ns/sysmlv2#type_OwnedSpecialization

type_OwnedSpecialization is an RDF property.

The ownedRelationships of this Type that are Specializations, for which the Type is the specific Type.

type_OwnedUnioning

http://open-services.net/ns/sysmlv2#type_OwnedUnioning

type_OwnedUnioning is an RDF property.

The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.

type_UnioningType

http://open-services.net/ns/sysmlv2#type_UnioningType

type_UnioningType is an RDF property.

The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

typeFeaturing_FeatureOfType

http://open-services.net/ns/sysmlv2#typeFeaturing_FeatureOfType

typeFeaturing_FeatureOfType is an RDF property.

The Feature that is featured by the featuringType. It is the source of the TypeFeaturing.

typeFeaturing_FeaturingType

http://open-services.net/ns/sysmlv2#typeFeaturing_FeaturingType

typeFeaturing_FeaturingType is an RDF property.

The Type that features the featureOfType. It is the target of the TypeFeaturing.

typeFeaturing_OwningFeatureOfType

http://open-services.net/ns/sysmlv2#typeFeaturing_OwningFeatureOfType

typeFeaturing_OwningFeatureOfType is an RDF property.

A featureOfType that is also the owningRelatedElement of this TypeFeaturing.

unioning_TypeUnioned

http://open-services.net/ns/sysmlv2#unioning_TypeUnioned

unioning_TypeUnioned is an RDF property.

Type with interpretations partly determined by unioningType, as described in Type::unioningType.

unioning_UnioningType

http://open-services.net/ns/sysmlv2#unioning_UnioningType

unioning_UnioningType is an RDF property.

Type that partly determines interpretations of typeUnioned, as described in Type::unioningType.

usage_Definition

http://open-services.net/ns/sysmlv2#usage_Definition

usage_Definition is an RDF property.

The Classifiers that are the types of this Usage. Nominally, these are Definitions, but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.

usage_DirectedUsage

http://open-services.net/ns/sysmlv2#usage_DirectedUsage

usage_DirectedUsage is an RDF property.

The usages of this Usage that are directedFeatures.

usage_IsReference

http://open-services.net/ns/sysmlv2#usage_IsReference

usage_IsReference is an RDF property.

Whether this Usage is a referential Usage, that is, it has `isComposite = false`.

usage_IsVariation

http://open-services.net/ns/sysmlv2#usage_IsVariation

usage_IsVariation is an RDF property.

Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be `VariantMemberships`.

usage_NestedAction

http://open-services.net/ns/sysmlv2#usage_NestedAction

usage_NestedAction is an RDF property.

The `ActionUsages` that are `nestedUsages` of this Usage.

usage_NestedAllocation

http://open-services.net/ns/sysmlv2#usage_NestedAllocation

usage_NestedAllocation is an RDF property.

The `AllocationUsages` that are `nestedUsages` of this Usage.

usage_NestedAnalysisCase

http://open-services.net/ns/sysmlv2#usage_NestedAnalysisCase

usage_NestedAnalysisCase is an RDF property.

The `AnalysisCaseUsages` that are `nestedUsages` of this Usage.

usage_NestedAttribute

http://open-services.net/ns/sysmlv2#usage_NestedAttribute

usage_NestedAttribute is an RDF property.

The `code>AttributeUsages` that are `nestedUsages` of this Usage.

usage_NestedCalculation

http://open-services.net/ns/sysmlv2#usage_NestedCalculation

usage_NestedCalculation is an RDF property.

The `CalculationUsage` that are `nestedUsages` of this Usage.

usage_NestedCase

http://open-services.net/ns/sysmlv2#usage_NestedCase

usage_NestedCase is an RDF property.

The `CaseUsages` that are `nestedUsages` of this Usage.

usage_NestedConcern

http://open-services.net/ns/sysmlv2#usage_NestedConcern

usage_NestedConcern is an RDF property.

The ConcernUsages that are nestedUsages of this Usage.

usage_NestedConnection

http://open-services.net/ns/sysmlv2#usage_NestedConnection

usage_NestedConnection is an RDF property.

The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.

usage_NestedConstraint

http://open-services.net/ns/sysmlv2#usage_NestedConstraint

usage_NestedConstraint is an RDF property.

The ConstraintUsages that are nestedUsages of this Usage.

usage_NestedEnumeration

http://open-services.net/ns/sysmlv2#usage_NestedEnumeration

usage_NestedEnumeration is an RDF property.

The code>EnumerationUsages that are nestedUsages of this Usage.

usage_NestedFlow

http://open-services.net/ns/sysmlv2#usage_NestedFlow

usage_NestedFlow is an RDF property.

The code>FlowConnectionUsages that are nestedUsages of this Usage.

usage_NestedInterface

http://open-services.net/ns/sysmlv2#usage_NestedInterface

usage_NestedInterface is an RDF property.

The InterfaceUsages that are nestedUsages of this Usage.

usage_NestedItem

http://open-services.net/ns/sysmlv2#usage_NestedItem

usage_NestedItem is an RDF property.

The ItemUsages that are nestedUsages of this Usage.

usage_NestedMetadata

http://open-services.net/ns/sysmlv2#usage_NestedMetadata

usage_NestedMetadata is an RDF property.

The MetadataUsages that are nestedUsages of this of this Usage.

usage_NestedOccurrence

http://open-services.net/ns/sysmlv2#usage_NestedOccurrence

usage_NestedOccurrence is an RDF property.

The OccurrenceUsages that are nestedUsages of this Usage.

usage_NestedPart

http://open-services.net/ns/sysmlv2#usage_NestedPart

usage_NestedPart is an RDF property.

The PartUsages that are nestedUsages of this Usage.

usage_NestedPort

http://open-services.net/ns/sysmlv2#usage_NestedPort

usage_NestedPort is an RDF property.

The PortUsages that are nestedUsages of this Usage.

usage_NestedReference

http://open-services.net/ns/sysmlv2#usage_NestedReference

usage_NestedReference is an RDF property.

The ReferenceUsages that are nestedUsages of this Usage.

usage_NestedRendering

http://open-services.net/ns/sysmlv2#usage_NestedRendering

usage_NestedRendering is an RDF property.

The RenderingUsages that are nestedUsages of this Usage.

usage_NestedRequirement

http://open-services.net/ns/sysmlv2#usage_NestedRequirement

usage_NestedRequirement is an RDF property.

The RequirementUsages that are nestedUsages of this Usage.

usage_NestedState

http://open-services.net/ns/sysmlv2#usage_NestedState

usage_NestedState is an RDF property.

The StateUsages that are nestedUsages of this Usage.

usage_NestedTransition

http://open-services.net/ns/sysmlv2#usage_NestedTransition

usage_NestedTransition is an RDF property.

The TransitionUsages that are nestedUsages of this Usage.

usage_NestedUsage

http://open-services.net/ns/sysmlv2#usage_NestedUsage

usage_NestedUsage is an RDF property.

The Usages that are ownedFeatures of this Usage.

usage_NestedUseCase

http://open-services.net/ns/sysmlv2#usage_NestedUseCase

usage_NestedUseCase is an RDF property.

The UseCaseUsages that are nestedUsages of this Usage.

usage_NestedVerificationCase

http://open-services.net/ns/sysmlv2#usage_NestedVerificationCase

usage_NestedVerificationCase is an RDF property.

The VerificationCaseUsages that are nestedUsages of this Usage.

usage_NestedView

http://open-services.net/ns/sysmlv2#usage_NestedView

usage_NestedView is an RDF property.

The ViewUsages that are nestedUsages of this Usage.

usage_NestedViewpoint

http://open-services.net/ns/sysmlv2#usage_NestedViewpoint

usage_NestedViewpoint is an RDF property.

The ViewpointUsages that are nestedUsages of this Usage.

usage_OwningDefinition

http://open-services.net/ns/sysmlv2#usage_OwningDefinition

usage_OwningDefinition is an RDF property.

The Definition that owns this Usage (if any).

usage_OwningUsage

http://open-services.net/ns/sysmlv2#usage_OwningUsage

usage_OwningUsage is an RDF property.

The Usage in which this Usage is nested (if any).

usage_Usage

http://open-services.net/ns/sysmlv2#usage_Usage

usage_Usage is an RDF property.

The Usages that are features of this Usage (not necessarily owned).

usage_Variant

http://open-services.net/ns/sysmlv2#usage_Variant

usage_Variant is an RDF property.

The Usages which represent the variants of this Usage as a variation point Usage, if *isVariation* = true. If *isVariation* = false, then there must be no variants.

usage_VariantMembership

http://open-services.net/ns/sysmlv2#usage_VariantMembership

usage_VariantMembership is an RDF property.

The ownedMemberships of this Usage that are VariantMemberships. If *isVariation* = true, then this must be all memberships of the Usage. If *isVariation* = false, then *variantMembership* must be empty.

useCaseDefinition_IncludedUseCase

http://open-services.net/ns/sysmlv2#useCaseDefinition_IncludedUseCase

useCaseDefinition_IncludedUseCase is an RDF property.

The UseCaseUsages that are included by this UseCaseDefinition, which are the *useCaseIncluded*s of the *IncludeUseCaseUsages* owned by this UseCaseDefinition.

useCaseUsage_IncludedUseCase

http://open-services.net/ns/sysmlv2#useCaseUsage_IncludedUseCase

useCaseUsage_IncludedUseCase is an RDF property.

The UseCaseUsages that are included by this UseCaseUse, which are the *useCaseIncluded*s of the *IncludeUseCaseUsages* owned by this UseCaseUsage.

useCaseUsage_UseCaseDefinition

http://open-services.net/ns/sysmlv2#useCaseUsage_UseCaseDefinition

useCaseUsage_UseCaseDefinition is an RDF property.

The UseCaseDefinition that is the definition of this UseCaseUsage.

variantMembership_OwnedVariantUsage

http://open-services.net/ns/sysmlv2#variantMembership_OwnedVariantUsage

variantMembership_OwnedVariantUsage is an RDF property.

The Usage that represents a variant in the context of the owningVariationDefinition or owningVariationUsage.

verificationCaseDefinition_VerifiedRequirement

http://open-services.net/ns/sysmlv2#verificationCaseDefinition_VerifiedRequirement

verificationCaseDefinition_VerifiedRequirement is an RDF property.

The RequirementUsages verified by this VerificationCaseDefinition, which are the verifiedRequirements of all RequirementVerificationMemberships of the objectiveRequirement.

verificationCaseUsage_VerificationCaseDefinition

http://open-services.net/ns/sysmlv2#verificationCaseUsage_VerificationCaseDefinition

verificationCaseUsage_VerificationCaseDefinition is an RDF property.

The VerificationCase that is the definition of this VerificationCaseUsage.

verificationCaseUsage_VerifiedRequirement

http://open-services.net/ns/sysmlv2#verificationCaseUsage_VerifiedRequirement

verificationCaseUsage_VerifiedRequirement is an RDF property.

The RequirementUsages verified by this VerificationCaseUsage, which are the verifiedRequirements of all RequirementVerificationMemberships of the objectiveRequirement.

viewDefinition_SatisfiedViewpoint

http://open-services.net/ns/sysmlv2#viewDefinition_SatisfiedViewpoint

viewDefinition_SatisfiedViewpoint is an RDF property.

The composite ownedRequirements of this ViewDefinition that are ViewpointUsages for viewpoints satisfied by the ViewDefinition.

viewDefinition_View

http://open-services.net/ns/sysmlv2#viewDefinition_View

viewDefinition_View is an RDF property.

The usages of this ViewDefinition that are ViewUsages.

viewDefinition_ViewCondition

http://open-services.net/ns/sysmlv2#viewDefinition_ViewCondition

viewDefinition_ViewCondition is an RDF property.

The Expressions related to this ViewDefinition by ElementFilterMemberships, which specify conditions on Elements to be rendered in a view.

viewDefinition_ViewRendering

http://open-services.net/ns/sysmlv2#viewDefinition_ViewRendering

viewDefinition_ViewRendering is an RDF property.

The RenderingUsage to be used to render views defined by this ViewDefinition, which is the referencedRendering of the ViewRenderingMembership of the ViewDefinition.

viewpointDefinition_ViewpointStakeholder

http://open-services.net/ns/sysmlv2#viewpointDefinition_ViewpointStakeholder

viewpointDefinition_ViewpointStakeholder is an RDF property.

The PartUsages that identify the stakeholders with concerns framed by this ViewpointDefinition, which are the owned and inherited stakeholderParameters of the framedConcerns of this ViewpointDefinition.

viewpointUsage_ViewpointDefinition

http://open-services.net/ns/sysmlv2#viewpointUsage_ViewpointDefinition

viewpointUsage_ViewpointDefinition is an RDF property.

The ViewpointDefinition that is the definition of this ViewpointUsage.

viewpointUsage_ViewpointStakeholder

http://open-services.net/ns/sysmlv2#viewpointUsage_ViewpointStakeholder

viewpointUsage_ViewpointStakeholder is an RDF property.

The PartUsages that identify the stakeholders with concerns framed by this ViewpointUsage, which are the owned and inherited stakeholderParameters of the framedConcerns of this ViewpointUsage.

viewRenderingMembership_OwnedRendering

http://open-services.net/ns/sysmlv2#viewRenderingMembership_OwnedRendering

viewRenderingMembership_OwnedRendering is an RDF property.

The owned RenderingUsage that is either itself the referencedRendering or subsets the referencedRendering.

viewRenderingMembership_ReferencedRendering

http://open-services.net/ns/sysmlv2#viewRenderingMembership_ReferencedRendering

viewRenderingMembership_ReferencedRendering is an RDF property.

The RenderingUsage that is referenced through this ViewRenderingMembership. It is the referencedFeature of the ownedReferenceSubsetting for the ownedRendering, if there is one, and, otherwise, the ownedRendering itself.

viewUsage_ExposedElement

http://open-services.net/ns/sysmlv2#viewUsage_ExposedElement

viewUsage_ExposedElement is an RDF property.

The Elements that are exposed by this ViewUsage, which are those memberElements of the imported Memberships from all the Expose Relationships that meet all the owned and inherited viewConditions.

viewUsage_SatisfiedViewpoint

http://open-services.net/ns/sysmlv2#viewUsage_SatisfiedViewpoint

viewUsage_SatisfiedViewpoint is an RDF property.

The nestedRequirements of this ViewUsage that are ViewpointUsages for (additional) viewpoints satisfied by the ViewUsage.

viewUsage_ViewCondition

http://open-services.net/ns/sysmlv2#viewUsage_ViewCondition

viewUsage_ViewCondition is an RDF property.

The Expressions related to this ViewUsage by ElementFilterMemberships, which specify conditions on Elements to be rendered in a view.

viewUsage_ViewDefinition

http://open-services.net/ns/sysmlv2#viewUsage_ViewDefinition

viewUsage_ViewDefinition is an RDF property.

The ViewDefinition that is the definition of this ViewUsage.

viewUsage_ViewRendering

http://open-services.net/ns/sysmlv2#viewUsage_ViewRendering

viewUsage_ViewRendering is an RDF property.

The RenderingUsage to be used to render views defined by this ViewUsage, which is the referencedRendering of the ViewRenderingMembership of the ViewUsage.

whileLoopActionUsage_UntilArgument

http://open-services.net/ns/sysmlv2#whileLoopActionUsage_UntilArgument

whileLoopActionUsage_UntilArgument is an RDF property.

The Expression whose result, if false, determines that the bodyAction should continue to be performed. It is the (optional) third owned parameter of the WhileLoopActionUsage.

whileLoopActionUsage_WhileArgument

http://open-services.net/ns/sysmlv2#whileLoopActionUsage_WhileArgument

whileLoopActionUsage_WhileArgument is an RDF property.

The Expression whose result, if true, determines that the bodyAction should continue to be performed. It is the first owned parameter of the WhileLoopActionUsage.

2.1.3 Resources (Individuals) in this namespace (19)

[featureDirectionKind_In](#), [featureDirectionKind_Inout](#), [featureDirectionKind_Out](#), [portionKind_Snapshot](#), [portionKind_Timeslice](#), [requirementConstraintKind_Assumption](#), [requirementConstraintKind_Requirement](#), [stateSubactionKind_Do](#), [stateSubactionKind_Entry](#), [stateSubactionKind_Exit](#), [transitionFeatureKind_Effect](#), [transitionFeatureKind_Guard](#), [transitionFeatureKind_Trigger](#), [triggerKind_After](#), [triggerKind_At](#), [triggerKind_When](#),

[visibilityKind_Private](#), [visibilityKind_Protected](#), [visibilityKind_Public](#)

featureDirectionKind_In

http://open-services.net/ns/sysmlv2#featureDirectionKind_In

featureDirectionKind_In is an RDF individual.

Values of the Feature on each instance of its domain are determined externally to that instance and used internally.

featureDirectionKind_Inout

http://open-services.net/ns/sysmlv2#featureDirectionKind_Inout

featureDirectionKind_Inout is an RDF individual.

Values of the Feature on each instance are determined either as in or out directions, or both.

featureDirectionKind_Out

http://open-services.net/ns/sysmlv2#featureDirectionKind_Out

featureDirectionKind_Out is an RDF individual.

Values of the Feature on each instance of its domain are determined internally to that instance and used externally.

portionKind_Snapshot

http://open-services.net/ns/sysmlv2#portionKind_Snapshot

portionKind_Snapshot is an RDF individual.

A snapshot of an Occurrence (a time slice with zero duration).

portionKind_Timeslice

http://open-services.net/ns/sysmlv2#portionKind_Timeslice

portionKind_Timeslice is an RDF individual.

A time slice of an Occurrence (a portion over time).

requirementConstraintKind_Assumption

http://open-services.net/ns/sysmlv2#requirementConstraintKind_Assumption

requirementConstraintKind_Assumption is an RDF individual.

Indicates that a member ConstraintUsage of a RequirementDefinition or RequirementUsage represents an assumption.

requirementConstraintKind_Requirement

http://open-services.net/ns/sysmlv2#requirementConstraintKind_Requirement

requirementConstraintKind_Requirement is an RDF individual.

Indicates that a member ConstraintUsage of a RequirementDefinition or RequirementUsage represents an requirement.

stateSubactionKind_Do

http://open-services.net/ns/sysmlv2#stateSubactionKind_Do

stateSubactionKind_Do is an RDF individual.

Indicates that the action of a StateSubactionMembership is a doAction.

stateSubactionKind_Entry

http://open-services.net/ns/sysmlv2#stateSubactionKind_Entry

stateSubactionKind_Entry is an RDF individual.

Indicates that the action of a StateSubactionMembership is an entryAction.

stateSubactionKind_Exit

http://open-services.net/ns/sysmlv2#stateSubactionKind_Exit

stateSubactionKind_Exit is an RDF individual.

Indicates that the action of a StateSubactionMembership is an exitAction.

transitionFeatureKind_Effect

http://open-services.net/ns/sysmlv2#transitionFeatureKind_Effect

transitionFeatureKind_Effect is an RDF individual.

Indicates that the transitionFeature of a TransitionFeatureMembership is an effectAction.

transitionFeatureKind_Guard

http://open-services.net/ns/sysmlv2#transitionFeatureKind_Guard

transitionFeatureKind_Guard is an RDF individual.

Indicates that the transitionFeature of a TransitionFeatureMembership is a guardExpression.

transitionFeatureKind_Trigger

http://open-services.net/ns/sysmlv2#transitionFeatureKind_Trigger

transitionFeatureKind_Trigger is an RDF individual.

Indicates that the transitionFeature of a TransitionFeatureMembership is a triggerAction.

triggerKind_After

http://open-services.net/ns/sysmlv2#triggerKind_After

triggerKind_After is an RDF individual.

Indicates a relative time trigger, corresponding to the TriggerAfter Function from the Triggers model in the Kernel Semantic Library.

triggerKind_At

http://open-services.net/ns/sysmlv2#triggerKind_At

triggerKind_At is an RDF individual.

Indicates an absolute time trigger, corresponding to the TriggerAt Function from the Triggers model in the Kernel Semantic Library.

triggerKind_When

http://open-services.net/ns/sysmlv2#triggerKind_When

triggerKind_When is an RDF individual.

Indicates a change trigger, corresponding to the TriggerWhen Function from the Triggers model in the Kernel Semantic Library.

visibilityKind_Private

http://open-services.net/ns/sysmlv2#visibilityKind_Private

visibilityKind_Private is an RDF individual.

Indicates a Membership is not visible outside its owning Namespace.

visibilityKind_Protected

http://open-services.net/ns/sysmlv2#visibilityKind_Protected

visibilityKind_Protected is an RDF individual.

An intermediate level of visibility between public and private. By default, it is equivalent to private for the purposes of normal access to and import of Elements from a Namespace. However, other Relationships may be specified to include Memberships with protected visibility in the list of memberships for a Namespace (e.g., Specialization).

visibilityKind_Public

http://open-services.net/ns/sysmlv2#visibilityKind_Public

visibilityKind_Public is an RDF individual.

Indicates that a Membership is publicly visible outside its owning Namespace.

3. Conformance

OSLC SysML v2 servers **MUST** use the vocabulary terms defined here where required, and with the meanings defined here.

OSLC SysML v2 servers **MAY** augment this vocabulary with additional classes, properties, and individuals.

Clause Number	Requirement
sml-1	OSLC SysML v2 defines a set of properties for OMG SysML v2 resources. However, service implementations are free to extend this set of properties. Clients MUST preserve properties it does not recognize when updating resources. OSLC SysML v2 Servers MAY ignore properties that it does not recognize. Additional properties may come from existing vocabularies (ie. Dublin Core, OWL). When additional properties do not come from a known vocabulary, it is recommended that they exist in their own unique namespace, and providers SHOULD NOT reuse namespaces defined in these specifications.
sml-2	All RDF/XML resources that include links with annotations MUST begin with an outer <code><rdf:RDF></code> element. This outer XML element is required to support the ability to include annotations on 'link' properties with additional <code><rdf:Description></code> elements reifying statements about the link.
sml-3	Service implementations and clients MUST be prepared to accept any form of valid RDF/XML. For example the following two resource forms are equivalent.



OSLC Systems Modeling Language Version 2.0 Part 3: Constraints

Project Specification Draft 01

25 April 2024

This stage:

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-shapes.html> (Authoritative)

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/psd01/sysml-shapes.pdf>

Previous stage:

N/A

Latest stage:

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-shapes.html> (Authoritative)

<https://docs.oasis-open-projects.org/oslc-op/sysml/v2.0/sysml-shapes.pdf>

Latest version:

<https://open-services.net/spec/sysml/latest>

Latest editor's draft:

<https://open-services.net/spec/sysml/latest-draft>

Open Project:

[OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#)

Project Chairs:

Jim Amsden (jamsden@us.ibm.com), [IBM](#)

Jad El-khoury (jad@kth.se), [KTH Royal Institute of Technology](#)

Editor:

Jim Amsden (jamsden@us.ibm.com), [IBM](#)

Additional components:

This specification is one component of a Work Product that also includes:

- *OSLC Systems Modeling Language Version 2.0. Part 1: Specification.* [sysml-spec.html](#)
- *OSLC Systems Modeling Language Version 2.0. Part 2: Vocabulary.* [sysml-vocab.html](#)
- *OSLC Systems Modeling Language Version 2.0. Part 3: Constraints (this document).* [sysml-shapes.html](#)
- *OSLC Systems Modeling Language Version 2.0. Part 4: Machine Readable Vocabulary Terms.* [sysml-vocab.ttl](#)
- *OSLC Systems Modeling Language Version 2.0. Part 5: Machine Readable Constraints.* [sysml-shapes.ttl](#)

Related work:

This specification is related to:

- *OMG Systems Modeling Language.* <https://www.omg.org/spec/SysML/>
- *Systems Modeling Application Programming Interface (API) and Services.* <https://www.omg.org/spec/SystemsModelingAPI/1.0/Beta1/PDF>

RDF Namespaces:

<http://open-services.net/ns/sysmlv2#>

Abstract:

OSLC Systems Modeling Language Version 2.0. Part 3: Constraints defines the standard OSLC constraint on the RDF vocabulary terms and resources that are the OSLC representation of the corresponding OMG Systems Modeling Language Version 2.0.

Status:

This document was last revised or approved by the [OASIS Open Services for Lifecycle Collaboration \(OSLC\) OP](#) on the above date. The level of approval is also listed above. Check the “Latest stage” location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Open Project are listed at <https://open-services.net/about/>.

Comments on this work can be provided by opening issues in the project repository or by sending email to the project’s public comment list oslc-op@lists.oasis-open-projects.org.

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and

display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this specification the following citation format should be used:

[OSLC-SYSML-2.0-Part3]

OSLC Systems Modeling Language Version 2.0 Part 3: Constraints. Edited by Jim Amsden. 25 April 2024. OASIS Project Specification Draft 01. <https://docs.oasis-open-projects.org/osl-op/sysml/v2.0/psd01/sysml-shapes.html>. Latest stage: <https://docs.oasis-open-projects.org/osl-op/sysml/v2.0/sysml-shapes.html>.

Notices

Copyright © OASIS Open 2024. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This specification is published under the [Attribution 4.0 International \(CC BY 4.0\)](#). Portions of this specification are also provided under the [Apache License 2.0](#).

All contributions made to this project have been made under the [OASIS Contributor License Agreement \(CLA\)](#).

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the [Open Projects IPR Statements page](#).

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Open Project or OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Project Specification or OASIS Standard, to notify the OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Open Project that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Open Project Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.

Table of Contents

- 1. [Introduction](#)
 - 1.1 [Terminology](#)
 - 1.2 [References](#)
 - 1.2.1 [Normative references](#)
 - 1.2.2 [Informative references](#)
 - 1.3 [Typographical Conventions and Use of RFC Terms](#)
- 2. [Resource Constraints](#)
- 3. [Conformance](#)

1. Introduction

This section is non-normative.

RDF vocabularies define the terms and resources for a domain of interest, life-cycle management in the case of OSLC SysML v2. These vocabularies are often specified in an open manner, without providing information such as property domain and range assertions, cardinalities, etc. This helps keep the vocabulary applicable for a wide range of uses and furthering integration with other vocabularies.

However, it is often desirable to closed down a vocabulary with specific constraints to facilitate using the vocabulary for a specific purpose. This document specifies the constraints for using the OSLC SysML v2 vocabulary in OSLC. Different sets of constraints may be applied to a vocabulary in order to tailor its use, without overly constraining the vocabulary for other usages.

These constraints apply to the core vocabulary defined in [OSLC SysML Version 2.0. Part 2: Vocabulary](#).

1.1 Terminology

This section is non-normative.

Terminology is based on OSLC Core Overview [[OSLCCore3](#)], W3C Linked Data Platform [[LDP](#)], W3C's Architecture of the World Wide Web [[WEBARCH](#)], Hyper-text Transfer Protocol [[HTTP11](#)]. Terminology for this specification is defined in part 1 of the multi-part specification.

1.2 References

1.2.1 Normative references

[[HTTP11](#)]

R. Fielding, Ed.; J. Reschke, Ed.. [Hypertext Transfer Protocol \(HTTP/1.1\): Message Syntax and Routing](#). IETF, June 2014. Proposed Standard. URL: <https://httpwg.org/specs/rfc7230.html>

[[LDP](#)]

Steve Speicher; John Arwe; Ashok Malhotra. [Linked Data Platform 1.0](#). W3C, 26 February 2015. W3C Recommendation. URL: <https://www.w3.org/TR/ldp/>

[[OSLCCore3](#)]

Jim Amsden; S. Speicher. [OSLC Core Version 3.0. Part 1: Overview](#). OASIS. Project Specification Draft. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/oslc-core.html>

[[RFC2119](#)]

S. Bradner. [Key words for use in RFCs to Indicate Requirement Levels](#). IETF, March 1997. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc2119>

[[RFC8174](#)]

B. Leiba. [Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words](https://www.rfc-editor.org/rfc/rfc8174). IETF, May 2017. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc8174>

1.2.2 Informative references

[WEBARCH]

Ian Jacobs; Norman Walsh. [Architecture of the World Wide Web, Volume One](https://www.w3.org/TR/webarch/). W3C, 15 December 2004. W3C Recommendation. URL: <https://www.w3.org/TR/webarch/>

1.3 Typographical Conventions and Use of RFC Terms

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words "**MUST**", "**MUST NOT**", "**REQUIRED**", "**SHALL**", "**SHALL NOT**", "**SHOULD**", "**SHOULD NOT**", "**RECOMMENDED**", "**NOT RECOMMENDED**", "**MAY**", and "**OPTIONAL**" in this specification are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

In addition to the namespace URIs and namespace prefixes `oslc`, `rdf`, `dcterms` and `foaf` defined in the [OSLC Core specification](#), OSLC SysML v2 defines the namespace URI of `http://open-services.net/ns/sysmlv2#` with a namespace prefix of `oslc_sysmlv2`

This specification also uses these namespace prefix definitions:

- `oslc` : `http://open-services.net/ns/core#` [[OSLCCore3](#)]

2. Resource Constraints

This section specifies the constraints for the SysML v2 resources. The resource properties are not limited to the ones defined in this specification, SysML v2 Servers may provide additional properties. It is recommended that any additional properties exist in their own unique namespace and not use the namespaces defined in these specifications.

- **Describes:** `http://open-services.net/ns/sysmlv2#AnnotatingElement`
- **Summary:** `AnnotatingElementShape`
- **Description:** An `AnnotatingElement` is an `Element` that provides additional description of or metadata on some other `Element`. An `AnnotatingElement` is either attached to its `annotatedElements` by `Annotation Relationships`, or it implicitly annotates its `owningNamespace`.

AnnotatingElement Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:annotatingElement_AnnotatedElement</code>	One-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are annotated by this AnnotatingElement . If annotation is not empty, these are the annotatedElements of the annotations . If annotation is empty, then it is the owningNamespace of the AnnotatingElement .
<code>oslc_sysmlv2:annotatingElement_Annotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The Annotations that relate this AnnotatingElement to its annotatedElements .
<code>oslc_sysmlv2:annotatingElement_OwnedAnnotatingRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this AnnotatingElement that are Annotations , for which this AnnotatingElement is the annotatingElement .
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-1].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#EventOccurrenceUsage>
- **Summary:** EventOccurrenceUsageShape
- **Description:** An **EventOccurrenceUsage** is an **OccurrenceUsage** that represents another **OccurrenceUsage** occurring as a *suboccurrence* of the containing occurrence of the **EventOccurrenceUsage**. Unless it is the **EventOccurrenceUsage** itself, the referenced **OccurrenceUsage** is related to the **EventOccurrenceUsage** by a **ReferenceSubsetting Relationship**.

EventOccurrenceUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:eventOccurrenceUsage_EventOccurrence	Exactly-one	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsage referenced as an event by this EventOccurrenceUsage. It is the referenceFeature of the ownedReferenceSubsetting for the EventOccurrenceUsage, if there is one, and, otherwise, the EventOccurrenceUsage itself.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-2].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ConjugatedPortDefinition`
- **Summary:** ConjugatedPortDefinitionShape
- **Description:** A `ConjugatedPortDefinition` is a `PortDefinition` that is a `PortDefinition` of its original `PortDefinition`. That is, a `ConjugatedPortDefinition` inherits all the `features` of the original `PortDefinition`, but input `flows` of the original `PortDefinition` become outputs on the `ConjugatedPortDefinition` and output `flows` of the original `PortDefinition` become inputs on the `ConjugatedPortDefinition`. Every `PortDefinition` (that is not itself a `ConjugatedPortDefinition`) has exactly one corresponding `ConjugatedPortDefinition`, whose effective name is the name of the `originalPortDefinition`, with the character `~` prepended.

ConjugatedPortDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:conjugatedPortDefinition_OriginalPortDefinition	Exactly-one	false	Resource	Either	oslc_sysmlv2:PortDefinition	The original PortDefinition for this ConjugatedPortDefinition, which is the owningNamespace of the ConjugatedPortDefinition.
oslc_sysmlv2:conjugatedPortDefinition_OwnedPortConjugator	Exactly-one	false	Resource	Either	oslc_sysmlv2:PortConjugation	The PortConjugation that is the ownedConjugator of this ConjugatedPortDefinition, linking it to its originalPortDefinition.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:definition_OwnedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The AnalysisCaseUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The AttributeUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The CalculationUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The CaseUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
<code>oslc_sysmlv2:definition_OwnedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The ConstraintUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The EnumerationUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The FlowConnectionUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The InterfaceUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespace</code> s from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:portDefinition_ConjugatedPortDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ConjugatedPortDefinition	The that is conjugate to this PortDefinition ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-3].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ActionDefinition>
- **Summary:** ActionDefinitionShape
- **Description:** An **ActionDefinition** is a **Definition** that is also a **Behavior** that defines an **Action** performed by a system or part of a system.

ActionDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition, if isVariation = true. If isVariation = false, the there must be no variants.
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships. If isVariation = true, then this must be all ownedMemberships of the Definition. If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition, restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types, but not including those of the remaining Types. For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction.
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true.
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-4] .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ReturnParameterMembership`
- **Summary:** ReturnParameterMembershipShape
- **Description:** A `ReturnParameterMembership` is a `ParameterMembership` that indicates that the `ownedMemberParameter` is the `result parameter` of a `Function` or `Expression`. The `direction` of the `ownedMemberParameter` must be `out`.

ReturnParameterMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:parameterMembership_OwnedMemberParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is identified as a parameter by this ParameterMembership .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-5].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#SuccessionAsUsage>
- **Summary:** SuccessionAsUsageShape
- **Description:** A **SuccessionAsUsage** is both a **ConnectorAsUsage** and a **Succession**.

SuccessionAsUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:succession_EffectStep	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	Steps that represent occurrences that are side effects of the transitionStep occurring.
oslc_sysmlv2:succession_GuardExpression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	Expressions that must evaluate to true before the transitionStep can occur.
oslc_sysmlv2:succession_TransitionStep	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Step	A Step that is typed by the Behavior TransitionPerformances::TransitionPerformance (from the Kernel Semantic Library) that has this Succession as its transitionLink .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:succession_TriggerStep	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	Steps that map incoming events to the timing of occurrences of the transitionStep . The values of triggerStep subset the list of acceptable events to be received by a Behavior or the object that performs it.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The <code>ActionUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The <code>AllocationUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The <code>AnalysisCaseUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The <code>code>AttributeUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The <code>CalculationUsage</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The <code>CaseUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The <code>ConcernUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The <code>ConnectorAsUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> . Note that this list includes <code>BindingConnectorAsUsages</code> and <code>SuccessionAsUsages</code> , even though these are <code>ConnectorAsUsages</code> but not <code>ConnectionUsages</code> .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The <code>code>EnumerationUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The <code>code>FlowConnectionUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-6].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#InvocationExpression>
- **Summary:** InvocationExpressionShape
- **Description:** An *InvocationExpression* is an *Expression* each of whose input *parameters* are bound to the *result* of an *argument* Expression.

InvocationExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespaces</code> from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .
<code>oslc_sysmlv2:expression_Function</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Function</code>	The <code>Function</code> that types this <code>Expression</code> .
<code>oslc_sysmlv2:expression_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Expression</code> meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-7].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#RequirementDefinition`
- **Summary:** RequirementDefinitionShape
- **Description:** A `RequirementDefinition` is a `ConstraintDefinition` that defines a requirement used in the context of a specification as a constraint that a valid solution must satisfy. The specification is relative to a specified subject, possibly in collaboration with one or more external actors.

RequirementDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Behavior.
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:function_Expression</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Expression</code>	The Expressions that are steps in the calculation of the result of this Function .
<code>oslc_sysmlv2:function_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have <code>isModelLevelEvaluable = true</code> . For all other Functions it is <code>false</code> .
<code>oslc_sysmlv2:function_Result</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:occurrenceDefinition_IsIndividual</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this OccurrenceDefinition is constrained to represent single individual.
<code>oslc_sysmlv2:occurrenceDefinition_LifeClass</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:LifeClass</code>	If <code>isIndividual</code> is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementDefinition_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementDefinition that represent actors involved in the requirement.
oslc_sysmlv2:requirementDefinition_AssumedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent assumptions of this RequirementDefinition , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = assumption .
oslc_sysmlv2:requirementDefinition_FramedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages framed by this RequirementDefinition , which are the ownedConcerns of all FramedConcernMemberships of the RequirementDefinition .
oslc_sysmlv2:requirementDefinition_ReqId	Zero-or-one	false	unspecified	Either	xsd:string	An optional modeler-specified identifier for this RequirementDefinition (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementDefinition .
oslc_sysmlv2:requirementDefinition_RequiredConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent requirements of this RequirementDefinition , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = requirement .
oslc_sysmlv2:requirementDefinition_StakeholderParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementDefinition that represent stakeholders for th requirement.
oslc_sysmlv2:requirementDefinition_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this RequirementDefinition that represents its subject.
oslc_sysmlv2:requirementDefinition_Text	Zero-or-many	false	unspecified	Either	xsd:string	An optional textual statement of the requirement represented by this RequirementDefinition , derived from the bodies of the documentation of the RequirementDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-8].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ItemFlowEnd>
- **Summary:** ItemFlowEndShape
- **Description:** An **ItemFlowEnd** is a **Feature** that is one of the **connectorEnds** giving the **source** or **target** of an **ItemFlow**. For **ItemFlows** typed by **FlowTransfer** or its specializations, **ItemFlowEnds** must have exactly one **ownedFeature**, which redefines **Transfer::source::sourceOutput** or **Transfer::target::targetInput** and redefines the corresponding feature of the **relatedElement** for its end.

ItemFlowEnd Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with <code>isEnd = true</code> .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-9].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Connector`
- **Summary:** ConnectorShape
- **Description:** A **Connector** is a usage of **Associations**, with links restricted according to instances of the **Type** in which they are used (domain of the **Connector**). The **associations** of the **Connector** restrict what kinds of things might be linked. The **Connector** further restricts these links to be between values of **Features** on instances of its domain.

Connector Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:feature_OwnedRedefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Redefinition</code>	The <code>ownedSubsettings</code> of this <code>Feature</code> that are <code>Redefinitions</code> , for which the <code>Feature</code> is the <code>redefiningFeature</code> .
<code>oslc_sysmlv2:feature_OwnedReferenceSubsetting</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:ReferenceSubsetting</code>	The one <code>ownedSubsetting</code> of this <code>Feature</code> , if any, that is a <code>ReferenceSubsetting</code> , for which the <code>Feature</code> is the <code>referencingFeature</code> .
<code>oslc_sysmlv2:feature_OwnedSubsetting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Subsetting</code>	The <code>ownedSpecializations</code> of this <code>Feature</code> that are <code>Subsettings</code> , for which the <code>Feature</code> is the <code>subsettingFeature</code> .
<code>oslc_sysmlv2:feature_OwnedTypeFeaturing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TypeFeaturing</code>	The <code>ownedRelationships</code> of this <code>Feature</code> that are <code>TypeFeaturings</code> and for which the <code>Feature</code> is the <code>featureOfType</code> .
<code>oslc_sysmlv2:feature_OwnedTyping</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureTyping</code>	The <code>ownedSpecializations</code> of this <code>Feature</code> that are <code>FeatureTypings</code> , for which the <code>Feature</code> is the <code>typedFeature</code> .
<code>oslc_sysmlv2:feature_OwningFeatureMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>FeatureMembership</code> that owns this <code>Feature</code> as an <code>ownedMemberFeature</code> , determining its <code>owningType</code> .
<code>oslc_sysmlv2:feature_OwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The <code>Type</code> that is the <code>owningType</code> of the <code>owningFeatureMembership</code> of this <code>Feature</code> .
<code>oslc_sysmlv2:feature_Type</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	<code>Types</code> that restrict the values of this <code>Feature</code> , such that the values must be instances of all the <code>types</code> . The types of a <code>Feature</code> are derived from its <code>typings</code> and the <code>types</code> of its <code>subsettings</code> . If the <code>Feature</code> is chained, then the <code>types</code> of the last <code>Feature</code> in the chain are also <code>types</code> of the chained <code>Feature</code> .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The <code>Memberships</code> in this <code>Namespace</code> that result from the <code>ownedImports</code> of this <code>Namespace</code> .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member <code>Elements</code> of this <code>Namespace</code> , which are the <code>memberElements</code> of all <code>memberships</code> of the <code>Namespace</code> .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All <code>Memberships</code> in this <code>Namespace</code> , including (at least) the union of <code>ownedMemberships</code> and <code>importedMemberships</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-10].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#FlowConnectionDefinition`
- **Summary:** FlowConnectionDefinitionShape
- **Description:** A **FlowConnectionDefinition** is a **ConnectionDefinition** and **ActionDefinition** that is also an **Interaction** representing flows between **Usages**.

FlowConnectionDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:connectionDefinition_ConnectionEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that define the things related by the ConnectionDefinition .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:definition_OwnedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The <code>EnumerationUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The <code>FlowConnectionUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The <code>InterfaceUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedItem</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ItemUsage</code>	The <code>ItemUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedMetadata</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:MetadataUsage</code>	The <code>MetadataUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedOccurrence</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceUsage</code>	The <code>OccurrenceUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedPart</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The <code>PartUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedPort</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PortUsage</code>	The <code>PortUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedReference</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ReferenceUsage</code>	The <code>ReferenceUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .
<code>oslc_sysmlv2:definition_OwnedRendering</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:RenderingUsage</code>	The <code>RenderingUsages</code> that are <code>ownedUsages</code> of this <code>Definition</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition.
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition, if isVariation = true. If isVariation = false, the there must be no variants.
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships. If isVariation = true, then this must be all ownedMemberships of the Definition. If isVariation = false, then variantMembershipmust be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type.
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships, for which the Type is the owningType. Each such FeatureMembership identifies an ownedFeature of the Type.
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings, have the Type as their typeIntersected.
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations, for which the Type is the specific Type.
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-11] .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#VariantMembership`
- **Summary:** VariantMembershipShape
- **Description:** A **VariantMembership** is a **Membership** between a variation point **Definition** or **Usage** and a **Usage** that represents a variant in the context of that variation. The **membershipOwningNamespace** for the **VariantMembership** must be either a **Definition** or a **Usage** with **isVariation** = **true**.

VariantMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:variantMembership_OwnedVariantUsage	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage that represents a variant in the context of the owningVariationDefinition Or owningVariationUsage .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-12].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#NullExpression`
- **Summary:** `NullExpressionShape`
- **Description:** A `NullExpression` is an `Expression` that results in a null value.

NullExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-13].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#LiteralString>
- **Summary:** LiteralStringShape
- **Description:** A **LiteralString** is a **LiteralExpression** that provides a **String** value as a result. Its **result parameter** must have the type **String**.

LiteralString Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:literalString_Value	Exactly-one	false	unspecified	Either	xsd:string	The String value that is the result of evaluating this LiteralString .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-14] .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#EnumerationUsage`
- **Summary:** EnumerationUsageShape
- **Description:** An `EnumerationUsage` is an `AttributeUsage` whose `attributeDefinition` is an `EnumerationDefinition`.

EnumerationUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:attributeUsage_AttributeDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:DataType	The DataTypes that are the types of this AttributeUsage . Nominally, these are AttributeDefinitions , but other kinds of kernel DataTypes are also allowed, to permit use of DataTypes from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:enumerationUsage_EnumerationDefinition	Exactly-one	false	Resource	Either	oslc_sysmlv2:EnumerationDefinition	The single EnumerationDefinition that is the type of this EnumerationUsage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:feature_ChainingFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
<code>oslc_sysmlv2:feature_Direction</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:FeatureDirectionKind</code>	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
<code>oslc_sysmlv2:feature_EndOwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
<code>oslc_sysmlv2:feature_FeaturingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
<code>oslc_sysmlv2:feature_IsComposite</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
<code>oslc_sysmlv2:feature_IsDerived</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature can always be computed from the values of other Features .
<code>oslc_sysmlv2:feature_IsEnd</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
<code>oslc_sysmlv2:feature_IsNonunique</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	isNonunique.
<code>oslc_sysmlv2:feature_IsOrdered</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether an order exists for the values of this Feature or not.
<code>oslc_sysmlv2:feature_IsPortion</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The <code>CaseUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The <code>ConcernUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The <code>ConnectorAsUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> . Note that this list includes <code>BindingConnectorAsUsages</code> and <code>SuccessionAsUsages</code> , even though these are <code>ConnectorAsUsages</code> but not <code>ConnectionUsages</code> .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The code>EnumerationUsages that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The code>FlowConnectionUsages that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The <code>InterfaceUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedItem</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ItemUsage</code>	The <code>ItemUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedMetadata</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:MetadataUsage</code>	The <code>MetadataUsages</code> that are <code>nestedUsages</code> of this of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedOccurrence</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceUsage</code>	The <code>OccurrenceUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedPart</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The <code>PartUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-15].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#OperatorExpression>
- **Summary:** OperatorExpressionShape
- **Description:** An **OperatorExpression** is an **InvocationExpression** whose **function** is determined by resolving its **operator** in the context of one of the standard packages from the Kernel Function Library.

OperatorExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:invocationExpression_Argument	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The value Expressions of the FeatureValues of the owned input parameters of the InvocationExpression .
oslc_sysmlv2:invocationExpression_Operand	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	operand.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:operatorExpression_Operator	Exactly-one	false	unspecified	Either	xsd:string	An operator symbol that names a corresponding Function from one of the standard packages from the Kernel Function Library .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-16].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#BooleanExpression`
- **Summary:** BooleanExpressionShape
- **Description:** A **BooleanExpression** is a **Boolean**-valued **Expression** whose type is a **Predicate**. It represents a logical condition resulting from the evaluation of the **Predicate**.

BooleanExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:expression_Function</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Function</code>	The Function that types this Expression .
<code>oslc_sysmlv2:expression_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
<code>oslc_sysmlv2:expression_Result</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	.
<code>oslc_sysmlv2:feature_ChainingFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
<code>oslc_sysmlv2:feature_Direction</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:FeatureDirectionKind</code>	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
<code>oslc_sysmlv2:feature_EndOwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
<code>oslc_sysmlv2:feature_FeaturingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-17].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#StateDefinition`
- **Summary:** StateDefinitionShape
- **Description:** A `StateDefinition` is the `Definition` of the Behavior of a system or part of a system in a certain state condition.

StateDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName () operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:stateDefinition_DoAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateDefinition to be performed while in the state defined by the StateDefinition . It is the owned ActionUsage related to the StateDefinition by a StateSubactionMembership with kind = do .
oslc_sysmlv2:stateDefinition_EntryAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateDefinition to be performed on entry to the state defined by the StateDefinition . It is the owned ActionUsage related to the StateDefinition by a StateSubactionMembership with kind = entry .
oslc_sysmlv2:stateDefinition_ExitAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateDefinition to be performed on exit to the state defined by the StateDefinition . It is the owned ActionUsage related to the StateDefinition by a StateSubactionMembership with kind = exit .
oslc_sysmlv2:stateDefinition_IsParallel	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the ownedStates of this StateDefinition are to all be performed in parallel. If true, none of the ownedActions (which includes ownedStates) may have any incoming or outgoing Transitions . If false, only one ownedState may be performed at a time.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:stateDefinition_State	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages , which are actions in the StateDefinition , that specify the discrete states in the behavior defined by the StateDefinition .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-18].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#NamespaceExpose`
- **Summary:** NamespaceExposeShape
- **Description:** A `NamespaceExpose` is an `Expose Relationship` that exposes the `Memberships` of a specific `importedNamespace` and, if `isRecursive = true`, additional `Memberships` recursively.

NamespaceExpose Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:import_ImportedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The effectively imported Element for this Import. For a MembershipImport, this is the memberElement of the importedMembership. For a NamespaceImport, it is the importedNamespace.
oslc_sysmlv2:import_ImportOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.
oslc_sysmlv2:import_IsImportAll	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to import memberships without regard to declared visibility.
oslc_sysmlv2:import_IsRecursive	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to recursively import Memberships from visible, owned sub-Namespace.
oslc_sysmlv2:import_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	The visibility level of the imported members from this Import relative to the importOwningNamespace.
oslc_sysmlv2:namespaceImport_ImportedNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace whose visible Memberships are imported by this NamespaceImport.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-19].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Specialization`
- **Summary:** SpecializationShape
- **Description:** `Specialization` is a `Relationship` between two `Types` that requires all instances of the `specific` type to also be instances of the `general` Type (i.e., the set of instances of the `specific` Type is a *subset*

of those of the **general** Type, which might be the same set).

Specialization Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:specialization_General	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a superset of all instances of the specific Type , which might be the same set.
oslc_sysmlv2:specialization_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the specific Type of this Specialization and owns it as its owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:specialization_Specific	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a subset of all instances of the general Type , which might be the same set.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-20].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#LibraryPackage`
- **Summary:** LibraryPackageShape
- **Description:** A **LibraryPackage** is a **Package** that is the container for a model library. A **LibraryPackage** is itself a library **Element** as are all **Elements** that are directly or indirectly contained in it.

LibraryPackage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:libraryPackage_IsStandard	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this LibraryPackage contains a standard library model. This should only be set to true for LibraryPackages in the standard Kernel Model Libraries or in normative model libraries for a language built on KerML.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:package_FilterCondition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Expression</code>	The model-level evaluable Boolean -valued Expression used to filter the members of this Package , which are owned by the Package are via ElementFilterMemberships .
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-21].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ViewpointUsage`
- **Summary:** ViewpointUsageShape
- **Description:** A **ViewpointUsage** is a **Usage** of a **ViewpointDefinition**.

ViewpointUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:constraintUsage_ConstraintDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The (single) Predicate that is the type of this ConstraintUsage . Nominally, this will be a ConstraintDefinition , but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:requirementUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementUsage that represent actors involved in the requirement.
oslc_sysmlv2:requirementUsage_AssumedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent assumptions of this RequirementUsage , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = assumption .
oslc_sysmlv2:requirementUsage_FramedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages framed by this RequirementUsage , which are the ownedConcerns of all FramedConcernMemberships of the RequirementUsage .
oslc_sysmlv2:requirementUsage_ReqId	Zero-or-one	false	unspecified	Either	xsd:string	An optional modeler-specified identifier for this RequirementUsage (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementUsage .
oslc_sysmlv2:requirementUsage_RequiredConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent requirements of this RequirementUsage , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = requirement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementUsage_RequirementDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementDefinition	The RequirementDefinition that is the single definition of this RequirementUsage .
oslc_sysmlv2:requirementUsage_StakeholderParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementUsage that represent stakeholders for the requirement.
oslc_sysmlv2:requirementUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this RequirementUsage that represents its subject.
oslc_sysmlv2:requirementUsage_Text	Zero-or-many	false	unspecified	Either	xsd:string	An optional textual statement of the requirement represented by this RequirementUsage , derived from the bodies of the documentation of the RequirementUsage..
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedViewpoint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ViewpointUsage</code>	The ViewpointUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_OwningDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Definition</code>	The Definition that owns this Usage (if any).
<code>oslc_sysmlv2:usage_OwningUsage</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usage in which this Usage is nested (if any).
<code>oslc_sysmlv2:usage_Usage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages that are features of this Usage (not necessarily owned).
<code>oslc_sysmlv2:usage_Variant</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
<code>oslc_sysmlv2:usage_VariantMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:VariantMembership</code>	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
<code>oslc_sysmlv2:viewpointUsage_ViewpointDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:ViewpointDefinition</code>	The ViewpointDefinition that is the definition of this ViewpointUsage ..
<code>oslc_sysmlv2:viewpointUsage_ViewpointStakeholder</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The PartUsages that identify the stakeholders with concerns framed by this ViewpointUsage , which are the owned and inherited stakeholderParameters of the framedConcerns of this ViewpointUsage .
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-22].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ConnectionDefinition`
- **Summary:** ConnectionDefinitionShape
- **Description:** A `ConnectionDefinition` is a `PartDefinition` that is also an `AssociationStructure`. The end **Features** of a `ConnectionDefinition` must be **Usages**.

ConnectionDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:connectionDefinition_ConnectionEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that define the things related by the ConnectionDefinition .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes, which are the Types derived from the intersectingType of the ownedIntersectings of this Type. For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types.
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator.
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-23].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Relationship`
- **Summary:** RelationshipShape
- **Description:** A **Relationship** is an **Element** that relates other **Element**. Some of its **relatedElements** may be owned, in which case those **ownedRelatedElements** will be deleted from a model if their **owningRelationship** is. A **Relationship** may also be owned by another **Element**, in which case the **ownedRelatedElements** of the **Relationship** are also considered to be transitively owned by the **owningRelatedElement** of the **Relationship**.

Relationship Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-24].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Intersecting`
- **Summary:** IntersectingShape
- **Description:** `Intersecting` is a `Relationship` that makes its `intersectingType` one of the `intersectingTypes` of its `typeIntersected`.

Intersecting Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName () operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:intersecting_IntersectingType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type that partly determines interpretations of typeIntersected, as described in Type::intersectingType.
oslc_sysmlv2:intersecting_TypeIntersected	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type with interpretations partly determined by intersectingType, as described in Type::intersectingType.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-25].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

• **Describes:** <http://open-services.net/ns/sysmlv2#ParameterMembership>

- **Summary:** ParameterMembershipShape
- **Description:** A **ParameterMembership** is a **FeatureMembership** that identifies its **memberFeature** as a parameter, which is always owned, and must have a **direction**. A **ParameterMembership** must be owned by a **Behavior** or a **Step**.

ParameterMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType, making it an ownedFeature of the owningType.
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership.
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType.
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership.
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement.
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace.
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:parameterMembership_OwnedMemberParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is identified as a parameter by this ParameterMembership .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-26].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Class`
- **Summary:** ClassShape
- **Description:** A **Class** is a **Classifier** of things (in the universe) that can be distinguished without regard to how they are related to other things (via **Features**). This means multiple things classified by the same **Class** can be distinguished, even when they are related other things in exactly the same way.

Class Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-27].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Subclassification`
- **Summary:** SubclassificationShape
- **Description:** Subclassification is Specialization in which both the specific and general Types are Classifier. This means all instances of the specific Classifier are also instances of the general Classifier.

Subclassification Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:specialization_General	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a superset of all instances of the specific Type , which might be the same set.
oslc_sysmlv2:specialization_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the specific Type of this Specialization and owns it as its owningRelatedElement .
oslc_sysmlv2:specialization_Specific	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a subset of all instances of the general Type , which might be the same set.
oslc_sysmlv2:subclassification_OwningClassifier	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifier that owns this Subclassification relationship, which must also be its subclassifier .
oslc_sysmlv2:subclassification_Subclassifier	Exactly-one	false	Resource	Either	oslc_sysmlv2:Classifier	The more specific Classifier in this Subclassification .
oslc_sysmlv2:subclassification_Superclassifier	Exactly-one	false	Resource	Either	oslc_sysmlv2:Classifier	The more general Classifier in this Subclassification .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-28].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Element`
- **Summary:** ElementShape
- **Description:** An **Element** is a constituent of a model that is uniquely identified relative to all other **Elements**. It can have **Relationships** with other **Elements**. Some of these **Relationships** might imply ownership of other **Elements**, which means that if an **Element** is deleted from a model, then so are all the **Elements** that it owns.

Element Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-29] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#TransitionFeatureMembership>
- **Summary:** TransitionFeatureMembershipShape
- **Description:** A **TransitionFeatureMembership** is a **FeatureMembership** for a trigger, guard or effect of a **TransitionUsage**, whose **transitionFeature** is a **AcceptActionUsage**, **Boolean**-valued **Expression** or

ActionUsage, depending on its kind. .

TransitionFeatureMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType, making it an ownedFeature of the owningType.
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership.
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType.
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership.
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:transitionFeatureMembership_Kind	Exactly-one	false	unspecified	Either	oslc_sysmlv2:TransitionFeatureKind	Whether this TransitionFeatureMembership is for a trigger , guard or effect .
oslc_sysmlv2:transitionFeatureMembership_TransitionFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Step	The Step that is the ownedMemberFeature of this TransitionFeatureMembership .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-30].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#FeatureValue>
- **Summary:** FeatureValueShape
- **Description:** A **FeatureValue** is a **Membership** that identifies a particular member **Expression** that provides the value of the **Feature** that owns the **FeatureValue**. The value is specified as either a bound value or an initial value, and as either a concrete or default value. A **Feature** can have at most one **FeatureValue**.

FeatureValue Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:featureValue_FeatureWithValue	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature to be provided a value.
oslc_sysmlv2:featureValue_IsDefault	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this FeatureValue is a concrete specification of the bound or initial value of the featureWithValue, or just a default value that may be overridden.
oslc_sysmlv2:featureValue_IsInitial	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this FeatureValue specifies a bound value or an initial value for the featureWithValue.
oslc_sysmlv2:featureValue_Value	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression that provides the value of the featureWithValue as its result.
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership.
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement.
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-31].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Comment`
- **Summary:** CommentShape
- **Description:** A `Comment` is an `AnnotatingElement` whose `body` in some way describes its `annotatedElements`.

Comment Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:annotatingElement_AnnotatedElement	One-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are annotated by this AnnotatingElement . If annotation is not empty, these are the annotatedElements of the annotations . If annotation is empty, then it is the owningNamespace of the AnnotatingElement .
oslc_sysmlv2:annotatingElement_Annotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The Annotations that relate this AnnotatingElement to its annotatedElements .
oslc_sysmlv2:annotatingElement_OwnedAnnotatingRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this AnnotatingElement that are Annotations , for which this AnnotatingElement is the annotatingElement .
oslc_sysmlv2:comment_Body	Exactly-one	false	unspecified	Either	xsd:string	The annotation text for the Comment .
oslc_sysmlv2:comment_Locale	Zero-or-one	false	unspecified	Either	xsd:string	Identification of the language of the body text and, optionally, the region and/or encoding. The format shall be a POSIX locale conformant to ISO/IEC 15897, with the format [language[_territory][.codeset][@modifier]] .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the <code>Element</code> that is intended to be shorter or in some way more succinct than its primary <code>name</code> . It may act as a modeler-specified identifier for the <code>Element</code> , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-32].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#FeatureChainExpression`
- **Summary:** FeatureChainExpressionShape
- **Description:** A `FeatureChainExpression` is an `OperatorExpression` whose operator is `". "`, which resolves to the `Function ControlFunctions::'.'` from the Kernel Functions Library. It evaluates to the result of chaining the `result Feature` of its single `argument Expression` with its `targetFeature`.

FeatureChainExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Copyright © OASIS Open 2024. All Rights Reserved.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:featureChainExpression_TargetFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is accessed by this FeatureChainExpression , which is its first non-parameter member . .
oslc_sysmlv2:invocationExpression_Argument	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The value Expressions of the FeatureValues of the owned input parameters of the InvocationExpression .
oslc_sysmlv2:invocationExpression_Operand	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	operand.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:operatorExpression_Operator	Exactly-one	false	unspecified	Either	xsd:string	An operator symbol that names a corresponding Function from one of the standard packages from the Kernel Function Library .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-33].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#UseCaseUsage`
- **Summary:** UseCaseUsageShape
- **Description:** A **UseCaseUsage** is a **Usage** of a **UseCaseDefinition**.

UseCaseUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:calculationUsage_CalculationDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that is the type of this CalculationUsage. Nominally, this would be a CalculationDefinition, but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries..
oslc_sysmlv2:caseUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseUsage that represent actors involved in the case.
oslc_sysmlv2:caseUsage_CaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:CaseDefinition	The CaseDefinition that is the type of this CaseUsage.
oslc_sysmlv2:caseUsage_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseUsage.
oslc_sysmlv2:caseUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseUsage that represents its subject.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout ..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc_sysmlv2:useCaseUsage_IncludedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are included by this UseCaseUse , which are the useCaseIncluded s of the IncludeUseCaseUsages owned by this UseCaseUsage ..
oslc_sysmlv2:useCaseUsage_UseCaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:UseCaseDefinition	The UseCaseDefinition that is the definition of this UseCaseUsage .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-34] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#DataType>
- **Summary:** DataTypeShape
- **Description:** A **DataType** is a **Classifier** of things (in the universe) that can only be distinguished by how they are related to other things (via Features). This means multiple things classified by the same **DataType**.

Data Type Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-35].

<i>Prefixed Name</i>	<i>Occurs</i>	<i>Read-only</i>	<i>Value-type</i>	<i>Representation</i>	<i>Range</i>	<i>Description</i>
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Expression>
- **Summary:** ExpressionShape
- **Description:** An **Expression** is a **Step** that is typed by a **Function**. An **Expression** that also has a **Function** as its **featuringType** is a computational step within that **Function**. An **Expression** always has a single **result** parameter, which redefines the **result** parameter of its defining **function**. This allows **Expressions** to be interconnected in tree structures, in which inputs to each **Expression** in the tree are determined as the results of other **Expression** in the tree.

Expression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-36].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#PartDefinition`
- **Summary:** PartDefinitionShape
- **Description:** A **PartDefinition** is an **ItemDefinition** of a **Class** of systems or parts of systems. Note that all parts may be considered items for certain purposes, but not all items are parts that can perform actions within a system.

PartDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:occurrenceDefinition_LifeClass</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:LifeClass</code>	If <code>isIndividual</code> is true, a <code>LifeClass</code> that specializes this <code>OccurrenceDefinition</code> , restricting it to represent an individual.
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>differencingTypes</code> are asserted to be those of the first of those <code>Types</code> , but not including those of the remaining <code>Types</code> . For example, a <code>Classifier</code> might be the difference of a <code>Classifier</code> for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a <code>Classifier</code> for people of a particular sex, identifying their children not of that sex (because the interpretations of the children <code>Feature</code> that identify those of that sex are also interpretations of the <code>Classifier</code> for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>features</code> of this <code>Type</code> that have a non-null <code>direction</code> .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>features</code> of this <code>Type</code> with <code>isEnd</code> = <code>true</code> .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>featureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>FeatureMemberships</code> for <code>features</code> of this <code>Type</code> , which include all <code>ownedFeatureMemberships</code> and those <code>inheritedMemberships</code> that are <code>FeatureMemberships</code> (but does <i>not</i> include any <code>importedMemberships</code>).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the <code>memberFeatures</code> of the <code>inheritedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All <code>Memberships</code> inherited by this <code>Type</code> via <code>Specialization</code> or <code>Conjugation</code> . These are included in the derived union for the <code>memberships</code> of the <code>Type</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-37].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#SendActionUsage>
- **Summary:** SendActionUsageShape
- **Description:** A **SendActionUsage** is an **ActionUsage** that specifies the sending of a payload given by the result of its **payloadArgument Expression** via a **MessageTransfer** whose **source** is given by the result of the **senderArgument Expression** and whose **target** is given by the result of the **receiverArgument Expression**. If no **senderArgument** is provided, the default is the **this** context for the action. If no **receiverArgument** is given, then the receiver is to be determined by, e.g., outgoing **Connections** from the sender.

SendActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespaces</code> from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:sendActionUsage_PayloadArgument	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	An Expression whose result is bound to the payload input parameter of this SendActionUsage .
oslc_sysmlv2:sendActionUsage_ReceiverArgument	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	An Expression whose result is bound to the receiver input parameter of this SendActionUsage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:sendActionUsage_SenderArgument</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Expression</code>	An Expression whose result is bound to the <i>sender</i> input parameter of this SendActionUsage .
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-38].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** http://open-services.net/ns/sysmlv2#LiteralExpression
- **Summary:** LiteralExpressionShape
- **Description:** A LiteralExpression is an Expression that provides a basic DataValue as a result.

LiteralExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-39].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URLs.

- **Describes:** `http://open-services.net/ns/sysmlv2#StakeholderMembership`
- **Summary:** StakeholderMembershipShape
- **Description:** A `StakeholderMembership` is a `ParameterMembership` that identifies a `PartUsage` as a `stakeholderParameter` of a `RequirementDefinition` or `RequirementUsage`, which specifies a role played by an entity with concerns framed by the `owningType`.

StakeholderMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:parameterMembership_OwnedMemberParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is identified as a parameter by this ParameterMembership .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:stakeholderMembership_OwnedStakeholderParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsage specifying the stakeholder.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-40].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URLs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ReferenceUsage`
- **Summary:** ReferenceUsageShape
- **Description:** A **ReferenceUsage** is a **Usage** that specifies a non-compositional (**isComposite** = **false**) reference to something. The **definition** of a **ReferenceUsage** can be any kind of **Classifier**, with the default being the top-level **Classifier Base::Anything** from the Kernel Semantic Library. This allows the specification of a generic reference without distinguishing if the thing referenced is an attribute value, item, action, etc.

ReferenceUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-41].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AllocationDefinition>
- **Summary:** AllocationDefinitionShape
- **Description:** An **AllocationDefinition** is a **ConnectionDefinition** that specifies that some or all of the responsibility to realize the intent of the **source** is allocated to the **target** instances. Such allocations define mappings across the various structures and hierarchies of a system model, perhaps as a precursor to more rigorous specifications and implementations. An **AllocationDefinition** can itself be refined using nested **allocations** that give a finer-grained decomposition of the containing allocation mapping.

AllocationDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:allocationDefinition_Allocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that refine the allocation mapping defined by this AllocationDefinition .
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:connectionDefinition_ConnectionEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that define the things related by the ConnectionDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-42].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ReferenceSubsetting`
- **Summary:** ReferenceSubsettingShape
- **Description:** ReferenceSubsetting is a kind of Subsetting in which the `referencedFeature` is syntactically distinguished from other `Features` subsetting by the `referencingFeature`. ReferenceSubsetting has the same semantics as Subsetting, but the `referenceFeature` may have a special purpose relative to the `referencingFeature`. For instance, ReferenceSubsetting is used to identify the `relatedFeatures` of a Connector.

ReferenceSubsetting Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:referenceSubsetting_ReferencedFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is referenced by the referencingFeature of this ReferenceSubsetting .
oslc_sysmlv2:referenceSubsetting_ReferencingFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that owns this ReferenceSubsetting relationship, which is also its subsettingFeature .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> to which this Relationship is considered to be directed.
oslc_sysmlv2:specialization_General	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A <code>Type</code> with a superset of all instances of the <code>specific Type</code> , which might be the same set.
oslc_sysmlv2:specialization_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The <code>Type</code> that is the <code>specific Type</code> of this <code>Specialization</code> and owns it as its <code>owningRelatedElement</code> .
oslc_sysmlv2:specialization_Specific	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A <code>Type</code> with a subset of all instances of the <code>general Type</code> , which might be the same set.
oslc_sysmlv2:subsetting_OwningFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	A <code>subsettingFeature</code> that is also the <code>owningRelatedElement</code> of this <code>Subsetting</code> .
oslc_sysmlv2:subsetting_SubsettedFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The <code>Feature</code> that is subsetted by the <code>subsettingFeature</code> of this <code>Subsetting</code> .
oslc_sysmlv2:subsetting_SubsettingFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The <code>Feature</code> that is a subset of the <code>subsettedFeature</code> of this <code>Subsetting</code> .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-43].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Invariant>
- **Summary:** InvariantShape
- **Description:** An **Invariant** is a **BooleanExpression** that is asserted to have a specific **Boolean** result value. If **isNegated = false**, then the result is asserted to be true. If **isNegated = true**, then the result is asserted to be false.

Invariant Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression.
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at model level, that is, using metadata within the model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:invariant_IsNegated	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Invariant is asserted to be false rather than true.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-44].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Type>
- **Summary:** TypeShape
- **Description:** A Type is a Namespace that is the most general kind of Element supporting the semantics of classification. A Type may be a Classifier or a Feature, defining conditions on what is classified by the Type (see also the description of isSufficient).

Type Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-45].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#AnalysisCaseUsage`
- **Summary:** AnalysisCaseUsageShape
- **Description:** An **AnalysisCaseUsage** is a **Usage** of an **AnalysisCaseDefinition**.

AnalysisCaseUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:analysisCaseUsage_AnalysisAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The composite usages of the AnalysisCaseUsage that are defined as AnalysisActions.
oslc_sysmlv2:analysisCaseUsage_AnalysisCaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:AnalysisCaseDefinition	The AnalysisCaseDefinition that is the definition of this AnalysisCaseUsage.
oslc_sysmlv2:analysisCaseUsage_ResultExpression	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	An Expression used to compute the result of the AnalysisCaseUsage, owned via a ResultExpressionMembership.
oslc_sysmlv2:calculationUsage_CalculationDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that is the type of this CalculationUsage. Nominally, this would be a CalculationDefinition, but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries..
oslc_sysmlv2:caseUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseUsage that represent actors involved in the case.
oslc_sysmlv2:caseUsage_CaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:CaseDefinition	The CaseDefinition that is the type of this CaseUsage.
oslc_sysmlv2:caseUsage_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseUsage.
oslc_sysmlv2:caseUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseUsage that represents its subject.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:expression_Function</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Function</code>	The Function that types this Expression .
<code>oslc_sysmlv2:expression_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
<code>oslc_sysmlv2:expression_Result</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	.
<code>oslc_sysmlv2:feature_ChainingFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
<code>oslc_sysmlv2:feature_Direction</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:FeatureDirectionKind</code>	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
<code>oslc_sysmlv2:feature_EndOwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
<code>oslc_sysmlv2:feature_FeaturingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
<code>oslc_sysmlv2:feature_IsComposite</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
<code>oslc_sysmlv2:feature_IsDerived</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature can always be computed from the values of other Features .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-46].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#FramedConcernMembership>
- **Summary:** FramedConcernMembershipShape
- **Description:** A **FramedConcernMembership** is a **RequirementConstraintMembership** for a framed **ConcernUsage** of a **RequirementDefinition** or **RequirementUsage**.

FramedConcernMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:framedConcernMembership_OwnedConcern	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsage that is the ownedConstraint of this FramedConcernMembership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:framedConcernMembership_ReferencedConcern	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsage that is referenced through this FramedConcernMembership . It is the referencedConstraint of the FramedConcernMembership considered as a RequirementConstraintMembership , which must be a ConcernUsage .
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:requirementConstraintMembership_Kind</code>	Exactly-one	false	unspecified	Either	<code>oslc_sysmlv2:RequirementConstraintKind</code>	Whether the <code>RequirementConstraintMembership</code> is for an assumed or required <code>ConstraintUsage</code> .
<code>oslc_sysmlv2:requirementConstraintMembership_OwnedConstraint</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsage</code> that is the <code>ownedMemberFeature</code> of this <code>RequirementConstraintMembership</code> .
<code>oslc_sysmlv2:requirementConstraintMembership_ReferencedConstraint</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsage</code> that is referenced through this <code>RequirementConstraintMembership</code> . It is the <code>referencedFeature</code> of the <code>ownedReferenceSubsetting</code> of the <code>ownedConstraint</code> , if there is one, and, otherwise, the <code>ownedConstraint</code> itself.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-47].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** http://open-services.net/ns/sysmlv2#AssignmentActionUsage
- **Summary:** AssignmentActionUsageShape
- **Description:** An **AssignmentActionUsage** is an **ActionUsage** that is defined, directly or indirectly, by the **ActionDefinition AssignmentAction** from the Systems Model Library. It specifies that the value of the **referent Feature**, relative to the target given by the result of the **targetArgument Expression**, should be set to the result of the **valueExpression**.

AssignmentActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:assignmentActionUsage_Referent	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature whose value is to be set.
oslc_sysmlv2:assignmentActionUsage_TargetArgument	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose value is an occurrence in the domain of the referent Feature, for which the value of the referent will be set to the result of the valueExpression by this AssignmentActionUsage.
oslc_sysmlv2:assignmentActionUsage_ValueExpression	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result is to be assigned to the referent Feature.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The <code>ActionUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The <code>AllocationUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The <code>AnalysisCaseUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The <code>code>AttributeUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The <code>CalculationUsage</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The <code>CaseUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The <code>ConcernUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The <code>ConnectorAsUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> . Note that this list includes <code>BindingConnectorAsUsages</code> and <code>SuccessionAsUsages</code> , even though these are <code>ConnectorAsUsages</code> but not <code>ConnectionUsages</code> .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The <code>code>EnumerationUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The <code>code>FlowConnectionUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-48].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Package>
- **Summary:** PackageShape
- **Description:** A **Package** is a **Namespace** used to group **Elements**, without any instance-level semantics. It may have one or more model-level evaluable **filterCondition Expressions** used to filter its **importedMemberships**. Any imported **member** must meet all of the **filterConditions**.

Package Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:package_FilterCondition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The model-level evaluable Boolean -valued Expression used to filter the members of this Package , which are owned by the Package are via ElementFilterMemberships .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-49].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ItemFeature>
- **Summary:** ItemFeatureShape
- **Description:** An **ItemFeature** is the **ownedFeature** of an **ItemFlow** that identifies the things carried by the kinds of transfers that are instances of the **ItemFlow**.

ItemFeature Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>jazz_am:elaborates</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	This resource elaborates the referenced resource.
<code>jazz_am:external</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	A generic link from a resource to an external web page.
<code>jazz_am:refine</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
<code>jazz_am:satisfy</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
<code>jazz_am:trace</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Copyright © OASIS Open 2024. All Rights Reserved.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType.
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature.
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-50].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ConstraintUsage`
- **Summary:** ConstraintUsageShape
- **Description:** A `ConstraintUsage` is an `OccurrenceUsage` that is also a `BooleanExpression`, and, so, is typed by a `Predicate`. Nominally, if the type is a `ConstraintDefinition`, a `ConstraintUsage` is a `Usage` of that `ConstraintDefinition`. However, other kinds of kernel `Predicates` are also allowed, to permit use of `Predicates` from the Kernel Model Libraries.

ConstraintUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .
oslc_sysmlv2:constraintUsage_ConstraintDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The (single) Predicate that is the type of this ConstraintUsage . Nominally, this will be a ConstraintDefinition , but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression.
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at model level, that is, using metadata within the model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-51].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#SubjectMembership`
- **Summary:** SubjectMembershipShape
- **Description:** A `SubjectMembership` is a `ParameterMembership` that indicates that its `ownedSubjectParameter` is the subject of its `owningType`. The `owningType` of a `SubjectMembership` must be a `RequirementDefinition`, `RequirementUsage`, `CaseDefinition`, or `CaseUsage`.

SubjectMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:parameterMembership_OwnedMemberParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is identified as a parameter by this ParameterMembership .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:subjectMembership_OwnedSubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage ownedMemberParameter of this SubjectMembership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-52].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#FeatureInverting>
- **Summary:** FeatureInvertingShape
- **Description:** A **FeatureInverting** is a **Relationship** between **Features** asserting that their interpretations (sequences) are the reverse of each other, identified as **featureInverted** and **invertingFeature**. For example, a **Feature** identifying each person's parents is the inverse of a **Feature** identifying each person's children. A person identified as a parent of another will identify that other as one of their children.

FeatureInverting Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureInverting_FeatureInverted	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is an inverse of the invertingFeature .
oslc_sysmlv2:featureInverting_InvertingFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is an inverse of the invertedFeature .
oslc_sysmlv2:featureInverting_OwningFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	A featureInverted that is also the owningRelatedElement of this FeatureInverting .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-53].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ElementFilterMembership>
- **Summary:** ElementFilterMembershipShape
- **Description:** `ElementFilterMembership` is a `Membership` between a `Namespace` and a model-level evaluable `Boolean`-valued `Expression`, asserting that imported `members` of the `Namespace` should be filtered using the `condition Expression`. A general `Namespace` does not define any specific filtering behavior, but such behavior may be defined for various specialized kinds of `Namespaces`.

ElementFilterMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:elementFilterMembership_Condition	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The model-level evaluable Boolean-valued Expression used to filter the imported members of the membershipOwningNamespace of this ElementFilterMembership.
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-54].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#IncludeUseCaseUsage`
- **Summary:** IncludeUseCaseUsageShape
- **Description:** An **IncludeUseCaseUsage** is a **UseCaseUsage** that represents the inclusion of a **UseCaseUsage** by a **UseCaseDefinition** or **UseCaseUsage**. Unless it is the **IncludeUseCaseUsage** itself, the **UseCaseUsage** to be included is related to the **includedUseCase** by a **ReferenceSubsetting Relationship**. An **IncludeUseCaseUsage** is also a **PerformActionUsage**, with its **useCaseIncluded** as the **performedAction**.

IncludeUseCaseUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:calculationUsage_CalculationDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that is the type of this CalculationUsage. Nominally, this would be a CalculationDefinition, but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries..
oslc_sysmlv2:caseUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseUsage that represent actors involved in the case.
oslc_sysmlv2:caseUsage_CaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:CaseDefinition	The CaseDefinition that is the type of this CaseUsage.
oslc_sysmlv2:caseUsage_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseUsage.
oslc_sysmlv2:caseUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseUsage that represents its subject.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:eventOccurrenceUsage_EventOccurrence	Exactly-one	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsage referenced as an event by this EventOccurrenceUsage. It is the referenceFeature of the ownedReferenceSubsetting for the EventOccurrenceUsage, if there is one, and, otherwise, the EventOccurrenceUsage itself.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:includeUseCaseUsage_UseCaseIncluded	Exactly-one	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsage to be included by this IncludeUseCaseUsage . It is the performedAction of the IncludeUseCaseUsage considered as a PerformActionUsage , which must be a UseCaseUsage .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:performActionUsage_PerformedAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage to be performed by this PerformedActionUsage . It is the eventOccurrence of the PerformActionUsage considered as an EventOccurrenceUsage , which must be an ActionUsage .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc_sysmlv2:useCaseUsage_IncludedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are included by this UseCaseUse , which are the useCaseIncluded s of the IncludeUseCaseUsages owned by this UseCaseUsage ..
oslc_sysmlv2:useCaseUsage_UseCaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:UseCaseDefinition	The UseCaseDefinition that is the definition of this UseCaseUsage .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-55] .

<i>Prefixed Name</i>	<i>Occurs</i>	<i>Read-only</i>	<i>Value-type</i>	<i>Representation</i>	<i>Range</i>	<i>Description</i>
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ItemUsage>
- **Summary:** ItemUsageShape
- **Description:** An **ItemUsage** is a **ItemUsage** whose **definition** is a **Structure**. Nominally, if the **definition** is an **ItemDefinition**, an **ItemUsage** is a **ItemUsage** of that **ItemDefinition** within a system. However, other kinds of Kernel **Structures** are also allowed, to permit use of **Structures** from the Kernel Model Libraries.

ItemUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true.
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition.
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage. Nominally, these are OccurrenceDefinitions, but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage, if it is so restricted.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types, but not including those of the remaining Types. For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-56].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#TextualRepresentation`
- **Summary:** TextualRepresentationShape
- **Description:** A `TextualRepresentation` is an `AnnotatingElement` whose `body` represents the `representedElement` in a given `language`. The `representedElement` must be the `owner` of the `TextualRepresentation`. The named `language` can be a natural language, in which case the `body` is an informal representation, or an artificial language, in which case the `body` is expected to be a formal, machine-parsable representation.

TextualRepresentation Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:annotatingElement_AnnotatedElement</code>	One-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are annotated by this AnnotatingElement . If annotation is not empty, these are the annotatedElements of the annotations . If annotation is empty, then it is the owningNamespace of the AnnotatingElement .
<code>oslc_sysmlv2:annotatingElement_Annotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The Annotations that relate this AnnotatingElement to its annotatedElements .
<code>oslc_sysmlv2:annotatingElement_OwnedAnnotatingRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this AnnotatingElement that are Annotations , for which this AnnotatingElement is the annotatingElement .
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:textualRepresentation_Body</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The textual representation of the representedElement in the given language .
<code>oslc_sysmlv2:textualRepresentation_Language</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The natural or artificial language in which the body text is written.
<code>oslc_sysmlv2:textualRepresentation_RepresentedElement</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Element that is represented by this TextualRepresentation .
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-57].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#JoinNode>
- **Summary:** JoinNodeShape
- **Description:** A **JoinNode** is a **ControlNode** that waits for the completion of all the predecessor **Actions** given by incoming **Successions**.

JoinNode Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures.
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type.
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships, for which the Type is the owningType. Each such FeatureMembership identifies an ownedFeature of the Type.
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings, have the Type as their typeIntersected.
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations, for which the Type is the specific Type.
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage. Nominally, these are Definitions, but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures.
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage, that is, it has isComposite = false.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-58].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#CalculationDefinition>
- **Summary:** CalculationDefinitionShape
- **Description:** A **CalculationDefinition** is an **ActionDefinition** that also defines a **Function** producing a **result**..

CalculationDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:calculationDefinition_Calculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The actions of this CalculationDefinition that are CalculationUsages .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-59].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ConjugatedPortTyping`
- **Summary:** ConjugatedPortTypingShape
- **Description:** A **ConjugatedPortTyping** is a **FeatureTyping** whose **type** is a **ConjugatedPortDefinition**. (This relationship is intended to be an abstract-syntax marker for a special surface notation for conjugated typing of ports.).

ConjugatedPortTyping Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:conjugatedPortTyping_ConjugatedPortDefinition	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConjugatedPortDefinition	The type of this ConjugatedPortTyping considered as a FeatureTyping , which must be a ConjugatedPortDefinition .
oslc_sysmlv2:conjugatedPortTyping_PortDefinition	Exactly-one	false	Resource	Either	oslc_sysmlv2:PortDefinition	The originalPortDefinition of the conjugatedPortDefinition of this ConjugatedPortTyping .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Standards Track Work Product

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureTyping_OwningFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	A typedFeature that is also the owningRelatedElement of this FeatureTyping .
oslc_sysmlv2:featureTyping_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is being applied by this FeatureTyping .
oslc_sysmlv2:featureTyping_TypedFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that has a type determined by this FeatureTyping .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:specialization_General</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	A <code>Type</code> with a superset of all instances of the <code>specific Type</code> , which might be the same set.
<code>oslc_sysmlv2:specialization_OwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The <code>Type</code> that is the <code>specific Type</code> of this <code>Specialization</code> and owns it as its <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:specialization_Specific</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	A <code>Type</code> with a subset of all instances of the <code>general Type</code> , which might be the same set.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-60].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#MergeNode>
- **Summary:** MergeNodeShape
- **Description:** A **MergeNode** is a **ControlNode** that asserts the merging of its incoming **Successions**. A **MergeNode** may have at most one outgoing **Successions**.

MergeNode Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-61].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ConnectionUsage>
- **Summary:** ConnectionUsageShape
- **Description:** A **ConnectionUsage** is a **ConnectorAsUsage** that is also a **PartUsage**. Nominally, if its type is a **ConnectionDefinition**, then a **ConnectionUsage** is a Usage of that **ConnectionDefinition**, representing a connection between parts of a system. However, other kinds of kernel **AssociationStructures** are also allowed, to permit use of **AssociationStructures** from the Kernel Model Libraries.

ConnectionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connectionUsage_ConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AssociationStructure	The AssociationStructures that are the types of this ConnectionUsage . Nominally, these are , but other kinds of Kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model Libraries.
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:partUsage_PartDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartDefinition	The itemDefinitions of this PartUsage that are PartDefinitions.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes, which are the Types derived from the intersectingType of the ownedIntersectings of this Type. For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types.
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator.
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-62].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#NamespaceImport>
- **Summary:** NamespaceImportShape
- **Description:** A **NamespaceImport** is an Import that imports **Memberships** from its **importedNamespace** into the **importOwningNamespace**. If **isRecursive = false**, then only the visible **Memberships** of the

`importedNamespace` are imported. If `isRecursive = true`, then, in addition, `Memberships` are recursively imported from any `ownedMembers` of the `importedNamespace` that are `Namespaces`.

NamespaceImport Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
<code>dcterms:type</code>	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
<code>jazz_am:derives</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
<code>jazz_am:elaborates</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	This resource elaborates the referenced resource.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>jazz_am:external</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	A generic link from a resource to an external web page.
<code>jazz_am:refine</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
<code>jazz_am:satisfy</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
<code>jazz_am:trace</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:import_ImportedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The effectively imported Element for this Import. For a MembershipImport , this is the memberElement of the importedMembership . For a NamespaceImport , it is the importedNamespace .
oslc_sysmlv2:import_ImportOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.
oslc_sysmlv2:import_IsImportAll	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to import memberships without regard to declared visibility.
oslc_sysmlv2:import_IsRecursive	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to recursively import Memberships from visible, owned sub-Namespaces.
oslc_sysmlv2:import_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	The visibility level of the imported members from this Import relative to the importOwningNamespace .
oslc_sysmlv2:namespaceImport_ImportedNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace whose visible Memberships are imported by this NamespaceImport .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-63].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** http://open-services.net/ns/sysmlv2#FeatureReferenceExpression
- **Summary:** FeatureReferenceExpressionShape
- **Description:** A FeatureReferenceExpression is an Expression whose result is bound to a referent Feature.

FeatureReferenceExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions, for which the Feature is the redefiningFeature.
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature, if any, that is a ReferenceSubsetting, for which the Feature is the referencingFeature.
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings, for which the Feature is the subsettingFeature.
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType.
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature.
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.
oslc_sysmlv2:featureReferenceExpression_Referent	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is referenced by this FeatureReferenceExpression, which is its first non-parameter member.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes, which are the Types derived from the intersectingType of the ownedIntersectings of this Type. For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types.
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator.
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-64].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AcceptActionUsage>
- **Summary:** AcceptActionUsageShape
- **Description:** An **AcceptActionUsage** is an **ActionUsage** that specifies the acceptance of an **incomingTransfer** from the **Occurrence** given by the result of its **receiverArgument** Expression. (If no **receiverArgument** is provided, the default is the **this** context of the AcceptActionUsage.) The payload of the accepted **Transfer** is output on its **payloadParameter**. Which **Transfers** may be accepted is determined by conformance to the typing and (potentially) binding of the **payloadParameter**.

AcceptActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:acceptActionUsage_PayloadArgument	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	An Expression whose result is bound to the payload parameter of this AcceptActionUsage . If provided, the AcceptActionUsage will only accept a Transfer with exactly this payload .
oslc_sysmlv2:acceptActionUsage_PayloadParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The nestedReference of this AcceptActionUsage that redefines the payload output parameter of the base AcceptActionUsage AcceptAction from the Systems Model Library.
oslc_sysmlv2:acceptActionUsage_ReceiverArgument	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	An Expression whose result is bound to the receiver input parameter of this AcceptActionUsage .
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-65].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#BindingConnector`
- **Summary:** BindingConnectorShape
- **Description:** A `BindingConnector` is a binary `Connector` that requires its `relatedFeatures` to identify the same things (have the same values).

BindingConnector Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a <code>Type</code> with <code>differencingTypes</code> are asserted to be those of the first of those <code>Types</code> , but not including those of the remaining <code>Types</code> . For example, a <code>Classifier</code> might be the difference of a <code>Classifier</code> for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a <code>Classifier</code> for people of a particular sex, identifying their children not of that sex (because the interpretations of the children <code>Feature</code> that identify those of that sex are also interpretations of the <code>Classifier</code> for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The <code>features</code> of this <code>Type</code> that have a non-null <code>direction</code> .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All <code>features</code> of this <code>Type</code> with <code>isEnd</code> = <code>true</code> .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The <code>ownedMemberFeatures</code> of the <code>featureMemberships</code> of this <code>Type</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-66].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#TriggerInvocationExpression`
- **Summary:** TriggerInvocationExpressionShape
- **Description:** A **TriggerInvocationExpression** is an **InvocationExpression** that invokes one of the trigger **Functions** from the Kernel Semantic Library **Triggers** package, as indicated by its **kind**.

TriggerInvocationExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:invocationExpression_Argument	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The value Expressions of the FeatureValues of the owned input parameters of the InvocationExpression .
oslc_sysmlv2:invocationExpression_Operand	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	operand.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:triggerInvocationExpression_Kind	Exactly-one	false	unspecified	Either	oslc_sysmlv2:TriggerKind	Indicates which of the Functions from the Triggers model in the Kernel Semantic Library is to be invoked by this TriggerInvocationExpression .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-67].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ViewUsage>
- **Summary:** ViewUsageShape
- **Description:** A **ViewUsage** is a usage of a **ViewDefinition** to specify the generation of a view of the **members** of a collection of **exposedNamespaces**. The **ViewUsage** can satisfy more **viewpoints** than its definition, and it can specialize the **viewRendering** specified by its definition.

ViewUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:partUsage_PartDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartDefinition	The itemDefinitions of this PartUsage that are PartDefinitions.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc_sysmlv2:viewUsage_ExposedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are exposed by this ViewUsage , which are those memberElements of the imported Memberships from all the Expose Relationships that meet all the owned and inherited viewConditions .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:viewUsage_SatisfiedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The nestedRequirements of this ViewUsage that are ViewpointUsages for (additional) viewpoints satisfied by the ViewUsage .
oslc_sysmlv2:viewUsage_ViewCondition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions related to this ViewUsage by ElementFilterMemberships , which specify conditions on Elements to be rendered in a view.
oslc_sysmlv2:viewUsage_ViewDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ViewDefinition	The ViewDefinition that is the definition of this ViewUsage .
oslc_sysmlv2:viewUsage_ViewRendering	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsage to be used to render views defined by this ViewUsage , which is the referencedRendering of the ViewRenderingMembership of the ViewUsage .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-68].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AttributeDefinition>
- **Summary:** AttributeDefinitionShape
- **Description:** An **AttributeDefinition** is a **Definition** and a **DataType** of information about a quality or characteristic of a system or part of a system that has no independent identity other than its value. All **features** of an **AttributeDefinition** must be referential (non-composite).

AttributeDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-69].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Metaclass`
- **Summary:** MetaclassShape
- **Description:** A `Metaclass` is a `Structure` used to type `MetadataFeatures`.

Metaclass Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-70].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#UseCaseDefinition`
- **Summary:** UseCaseDefinitionShape
- **Description:** A `UseCaseDefinition` is a `CaseDefinition` that specifies a set of actions performed by its subject, in interaction with one or more actors external to the subject. The objective is to yield an observable result that is of value to one or more of the actors.

UseCaseDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:behavior_Step</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Step</code>	The Steps that make up this Behavior .
<code>oslc_sysmlv2:calculationDefinition_Calculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The actions of this CalculationDefinition that are CalculationUsages .
<code>oslc_sysmlv2:caseDefinition_ActorParameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The parameters of this CaseDefinition that represent actors involved in the case.
<code>oslc_sysmlv2:caseDefinition_ObjectiveRequirement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:RequirementUsage</code>	The RequirementUsage representing the objective of this CaseDefinition .
<code>oslc_sysmlv2:caseDefinition_SubjectParameter</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The parameter of this CaseDefinition that represents its subject.
<code>oslc_sysmlv2:classifier_OwnedSubclassification</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Subclassification</code>	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
<code>oslc_sysmlv2:definition_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The usages of this Definition that are directedFeatures .
<code>oslc_sysmlv2:definition_IsVariation</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
<code>oslc_sysmlv2:definition_OwnedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The ActionUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The AllocationUsages that are ownedUsages of this Definition .
<code>oslc_sysmlv2:definition_OwnedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The AnalysisCaseUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition.
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:useCaseDefinition_IncludedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are included by this UseCaseDefinition , which are the useCaseIncluded s of the IncludeUseCaseUsages owned by this UseCaseDefinition ..
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-71].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Step>
- **Summary:** StepShape
- **Description:** A **Step** is a **Feature** that is typed by one or more **Behaviors**. **Steps** may be used by one **Behavior** to coordinate the performance of other **Behaviors**, supporting a steady refinement of behavioral descriptions. **Steps** can be ordered in time and can be connected using **ItemFlows** to specify things flowing between their **parameters**.

Step Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-72].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URLs.

- **Describes:** `http://open-services.net/ns/sysmlv2#AssociationStructure`
- **Summary:** AssociationStructureShape
- **Description:** An **AssociationStructure** is an **Association** that is also a **Structure**, classifying link objects that are both links and objects. As objects, link objects can be created and destroyed, and their non-end **Features** can change over time. However, the values of the end **Features** of a link object are fixed and cannot change over its lifetime.

AssociationStructure Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElement of this Relationship that owns the Relationship, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Disjoinings</code> , for which the <code>Type</code> is the <code>typeDisjoined Type</code> .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-73].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ResultExpressionMembership>
- **Summary:** ResultExpressionMembershipShape
- **Description:** A **ResultExpressionMembership** is a **FeatureMembership** that indicates that the **ownedResultExpression** provides the result values for the **Function** or **Expression** that owns it. The owning **Function** or **Expression** must contain a **BindingConnector** between the **result parameter** of the **ownedResultExpression** and the **result parameter** of the owning **Function** or **Expression**.

ResultExpressionMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:resultExpressionMembership_OwnedResultExpression	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression that provides the result for the owner of the ResultExpressionMembership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-74].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#MembershipImport`
- **Summary:** MembershipImportShape
- **Description:** A `MembershipImport` is an `Import` that imports its `importedMembership` into the `importOwningNamespace`. If `isRecursive = true` and the `memberElement` of the `importedMembership` is a `Namespace`, then the equivalent of a recursive `NamespaceImport` is also performed on that `Namespace`.

MembershipImport Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:import_ImportedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The effectively imported Element for this Import. For a MembershipImport , this is the memberElement of the importedMembership . For a NamespaceImport , it is the importedNamespace .
oslc_sysmlv2:import_ImportOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.
oslc_sysmlv2:import_IsImportAll	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to import memberships without regard to declared visibility.
oslc_sysmlv2:import_IsRecursive	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to recursively import Memberships from visible, owned sub-Namespace.
oslc_sysmlv2:import_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	The visibility level of the imported members from this Import relative to the importOwningNamespace .
oslc_sysmlv2:membershipImport_ImportedMembership	Exactly-one	false	Resource	Either	oslc_sysmlv2:Membership	The Membership to be imported.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-75].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#PortUsage`
- **Summary:** PortUsageShape
- **Description:** A **PortUsage** is a usage of a **PortDefinition**. A **PortUsage** itself as well as all its **nestedUsages** must be referential (non-composite).

PortUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:portUsage_PortDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortDefinition	The occurrenceDefinitions of this PortUsage , which must all be PortDefinitions ..
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-76].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ConstraintDefinition>
- **Summary:** ConstraintDefinitionShape
- **Description:** A **ConstraintDefinition** is an **OccurrenceDefinition** that is also a **Predicate** that defines a constraint that may be asserted to hold on a system or part of a system.

ConstraintDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Behavior.
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-77].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#SelectExpression>
- **Summary:** SelectExpressionShape
- **Description:** A **SelectExpression** is an **OperatorExpression** whose operator is "select", which resolves to the **Function ControlFunctions::select** from the Kernel Functions Library.

SelectExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:invocationExpression_Argument	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The value Expressions of the FeatureValues of the owned input parameters of the InvocationExpression .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:invocationExpression_Operand</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Expression</code>	operand.
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:operatorExpression_Operator</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	An operator symbol that names a corresponding Function from one of the standard packages from the Kernel Function Library .
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-78].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#PortConjugation`
- **Summary:** PortConjugationShape
- **Description:** A `PortConjugation` is a `ConjugationRelationship` between a `PortDefinition` and its corresponding `ConjugatedPortDefinition`. As a result of this `Relationship`, the `ConjugatedPortDefinition` inherits all the `features` of the original `PortDefinition`, but input `flows` of the original `PortDefinition` become outputs on the `ConjugatedPortDefinition` and output `flows` of the original `PortDefinition` become inputs on the `ConjugatedPortDefinition`.

PortConjugation Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefix	Property Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms	source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms	title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms	type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am	derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am	elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am	external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am	refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am	satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am	trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2	conjugation_ConjugatedType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the result of applying Conjugation to the originalType .
oslc_sysmlv2	conjugation_OriginalType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type to be conjugated.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:conjugation_OwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The <code>conjugatedType</code> of this <code>Conjugation</code> that is also its <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this <code>Element</code> .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the <code>Element</code> that is intended to be shorter or in some way more succinct than its primary <code>name</code> . It may act as a modeler-specified identifier for the <code>Element</code> , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:portConjugation_ConjugatedPortDefinition</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:ConjugatedPortDefinition</code>	The ConjugatedPortDefinition that is conjugate to the originalPortDefinition .
<code>oslc_sysmlv2:portConjugation_OriginalPortDefinition</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:PortDefinition</code>	The PortDefinition being conjugated.
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElement of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-79].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Succession>
- **Summary:** SuccessionShape
- **Description:** A **Succession** is a binary **Connector** that requires its **relatedFeatures** to happen separately in time.

Succession Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature, derived from the chainingFeatures of the ownedFeatureChainings of this Feature, in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature.
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:succession_EffectStep	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	Steps that represent occurrences that are side effects of the transitionStep occurring.
oslc_sysmlv2:succession_GuardExpression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	Expressions that must evaluate to true before the transitionStep can occur.
oslc_sysmlv2:succession_TransitionStep	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Step	A Step that is typed by the Behavior TransitionPerformances::TransitionPerformance (from the Kernel Semantic Library) that has this Succession as its transitionLink .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:succession_TriggerStep	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	Steps that map incoming events to the timing of occurrences of the transitionStep . The values of triggerStep subset the list of acceptable events to be received by a Behavior or the object that performs it.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-80].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#MetadataDefinition>
- **Summary:** MetadataDefinitionShape
- **Description:** A **MetadataDefinition** is an **ItemDefinition** that is also a **Metaclass**.

MetadataDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element . Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName () operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Disjoinings</code> , for which the <code>Type</code> is the <code>typeDisjoined Type</code> .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-81].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#IfActionUsage`
- **Summary:** `IfActionUsageShape`
- **Description:** An `IfActionUsage` is an `ActionUsage` that specifies that the `thenAction ActionUsage` should be performed if the result of the `ifArgument Expression` is true. It may also optionally specify an `elseAction ActionUsage` that is performed if the result of the `ifArgument` is false.

IfActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:ifActionUsage_ElseAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage that is to be performed if the result of the ifArgument is false. It is the (optional) third parameter of the IfActionUsage .
oslc_sysmlv2:ifActionUsage_IfArgument	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result determines whether the thenAction or (optionally) the elseAction is performed. It is the first parameter of the IfActionUsage ..
oslc_sysmlv2:ifActionUsage_ThenAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage that is to be performed if the result of the ifArgument is true. It is the second parameter of the IfActionUsage ..
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The <code>CaseUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The <code>ConcernUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The <code>ConnectorAsUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> . Note that this list includes <code>BindingConnectorAsUsages</code> and <code>SuccessionAsUsages</code> , even though these are <code>ConnectorAsUsages</code> but not <code>ConnectionUsages</code> .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The <code>ConstraintUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The code>EnumerationUsages that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The code>FlowConnectionUsages that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The <code>InterfaceUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedItem</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ItemUsage</code>	The <code>ItemUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedMetadata</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:MetadataUsage</code>	The <code>MetadataUsages</code> that are <code>nestedUsages</code> of this of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedOccurrence</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceUsage</code>	The <code>OccurrenceUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .
<code>oslc_sysmlv2:usage_NestedPart</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The <code>PartUsages</code> that are <code>nestedUsages</code> of this <code>Usage</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-82] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#TypeFeaturing>
- **Summary:** TypeFeaturingShape
- **Description:** A **TypeFeaturing** is a **Featuring Relationship** in which the **featureOfType** is the **source** and the **featuringType** is the **target**.

TypeFeaturing Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:typeFeaturing_FeatureOfType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType . It is the source of the TypeFeaturing .
oslc_sysmlv2:typeFeaturing_FeaturingType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType . It is the target of the TypeFeaturing .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:typeFeaturing_OwningFeatureOfType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	A featureOfType that is also the owningRelatedElement of this TypeFeaturing .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-83].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#EndFeatureMembership>
- **Summary:** EndFeatureMembershipShape
- **Description:** **EndFeatureMembership** is a **FeatureMembership** that requires its **memberFeature** be owned and have **isEnd = true**.

EndFeatureMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The <code>relatedElements</code> to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-84].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AttributeUsage>

- **Summary:** AttributeUsageShape
- **Description:** An **AttributeUsage** is a **Usage** whose type is a **DataType**. Nominally, if the type is an **AttributeDefinition**, an **AttributeUsage** is a usage of a **AttributeDefinition** to represent the value of some system quality or characteristic. However, other kinds of kernel **DataTypes** are also allowed, to permit use of **DataTypes** from the Kernel Model Libraries. An **AttributeUsage** itself as well as all its nested **features** must be referential (non-composite).

AttributeUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:attributeUsage_AttributeDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:DataType	The DataTypes that are the types of this AttributeUsage . Nominally, these are AttributeDefinitions , but other kinds of kernel DataTypes are also allowed, to permit use of DataTypes from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType.
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature.
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-85].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Predicate>
- **Summary:** PredicateShape
- **Description:** A **Predicate** is a **Function** whose **result parameter** has type **Boolean** and multiplicity **1..1**.

Predicate Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout .
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-86].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#MetadataAccessExpression`
- **Summary:** MetadataAccessExpressionShape
- **Description:** A `MetadataAccessExpression` is an `Expression` whose `result` is a sequence of instances of `Metaclasses` representing all the `MetadataFeature` annotations of the `referencedElement`. In addition, the sequence includes an instance of the reflective `Metaclass` corresponding to the MOF class of the `referencedElement`, with values for all the abstract syntax properties of the `referencedElement`.

MetadataAccessExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement.
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement, if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespaces</code> from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .
<code>oslc_sysmlv2:expression_Function</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Function</code>	The <code>Function</code> that types this <code>Expression</code> .
<code>oslc_sysmlv2:expression_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Expression</code> meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:metadataAccessExpression_ReferencedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element whose metadata is being accessed.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-87].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Interaction>
- **Summary:** InteractionShape
- **Description:** An **Interaction** is a **Behavior** that is also an **Association**, providing a context for multiple objects that have behaviors that impact one another.

Interaction Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types, but not including those of the remaining Types. For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction.
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true.
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-88].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#DecisionNode`
- **Summary:** `DecisionNodeShape`
- **Description:** A `DecisionNode` is a `ControlNode` that makes a selection from its outgoing `Successions`.

DecisionNode Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Copyright © OASIS Open 2024. All Rights Reserved.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Copyright © OASIS Open 2024. All Rights Reserved.

Standards Track Work Product

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_OwningUsage</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usage in which this Usage is nested (if any).
<code>oslc_sysmlv2:usage_Usage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages that are features of this Usage (not necessarily owned).
<code>oslc_sysmlv2:usage_Variant</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
<code>oslc_sysmlv2:usage_VariantMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:VariantMembership</code>	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-89].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#CaseDefinition`
- **Summary:** CaseDefinitionShape
- **Description:** A **CaseDefinition** is a **CalculationDefinition** for a process, often involving collecting evidence or data, relative to a subject, possibly involving the collaboration of one or more other actors, producing a result that meets an objective.

CaseDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:calculationDefinition_Calculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The actions of this CalculationDefinition that are CalculationUsages .
oslc_sysmlv2:caseDefinition_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseDefinition that represent actors involved in the case.
oslc_sysmlv2:caseDefinition_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseDefinition .
oslc_sysmlv2:caseDefinition_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseDefinition that represents its subject.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures.
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type.
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships, for which the Type is the owningType. Each such FeatureMembership identifies an ownedFeature of the Type.
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings, have the Type as their typeIntersected.
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations, for which the Type is the specific Type.
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-90].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#WhileLoopActionUsage`
- **Summary:** WhileLoopActionUsageShape
- **Description:** A `WhileLoopActionUsage` is a `LoopActionUsage` that specifies that the `bodyAction ActionUsage` should be performed repeatedly while the result of the `whileArgument Expression` is true or until the result of the `untilArgument Expression` (if provided) is true. The `whileArgument Expression` is evaluated before each (possible) performance of the `bodyAction`, and the `untilArgument Expression` is evaluated after each performance of the `bodyAction`.

WhileLoopActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:loopActionUsage_BodyAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage to be performed repeatedly by the LoopActionUsage . It is the second parameter of the LoopActionUsage .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc_sysmlv2:whileLoopActionUsage_UntilArgument	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result, if false, determines that the bodyAction should continue to be performed. It is the (optional) third owned parameter of the WhileLoopActionUsage .
oslc_sysmlv2:whileLoopActionUsage_WhileArgument	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result, if true, determines that the bodyAction should continue to be performed. It is the first owned parameter of the WhileLoopActionUsage .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-91] .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmLv2#ExhibitStateUsage>
- **Summary:** ExhibitStateUsageShape
- **Description:** An [ExhibitStateUsage](#) is a [StateUsage](#) that represents the exhibiting of a [StateUsage](#). Unless it is the [StateUsage](#) itself, the [StateUsage](#) to be exhibited is related to the [ExhibitStateUsage](#) by a [ReferenceSubsetting Relationship](#). An [ExhibitStateUsage](#) is also a [PerformActionUsage](#), with its [exhibitedState](#) as the [performedAction](#).

ExhibitStateUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:eventOccurrenceUsage_EventOccurrence	Exactly-one	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsage referenced as an event by this EventOccurrenceUsage. It is the referenceFeature of the ownedReferenceSubsetting for the EventOccurrenceUsage, if there is one, and, otherwise, the EventOccurrenceUsage itself.
oslc_sysmlv2:exhibitStateUsage_ExhibitedState	Exactly-one	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsage to be exhibited by the ExhibitStateUsage. It is the performedAction of the ExhibitStateUsage considered as a PerformActionUsage, which must be a StateUsage.

Copyright © OASIS Open 2024. All Rights Reserved.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:performActionUsage_PerformedAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage to be performed by this PerformedActionUsage . It is the eventOccurrence of the PerformActionUsage considered as an EventOccurrenceUsage , which must be an ActionUsage .
oslc_sysmlv2:stateUsage_DoAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateUsage to be performed while in the state defined by the StateDefinition . It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = do .
oslc_sysmlv2:stateUsage_EntryAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateUsage to be performed on entry to the state defined by the StateDefinition . It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = entry .
oslc_sysmlv2:stateUsage_ExitAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateUsage to be performed on exit to the state defined by the StateDefinition . It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = exit .
oslc_sysmlv2:stateUsage_IsParallel	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the nestedStates of this StateUsage are to all be performed in parallel. If true, none of the nestedActions (which include nestedStates) may have any incoming or outgoing Transitions . If false, only one nestedState may be performed at a time.
oslc_sysmlv2:stateUsage_StateDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this StateUsage . Nominally, these would be StateDefinitions , but kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The <code>Classifiers</code> that are the types of this <code>Usage</code> . Nominally, these are <code>Definitions</code> , but other kinds of Kernel <code>Classifiers</code> are also allowed, to permit use of <code>Classifiers</code> from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The <code>usages</code> of this <code>Usage</code> that are <code>directedFeatures</code> .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Usage</code> is a referential <code>Usage</code> , that is, it has <code>isComposite = false</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-92] .
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ViewDefinition`
- **Summary:** ViewDefinitionShape
- **Description:** A **ViewDefinition** is a **PartDefinition** that specifies how a view artifact is constructed to satisfy a **viewpoint**. It specifies a **viewConditions** to define the model content to be presented and a **viewRendering** to define how the model content is presented.

ViewDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:viewDefinition_SatisfiedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The composite ownedRequirements of this ViewDefinition that are ViewpointUsages for viewpoints satisfied by the ViewDefinition .
oslc_sysmlv2:viewDefinition_View	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The usages of this ViewDefinition that are ViewUsages .
oslc_sysmlv2:viewDefinition_ViewCondition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions related to this ViewDefinition by ElementFilterMemberships , which specify conditions on Elements to be rendered in a view.
oslc_sysmlv2:viewDefinition_ViewRendering	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsage to be used to render views defined by this ViewDefinition , which is the referencedRendering of the ViewRenderingMembership of the ViewDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-93].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#LifeClass>
- **Summary:** LifeClassShape
- **Description:** A **LifeClass** is a **Class** that specializes both the **Class Occurrences::Life** from the Kernel Semantic Library and a single **OccurrenceDefinition**, and has a multiplicity of 0..1. This constrains the **OccurrenceDefinition** being specialized to have at most one instance that is a complete **Life**.

LifeClass Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-94].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URLs.

- **Describes:** `http://open-services.net/ns/sysmlv2#RequirementConstraintMembership`
- **Summary:** RequirementConstraintMembershipShape
- **Description:** A `RequirementConstraintMembership` is a `FeatureMembership` for an assumed or required `ConstraintUsage` of a `RequirementDefinition` or `RequirementUsage`..

RequirementConstraintMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:requirementConstraintMembership_Kind	Exactly-one	false	unspecified	Either	oslc_sysmlv2:RequirementConstraintKind	Whether the RequirementConstraintMembership is for an assumed or required ConstraintUsage .
oslc_sysmlv2:requirementConstraintMembership_OwnedConstraint	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsage that is the ownedMemberFeature of this RequirementConstraintMembership .
oslc_sysmlv2:requirementConstraintMembership_ReferencedConstraint	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsage that is referenced through this RequirementConstraintMembership . It is the referencedFeature of the ownedReferenceSubsetting of the ownedConstraint , if there is one, and, otherwise, the ownedConstraint itself.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-95].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URLs.

- **Describes:** `http://open-services.net/ns/sysmlv2#OccurrenceUsage`
- **Summary:** OccurrenceUsageShape
- **Description:** An **OccurrenceUsage** is a **Usage** whose **types** are all **Classes**. Nominally, if a **type** is an **OccurrenceDefinition**, an **OccurrenceUsage** is a **Usage** of that **OccurrenceDefinition** within a system. However, other types of Kernel **Classes** are also allowed, to permit use of **Classes** from the Kernel Model Libraries.

OccurrenceUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The <code>Classifiers</code> that are the types of this <code>Usage</code> . Nominally, these are <code>Definitions</code> , but other kinds of Kernel <code>Classifiers</code> are also allowed, to permit use of <code>Classifiers</code> from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The <code>usages</code> of this <code>Usage</code> that are <code>directedFeatures</code> .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Usage</code> is a referential <code>Usage</code> , that is, it has <code>isComposite = false</code> .
<code>oslc_sysmlv2:usage_IsVariation</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Usage</code> is for a variation point or not. If true, then all the <code>memberships</code> of the <code>Usage</code> must be <code>VariantMemberships</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-96].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#RenderingDefinition>
- **Summary:** RenderingDefinitionShape
- **Description:** A **RenderingDefinition** is a **PartDefinition** that defines a specific rendering of the content of a model view (e.g., symbols, style, layout, etc.).

RenderingDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:renderingDefinition_Rendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The usages of a RenderingDefinition that are RenderingUsages .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-97].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#CalculationUsage`
- **Summary:** CalculationUsageShape
- **Description:** A **CalculationUsage** is an **ActionUsage** that is also an **Expression**, and, so, is typed by a **Function**. Nominally, if the **type** is a **CalculationDefinition**, a **CalculationUsage** is a **Usage** of that **CalculationDefinition** within a system. However, other kinds of kernel **Functions** are also allowed, to permit use of **Functions** from the Kernel Model Libraries.

CalculationUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:calculationUsage_CalculationDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that is the type of this CalculationUsage . Nominally, this would be a CalculationDefinition , but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries..
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression.
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at model level, that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature, derived from the chainingFeatures of the ownedFeatureChainings of this Feature, in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-98] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#LiteralBoolean>
- **Summary:** LiteralBooleanShape
- **Description:** **LiteralBoolean** is a **LiteralExpression** that provides a **Boolean** value as a result. Its **result parameter** must have type **Boolean**.

LiteralBoolean Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:literalBoolean_Value	Exactly-one	false	unspecified	Either	xsd:boolean	The Boolean value that is the result of evaluating this LiteralBoolean .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-99].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#LiteralRational`
- **Summary:** LiteralRationalShape
- **Description:** A `LiteralRational` is a `LiteralExpression` that provides a `Rational` value as a result. Its `result parameter` must have the type `Rational`.

LiteralRational Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:literalRational_Value	Exactly-one	false	unspecified	Either	xsd:float	The value whose rational approximation is the result of evaluating this LiteralRational .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-100].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Documentation>
- **Summary:** DocumentationShape
- **Description:** Documentation is a Comment that specifically documents a documentedElement, which must be its owner.

Documentation Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:annotatingElement_AnnotatedElement	One-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are annotated by this AnnotatingElement. If annotation is not empty, these are the annotatedElements of the annotations. If annotation is empty, then it is the owningNamespace of the AnnotatingElement.
oslc_sysmlv2:annotatingElement_Annotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The Annotations that relate this AnnotatingElement to its annotatedElements.
oslc_sysmlv2:annotatingElement_OwnedAnnotatingRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this AnnotatingElement that are Annotations, for which this AnnotatingElement is the annotatingElement.
oslc_sysmlv2:comment_Body	Exactly-one	false	unspecified	Either	xsd:string	The annotation text for the Comment.
oslc_sysmlv2:comment_Locale	Zero-or-one	false	unspecified	Either	xsd:string	Identification of the language of the body text and, optionally, the region and/or encoding. The format shall be a POSIX locale conformant to ISO/IEC 15897, with the format [language[_territory][.codeset][@modifier]].
oslc_sysmlv2:documentation_DocumentedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that is documented by this Documentation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-101].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ForkNode`
- **Summary:** ForkNodeShape
- **Description:** A **ForkNode** is a **ControlNode** that must be followed by successor **Actions** as given by all its outgoing **Successions**.

ForkNode Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage, if isVariation = true. If isVariation = false, then there must be no variants.
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-102].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Annotation>
- **Summary:** AnnotationShape
- **Description:** An Annotation is a Relationship between an AnnotatingElement and the Element that is annotated by that AnnotatingElement.

Annotation Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:annotation_AnnotatedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that is annotated by the annotatingElement of this Annotation .
oslc_sysmlv2:annotation_AnnotatingElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:AnnotatingElement	The AnnotatingElement that annotates the annotatedElement of this Annotation .
oslc_sysmlv2:annotation_OwningAnnotatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The annotatedElement of this Annotation , when it is also its owningRelatedElement .
oslc_sysmlv2:annotation_OwningAnnotatingElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:AnnotatingElement	The annotatingElement of this Annotation , when it is also its owningRelatedElement .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element . Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-103].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#FeatureMembership>
- **Summary:** FeatureMembershipShape
- **Description:** A **FeatureMembership** is an **OwningMembership** between a **Feature** in an **owningType** that is also a **Featuring Relationship** between the **Feature** and the **Type**, in which the **featuringType** is the **source** and the **featureOfType** is the **target**. A **FeatureMembership** is always owned by its **owningType**, which is the **featuringType** for the **FeatureMembership** considered as a **Featuring**.

FeatureMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-104].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Conjugation>

- **Summary:** ConjugationShape
- **Description:** *Conjugation* is a *Relationship* between two types in which the *conjugatedType* inherits all the *Features* of the *originalType*, but with all *input* and *output Features* reversed. That is, any *Features* with a *direction in* relative to the *originalType* are considered to have an effective *direction* of *out* relative to the *conjugatedType* and, similarly, *Features* with *direction out* in the *originalType* are considered to have an effective *direction* of *in* in the *conjugatedType*. *Features* with *direction inout*, or with no *direction*, in the *originalType*, are inherited without change.

Conjugation Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:conjugation_ConjugatedType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the result of applying Conjugation to the originalType .
oslc_sysmlv2:conjugation_OriginalType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type to be conjugated.
oslc_sysmlv2:conjugation_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The conjugatedType of this Conjugation that is also its owningRelatedElement .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement, if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this Element has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespaces</code> from a root <code>Namespace</code> to this Element.
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of Elements to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this Element.
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-105].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#SatisfyRequirementUsage`
- **Summary:** SatisfyRequirementUsageShape
- **Description:** A SatisfyRequirementUsage is an AssertConstraintUsage that asserts, by default, that a satisfied RequirementUsage is true for a specific satisfyingFeature, or, if isNegated = true, that the RequirementUsage is false. The satisfied RequirementUsage is related to the SatisfyRequirementUsage by a ReferenceSubsetting Relationship.

SatisfyRequirementUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:assertConstraintUsage_AssertedConstraint	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsage to be performed by the AssertConstraintUsage . It is the referenceFeature of the ownedReferenceSubsetting for the AssertConstraintUsage , if there is one, and, otherwise, the AssertConstraintUsage itself.
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .
oslc_sysmlv2:constraintUsage_ConstraintDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The (single) Predicate that is the type of this ConstraintUsage . Nominally, this will be a ConstraintDefinition , but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:invariant_IsNegated	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Invariant is asserted to be false rather than true.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Class</code>	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
<code>oslc_sysmlv2:occurrenceUsage_PortionKind</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:PortionKind</code>	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
<code>oslc_sysmlv2:requirementUsage_ActorParameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The parameters of this RequirementUsage that represent actors involved in the requirement.
<code>oslc_sysmlv2:requirementUsage_AssumedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The owned ConstraintUsages that represent assumptions of this RequirementUsage , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = assumption .
<code>oslc_sysmlv2:requirementUsage_FramedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages framed by this RequirementUsage , which are the ownedConcerns of all FramedConcernMemberships of the RequirementUsage .
<code>oslc_sysmlv2:requirementUsage_ReqId</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional modeler-specified identifier for this RequirementUsage (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementUsage .
<code>oslc_sysmlv2:requirementUsage_RequiredConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The owned ConstraintUsages that represent requirements of this RequirementUsage , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = requirement .
<code>oslc_sysmlv2:requirementUsage_RequirementDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:RequirementDefinition</code>	The RequirementDefinition that is the single definition of this RequirementUsage .
<code>oslc_sysmlv2:requirementUsage_StakeholderParameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The parameters of this RequirementUsage that represent stakeholders for the requirement.
<code>oslc_sysmlv2:requirementUsage_SubjectParameter</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The parameter of this RequirementUsage that represents its subject.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementUsage_Text	Zero-or-many	false	unspecified	Either	xsd:string	An optional textual statement of the requirement represented by this RequirementUsage , derived from the bodies of the documentation of the RequirementUsage..
oslc_sysmlv2:satisfyRequirementUsage_SatisfiedRequirement	Exactly-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage that is satisfied by the satisfyingSubject of this SatisfyRequirementUsage . It is the assertedConstraint of the SatisfyRequirementUsage considered as an AssertConstraintUsage , which must be a RequirementUsage .
oslc_sysmlv2:satisfyRequirementUsage_SatisfyingFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that represents the actual subject that is asserted to satisfy the satisfiedRequirement . The satisfyingFeature is bound to the subjectParameter of the SatisfyRequirementUsage .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The usages of this Usage that are directedFeatures .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is a referential Usage , that is, it has isComposite = false .
<code>oslc_sysmlv2:usage_IsVariation</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
<code>oslc_sysmlv2:usage_NestedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The ActionUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The AllocationUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The AnalysisCaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The code>AttributeUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The CalculationUsage that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The CaseUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The ConstraintUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The code>EnumerationUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The code>FlowConnectionUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The InterfaceUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedItem</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ItemUsage</code>	The ItemUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedMetadata</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:MetadataUsage</code>	The MetadataUsages that are nestedUsages of this of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedView</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ViewUsage</code>	The ViewUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedViewpoint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ViewpointUsage</code>	The ViewpointUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_OwningDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Definition</code>	The Definition that owns this Usage (if any).
<code>oslc_sysmlv2:usage_OwningUsage</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usage in which this Usage is nested (if any).
<code>oslc_sysmlv2:usage_Usage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages that are features of this Usage (not necessarily owned).
<code>oslc_sysmlv2:usage_Variant</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
<code>oslc_sysmlv2:usage_VariantMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:VariantMembership</code>	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-106].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AssertConstraintUsage>
- **Summary:** AssertConstraintUsageShape
- **Description:** An **AssertConstraintUsage** is a **ConstraintUsage** that is also an **Invariant** and, so, is asserted to be true (by default). Unless it is the **AssertConstraintUsage** itself, the asserted **ConstraintUsage** is related to the **AssertConstraintUsage** by a ReferenceSubsetting **Relationship**.

AssertConstraintUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:assertConstraintUsage_AssertedConstraint	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsage to be performed by the AssertConstraintUsage . It is the referenceFeature of the ownedReferenceSubsetting for the AssertConstraintUsage , if there is one, and, otherwise, the AssertConstraintUsage itself.
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .
oslc_sysmlv2:constraintUsage_ConstraintDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The (single) Predicate that is the type of this ConstraintUsage . Nominally, this will be a ConstraintDefinition , but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this Element has no <code>owningNamespace</code> or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of Elements to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:expression_Function</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Function</code>	The Function that types this Expression .
<code>oslc_sysmlv2:expression_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
<code>oslc_sysmlv2:expression_Result</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	.
<code>oslc_sysmlv2:feature_ChainingFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that are chained together to determine the values of this Feature , derived from the <code>chainingFeatures</code> of the <code>ownedFeatureChainings</code> of this Feature , in the same order. The values of a Feature with <code>chainingFeatures</code> are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in <code>chainingFeatures</code> , and so on, to values of the last Feature .
<code>oslc_sysmlv2:feature_Direction</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:FeatureDirectionKind</code>	Indicates how values of this Feature are determined or used (as specified for the <code>FeatureDirectionKind</code>).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions, for which the Feature is the redefiningFeature.
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature, if any, that is a ReferenceSubsetting, for which the Feature is the referencingFeature.
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings, for which the Feature is the subsettingFeature.
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType.
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature.
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.
oslc_sysmlv2:invariant_IsNegated	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Invariant is asserted to be false rather than true.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:occurrenceUsage_IndividualDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceDefinition</code>	The at most one occurrenceDefinition that has isIndividual = true .
<code>oslc_sysmlv2:occurrenceUsage_IsIndividual</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
<code>oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Class</code>	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
<code>oslc_sysmlv2:occurrenceUsage_PortionKind</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:PortionKind</code>	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-107].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#FeatureTyping>
- **Summary:** FeatureTypingShape
- **Description:** FeatureTyping is Specialization in which the specific Type is a Feature. This means the set of instances of the (specific) typedFeature is a subset of the set of instances of the (general) type. In the simplest case, the type is a Classifier, whereupon the typedFeature has values that are instances of the Classifier.

FeatureTyping Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureTyping_OwningFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	A typedFeature that is also the owningRelatedElement of this FeatureTyping .
oslc_sysmlv2:featureTyping_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is being applied by this FeatureTyping .
oslc_sysmlv2:featureTyping_TypedFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that has a type determined by this FeatureTyping .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:specialization_General	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a superset of all instances of the specific Type , which might be the same set.
oslc_sysmlv2:specialization_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the specific Type of this Specialization and owns it as its owningRelatedElement .
oslc_sysmlv2:specialization_Specific	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a subset of all instances of the general Type , which might be the same set.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-108].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#VerificationCaseDefinition>
- **Summary:** VerificationCaseDefinitionShape
- **Description:** A **VerificationCaseDefinition** is a **CaseDefinition** for the purpose of verification of the subject of the case against its requirements.

VerificationCaseDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:calculationDefinition_Calculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The actions of this CalculationDefinition that are CalculationUsages .
oslc_sysmlv2:caseDefinition_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseDefinition that represent actors involved in the case.
oslc_sysmlv2:caseDefinition_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseDefinition .
oslc_sysmlv2:caseDefinition_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseDefinition that represents its subject.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:verificationCaseDefinition_VerifiedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages verified by this VerificationCaseDefinition , which are the verifiedRequirements of all RequirementVerificationMemberships of the objectiveRequirement .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-109].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Structure>
- **Summary:** StructureShape
- **Description:** A **Structure** is a **Class** of objects in the modeled universe that are primarily structural in nature. While such an object is not itself behavioral, it may be involved in and acted on by **Behaviors**, and it may be the performer of some of them.

Structure Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-110].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ControlNode`
- **Summary:** ControlNodeShape
- **Description:** A **ControlNode** is an **ActionUsage** that does not have any inherent behavior but provides constraints on incoming and outgoing **Successions** that are used to control other **Actions**. A **ControlNode** must be a composite owned **usage** of an **ActionDefinition** or **ActionUsage**.

ControlNode Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-111].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Membership`
- **Summary:** MembershipShape
- **Description:** A **Membership** is a **Relationship** between a **Namespace** and an **Element** that indicates the **Element** is a **member** of (i.e., is contained in) the Namespace. Any **memberNames** specify how the **memberElement** is identified in the **Namespace** and the **visibility** specifies whether or not the **memberElement** is publicly visible from outside the **Namespace**.

Membership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-112].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#RenderingUsage>
- **Summary:** RenderingUsageShape
- **Description:** A **RenderingUsage** is the usage of a **RenderingDefinition** to specify the rendering of a specific model view to produce a physical view artifact.

RenderingUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:partUsage_PartDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartDefinition	The itemDefinitions of this PartUsage that are PartDefinitions.
oslc_sysmlv2:renderingUsage_RenderingDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RenderingDefinition	The RenderingDefinition that is the definition of this RenderingUsage .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-113] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AllocationUsage>
- **Summary:** AllocationUsageShape
- **Description:** An **AllocationUsage** is a usage of an **AllocationDefinition** asserting the allocation of the **source** feature to the **target** feature.

AllocationUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:allocationUsage_AllocationDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationDefinition	The AllocationDefinitions that are the types of this AllocationUsage.
oslc_sysmlv2:connectionUsage_ConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AssociationStructure	The AssociationStructures that are the types of this ConnectionUsage. Nominally, these are , but other kinds of Kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model Libraries.
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector.
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector, which redefine the endFeatures of the associations of the Connector. The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector.
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector.
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector. It is the first relatedFeature.
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector. This includes all the relatedFeatures other than the sourceFeature.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespace</code> s from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:partUsage_PartDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartDefinition	The itemDefinitions of this PartUsage that are PartDefinitions.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-114] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Featuring>

- **Summary:** FeaturingShape
- **Description:** Featuring is a Relationship between a Type and a Feature that is featured by that Type. It asserts that every instance in the domain of the feature must be classified by the type.

Featuring Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-115].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Definition>
- **Summary:** DefinitionShape
- **Description:** A **Definition** is a **Classifier** of **Usages**. The actual kinds of **Definition** that may appear in a model are given by the subclasses of **Definition** (possibly as extended with user-defined *SemanticMetadata*).

Definition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of Elements to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The Memberships in this Namespace that result from the ownedImports of this Namespace .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-116].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Usage`
- **Summary:** UsageShape
- **Description:** A **Usage** is a usage of a **Definition**. A **Usage** may only be an **ownedFeature** of a **Definition** or another **Usage**.

Usage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature, derived from the chainingFeatures of the ownedFeatureChainings of this Feature, in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature.
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature.
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature, such that any instance in the domain of the Feature must be classified by all of these Types, including at least all the featuringTypes of its typeFeaturings. If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType.
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature.
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixes	Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2	usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
	usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
	usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
	usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
	usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.
	usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
	usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
	usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
	usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2	usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
	usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-117].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#FlowConnectionUsage`
- **Summary:** FlowConnectionUsageShape
- **Description:** A FlowConnectionUsage is a ConnectionUsage that is also an ItemFlow.

FlowConnectionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:connectionUsage_ConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AssociationStructure	The AssociationStructures that are the types of this ConnectionUsage . Nominally, these are , but other kinds of Kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model Libraries.
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the <code>Element</code> that is intended to be shorter or in some way more succinct than its primary <code>name</code> . It may act as a modeler-specified identifier for the <code>Element</code> , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespaces</code> from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:flowConnectionUsage_FlowConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Interaction	The Interactions that are the types of this FlowConnectionUsage . Nominally, these are FlowConnectionDefinitions , but other kinds of Kernel Interactions are also allowed, to permit use of Interactions from the Kernel Model Libraries.
oslc_sysmlv2:itemFlow_Interaction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Interaction	The Interactions that type this ItemFlow . Interactions are both Associations and Behaviors , which can type Connectors and Steps , respectively.
oslc_sysmlv2:itemFlow_ItemFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ItemFeature	The ownedFeature of the ItemFlow that is an ItemFeature (if any).
oslc_sysmlv2:itemFlow_ItemFlowEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemFlowEnd	The connectorEnds of this ItemFlow that are ItemFlowEnds .
oslc_sysmlv2:itemFlow_ItemType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The type of values transferred, which is the type of the itemFeature of the ItemFlow .
oslc_sysmlv2:itemFlow_SourceOutputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that provides the items carried by the ItemFlow . It must be an owned output of the source of the ItemFlow .
oslc_sysmlv2:itemFlow_TargetInputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that receives the values carried by the ItemFlow . It must be an owned output of the target participant of the ItemFlow .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage . Nominally, these are ItemDefinitions , but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:partUsage_PartDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartDefinition	The itemDefinitions of this PartUsage that are PartDefinitions.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The <code>Behaviors</code> that type this <code>Step</code> .
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>parameters</code> of this <code>Step</code> , which are defined as its <code>directedFeatures</code> , whose values are passed into and/or out of a performance of the <code>Step</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-118].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#CollectExpression>
- **Summary:** CollectExpressionShape
- **Description:** A **CollectExpression** is an **OperatorExpression** whose **operator** is "**collect**", which resolves to the **Function ControlFunctions::collect** from the Kernel Functions Library.

CollectExpression Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of Elements to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:expression_Function</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Function</code>	The Function that types this Expression .
<code>oslc_sysmlv2:expression_IsModelLevelEvaluable</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
<code>oslc_sysmlv2:expression_Result</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	.
<code>oslc_sysmlv2:feature_ChainingFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
<code>oslc_sysmlv2:feature_Direction</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:FeatureDirectionKind</code>	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
<code>oslc_sysmlv2:feature_EndOwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
<code>oslc_sysmlv2:feature_FeaturingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:invocationExpression_Argument	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The value Expressions of the FeatureValues of the owned input parameters of the InvocationExpression .
oslc_sysmlv2:invocationExpression_Operand	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	operand.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:operatorExpression_Operator	Exactly-one	false	unspecified	Either	xsd:string	An operator symbol that names a corresponding Function from one of the standard packages from the Kernel Function Library .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout ..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-119].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#RequirementVerificationMembership>
- **Summary:** RequirementVerificationMembershipShape
- **Description:** A **RequirementVerificationMembership** is a **RequirementConstraintMembership** used in the objective of a **VerificationCase** to identify a **RequirementUsage** that is verified by the **VerificationCase**.

RequirementVerificationMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:requirementConstraintMembership_Kind	Exactly-one	false	unspecified	Either	oslc_sysmlv2:RequirementConstraintKind	Whether the RequirementConstraintMembership is for an assumed or required ConstraintUsage .
oslc_sysmlv2:requirementConstraintMembership_OwnedConstraint	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsage that is the ownedMemberFeature of this RequirementConstraintMembership .
oslc_sysmlv2:requirementConstraintMembership_ReferencedConstraint	Exactly-one	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsage that is referenced through this RequirementConstraintMembership . It is the referencedFeature of the ownedReferenceSubsetting of the ownedConstraint , if there is one, and, otherwise, the ownedConstraint itself.
oslc_sysmlv2:requirementVerificationMembership_OwnedRequirement	Exactly-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The owned RequirementUsage that acts as the ownedConstraint for this RequirementVerificationMembership . This will either be the verifiedRequirement , or it will subset the verifiedRequirement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementVerificationMembership_VerifiedRequirement	Exactly-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage that is identified as being verified. It is the referencedConstraint of the RequirementVerificationMembership considered as a RequirementConstraintMembership , which must be a RequirementUsage .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-120].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#StateUsage>
- **Summary:** StateUsageShape

- **Description:** A **StateUsage** is an **ActionUsage** that is nominally the **Usage** of a **StateDefinition**. However, other kinds of kernel **Behaviors** are also allowed as **types**, to permit use of **Behaviors** .

StateUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature, derived from the chainingFeatures of the ownedFeatureChainings of this Feature, in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature.
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:stateUsage_DoAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateUsage to be performed while in the state defined by the StateDefinition . It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = do .
oslc_sysmlv2:stateUsage_EntryAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateUsage to be performed on entry to the state defined by the StateDefinition . It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = entry .
oslc_sysmlv2:stateUsage_ExitAction	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage of this StateUsage to be performed on exit to the state defined by the StateDefinition . It is the owned ActionUsage related to the StateUsage by a StateSubactionMembership with kind = exit .
oslc_sysmlv2:stateUsage_IsParallel	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the nestedStates of this StateUsage are to all be performed in parallel. If true, none of the nestedActions (which include nestedStates) may have any incoming or outgoing Transitions . If false, only one nestedState may be performed at a time.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:stateUsage_StateDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this StateUsage . Nominally, these would be StateDefinitions , but kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage, if isVariation = true. If isVariation = false, then there must be no variants.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-121].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#BindingConnectorAsUsage>
- **Summary:** BindingConnectorAsUsageShape
- **Description:** A BindingConnectorAsUsage is both a BindingConnector and a ConnectorAsUsage.

BindingConnectorAsUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement, if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The TextualRepresentations that annotate this Element .
<code>oslc_sysmlv2:feature_ChainingFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
<code>oslc_sysmlv2:feature_Direction</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:FeatureDirectionKind</code>	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
<code>oslc_sysmlv2:feature_EndOwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElement of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage, if isVariation = true. If isVariation = false, then there must be no variants.
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-122].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#InterfaceDefinition>
- **Summary:** InterfaceDefinitionShape
- **Description:** An InterfaceDefinition is a ConnectionDefinition all of whose ends are PortUsages, defining an interface between elements that interact through such ports.

InterfaceDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:connectionDefinition_ConnectionEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that define the things related by the ConnectionDefinition .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:interfaceDefinition_InterfaceEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are the connectionEnds of this InterfaceDefinition. .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-123].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#MetadataUsage>
- **Summary:** MetadataUsageShape
- **Description:** A **MetadataUsage** is a **Usage** and a **MetadataFeature**, used to annotate other **Elements** in a system model with metadata. As a **MetadataFeature**, its type must be a **Metaclass**, which will nominally be a **MetadataDefinition**. However, any kernel **Metaclass** is also allowed, to permit use of **Metaclasses** from the Kernel Model Libraries.

MetadataUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:annotatingElement_AnnotatedElement	One-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are annotated by this AnnotatingElement . If annotation is not empty, these are the annotatedElements of the annotations . If annotation is empty, then it is the owningNamespace of the AnnotatingElement .
oslc_sysmlv2:annotatingElement_Annotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The Annotations that relate this AnnotatingElement to its annotatedElements .
oslc_sysmlv2:annotatingElement_OwnedAnnotatingRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this AnnotatingElement that are Annotations , for which this AnnotatingElement is the annotatingElement .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature, derived from the chainingFeatures of the ownedFeatureChainings of this Feature, in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature.
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:metadataFeature_Metaclass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Metaclass	The type of this MetadataFeature , which must be a Metaclass .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:metadataUsage_MetadataDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Metaclass	The MetadataDefinition that is the definition of this MetadataUsage .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The usages of this Usage that are directedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is a referential Usage , that is, it has <code>isComposite = false</code> .
<code>oslc_sysmlv2:usage_IsVariation</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
<code>oslc_sysmlv2:usage_NestedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The ActionUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The AllocationUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The AnalysisCaseUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The code>AttributeUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The CalculationUsage that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The CaseUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The ConstraintUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The code>EnumerationUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The code>FlowConnectionUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The InterfaceUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedItem</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ItemUsage</code>	The ItemUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedMetadata</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:MetadataUsage</code>	The MetadataUsages that are nestedUsages of this of this Usage .
<code>oslc_sysmlv2:usage_NestedOccurrence</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceUsage</code>	The OccurrenceUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedPart</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The PartUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedPort</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PortUsage</code>	The PortUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedReference</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ReferenceUsage</code>	The ReferenceUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedRendering</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:RenderingUsage</code>	The RenderingUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedRequirement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:RequirementUsage</code>	The RequirementUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-124].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ItemFlow>
- **Summary:** ItemFlowShape
- **Description:** An ItemFlow is a Step that represents the transfer of objects or data values from one Feature to another. ItemFlows can take non-zero time to complete.

ItemFlow Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:itemFlow_Interaction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Interaction	The Interactions that type this ItemFlow . Interactions are both Associations and Behaviors , which can type Connectors and Steps , respectively.
oslc_sysmlv2:itemFlow_ItemFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ItemFeature	The ownedFeature of the ItemFlow that is an ItemFeature (if any).
oslc_sysmlv2:itemFlow_ItemFlowEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemFlowEnd	The connectorEnds of this ItemFlow that are ItemFlowEnds .
oslc_sysmlv2:itemFlow_ItemType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The type of values transferred, which is the type of the itemFeature of the ItemFlow .
oslc_sysmlv2:itemFlow_SourceOutputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that provides the items carried by the ItemFlow . It must be an owned output of the source of the ItemFlow .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:itemFlow_TargetInputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that receives the values carried by the ItemFlow . It must be an owned output of the target participant of the ItemFlow .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Disjoinings</code> , for which the <code>Type</code> is the <code>typeDisjoined</code> <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific</code> <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-125] .
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#FeatureChaining`
- **Summary:** FeatureChainingShape
- **Description:** FeatureChaining is a Relationship that makes its target Feature one of the chainingFeatures of its owning Feature.

FeatureChaining Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureChaining_ChainingFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature whose values partly determine values of featureChained , as described in Feature::chainingFeature .
oslc_sysmlv2:featureChaining_FeatureChained	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature whose values are partly determined by values of the chainingFeature , as described in Feature::chainingFeature .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-126].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** http://open-services.net/ns/sysmlv2#Differencing
- **Summary:** DifferencingShape
- **Description:** Differencing is a Relationship that makes its differencingType one of the differencingTypes of its typeDifferenced.

Differencing Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:differencing_DifferencingType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type that partly determines interpretations of typeDifferenced, as described in Type::differencingType.
oslc_sysmlv2:differencing_TypeDifferenced	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type with interpretations partly determined by differencingType, as described in Type::differencingType.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the <code>ownedRelationships</code> of this Element. This property may be true, even if there are not actually any <code>ownedRelationships</code> with <code>isImplied = true</code> , meaning that no such Relationships are actually implied for this Element. However, if it is false, then <code>ownedRelationships</code> may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the <code>declaredName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>name</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The <code>ownedRelationships</code> of this <code>Element</code> that are <code>Annotations</code> , for which this <code>Element</code> is the <code>annotatedElement</code> .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the <code>ownedRelatedElements</code> of the <code>ownedRelationships</code> of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-127].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#SuccessionItemFlow`
- **Summary:** SuccessionItemFlowShape
- **Description:** A `SuccessionItemFlow` is an `ItemFlow` that also provides temporal ordering. It classifies *Transfers* that cannot start until the source *Occurrence* has completed and that must complete before the target *Occurrence* can start.

SuccessionItemFlow Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:itemFlow_Interaction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Interaction	The Interactions that type this ItemFlow . Interactions are both Associations and Behaviors , which can type Connectors and Steps , respectively.
oslc_sysmlv2:itemFlow_ItemFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ItemFeature	The ownedFeature of the ItemFlow that is an ItemFeature (if any).
oslc_sysmlv2:itemFlow_ItemFlowEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemFlowEnd	The connectorEnds of this ItemFlow that are ItemFlowEnds .
oslc_sysmlv2:itemFlow_ItemType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The type of values transferred, which is the type of the itemFeature of the ItemFlow .
oslc_sysmlv2:itemFlow_SourceOutputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that provides the items carried by the ItemFlow . It must be an owned output of the source of the ItemFlow .
oslc_sysmlv2:itemFlow_TargetInputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that receives the values carried by the ItemFlow . It must be an owned output of the target participant of the ItemFlow .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
<code>oslc_sysmlv2:succession_EffectStep</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Step</code>	Steps that represent occurrences that are side effects of the transitionStep occurring.
<code>oslc_sysmlv2:succession_GuardExpression</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Expression</code>	Expressions that must evaluate to true before the transitionStep can occur.
<code>oslc_sysmlv2:succession_TransitionStep</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Step</code>	A Step that is typed by the Behavior TransitionPerformances::TransitionPerformance (from the Kernel Semantic Library) that has this Succession as its transitionLink .
<code>oslc_sysmlv2:succession_TriggerStep</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Step</code>	Steps that map incoming events to the timing of occurrences of the transitionStep . The values of triggerStep subset the list of acceptable events to be received by a Behavior or the object that performs it.
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-128].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#MultiplicityRange`
- **Summary:** MultiplicityRangeShape
- **Description:** A **MultiplicityRange** is a **Multiplicity** whose value is defined to be the (inclusive) range of natural numbers given by the result of a **lowerBound Expression** and the result of an **upperBound Expression**. The result of these **Expressions** shall be of type **Natural**. If the result of the **upperBound Expression** is the unbounded value *****, then the specified range includes all natural numbers greater than or equal to the **lowerBound** value. If no **lowerBound Expression**, then the default is that the lower bound has the same value as the upper bound, except if the **upperBound** evaluates to *****, in which case the default for the lower bound is 0.

MultiplicityRange Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>jazz_am:trace</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
<code>oslc_sysmlv2:element_AliasIds</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:multiplicityRange_Bound	One-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The owned Expressions of the MultiplicityRange whose results provide its bounds. These must be the only ownedMembers of the MultiplicityRange .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:multiplicityRange_LowerBound	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result provides the lower bound of the MultiplicityRange . If no lowerBound Expression is given, then the lower bound shall have the same value as the upper bound, unless the upper bound is unbounded (*), in which case the lower bound shall be 0.
oslc_sysmlv2:multiplicityRange_UpperBound	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result is the upper bound of the MultiplicityRange .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-129].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#LiteralInfinity`
- **Summary:** LiteralInfinityShape
- **Description:** A **LiteralInfinity** is a **LiteralExpression** that provides the positive infinity value (*). It's **result** must have the type **Positive**.

LiteralInfinity Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:feature_OwnedTypeFeaturing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TypeFeaturing</code>	The <code>ownedRelationships</code> of this <code>Feature</code> that are <code>TypeFeaturings</code> and for which the <code>Feature</code> is the <code>featureOfType</code> .
<code>oslc_sysmlv2:feature_OwnedTyping</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureTyping</code>	The <code>ownedSpecializations</code> of this <code>Feature</code> that are <code>FeatureTypings</code> , for which the <code>Feature</code> is the <code>typedFeature</code> .
<code>oslc_sysmlv2:feature_OwningFeatureMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>FeatureMembership</code> that owns this <code>Feature</code> as an <code>ownedMemberFeature</code> , determining its <code>owningType</code> .
<code>oslc_sysmlv2:feature_OwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The <code>Type</code> that is the <code>owningType</code> of the <code>owningFeatureMembership</code> of this <code>Feature</code> .
<code>oslc_sysmlv2:feature_Type</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	<code>Types</code> that restrict the values of this <code>Feature</code> , such that the values must be instances of all the <code>types</code> . The types of a <code>Feature</code> are derived from its <code>typings</code> and the <code>types</code> of its <code>subsettings</code> . If the <code>Feature</code> is chained, then the <code>types</code> of the last <code>Feature</code> in the chain are also <code>types</code> of the chained <code>Feature</code> .
<code>oslc_sysmlv2:namespace_ImportedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The <code>Memberships</code> in this <code>Namespace</code> that result from the <code>ownedImports</code> of this <code>Namespace</code> .
<code>oslc_sysmlv2:namespace_Member</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The set of all member <code>Elements</code> of this <code>Namespace</code> , which are the <code>memberElements</code> of all <code>memberships</code> of the <code>Namespace</code> .
<code>oslc_sysmlv2:namespace_Membership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All <code>Memberships</code> in this <code>Namespace</code> , including (at least) the union of <code>ownedMemberships</code> and <code>importedMemberships</code> .
<code>oslc_sysmlv2:namespace_OwnedImport</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Import</code>	The <code>ownedRelationships</code> of this <code>Namespace</code> that are <code>Imports</code> , for which the <code>Namespace</code> is the <code>importOwningNamespace</code> .
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned <code>members</code> of this <code>Namespace</code> , which are the <code>ownedMemberElements</code> of the <code>ownedMemberships</code> of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The <code>ownedRelationships</code> of this <code>Namespace</code> that are <code>Memberships</code> , for which the <code>Namespace</code> is the <code>membershipOwningNamespace</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .
<code>oslc_sysmlv2:step_Parameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-130].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#InterfaceUsage>
- **Summary:** InterfaceUsageShape
- **Description:** An **InterfaceUsage** is a Usage of an **InterfaceDefinition** to represent an interface connecting parts of a system through specific ports.

InterfaceUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connectionUsage_ConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AssociationStructure	The AssociationStructures that are the types of this ConnectionUsage . Nominally, these are , but other kinds of Kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:interfaceUsage_InterfaceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceDefinition	The InterfaceDefinitions that type this InterfaceUsage .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:namespace_OwnedMember</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
<code>oslc_sysmlv2:namespace_OwnedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
<code>oslc_sysmlv2:occurrenceUsage_IndividualDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceDefinition</code>	The at most one occurrenceDefinition that has isIndividual = true .
<code>oslc_sysmlv2:occurrenceUsage_IsIndividual</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
<code>oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Class</code>	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
<code>oslc_sysmlv2:occurrenceUsage_PortionKind</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:PortionKind</code>	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
<code>oslc_sysmlv2:partUsage_PartDefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartDefinition</code>	The itemDefinitions of this PartUsage that are PartDefinitions.
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElement of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements from which this Relationship is considered to be directed..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-131].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#PerformActionUsage>
- **Summary:** PerformActionUsageShape
- **Description:** A **PerformActionUsage** is an **ActionUsage** that represents the performance of an **ActionUsage**. Unless it is the **PerformActionUsage** itself, the **ActionUsage** to be performed is related to the **PerformActionUsage** by a **ReferenceSubsetting** relationship. A **PerformActionUsage** is also an **EventOccurrenceUsage**, with its **performedAction** as the **eventOccurrence**.

PerformActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:eventOccurrenceUsage_EventOccurrence	Exactly-one	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsage referenced as an event by this EventOccurrenceUsage . It is the referenceFeature of the ownedReferenceSubsetting for the EventOccurrenceUsage , if there is one, and, otherwise, the EventOccurrenceUsage itself.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings, for which the Feature is the typedFeature.
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature, determining its owningType.
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature.
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature, such that the values must be instances of all the types. The types of a Feature are derived from its typings and the types of its subsettings. If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true.
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:performActionUsage_PerformedAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage to be performed by this PerformedActionUsage . It is the eventOccurrence of the PerformActionUsage considered as an EventOccurrenceUsage , which must be an ActionUsage .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes, which are the Types derived from the intersectingType of the ownedIntersectings of this Type. For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types.
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator.
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage, if isVariation = true. If isVariation = false, then there must be no variants.
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-132].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#TransitionUsage>
- **Summary:** TransitionUsageShape
- **Description:** A TransitionUsage is an ActionUsage representing a triggered transition between ActionUsages or StateUsages. When triggered by a triggerAction, when its guardExpression is true, the TransitionUsage asserts that its source is exited, then its effectAction (if any) is performed, and then its target is entered.

TransitionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:transitionUsage_EffectAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that define the effects of this TransitionUsage , which are the ownedFeatures of the TransitionUsage related to it by TransitionFeatureMemberships with kind = effect , which must all be ActionUsages .
oslc_sysmlv2:transitionUsage_GuardExpression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that define the guards of this TransitionUsage , which are the ownedFeatures of the TransitionUsage related to it by TransitionFeatureMemberships with kind = guard , which must all be Expressions .
oslc_sysmlv2:transitionUsage_Source	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The source ActionUsage of this TransitionUsage , which becomes the source of the succession for the TransitionUsage .
oslc_sysmlv2:transitionUsage_Succession	Exactly-one	false	Resource	Either	oslc_sysmlv2:Succession	The Succession that is the ownedFeature of this TransitionUsage , which, if the TransitionUsage is triggered, asserts the temporal ordering of the source and target .
oslc_sysmlv2:transitionUsage_Target	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The target ActionUsage of this TransitionUsage , which is the targetFeature of the succession for the TransitionUsage ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:transitionUsage_TriggerAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AcceptActionUsage	The AcceptActionUsages that define the triggers of this TransitionUsage , which are the ownedFeatures of the TransitionUsage related to it by TransitionFeatureMemberships with kind = trigger , which must all be AcceptActionUsages .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The <code>Classifiers</code> that are the types of this <code>Usage</code> . Nominally, these are <code>Definitions</code> , but other kinds of Kernel <code>Classifiers</code> are also allowed, to permit use of <code>Classifiers</code> from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The <code>usages</code> of this <code>Usage</code> that are <code>directedFeatures</code> .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Usage</code> is a referential <code>Usage</code> , that is, it has <code>isComposite = false</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-133].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#VerificationCaseUsage`
- **Summary:** VerificationCaseUsageShape
- **Description:** A `VerificationCaseUsage` is a Usage of a `VerificationCaseDefinition`.

VerificationCaseUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:calculationUsage_CalculationDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that is the type of this CalculationUsage. Nominally, this would be a CalculationDefinition, but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries..
oslc_sysmlv2:caseUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseUsage that represent actors involved in the case.
oslc_sysmlv2:caseUsage_CaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:CaseDefinition	The CaseDefinition that is the type of this CaseUsage.
oslc_sysmlv2:caseUsage_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseUsage.
oslc_sysmlv2:caseUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseUsage that represents its subject.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The usages of this Usage that are directedFeatures .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is a referential Usage , that is, it has isComposite = false .
<code>oslc_sysmlv2:usage_IsVariation</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
<code>oslc_sysmlv2:usage_NestedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The ActionUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The AllocationUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The AnalysisCaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The code>AttributeUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The CalculationUsage that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The CaseUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The ConstraintUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The code>EnumerationUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedFlow</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FlowConnectionUsage</code>	The code>FlowConnectionUsages that are nestedUsages of this Usage.
<code>oslc_sysmlv2:usage_NestedInterface</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:InterfaceUsage</code>	The InterfaceUsages that are nestedUsages of this Usage.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_NestedItem</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ItemUsage</code>	The ItemUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedMetadata</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:MetadataUsage</code>	The MetadataUsages that are nestedUsages of this of this Usage .
<code>oslc_sysmlv2:usage_NestedOccurrence</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:OccurrenceUsage</code>	The OccurrenceUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedPart</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The PartUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedPort</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PortUsage</code>	The PortUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedReference</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ReferenceUsage</code>	The ReferenceUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedRendering</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:RenderingUsage</code>	The RenderingUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedRequirement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:RequirementUsage</code>	The RequirementUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedState</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:StateUsage</code>	The StateUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedTransition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TransitionUsage</code>	The TransitionUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The Usages that are ownedFeatures of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc_sysmlv2:verificationCaseUsage_VerificationCaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:VerificationCaseDefinition	The VerificationCase that is the definition of this VerificationCaseUsage .
oslc_sysmlv2:verificationCaseUsage_VerifiedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages verified by this VerificationCaseUsage , which are the verifiedRequirements of all RequirementVerificationMemberships of the objectiveRequirement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-134].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#PortDefinition>
- **Summary:** PortDefinitionShape
- **Description:** A **PortDefinition** defines a point at which external entities can connect to and interact with a system or part of a system. Any **ownedUsages** of a **PortDefinition**, other than **PortUsages**, must not be composite.

PortDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:portDefinition_ConjugatedPortDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ConjugatedPortDefinition	The that is conjugate to this PortDefinition ..
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout ..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-135].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#LiteralInteger`
- **Summary:** LiteralIntegerShape
- **Description:** A **LiteralInteger** is a **LiteralExpression** that provides an **Integer** value as a result. Its **result parameter** must have the type **Integer**.

LiteralInteger Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:literalInteger_Value	Exactly-one	false	unspecified	Either	xsd:integer	The Integer value that is the result of evaluating this LiteralInteger .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-136].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ViewpointDefinition>
- **Summary:** ViewpointDefinitionShape
- **Description:** A **ViewpointDefinition** is a **RequirementDefinition** that specifies one or more stakeholder concerns that are to be satisfied by creating a view of a model.

ViewpointDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Behavior.
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:requirementDefinition_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementDefinition that represent actors involved in the requirement.
oslc_sysmlv2:requirementDefinition_AssumedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent assumptions of this RequirementDefinition , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = assumption .
oslc_sysmlv2:requirementDefinition_FramedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages framed by this RequirementDefinition , which are the ownedConcerns of all FramedConcernMemberships of the RequirementDefinition .
oslc_sysmlv2:requirementDefinition_ReqId	Zero-or-one	false	unspecified	Either	xsd:string	An optional modeler-specified identifier for this RequirementDefinition (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementDefinition_RequiredConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent requirements of this RequirementDefinition , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = requirement .
oslc_sysmlv2:requirementDefinition_StakeholderParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementDefinition that represent stakeholders for th requirement.
oslc_sysmlv2:requirementDefinition_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this RequirementDefinition that represents its subject.
oslc_sysmlv2:requirementDefinition_Text	Zero-or-many	false	unspecified	Either	xsd:string	An optional textual statement of the requirement represented by this RequirementDefinition , derived from the bodies of the documentation of the RequirementDefinition .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:viewpointDefinition_ViewpointStakeholder</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The PartUsages that identify the stakeholders with concerns framed by this ViewpointDefinition , which are the owned and inherited stakeholderParameters of the framedConcerns of this ViewpointDefinition .
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-137].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#LoopActionUsage>

- **Summary:** LoopActionUsageShape
- **Description:** A **LoopActionUsage** is an **ActionUsage** that specifies that its **bodyAction** should be performed repeatedly. Its subclasses **WhileLoopActionUsage** and **ForLoopActionUsage** provide different ways to determine how many times the **bodyAction** should be performed.

LoopActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:loopActionUsage_BodyAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage to be performed repeatedly by the LoopActionUsage . It is the second parameter of the LoopActionUsage .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-138].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#MembershipExpose`
- **Summary:** MembershipExposeShape
- **Description:** A `MembershipExpose` is an `Expose` that exposes a specific `importedMembership` and, if `isRecursive = true`, additional `Memberships` recursively..

MembershipExpose Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:import_ImportedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The effectively imported Element for this Import. For a MembershipImport , this is the memberElement of the importedMembership . For a NamespaceImport , it is the importedNamespace .
oslc_sysmlv2:import_ImportOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.
oslc_sysmlv2:import_IsImportAll	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to import memberships without regard to declared visibility.
oslc_sysmlv2:import_IsRecursive	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to recursively import Memberships from visible, owned sub-Namespace.
oslc_sysmlv2:import_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	The visibility level of the imported members from this Import relative to the importOwningNamespace .
oslc_sysmlv2:membershipImport_ImportedMembership	Exactly-one	false	Resource	Either	oslc_sysmlv2:Membership	The Membership to be imported.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-139].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ActorMembership>
- **Summary:** ActorMembershipShape
- **Description:** An **ActorMembership** is a **ParameterMembership** that identifies a **PartUsage** as an *actor* **parameter**, which specifies a role played by an external entity in interaction with the **owningType** of the **ActorMembership**.

ActorMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actorMembership_OwnedActorParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsage specifying the actor.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:parameterMembership_OwnedMemberParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is identified as a parameter by this ParameterMembership .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-140].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ViewRenderingMembership>
- **Summary:** ViewRenderingMembershipShape
- **Description:** A **ViewRenderingMembership** is a FeatureMembership that identifies the **viewRendering** of a **ViewDefinition** or **ViewUsage**..

ViewRenderingMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:viewRenderingMembership_OwnedRendering</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:RenderingUsage</code>	The owned <code>RenderingUsage</code> that is either itself the <code>referencedRendering</code> or subsets the <code>referencedRendering</code> .
<code>oslc_sysmlv2:viewRenderingMembership_ReferencedRendering</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:RenderingUsage</code>	The <code>RenderingUsage</code> that is referenced through this <code>ViewRenderingMembership</code> . It is the <code>referencedFeature</code> of the <code>ownedReferenceSubsetting</code> for the <code>ownedRendering</code> , if there is one, and, otherwise, the <code>ownedRendering</code> itself.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-141].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Import`
- **Summary:** ImportShape
- **Description:** An **Import** is an **Relationship** between its **importOwningNamespace** and either a **Membership** (for a **MembershipImport**) or another **Namespace** (for a **NamespaceImport**), which determines a set of **Memberships** that become **importedMemberships** of the **importOwningNamespace**. If **isImportAll** = **false** (the default), then only public **Memberships** are considered "visible". If **isImportAll** = **true**, then all **Memberships** are considered "visible", regardless of their declared **visibility**. If **isRecursive** = **true**, then visible **Memberships** are also recursively imported from owned sub-**Namespaces**.

Import Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:import_ImportedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The effectively imported Element for this Import. For a MembershipImport , this is the memberElement of the importedMembership . For a NamespaceImport , it is the importedNamespace .
oslc_sysmlv2:import_ImportOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.
oslc_sysmlv2:import_IsImportAll	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to import memberships without regard to declared visibility.
oslc_sysmlv2:import_IsRecursive	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to recursively import Memberships from visible, owned sub-Namespaces.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:import_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	The visibility level of the imported members from this Import relative to the importOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-142].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Behavior>
- **Summary:** BehaviorShape
- **Description:** A **Behavior** coordinates occurrences of other **Behaviors**, as well as changes in objects. **Behaviors** can be decomposed into **Steps** and be characterized by **parameters**.

Behavior Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
<code>dcterms:type</code>	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
<code>jazz_am:derives</code>	Zero-or-many	false	Resource	Reference	<code>oslc:Any</code>	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Behavior.
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-143].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Expose>
- **Summary:** ExposeShape
- **Description:** An **Expose** is an **Import** of **Memberships** into a **ViewUsage** that provide the **Elements** to be included in a view. Visibility is always ignored for an **Expose** (i.e., **isImportAll** = **true**).

Expose Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:import_ImportedElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The effectively imported Element for this Import. For a MembershipImport , this is the memberElement of the importedMembership . For a NamespaceImport , it is the importedNamespace .
oslc_sysmlv2:import_ImportOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace into which Memberships are imported by this Import, which must be the owningRelatedElement of the Import.
oslc_sysmlv2:import_IsImportAll	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to import memberships without regard to declared visibility.
oslc_sysmlv2:import_IsRecursive	Exactly-one	false	unspecified	Either	xsd:boolean	Whether to recursively import Memberships from visible, owned sub-Namespaces.
oslc_sysmlv2:import_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	The visibility level of the imported members from this Import relative to the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-144].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#RequirementUsage`

- **Summary:** RequirementUsageShape
- **Description:** A RequirementUsage is a Usage of a RequirementDefinition.

RequirementUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .
oslc_sysmlv2:constraintUsage_ConstraintDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The (single) Predicate that is the type of this ConstraintUsage . Nominally, this will be a ConstraintDefinition , but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:requirementUsage_ActorParameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The parameters of this RequirementUsage that represent actors involved in the requirement.
<code>oslc_sysmlv2:requirementUsage_AssumedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The owned ConstraintUsages that represent assumptions of this RequirementUsage , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = assumption .
<code>oslc_sysmlv2:requirementUsage_FramedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages framed by this RequirementUsage , which are the ownedConcerns of all FramedConcernMemberships of the RequirementUsage .
<code>oslc_sysmlv2:requirementUsage_ReqId</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional modeler-specified identifier for this RequirementUsage (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementUsage .
<code>oslc_sysmlv2:requirementUsage_RequiredConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The owned ConstraintUsages that represent requirements of this RequirementUsage , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = requirement .
<code>oslc_sysmlv2:requirementUsage_RequirementDefinition</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:RequirementDefinition</code>	The RequirementDefinition that is the single definition of this RequirementUsage .
<code>oslc_sysmlv2:requirementUsage_StakeholderParameter</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartUsage</code>	The parameters of this RequirementUsage that represent stakeholders for the requirement.
<code>oslc_sysmlv2:requirementUsage_SubjectParameter</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The parameter of this RequirementUsage that represents its subject.
<code>oslc_sysmlv2:requirementUsage_Text</code>	Zero-or-many	false	unspecified	Either	<code>xsd:string</code>	An optional textual statement of the requirement represented by this RequirementUsage , derived from the bodies of the documentation of the RequirementUsage..
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .

Copyright © OASIS Open 2024. All Rights Reserved.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage, if isVariation = true. If isVariation = false, then there must be no variants.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-145] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#CaseUsage>
- **Summary:** CaseUsageShape
- **Description:** A **CaseUsage** is a **Usage** of a **CaseDefinition**.

CaseUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:calculationUsage_CalculationDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that is the type of this CalculationUsage. Nominally, this would be a CalculationDefinition, but a kernel Function is also allowed, to permit use of Functions from the Kernel Model Libraries..
oslc_sysmlv2:caseUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseUsage that represent actors involved in the case.
oslc_sysmlv2:caseUsage_CaseDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:CaseDefinition	The CaseDefinition that is the type of this CaseUsage.
oslc_sysmlv2:caseUsage_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseUsage.
oslc_sysmlv2:caseUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseUsage that represents its subject.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression.
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at model level, that is, using metadata within the model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:feature_IsPortion</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
<code>oslc_sysmlv2:feature_IsReadOnly</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature can change over the lifetime of an instance of the domain.
<code>oslc_sysmlv2:feature_IsUnique</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether or not values for this Feature must have no duplicates or not.
<code>oslc_sysmlv2:feature_OwnedFeatureChaining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureChaining</code>	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
<code>oslc_sysmlv2:feature_OwnedFeatureInverting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureInverting</code>	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
<code>oslc_sysmlv2:feature_OwnedRedefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Redefinition</code>	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
<code>oslc_sysmlv2:feature_OwnedReferenceSubsetting</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:ReferenceSubsetting</code>	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
<code>oslc_sysmlv2:feature_OwnedSubsetting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Subsetting</code>	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
<code>oslc_sysmlv2:feature_OwnedTypeFeaturing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TypeFeaturing</code>	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
<code>oslc_sysmlv2:feature_OwnedTyping</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureTyping</code>	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
<code>oslc_sysmlv2:feature_OwningFeatureMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
<code>oslc_sysmlv2:feature_OwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step.
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Step.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types, but not including those of the remaining Types. For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction.
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true.
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-146] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#OwningMembership>
- **Summary:** OwningMembershipShape
- **Description:** An **OwningMembership** is a **Membership** that owns its **memberElement** as a **ownedRelatedElement**. The **ownedMemberElement** becomes an **ownedMember** of the **membershipOwningNamespace**.

OwningMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement.
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-147].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URLs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Function>
- **Summary:** FunctionShape
- **Description:** A **Function** is a **Behavior** that has an **out parameter** that is identified as its **result**. A **Function** represents the performance of a calculation that produces the values of its **result parameter**. This calculation may be decomposed into **Expressions** that are **steps** of the **Function**.

Function Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type.
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type, which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does not include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships.
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation. These are included in the derived union for the memberships of the Type.
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes, which are the Types derived from the intersectingType of the ownedIntersectings of this Type. For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types.
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator.
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-148].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Redefinition`
- **Summary:** RedefinitionShape
- **Description:** **Redefinition** is a kind of **Subsetting** that requires the **redefinedFeature** and the **redefiningFeature** to have the same values (on each instance of the domain of the **redefiningFeature**). This means any restrictions on the **redefiningFeature**, such as **type** or **multiplicity**, also apply to the **redefinedFeature** (on each instance of the domain of the **redefiningFeature**), and vice versa. The **redefinedFeature** might have values for instances of the domain of the **redefiningFeature**, but only as instances of the domain of the **redefinedFeature** that happen to also be instances of the domain of the **redefiningFeature**. This is supported by the constraints inherited from **Subsetting** on the domains of the **redefiningFeature** and **redefinedFeature**. However, these constraints are narrowed for **Redefinition** to require the **owningTypes** of the **redefiningFeature** and **redefinedFeature** to be different and the **redefinedFeature** to not be inherited into the **owningNamespace** of the **redefiningFeature**. This enables the **redefiningFeature** to have the same name as the **redefinedFeature**, if desired.

Redefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:redefinition_RedefinedFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is redefined by the redefiningFeature of this Redefinition .
oslc_sysmlv2:redefinition_RedefiningFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is redefining the redefinedFeature of this Redefinition .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:specialization_General	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a superset of all instances of the specific Type , which might be the same set.
oslc_sysmlv2:specialization_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the specific Type of this Specialization and owns it as its owningRelatedElement .
oslc_sysmlv2:specialization_Specific	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a subset of all instances of the general Type , which might be the same set.
oslc_sysmlv2:subsetting_OwningFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	A subsettingFeature that is also the owningRelatedElement of this Subsetting .
oslc_sysmlv2:subsetting_SubsettedFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is subsetted by the subsettingFeature of this Subsetting .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:subsetting_SubsettingFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is a subset of the subsettingFeature of this Subsetting .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-149].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#AnalysisCaseDefinition>
- **Summary:** AnalysisCaseDefinitionShape
- **Description:** An **AnalysisCaseDefinition** is a **CaseDefinition** for the case of carrying out an analysis.

AnalysisCaseDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionDefinition_Action	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are steps in this ActionDefinition , which define the actions that specify the behavior of the ActionDefinition .
oslc_sysmlv2:analysisCaseDefinition_AnalysisAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The composite actions of the AnalysisCaseDefinition that are defined as AnalysisActions .
oslc_sysmlv2:analysisCaseDefinition_ResultExpression	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Expression	An Expression used to compute the result of the AnalysisCaseDefinition , owned via a ResultExpressionMembership .
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Behavior .
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior .
oslc_sysmlv2:calculationDefinition_Calculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The actions of this CalculationDefinition that are CalculationUsages .
oslc_sysmlv2:caseDefinition_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this CaseDefinition that represent actors involved in the case.
oslc_sysmlv2:caseDefinition_ObjectiveRequirement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage representing the objective of this CaseDefinition .
oslc_sysmlv2:caseDefinition_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this CaseDefinition that represents its subject.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the <code>owningRelatedElement</code> .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespace</code> s from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .
<code>oslc_sysmlv2:function_Expression</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Expression</code>	The <code>Expressions</code> that are <code>steps</code> in the calculation of the <code>result</code> of this <code>Function</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The features of this Type that have a non-null direction .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features of this Type with isEnd = true .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the featureMemberships of this Type .
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-150].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Unioning`
- **Summary:** UnioningShape
- **Description:** Unioning is a Relationship that makes its unioningType one of the unioningTypes of its typeUnioned.

Unioning Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the <code>owningRelatedElement</code> of the <code>owningRelationship</code> of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The <code>owningRelationship</code> of this <code>Element</code> , if that <code>Relationship</code> is a <code>Membership</code> .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The <code>Namespace</code> that owns this <code>Element</code> , which is the <code>membershipOwningNamespace</code> of the <code>owningMembership</code> of this <code>Element</code> , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an <code>ownedRelatedElement</code> , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this <code>Element</code> , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The <code>qualifiedName</code> is null if this <code>Element</code> has no <code>owningNamespace</code> or if there is not a complete ownership chain of named <code>Namespace</code> s from a root <code>Namespace</code> to this <code>Element</code> .
<code>oslc_sysmlv2:element_ShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The short name to be used for this <code>Element</code> during name resolution within its <code>owningNamespace</code> . This is derived using the <code>effectiveShortName()</code> operation. By default, it is the same as the <code>declaredShortName</code> , but this is overridden for certain kinds of <code>Elements</code> to compute a <code>shortName</code> even when the <code>declaredName</code> is null.
<code>oslc_sysmlv2:element_TextualRepresentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TextualRepresentation</code>	The <code>TextualRepresentations</code> that annotate this <code>Element</code> .
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:unioning_TypeUnioned	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type with interpretations partly determined by unioningType , as described in Type::unioningType .
oslc_sysmlv2:unioning_UnioningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type that partly determines interpretations of typeUnioned , as described in Type::unioningType .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-151] .
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#SuccessionFlowConnectionUsage>
- **Summary:** SuccessionFlowConnectionUsageShape
- **Description:** A **SuccessionFlowConnectionUsage** is a **FlowConnectionUsage** that is also a **SuccessionItemFlow**.

SuccessionFlowConnectionUsage Properties

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage . Nominally, these would be ActionDefinitions , but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:connectionUsage_ConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AssociationStructure	The AssociationStructures that are the types of this ConnectionUsage . Nominally, these are , but other kinds of Kernel AssociationStructures are also allowed, to permit use of AssociationStructures from the Kernel Model Libraries.
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:flowConnectionUsage_FlowConnectionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Interaction	The Interactions that are the types of this FlowConnectionUsage . Nominally, these are FlowConnectionDefinitions , but other kinds of Kernel Interactions are also allowed, to permit use of Interactions from the Kernel Model Libraries.
oslc_sysmlv2:itemFlow_Interaction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Interaction	The Interactions that type this ItemFlow . Interactions are both Associations and Behaviors , which can type Connectors and Steps , respectively.
oslc_sysmlv2:itemFlow_ItemFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ItemFeature	The ownedFeature of the ItemFlow that is an ItemFeature (if any).
oslc_sysmlv2:itemFlow_ItemFlowEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemFlowEnd	The connectorEnds of this ItemFlow that are ItemFlowEnds .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:itemFlow_ItemType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The type of values transferred, which is the type of the itemFeature of the ItemFlow .
oslc_sysmlv2:itemFlow_SourceOutputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that provides the items carried by the ItemFlow . It must be an owned output of the source of the ItemFlow .
oslc_sysmlv2:itemFlow_TargetInputFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that receives the values carried by the ItemFlow . It must be an owned output of the target participant of the ItemFlow .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:occurrenceUsage_IsIndividual</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
<code>oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Class</code>	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
<code>oslc_sysmlv2:occurrenceUsage_PortionKind</code>	Zero-or-one	false	unspecified	Either	<code>oslc_sysmlv2:PortionKind</code>	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
<code>oslc_sysmlv2:partUsage_PartDefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:PartDefinition</code>	The itemDefinitions of this PartUsage that are PartDefinitions.
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElement of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:step_Behavior</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Behavior</code>	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:succession_EffectStep	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	Steps that represent occurrences that are side effects of the transitionStep occurring.
oslc_sysmlv2:succession_GuardExpression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	Expressions that must evaluate to true before the transitionStep can occur.
oslc_sysmlv2:succession_TransitionStep	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Step	A Step that is typed by the Behavior TransitionPerformances::TransitionPerformance (from the Kernel Semantic Library) that has this Succession as its transitionLink .
oslc_sysmlv2:succession_TriggerStep	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	Steps that map incoming events to the timing of occurrences of the transitionStep . The values of triggerStep subset the list of acceptable events to be received by a Behavior or the object that performs it.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-152].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Namespace`
- **Summary:** NamespaceShape
- **Description:** A **Namespace** is an **Element** that contains other **Elements**, known as its **members**, via **Membership Relationships** with those **Elements**. The **members** of a **Namespace** may be owned by the **Namespace**, aliased in the **Namespace**, or imported into the **Namespace** via **Import Relationships**.

Namespace Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_DeclaredName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	Exactly-one	false	unspecified	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
<code>oslc_sysmlv2:element_IsImpliedIncluded</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-153].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Dependency>
- **Summary:** DependencyShape
- **Description:** A **Dependency** is a **Relationship** that indicates that one or more **client Elements** require one more **supplier Elements** for their complete specification. In general, this means that a change to one of the **supplier Elements** may necessitate a change to, or re-specification of, the **client Elements**.

Dependency Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:dependency_Client	One-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Element or Elements dependent on the supplier Elements .
oslc_sysmlv2:dependency_Supplier	One-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Element or Elements on which the client Elements depend in some respect.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-154].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#OccurrenceDefinition>
- **Summary:** OccurrenceDefinitionShape
- **Description:** An **OccurrenceDefinition** is a **Definition** of a **Class** of individuals that have an independent life over time and potentially an extent over space. This includes both structural things and behaviors that act on such structures.

OccurrenceDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false , the there must be no variants .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout .
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-155].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ForLoopActionUsage>
- **Summary:** ForLoopActionUsageShape
- **Description:** A **ForLoopActionUsage** is a **LoopActionUsage** that specifies that its **bodyAction ActionUsage** should be performed once for each value, in order, from the sequence of values obtained as the result of the **seqArgument Expression**, with the **loopVariable** set to the value for each iteration.

ForLoopActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:forLoopActionUsage_LoopVariable	Exactly-one	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ownedFeature of this ForLoopActionUsage that acts as the loop variable, which is assigned the successive values of the input sequence on each iteration. It is the ownedFeature that redefines ForLoopAction::var..
oslc_sysmlv2:forLoopActionUsage_SeqArgument	Exactly-one	false	Resource	Either	oslc_sysmlv2:Expression	The Expression whose result provides the sequence of values to which the loopVariable is set for each iterative performance of the bodyAction . It is the Expression whose result is bound to the seq input parameter of this ForLoopActionUsage .
oslc_sysmlv2:loopActionUsage_BodyAction	Exactly-one	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsage to be performed repeatedly by the LoopActionUsage . It is the second parameter of the LoopActionUsage .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships, for which the Namespace is the membershipOwningNamespace.
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true.
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition.
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage. Nominally, these are OccurrenceDefinitions, but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage, if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step.
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Step.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The <code>Classifiers</code> that are the types of this <code>Usage</code> . Nominally, these are <code>Definitions</code> , but other kinds of Kernel <code>Classifiers</code> are also allowed, to permit use of <code>Classifiers</code> from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The <code>usages</code> of this <code>Usage</code> that are <code>directedFeatures</code> .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Usage</code> is a referential <code>Usage</code> , that is, it has <code>isComposite = false</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-156].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#MetadataFeature>
- **Summary:** MetadataFeatureShape
- **Description:** A **MetadataFeature** is a **Feature** that is an **AnnotatingElement** used to annotate another **Element** with metadata. It is typed by a **Metaclass**. All its **ownedFeatures** must redefine **features** of its **metaclass** and any feature bindings must be model-level evaluable.

MetadataFeature Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:annotatingElement_AnnotatedElement	One-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are annotated by this AnnotatingElement . If annotation is not empty, these are the annotatedElements of the annotations . If annotation is empty, then it is the owningNamespace of the AnnotatingElement .
oslc_sysmlv2:annotatingElement_Annotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The Annotations that relate this AnnotatingElement to its annotatedElements .
oslc_sysmlv2:annotatingElement_OwnedAnnotatingRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this AnnotatingElement that are Annotations , for which this AnnotatingElement is the annotatingElement .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:feature_OwnedFeatureChaining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureChaining</code>	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
<code>oslc_sysmlv2:feature_OwnedFeatureInverting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureInverting</code>	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
<code>oslc_sysmlv2:feature_OwnedRedefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Redefinition</code>	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
<code>oslc_sysmlv2:feature_OwnedReferenceSubsetting</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:ReferenceSubsetting</code>	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
<code>oslc_sysmlv2:feature_OwnedSubsetting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Subsetting</code>	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
<code>oslc_sysmlv2:feature_OwnedTypeFeaturing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TypeFeaturing</code>	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
<code>oslc_sysmlv2:feature_OwnedTyping</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureTyping</code>	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
<code>oslc_sysmlv2:feature_OwningFeatureMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
<code>oslc_sysmlv2:feature_OwningType</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The Type that is the owningType of the owningFeatureMembership of this Feature .
<code>oslc_sysmlv2:feature_Type</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
<code>oslc_sysmlv2:metadataFeature_Metaclass</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Metaclass</code>	The type of this MetadataFeature , which must be a Metaclass .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout .
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-157].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ObjectiveMembership>
- **Summary:** ObjectiveMembershipShape
- **Description:** An **ObjectiveMembership** is a **FeatureMembership** that indicates that its **ownedObjectiveRequirement** is the objective **RequirementUsage** for its **owningType**, which must be a **CaseDefinition** or **CaseUsage**.

ObjectiveMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType , making it an ownedFeature of the owningType .
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership .
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType .
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:objectiveMembership_OwnedObjectiveRequirement	Exactly-one	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsage that is the ownedMemberFeature of this RequirementUsage.
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-158].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Feature>
- **Summary:** FeatureShape
- **Description:** A **Feature** is a **Type** that classifies relations between multiple things (in the universe). The domain of the relation is the intersection of the **featuringTypes** of the **Feature**. (The domain of a **Feature** with no **featuringTypes** is implicitly the most general **Type Base: :Anything** from the Kernel Semantic Library.) The co-domain of the relation is the intersection of the **types** of the **Feature**. .

Feature Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the <code>effectiveName()</code> operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-159].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#EnumerationDefinition`
- **Summary:** EnumerationDefinitionShape
- **Description:** An **EnumerationDefinition** is an **AttributeDefinition** all of whose instances are given by an explicit list of **enumeratedValues**. This is realized by requiring that the **EnumerationDefinition** have **isVariation = true**, with the **enumeratedValues** being its **variants**.

EnumerationDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
---------------	--------	-----------	------------	----------------	-------	-------------

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example ‘Car’.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:enumerationDefinition_EnumeratedValue	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	EnumerationUsages of this EnumerationDefinition that have distinct, fixed values. Each enumeratedValue specifies one of the allowed instances of the EnumerationDefinition .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-160].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ActionUsage`
- **Summary:** ActionUsageShape
- **Description:** An **ActionUsage** is a **Usage** that is also a **Step**, and, so, is typed by a **Behavior**. Nominally, if the type is an **ActionDefinition**, an **ActionUsage** is a **Usage** of that **ActionDefinition** within a system. However, other kinds of kernel **Behaviors** are also allowed, to permit use of **Behaviors** from the Kernel Model Libraries.

ActionUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:actionUsage_ActionDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that are the types of this ActionUsage. Nominally, these would be ActionDefinitions, but other kinds of Kernel Behaviors are also allowed, to permit use of Behaviors from the Kernel Model Libraries.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc_sysmlv2:usage_Definition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Classifier</code>	The <code>Classifiers</code> that are the types of this <code>Usage</code> . Nominally, these are <code>Definitions</code> , but other kinds of Kernel <code>Classifiers</code> are also allowed, to permit use of <code>Classifiers</code> from the Kernel Model Libraries.
<code>oslc_sysmlv2:usage_DirectedUsage</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Usage</code>	The <code>usages</code> of this <code>Usage</code> that are <code>directedFeatures</code> .
<code>oslc_sysmlv2:usage_IsReference</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this <code>Usage</code> is a referential <code>Usage</code> , that is, it has <code>isComposite = false</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:usage_IsVariation</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
<code>oslc_sysmlv2:usage_NestedAction</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The ActionUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAllocation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AllocationUsage</code>	The AllocationUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAnalysisCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AnalysisCaseUsage</code>	The AnalysisCaseUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedAttribute</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:AttributeUsage</code>	The <code>>AttributeUsages</code> that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedCalculation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CalculationUsage</code>	The CalculationUsage that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedCase</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:CaseUsage</code>	The CaseUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedConcern</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConcernUsage</code>	The ConcernUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedConnection</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConnectorAsUsage</code>	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
<code>oslc_sysmlv2:usage_NestedConstraint</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:ConstraintUsage</code>	The ConstraintUsages that are nestedUsages of this Usage .
<code>oslc_sysmlv2:usage_NestedEnumeration</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:EnumerationUsage</code>	The <code>>EnumerationUsages</code> that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-161].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#Disjoining`
- **Summary:** DisjoiningShape
- **Description:** A **Disjoining** is a **Relationship** between **Types** asserted to have interpretations that are not shared (disjoint) between them, identified as **typeDisjoined** and **disjoiningType**. For example, a **Classifier** for mammals is disjoint from a **Classifier** for minerals, and a **Feature** for people's parents is disjoint from a **Feature** for their children.

Disjoining Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:disjoining_DisjoiningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type asserted to be disjoint with the typeDisjoined.
oslc_sysmlv2:disjoining_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	A typeDisjoined that is also an owningRelatedElement.
oslc_sysmlv2:disjoining_TypeDisjoined	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	Type asserted to be disjoint with the disjoiningType.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-162].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Association>
- **Summary:** AssociationShape
- **Description:** An **Association** is a **Relationship** and a **Classifier** to enable classification of links between things (in the universe). The co-domains (**types**) of the **associationEnd Features** are the **relatedTypes**, as co-domain and participants (linked things) of an **Association** identify each other.

Association Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:association_AssociationEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of the Association that identify the things that can be related by it. A concrete Association must have at least two associationEnds . When it has exactly two, the Association is called a <i>binary Association</i> .
oslc_sysmlv2:association_RelatedType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The types of the associationEnds of the Association , which are the relatedElements of the Association considered as a Relationship .
oslc_sysmlv2:association_SourceType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The source relatedType for this Association . It is the first relatedType of the Association .
oslc_sysmlv2:association_TargetType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The target relatedTypes for this Association . This includes all the relatedTypes other than the sourceType .
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_IsImplied</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
<code>oslc_sysmlv2:relationship_OwnedRelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> of this Relationship that are owned by the Relationship.
<code>oslc_sysmlv2:relationship_OwningRelatedElement</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElement</code> of this Relationship that owns the Relationship, if any.
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the <code>source</code> and <code>target</code> Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The <code>relatedElements</code> to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:type_DifferencingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>differencingTypes</code> are asserted to be those of the first of those <code>Types</code> , but not including those of the remaining <code>Types</code> . For example, a <code>Classifier</code> might be the difference of a <code>Classifier</code> for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a <code>Classifier</code> for people of a particular sex, identifying their children not of that sex (because the interpretations of the children <code>Feature</code> that identify those of that sex are also interpretations of the <code>Classifier</code> for that sex).
<code>oslc_sysmlv2:type_DirectedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>features</code> of this <code>Type</code> that have a non-null <code>direction</code> .
<code>oslc_sysmlv2:type_EndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>features</code> of this <code>Type</code> with <code>isEnd</code> = <code>true</code> .
<code>oslc_sysmlv2:type_Feature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>featureMemberships</code> of this <code>Type</code> .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_FeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
<code>oslc_sysmlv2:type_InheritedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
<code>oslc_sysmlv2:type_InheritedMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Membership</code>	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
<code>oslc_sysmlv2:type_Input</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction in or inout..
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-163].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#PartUsage>
- **Summary:** PartUsageShape
- **Description:** A [PartUsage](#) is a usage of a [PartDefinition](#) to represent a system or a part of a system. At least one of the [itemDefinitions](#) of the [PartUsage](#) must be a [PartDefinition](#).

PartUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixes Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:feature_IsNonunique</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	isNonunique.
<code>oslc_sysmlv2:feature_IsOrdered</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether an order exists for the values of this Feature or not.
<code>oslc_sysmlv2:feature_IsPortion</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
<code>oslc_sysmlv2:feature_IsReadOnly</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether the values of this Feature can change over the lifetime of an instance of the domain.
<code>oslc_sysmlv2:feature_IsUnique</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether or not values for this Feature must have no duplicates or not.
<code>oslc_sysmlv2:feature_OwnedFeatureChaining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureChaining</code>	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
<code>oslc_sysmlv2:feature_OwnedFeatureInverting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureInverting</code>	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
<code>oslc_sysmlv2:feature_OwnedRedefinition</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Redefinition</code>	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
<code>oslc_sysmlv2:feature_OwnedReferenceSubsetting</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:ReferenceSubsetting</code>	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
<code>oslc_sysmlv2:feature_OwnedSubsetting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Subsetting</code>	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
<code>oslc_sysmlv2:feature_OwnedTypeFeaturing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:TypeFeaturing</code>	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
<code>oslc_sysmlv2:feature_OwnedTyping</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureTyping</code>	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:itemUsage_ItemDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Structure	The Structures that are the definitions of this ItemUsage. Nominally, these are ItemDefinitions, but other kinds of Kernel Structures are also allowed, to permit use of Structures from the Kernel Library.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:partUsage_PartDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartDefinition	The itemDefinitions of this PartUsage that are PartDefinitions.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage.
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage, if isVariation = true. If isVariation = false, then there must be no variants.
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships. If isVariation = true, then this must be all memberships of the Usage. If isVariation = false, then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-164].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Multiplicity>
- **Summary:** MultiplicityShape
- **Description:** A Multiplicity is a Feature whose co-domain is a set of natural numbers giving the allowed cardinalities of each typeWithMultiplicity. The cardinality of a Type is defined as follows, depending on whether the Type is a Classifier or Feature. .

Multiplicity Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:element_IsLibraryElement</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether this Element is contained in the ownership tree of a library model.
<code>oslc_sysmlv2:element_Name</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
<code>oslc_sysmlv2:element_OwnedAnnotation</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Annotation</code>	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
<code>oslc_sysmlv2:element_OwnedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
<code>oslc_sysmlv2:element_OwnedRelationship</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationships for which this Element is the owningRelatedElement .
<code>oslc_sysmlv2:element_Owner</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
<code>oslc_sysmlv2:element_OwningMembership</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:OwningMembership</code>	The owningRelationship of this Element , if that Relationship is a Membership .
<code>oslc_sysmlv2:element_OwningNamespace</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Namespace</code>	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
<code>oslc_sysmlv2:element_OwningRelationship</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Relationship</code>	The Relationship for which this Element is an ownedRelatedElement , if any.
<code>oslc_sysmlv2:element_QualifiedName</code>	Zero-or-one	false	unspecified	Either	<code>xsd:string</code>	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constrains the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-165].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ConcernDefinition`
- **Summary:** ConcernDefinitionShape
- **Description:** A **ConcernDefinition** is a **RequirementDefinition** that one or more stakeholders may be interested in having addressed. These stakeholders are identified by the **ownedStakeholders** of the **ConcernDefinition**.

ConcernDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:behavior_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Behavior, which are defined as its directedFeatures, whose values are passed into and/or out of a performance of the Behavior.
oslc_sysmlv2:behavior_Step	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Step	The Steps that make up this Behavior.
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications, for which this Classifier is the subclassifier.
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures.
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships.
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition .

Prefix Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition , if isVariation = true. If isVariation = false, the there must be no variants .
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships . If isVariation = true, then this must be all ownedMemberships of the Definition . If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:function_Expression	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Expression	The Expressions that are steps in the calculation of the result of this Function .
oslc_sysmlv2:function_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Function can be used as the function of a model-level evaluable InvocationExpression . Certain Functions from the Kernel Functions Library are considered to have isModelLevelEvaluable = true . For all other Functions it is false .
oslc_sysmlv2:function_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The result parameter of the Function , which is owned by the Function via a ReturnParameterMembership .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:requirementDefinition_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementDefinition that represent actors involved in the requirement.
oslc_sysmlv2:requirementDefinition_AssumedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent assumptions of this RequirementDefinition , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = assumption .
oslc_sysmlv2:requirementDefinition_FramedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages framed by this RequirementDefinition , which are the ownedConcerns of all FramedConcernMemberships of the RequirementDefinition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementDefinition_ReqId	Zero-or-one	false	unspecified	Either	xsd:string	An optional modeler-specified identifier for this RequirementDefinition (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementDefinition .
oslc_sysmlv2:requirementDefinition_RequiredConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent requirements of this RequirementDefinition , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementDefinition with kind = requirement .
oslc_sysmlv2:requirementDefinition_StakeholderParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementDefinition that represent stakeholders for th requirement.
oslc_sysmlv2:requirementDefinition_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this RequirementDefinition that represents its subject.
oslc_sysmlv2:requirementDefinition_Text	Zero-or-many	false	unspecified	Either	xsd:string	An optional textual statement of the requirement represented by this RequirementDefinition , derived from the bodies of the documentation of the RequirementDefinition .
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout ..
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings, having the Type as their typeUnioned.
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type. For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-166].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ConcernUsage>
- **Summary:** ConcernUsageShape

- **Description:** A **ConcernUsage** is a **Usage** of a **ConcernDefinition**.

ConcernUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:booleanExpression_Predicate	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The Predicate that types this BooleanExpression .
oslc_sysmlv2:concernUsage_ConcernDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ConcernDefinition	The ConcernDefinition that is the single type of this ConcernUsage.
oslc_sysmlv2:constraintUsage_ConstraintDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Predicate	The (single) Predicate that is the type of this ConstraintUsage . Nominally, this will be a ConstraintDefinition , but other kinds of Predicates are also allowed, to permit use of Predicates from the Kernel Model Libraries.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:expression_Function	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Function	The Function that types this Expression .
oslc_sysmlv2:expression_IsModelLevelEvaluable	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Expression meets the constraints necessary to be evaluated at <i>model level</i> , that is, using metadata within the model.
oslc_sysmlv2:expression_Result	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures , and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceUsage_IndividualDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OccurrenceDefinition	The at most one occurrenceDefinition that has isIndividual = true .
oslc_sysmlv2:occurrenceUsage_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceUsage represents the usage of the specific individual (or portion of it) represented by its individualDefinition .
oslc_sysmlv2:occurrenceUsage_OccurrenceDefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Class	The Classes that are the types of this OccurrenceUsage . Nominally, these are OccurrenceDefinitions , but other kinds of kernel Classes are also allowed, to permit use of Classes from the Kernel Model Libraries.
oslc_sysmlv2:occurrenceUsage_PortionKind	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:PortionKind	The kind of (temporal) portion of the life of the occurrenceDefinition represented by this OccurrenceUsage , if it is so restricted.
oslc_sysmlv2:requirementUsage_ActorParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementUsage that represent actors involved in the requirement.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:requirementUsage_AssumedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent assumptions of this RequirementUsage , derived as the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = assumption .
oslc_sysmlv2:requirementUsage_FramedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages framed by this RequirementUsage , which are the ownedConcerns of all FramedConcernMemberships of the RequirementUsage .
oslc_sysmlv2:requirementUsage_ReqId	Zero-or-one	false	unspecified	Either	xsd:string	An optional modeler-specified identifier for this RequirementUsage (used, e.g., to link it to an original requirement text in some source document), which is the declaredShortName for the RequirementUsage .
oslc_sysmlv2:requirementUsage_RequiredConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The owned ConstraintUsages that represent requirements of this RequirementUsage , which are the ownedConstraints of the RequirementConstraintMemberships of the RequirementUsage with kind = requirement .
oslc_sysmlv2:requirementUsage_RequirementDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:RequirementDefinition	The RequirementDefinition that is the single definition of this RequirementUsage .
oslc_sysmlv2:requirementUsage_StakeholderParameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The parameters of this RequirementUsage that represent stakeholders for the requirement.
oslc_sysmlv2:requirementUsage_SubjectParameter	Exactly-one	false	Resource	Either	oslc_sysmlv2:Usage	The parameter of this RequirementUsage that represents its subject.
oslc_sysmlv2:requirementUsage_Text	Zero-or-many	false	unspecified	Either	xsd:string	An optional textual statement of the requirement represented by this RequirementUsage , derived from the bodies of the documentation of the RequirementUsage..
oslc_sysmlv2:step_Behavior	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Behavior	The Behaviors that type this Step .
oslc_sysmlv2:step_Parameter	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The parameters of this Step , which are defined as its directedFeatures , whose values are passed into and/or out of a performance of the Step .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage . Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages , even though these are ConnectorAsUsages but not ConnectionUsages .
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage .

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage .
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-167].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Classifier>
- **Summary:** ClassifierShape
- **Description:** A **Classifier** is a **Type** that classifies:.

Classifier Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.

Standards Track Work Product

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element , derived as the ownedRelatedElements of the ownedRelationships of this Element .
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element , derived as the owningRelatedElement of the owningRelationship of this Element , if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .

Copyright © OASIS Open 2024. All Rights Reserved.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_IntersectingType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
<code>oslc_sysmlv2:type_IsAbstract</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
<code>oslc_sysmlv2:type_IsConjugated</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Indicates whether this Type has an ownedConjugator .
<code>oslc_sysmlv2:type_IsSufficient</code>	Exactly-one	false	unspecified	Either	<code>xsd:boolean</code>	Whether all things that meet the classification conditions of this Type must be classified by the Type .
<code>oslc_sysmlv2:type_Multiplicity</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Multiplicity</code>	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
<code>oslc_sysmlv2:type_Output</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All features related to this Type by FeatureMemberships that have direction out or inout .
<code>oslc_sysmlv2:type_OwnedConjugator</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Conjugation</code>	A Conjugation owned by this Type for which the Type is the originalType .
<code>oslc_sysmlv2:type_OwnedDifferencing</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Differencing</code>	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All endFeatures of this Type that are ownedFeatures .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-168].

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** `http://open-services.net/ns/sysmlv2#ItemDefinition`
- **Summary:** ItemDefinitionShape
- **Description:** An `ItemDefinition` is an `OccurrenceDefinition` of the `Structure` of things that may themselves be systems or parts of systems, but may also be things that are acted on by a system or parts of a system, but which do not necessarily perform actions themselves. This includes items that can be exchanged between parts of a system, such as water or electrical signals.

ItemDefinition Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>dcterms:contributor</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:created</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
<code>dcterms:creator</code>	Zero-or-many	false	AnyResource	Either	<code>oslc:Any</code>	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
<code>dcterms:description</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
<code>dcterms:identifier</code>	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
<code>dcterms:modified</code>	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
<code>dcterms:source</code>	Zero-or-one	false	Resource	Reference	<code>oslc:Any</code>	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
<code>dcterms:title</code>	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:classifier_OwnedSubclassification	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subclassification	The ownedSpecializations of this Classifier that are Subclassifications , for which this Classifier is the subclassifier .
oslc_sysmlv2:definition_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Definition that are directedFeatures .
oslc_sysmlv2:definition_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Definition is for a variation point or not. If true, then all the memberships of the Definition must be VariantMemberships .
oslc_sysmlv2:definition_OwnedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are ownedUsages of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The AttributeUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The code>CaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are ownedUsages of this Definition. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:definition_OwnedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The EnumerationUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The FlowConnectionUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are ownedUsages of this Definition.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are ownedUsages of this Definition .
oslc_sysmlv2:definition_OwnedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Definition .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:definition_OwnedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_OwnedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are ownedUsages of this Definition.
oslc_sysmlv2:definition_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Definition (not necessarily owned).
oslc_sysmlv2:definition_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Definition as a variation point Definition, if isVariation = true. If isVariation = false, the there must be no variants.
oslc_sysmlv2:definition_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Definition that are VariantMemberships. If isVariation = true, then this must be all ownedMemberships of the Definition. If isVariation = false, then variantMembership must be empty.
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element.
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name. It may act as a modeler-specified identifier for the Element, though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true, meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may not contain any implied Relationships. That is, either all required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveName() operation. By default, it is the same as the declaredName, but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations, for which this Element is the annotatedElement.
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace.
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace, which are the memberElements of all memberships of the Namespace.
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace, including (at least) the union of ownedMemberships and importedMemberships.
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports, for which the Namespace is the importOwningNamespace.
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace, which are the ownedMemberElements of the ownedMemberships of the ..

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:occurrenceDefinition_IsIndividual	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this OccurrenceDefinition is constrained to represent single individual.
oslc_sysmlv2:occurrenceDefinition_LifeClass	Zero-or-one	false	Resource	Either	oslc_sysmlv2:LifeClass	If isIndividual is true, a LifeClass that specializes this OccurrenceDefinition , restricting it to represent an individual.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:type_OwnedDisjoining</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Disjoining</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Disjoinings</code> , for which the <code>Type</code> is the <code>typeDisjoined Type</code> .
<code>oslc_sysmlv2:type_OwnedEndFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	All <code>endFeatures</code> of this <code>Type</code> that are <code>ownedFeatures</code> .
<code>oslc_sysmlv2:type_OwnedFeature</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The <code>ownedMemberFeatures</code> of the <code>ownedFeatureMemberships</code> of this <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedFeatureMembership</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:FeatureMembership</code>	The <code>ownedMemberships</code> of this <code>Type</code> that are <code>FeatureMemberships</code> , for which the <code>Type</code> is the <code>owningType</code> . Each such <code>FeatureMembership</code> identifies an <code>ownedFeature</code> of the <code>Type</code> .
<code>oslc_sysmlv2:type_OwnedIntersecting</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Intersecting</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Intersectings</code> , have the <code>Type</code> as their <code>typeIntersected</code> .
<code>oslc_sysmlv2:type_OwnedSpecialization</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Specialization</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Specializations</code> , for which the <code>Type</code> is the <code>specific Type</code> .
<code>oslc_sysmlv2:type_OwnedUnioning</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Unioning</code>	The <code>ownedRelationships</code> of this <code>Type</code> that are <code>Unionings</code> , having the <code>Type</code> as their <code>typeUnioned</code> .
<code>oslc_sysmlv2:type_UnioningType</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	The interpretations of a <code>Type</code> with <code>unioningTypes</code> are asserted to be the same as those of all the <code>unioningTypes</code> together, which are the <code>Types</code> derived from the <code>unioningType</code> of the <code>ownedUnionings</code> of this <code>Type</code> . For example, a <code>Classifier</code> for people might be the union of <code>Classifiers</code> for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-169].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

- **Describes:** http://open-services.net/ns/sysmlv2#StateSubactionMembership
- **Summary:** StateSubactionMembershipShape
- **Description:** A StateSubactionMembership is a FeatureMembership for an entry, do or exit ActionUsage of a StateDefinition or StateUsage..

StateSubactionMembership Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement.
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element, if that Relationship is a Membership.
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element, which is the membershipOwningNamespace of the owningMembership of this Element, if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement, if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element, represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element.
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace. This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName, but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element.
oslc_sysmlv2:featureMembership_OwnedMemberFeature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that this FeatureMembership relates to its owningType, making it an ownedFeature of the owningType.
oslc_sysmlv2:featureMembership_OwningType	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that owns this FeatureMembership.
oslc_sysmlv2:featuring_Feature	Exactly-one	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that is featured by the featuringType.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:featuring_Type	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that features the featureOfType ..
oslc_sysmlv2:membership_MemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes a member of the membershipOwningNamespace due to this Membership .
oslc_sysmlv2:membership_MemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the memberElement .
oslc_sysmlv2:membership_MemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_MembershipOwningNamespace	Exactly-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace of which the memberElement becomes a member due to this Membership ..
oslc_sysmlv2:membership_MemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name of the memberElement relative to the membershipOwningNamespace .
oslc_sysmlv2:membership_Visibility	Exactly-one	false	unspecified	Either	oslc_sysmlv2:VisibilityKind	Whether or not the Membership of the memberElement in the membershipOwningNamespace is publicly visible outside that Namespace .
oslc_sysmlv2:owningMembership_OwnedMemberElement	Exactly-one	false	Resource	Either	oslc_sysmlv2:Element	The Element that becomes an ownedMember of the membershipOwningNamespace due to this OwningMembership .
oslc_sysmlv2:owningMembership_OwnedMemberElementId	Exactly-one	false	unspecified	Either	xsd:string	The elementId of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberName	Zero-or-one	false	unspecified	Either	xsd:string	The name of the ownedMemberElement .
oslc_sysmlv2:owningMembership_OwnedMemberShortName	Zero-or-one	false	unspecified	Either	xsd:string	The shortName of the ownedMemberElement .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:relationship_RelatedElement</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
<code>oslc_sysmlv2:relationship_Source</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements from which this Relationship is considered to be directed..
<code>oslc_sysmlv2:relationship_Target</code>	Zero-or-many	false	Resource	Either	<code>oslc_sysmlv2:Element</code>	The relatedElements to which this Relationship is considered to be directed.
<code>oslc_sysmlv2:stateSubactionMembership_Action</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:ActionUsage</code>	The ActionUsage that is the ownedMemberFeature of this StateSubactionMembership .
<code>oslc_sysmlv2:stateSubactionMembership_Kind</code>	Exactly-one	false	unspecified	Either	<code>oslc_sysmlv2:StateSubactionKind</code>	Whether this StateSubactionMembership is for an entry , do or exit ActionUsage ..
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-170] .
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#Subsetting>
- **Summary:** SubsettingShape

- **Description:** **Subsetting** is **Specialization** in which the **specific** and **general Types** are **Features**. This means all values of the **subsettingFeature** (on instances of its domain, i.e., the intersection of its **featuringTypes**) are values of the **subsettingFeature** on instances of its domain. To support this the domain of the **subsettingFeature** must be the same or specialize (at least indirectly) the domain of the **subsettingFeature** (via **Specialization**), and the co-domain (intersection of the **types**) of the **subsettingFeature** must specialize the co-domain of the **subsettingFeature**.

Subsetting Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.

Standards Track Work Product

Prefixes	Value-type	Occurs	Read-only	Representation	Range	Description
<code>jazz_am:elaborates</code>	Resource	Zero-or-many	false	Reference	<code>oslc:Any</code>	This resource elaborates the referenced resource.
<code>jazz_am:external</code>	Resource	Zero-or-many	false	Reference	<code>oslc:Any</code>	A generic link from a resource to an external web page.
<code>jazz_am:refine</code>	Resource	Zero-or-many	false	Reference	<code>oslc:Any</code>	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
<code>jazz_am:satisfy</code>	Resource	Zero-or-many	false	Reference	<code>oslc:Any</code>	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
<code>jazz_am:trace</code>	Resource	Zero-or-many	false	Reference	<code>oslc:Any</code>	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
<code>oslc_sysmlv2:element_AliasIds</code>	unspecified	Zero-or-many	false	Either	<code>xsd:string</code>	Various alternative identifiers for this Element. Generally, these will be set by tools.
<code>oslc_sysmlv2:element_DeclaredName</code>	unspecified	Zero-or-one	false	Either	<code>xsd:string</code>	The declared name of this Element .
<code>oslc_sysmlv2:element_DeclaredShortName</code>	unspecified	Zero-or-one	false	Either	<code>xsd:string</code>	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
<code>oslc_sysmlv2:element_Documentation</code>	Resource	Zero-or-many	false	Either	<code>oslc_sysmlv2:Documentation</code>	The Documentation owned by this Element.
<code>oslc_sysmlv2:element_ElementId</code>	unspecified	Exactly-one	false	Either	<code>xsd:string</code>	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespaces from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:specialization_General	Exactly-one	false	Resource	Either	oslc_sysmlv2:Type	A Type with a superset of all instances of the specific Type , which might be the same set.
oslc_sysmlv2:specialization_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the specific Type of this Specialization and owns it as its owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
<code>oslc_sysmlv2:specialization_Specific</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Type</code>	A Type with a subset of all instances of the general Type , which might be the same set.
<code>oslc_sysmlv2:subsetting_OwningFeature</code>	Zero-or-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	A subsettingFeature that is also the owningRelatedElement of this Subsetting .
<code>oslc_sysmlv2:subsetting_SubsettedFeature</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that is subsetted by the subsettingFeature of this Subsetting .
<code>oslc_sysmlv2:subsetting_SubsettingFeature</code>	Exactly-one	false	Resource	Either	<code>oslc_sysmlv2:Feature</code>	The Feature that is a subset of the subsettedFeature of this Subsetting .
<code>oslc:instanceShape</code>	Zero-or-one	false	Resource	Reference	<code>oslc:ResourceShape</code>	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
<code>oslc:serviceProvider</code>	Zero-or-many	false	Resource	Reference	<code>oslc:ServiceProvider</code>	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
<code>oslc:shortTitle</code>	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML <code></code> element [sml-171].
<code>rdf:type</code>	Zero-or-many	false	Resource	Reference	<code>rdfs:Class</code>	The resource type URIs.

- **Describes:** <http://open-services.net/ns/sysmlv2#ConnectorAsUsage>
- **Summary:** ConnectorAsUsageShape
- **Description:** A **ConnectorAsUsage** is both a **Connector** and a **Usage**. **ConnectorAsUsage** cannot itself be instantiated in a SysML model, but it is the base class for the concrete classes **BindingConnectorAsUsage**, **SuccessionAsUsage** and **ConnectionUsage**.

ConnectorAsUsage Properties

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
dcterms:contributor	Zero-or-many	false	AnyResource	Either	oslc:Any	Contributor or contributors to the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:created	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of resource creation.
dcterms:creator	Zero-or-many	false	AnyResource	Either	oslc:Any	Creator or creators of the resource. It is likely that the target resource will be a foaf:Person but that is not necessarily the case.
dcterms:description	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Descriptive text about resource represented as rich text in XHTML content.
dcterms:identifier	Exactly-one	true	string	N/A	Unspecified	A unique identifier for a resource. Typically read-only and assigned by the service provider when a resource is created. Not typically intended for end-user display.
dcterms:modified	Zero-or-one	false	dateTime	N/A	Unspecified	Timestamp of latest resource modification.
dcterms:source	Zero-or-one	false	Resource	Reference	oslc:Any	The resource URI a client can perform a get on to obtain the original non-OSLC AM formatted resource that was used to create this resource. The source resource is usually a binary or proprietary format that the service provider can consume and convert into an OSLC AM format. The service may use content negotiation with the Accept header to obtain the desired content type.
dcterms:title	Exactly-one	false	XMLLiteral	N/A	Unspecified	Title of the resource represented as rich text in XHTML content.
dcterms:type	Zero-or-many	false	string	N/A	Unspecified	A short string representation for the type, for example 'Car'.
jazz_am:derives	Zero-or-many	false	Resource	Reference	oslc:Any	The resource that derives from another resource originated from or is significantly influenced by the referenced resource. For example a model element derives from a requirement.
jazz_am:elaborates	Zero-or-many	false	Resource	Reference	oslc:Any	This resource elaborates the referenced resource.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
jazz_am:external	Zero-or-many	false	Resource	Reference	oslc:Any	A generic link from a resource to an external web page.
jazz_am:refine	Zero-or-many	false	Resource	Reference	oslc:Any	The target is a refinement of the source. (e.g. a use case scenario might be a refinement of a textual requirement that describes the interaction).
jazz_am:satisfy	Zero-or-many	false	Resource	Reference	oslc:Any	The model element satisfies the requirement (e.g. The use case satisfies a functional requirement).
jazz_am:trace	Zero-or-many	false	Resource	Reference	oslc:Any	The model element has a trace to the requirement (e.g. An attribute or its value are traced to a requirement).
oslc_sysmlv2:connector_Association	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Association	The Associations that type the Connector .
oslc_sysmlv2:connector_ConnectorEnd	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The endFeatures of a Connector , which redefine the endFeatures of the associations of the Connector . The connectorEnds determine via ReferenceSubsetting Relationships which Features are related by the Connector .
oslc_sysmlv2:connector_RelatedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Features that are related by this Connector considered as a Relationship and that restrict the links it identifies, given by the referenced Features of the connectorEnds of the Connector .
oslc_sysmlv2:connector_SourceFeature	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Feature	The source relatedFeature for this Connector . It is the first relatedFeature .
oslc_sysmlv2:connector_TargetFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The target relatedFeatures for this Connector . This includes all the relatedFeatures other than the sourceFeature .
oslc_sysmlv2:element_AliasIds	Zero-or-many	false	unspecified	Either	xsd:string	Various alternative identifiers for this Element. Generally, these will be set by tools.
oslc_sysmlv2:element_DeclaredName	Zero-or-one	false	unspecified	Either	xsd:string	The declared name of this Element .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_DeclaredShortName	Zero-or-one	false	unspecified	Either	xsd:string	An optional alternative name for the Element that is intended to be shorter or in some way more succinct than its primary name . It may act as a modeler-specified identifier for the Element , though it is then the responsibility of the modeler to maintain the uniqueness of this identifier within a model or relative to some other context.
oslc_sysmlv2:element_Documentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Documentation	The Documentation owned by this Element.
oslc_sysmlv2:element_ElementId	Exactly-one	false	unspecified	Either	xsd:string	The globally unique identifier for this Element. This is intended to be set by tooling, and it must not change during the lifetime of the Element.
oslc_sysmlv2:element_IsImpliedIncluded	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all necessary implied Relationships have been included in the ownedRelationships of this Element. This property may be true, even if there are not actually any ownedRelationships with isImplied = true , meaning that no such Relationships are actually implied for this Element. However, if it is false, then ownedRelationships may <i>not</i> contain any implied Relationships. That is, either <i>all</i> required implied Relationships must be included, or none of them.
oslc_sysmlv2:element_IsLibraryElement	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Element is contained in the ownership tree of a library model.
oslc_sysmlv2:element_Name	Zero-or-one	false	unspecified	Either	xsd:string	The name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveName() operation. By default, it is the same as the declaredName , but this is overridden for certain kinds of Elements to compute a name even when the declaredName is null.
oslc_sysmlv2:element_OwnedAnnotation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Annotation	The ownedRelationships of this Element that are Annotations , for which this Element is the annotatedElement .
oslc_sysmlv2:element_OwnedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements owned by this Element, derived as the ownedRelatedElements of the ownedRelationships of this Element.
oslc_sysmlv2:element_OwnedRelationship	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationships for which this Element is the owningRelatedElement .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:element_Owner	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The owner of this Element, derived as the owningRelatedElement of the owningRelationship of this Element, if any.
oslc_sysmlv2:element_OwningMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:OwningMembership	The owningRelationship of this Element , if that Relationship is a Membership .
oslc_sysmlv2:element_OwningNamespace	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Namespace	The Namespace that owns this Element , which is the membershipOwningNamespace of the owningMembership of this Element , if any.
oslc_sysmlv2:element_OwningRelationship	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Relationship	The Relationship for which this Element is an ownedRelatedElement , if any.
oslc_sysmlv2:element_QualifiedName	Zero-or-one	false	unspecified	Either	xsd:string	The full ownership-qualified name of this Element , represented in a form that is valid according to the KerML textual concrete syntax for qualified names (including use of unrestricted name notation and escaped characters, as necessary). The qualifiedName is null if this Element has no owningNamespace or if there is not a complete ownership chain of named Namespace s from a root Namespace to this Element .
oslc_sysmlv2:element_ShortName	Zero-or-one	false	unspecified	Either	xsd:string	The short name to be used for this Element during name resolution within its owningNamespace . This is derived using the effectiveShortName() operation. By default, it is the same as the declaredShortName , but this is overridden for certain kinds of Elements to compute a shortName even when the declaredName is null.
oslc_sysmlv2:element_TextualRepresentation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TextualRepresentation	The TextualRepresentations that annotate this Element .
oslc_sysmlv2:feature_ChainingFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The Feature that are chained together to determine the values of this Feature , derived from the chainingFeatures of the ownedFeatureChainings of this Feature , in the same order. The values of a Feature with chainingFeatures are the same as values of the last Feature in the chain, which can be found by starting with the values of the first Feature (for each instance of the domain of the original Feature), then using each of those as domain instances to find the values of the second Feature in chainingFeatures, and so on, to values of the last Feature .
oslc_sysmlv2:feature_Direction	Zero-or-one	false	unspecified	Either	oslc_sysmlv2:FeatureDirectionKind	Indicates how values of this Feature are determined or used (as specified for the FeatureDirectionKind).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_EndOwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is related to this Feature by an EndFeatureMembership in which the Feature is an ownedMemberFeature .
oslc_sysmlv2:feature_FeaturingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that feature this Feature , such that any instance in the domain of the Feature must be classified by all of these Types , including at least all the featuringTypes of its typeFeaturings . If the Feature is chained, then the featuringTypes of the first Feature in the chain are also featuringTypes of the chained Feature .
oslc_sysmlv2:feature_IsComposite	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the Feature is a composite feature of its featuringType . If so, the values of the Feature cannot exist after its featuring instance no longer does.
oslc_sysmlv2:feature_IsDerived	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can always be computed from the values of other Features .
oslc_sysmlv2:feature_IsEnd	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not the this Feature is an end Feature , requiring a different interpretation of the multiplicity of the Feature .
oslc_sysmlv2:feature_IsNonunique	Exactly-one	false	unspecified	Either	xsd:boolean	isNonunique.
oslc_sysmlv2:feature_IsOrdered	Exactly-one	false	unspecified	Either	xsd:boolean	Whether an order exists for the values of this Feature or not.
oslc_sysmlv2:feature_IsPortion	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature are contained in the space and time of instances of the domain of the Feature and represent the same thing as those instances.
oslc_sysmlv2:feature_IsReadOnly	Exactly-one	false	unspecified	Either	xsd:boolean	Whether the values of this Feature can change over the lifetime of an instance of the domain.
oslc_sysmlv2:feature_IsUnique	Exactly-one	false	unspecified	Either	xsd:boolean	Whether or not values for this Feature must have no duplicates or not.
oslc_sysmlv2:feature_OwnedFeatureChaining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureChaining	The ownedRelationships of this Feature that are FeatureChainings , for which the Feature will be the featureChained .
oslc_sysmlv2:feature_OwnedFeatureInverting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureInverting	The ownedRelationships of this Feature that are FeatureInvertings and for which the Feature is the featureInverted .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:feature_OwnedRedefinition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Redefinition	The ownedSubsettings of this Feature that are Redefinitions , for which the Feature is the redefiningFeature .
oslc_sysmlv2:feature_OwnedReferenceSubsetting	Zero-or-one	false	Resource	Either	oslc_sysmlv2:ReferenceSubsetting	The one ownedSubsetting of this Feature , if any, that is a ReferenceSubsetting , for which the Feature is the referencingFeature .
oslc_sysmlv2:feature_OwnedSubsetting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Subsetting	The ownedSpecializations of this Feature that are Subsettings , for which the Feature is the subsettingFeature .
oslc_sysmlv2:feature_OwnedTypeFeaturing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TypeFeaturing	The ownedRelationships of this Feature that are TypeFeaturings and for which the Feature is the featureOfType .
oslc_sysmlv2:feature_OwnedTyping	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureTyping	The ownedSpecializations of this Feature that are FeatureTypings , for which the Feature is the typedFeature .
oslc_sysmlv2:feature_OwningFeatureMembership	Zero-or-one	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMembership that owns this Feature as an ownedMemberFeature , determining its owningType .
oslc_sysmlv2:feature_OwningType	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Type	The Type that is the owningType of the owningFeatureMembership of this Feature .
oslc_sysmlv2:feature_Type	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	Types that restrict the values of this Feature , such that the values must be instances of all the types . The types of a Feature are derived from its typings and the types of its subsettings . If the Feature is chained, then the types of the last Feature in the chain are also types of the chained Feature .
oslc_sysmlv2:namespace_ImportedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The Memberships in this Namespace that result from the ownedImports of this Namespace .
oslc_sysmlv2:namespace_Member	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The set of all member Elements of this Namespace , which are the memberElements of all memberships of the Namespace .
oslc_sysmlv2:namespace_Membership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships in this Namespace , including (at least) the union of ownedMemberships and importedMemberships .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:namespace_OwnedImport	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Import	The ownedRelationships of this Namespace that are Imports , for which the Namespace is the importOwningNamespace .
oslc_sysmlv2:namespace_OwnedMember	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The owned members of this Namespace , which are the ownedMemberElements of the ownedMemberships of the ..
oslc_sysmlv2:namespace_OwnedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	The ownedRelationships of this Namespace that are Memberships , for which the Namespace is the membershipOwningNamespace .
oslc_sysmlv2:relationship_IsImplied	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Relationship was generated by tooling to meet semantic rules, rather than being directly created by a modeler.
oslc_sysmlv2:relationship_OwnedRelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements of this Relationship that are owned by the Relationship.
oslc_sysmlv2:relationship_OwningRelatedElement	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Element	The relatedElement of this Relationship that owns the Relationship, if any.
oslc_sysmlv2:relationship_RelatedElement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The Elements that are related by this Relationship, derived as the union of the source and target Elements of the Relationship.
oslc_sysmlv2:relationship_Source	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements from which this Relationship is considered to be directed..
oslc_sysmlv2:relationship_Target	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Element	The relatedElements to which this Relationship is considered to be directed.
oslc_sysmlv2:type_DifferencingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with differencingTypes are asserted to be those of the first of those Types , but not including those of the remaining Types . For example, a Classifier might be the difference of a Classifier for people and another for people of a particular nationality, leaving people who are not of that nationality. Similarly, a feature of people might be the difference between a feature for their children and a Classifier for people of a particular sex, identifying their children not of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_DirectedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The features of this Type that have a non-null direction .
oslc_sysmlv2:type_EndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features of this Type with isEnd = true .
oslc_sysmlv2:type_Feature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the featureMemberships of this Type .
oslc_sysmlv2:type_FeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The FeatureMemberships for features of this Type , which include all ownedFeatureMemberships and those inheritedMemberships that are FeatureMemberships (but does <i>not</i> include any importedMemberships).
oslc_sysmlv2:type_InheritedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All the memberFeatures of the inheritedMemberships of this Type that are FeatureMemberships .
oslc_sysmlv2:type_InheritedMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Membership	All Memberships inherited by this Type via Specialization or Conjugation . These are included in the derived union for the memberships of the Type .
oslc_sysmlv2:type_Input	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction in or inout ..
oslc_sysmlv2:type_IntersectingType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with intersectingTypes are asserted to be those in common among the intersectingTypes , which are the Types derived from the intersectingType of the ownedIntersectings of this Type . For example, a Classifier might be an intersection of Classifiers for people of a particular sex and of a particular nationality. Similarly, a feature for people's children of a particular sex might be the intersection of a Feature for their children and a Classifier for people of that sex (because the interpretations of the children Feature that identify those of that sex are also interpretations of the Classifier for that sex).
oslc_sysmlv2:type_IsAbstract	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether instances of this Type must also be instances of at least one of its specialized Types .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_IsConjugated	Exactly-one	false	unspecified	Either	xsd:boolean	Indicates whether this Type has an ownedConjugator .
oslc_sysmlv2:type_IsSufficient	Exactly-one	false	unspecified	Either	xsd:boolean	Whether all things that meet the classification conditions of this Type must be classified by the Type .
oslc_sysmlv2:type_Multiplicity	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Multiplicity	An ownedMember of this Type that is a Multiplicity , which constraints the cardinality of the Type . If there is no such ownedMember , then the cardinality of this Type is constrained by all the Multiplicity constraints applicable to any direct supertypes.
oslc_sysmlv2:type_Output	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All features related to this Type by FeatureMemberships that have direction out or inout ..
oslc_sysmlv2:type_OwnedConjugator	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Conjugation	A Conjugation owned by this Type for which the Type is the originalType .
oslc_sysmlv2:type_OwnedDifferencing	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Differencing	The ownedRelationships of this Type that are Differencings , having this Type as their typeDifferenced .
oslc_sysmlv2:type_OwnedDisjoining	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Disjoining	The ownedRelationships of this Type that are Disjoinings , for which the Type is the typeDisjoined Type .
oslc_sysmlv2:type_OwnedEndFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	All endFeatures of this Type that are ownedFeatures .
oslc_sysmlv2:type_OwnedFeature	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Feature	The ownedMemberFeatures of the ownedFeatureMemberships of this Type .
oslc_sysmlv2:type_OwnedFeatureMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FeatureMembership	The ownedMemberships of this Type that are FeatureMemberships , for which the Type is the owningType . Each such FeatureMembership identifies an ownedFeature of the Type .
oslc_sysmlv2:type_OwnedIntersecting	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Intersecting	The ownedRelationships of this Type that are Intersectings , have the Type as their typeIntersected .
oslc_sysmlv2:type_OwnedSpecialization	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Specialization	The ownedRelationships of this Type that are Specializations , for which the Type is the specific Type .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:type_OwnedUnioning	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Unioning	The ownedRelationships of this Type that are Unionings , having the Type as their typeUnioned .
oslc_sysmlv2:type_UnioningType	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Type	The interpretations of a Type with unioningTypes are asserted to be the same as those of all the unioningTypes together, which are the Types derived from the unioningType of the ownedUnionings of this Type . For example, a Classifier for people might be the union of Classifiers for all the sexes. Similarly, a feature for people's children might be the union of features dividing them in the same ways as people in general.
oslc_sysmlv2:usage_Definition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Classifier	The Classifiers that are the types of this Usage . Nominally, these are Definitions , but other kinds of Kernel Classifiers are also allowed, to permit use of Classifiers from the Kernel Model Libraries.
oslc_sysmlv2:usage_DirectedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The usages of this Usage that are directedFeatures .
oslc_sysmlv2:usage_IsReference	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is a referential Usage , that is, it has isComposite = false .
oslc_sysmlv2:usage_IsVariation	Exactly-one	false	unspecified	Either	xsd:boolean	Whether this Usage is for a variation point or not. If true, then all the memberships of the Usage must be VariantMemberships .
oslc_sysmlv2:usage_NestedAction	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ActionUsage	The ActionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAllocation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AllocationUsage	The AllocationUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAnalysisCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AnalysisCaseUsage	The AnalysisCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedAttribute	Zero-or-many	false	Resource	Either	oslc_sysmlv2:AttributeUsage	The code>AttributeUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedCalculation	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CalculationUsage	The CalculationUsage that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:CaseUsage	The CaseUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConcern	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConcernUsage	The ConcernUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedConnection	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConnectorAsUsage	The ConnectorAsUsages that are nestedUsages of this Usage. Note that this list includes BindingConnectorAsUsages and SuccessionAsUsages, even though these are ConnectorAsUsages but not ConnectionUsages.
oslc_sysmlv2:usage_NestedConstraint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ConstraintUsage	The ConstraintUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedEnumeration	Zero-or-many	false	Resource	Either	oslc_sysmlv2:EnumerationUsage	The code>EnumerationUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedFlow	Zero-or-many	false	Resource	Either	oslc_sysmlv2:FlowConnectionUsage	The code>FlowConnectionUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedInterface	Zero-or-many	false	Resource	Either	oslc_sysmlv2:InterfaceUsage	The InterfaceUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedItem	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ItemUsage	The ItemUsages that are nestedUsages of this Usage.
oslc_sysmlv2:usage_NestedMetadata	Zero-or-many	false	Resource	Either	oslc_sysmlv2:MetadataUsage	The MetadataUsages that are nestedUsages of this of this Usage.
oslc_sysmlv2:usage_NestedOccurrence	Zero-or-many	false	Resource	Either	oslc_sysmlv2:OccurrenceUsage	The OccurrenceUsages that are nestedUsages of this Usage.

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedPart	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PartUsage	The PartUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedPort	Zero-or-many	false	Resource	Either	oslc_sysmlv2:PortUsage	The PortUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedReference	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ReferenceUsage	The ReferenceUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRendering	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RenderingUsage	The RenderingUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedRequirement	Zero-or-many	false	Resource	Either	oslc_sysmlv2:RequirementUsage	The RequirementUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedState	Zero-or-many	false	Resource	Either	oslc_sysmlv2:StateUsage	The StateUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedTransition	Zero-or-many	false	Resource	Either	oslc_sysmlv2:TransitionUsage	The TransitionUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedUsage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are ownedFeatures of this Usage .
oslc_sysmlv2:usage_NestedUseCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:UseCaseUsage	The UseCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedVerificationCase	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VerificationCaseUsage	The VerificationCaseUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_NestedView	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewUsage	The ViewUsages that are nestedUsages of this Usage .

Prefixed Name	Occurs	Read-only	Value-type	Representation	Range	Description
oslc_sysmlv2:usage_NestedViewpoint	Zero-or-many	false	Resource	Either	oslc_sysmlv2:ViewpointUsage	The ViewpointUsages that are nestedUsages of this Usage .
oslc_sysmlv2:usage_OwningDefinition	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Definition	The Definition that owns this Usage (if any).
oslc_sysmlv2:usage_OwningUsage	Zero-or-one	false	Resource	Either	oslc_sysmlv2:Usage	The Usage in which this Usage is nested (if any).
oslc_sysmlv2:usage_Usage	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages that are features of this Usage (not necessarily owned).
oslc_sysmlv2:usage_Variant	Zero-or-many	false	Resource	Either	oslc_sysmlv2:Usage	The Usages which represent the variants of this Usage as a variation point Usage , if isVariation = true . If isVariation = false , then there must be no variants .
oslc_sysmlv2:usage_VariantMembership	Zero-or-many	false	Resource	Either	oslc_sysmlv2:VariantMembership	The ownedMemberships of this Usage that are VariantMemberships . If isVariation = true , then this must be all memberships of the Usage . If isVariation = false , then variantMembership must be empty.
oslc:instanceShape	Zero-or-one	false	Resource	Reference	oslc:ResourceShape	The URI of a Resource Shape that describes the possible properties, occurrence, value types, allowed values and labels. This shape information is useful in displaying the subject resource as well as guiding clients in performing modifications. Instance shapes may be specific to the authenticated user associated with the request that retrieved the resource, the current state of the resource and other factors and thus should not be cached.
oslc:serviceProvider	Zero-or-many	false	Resource	Reference	oslc:ServiceProvider	A link to the resource's OSLC Service Provider. There may be cases when the subject resource is available from a service provider that implements multiple domain specifications, which could result in multiple values for this property.
oslc:shortTitle	Zero-or-one	false	XMLLiteral	N/A	Unspecified	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element [sml-172].
rdf:type	Zero-or-many	false	Resource	Reference	rdfs:Class	The resource type URIs.

3. Conformance

OSLC SysML v2 servers **MUST** follow the constraints defined here where required, and with the meanings defined here.

OSLC SysML v2 servers **MAY** provide additional constraints for specific purposes.

Clause Number	Requirement
sml-172	Short name identifying a resource, often used as an abbreviated identifier for presentation to end-users. SHOULD include only content that is valid inside an XHTML element