

\* Exemple de requête pour convertir une monnaie du dollar américain à l'euro:

\*

Parameters

Cancel

Name	Description
<b>from</b> * required string (query)	Code ISO de la devise source (ex: USD) <input type="text" value="USD"/>
<b>to</b> * required string (query)	Code ISO de la devise cible (ex: XAF) <input type="text" value="EUR"/>
<b>amount</b> * required number(\$double) (query)	Montant à convertir <input type="text" value="100"/>

Execute

Clear

Responses

Curl

```
curl -X 'GET' \
'http://localhost:8080/api/convert?from=USD&to=EUR&amount=100' \
-H 'accept: */*'
```

Request URL

```
http://localhost:8080/api/convert?from=USD&to=EUR&amount=100
```

Server response

Code	Details
200	<div><div>Response body</div><div><pre>{   "from": "USD",   "to": "EUR",   "amount": 100,   "rate": 0.8747,   "result": 87.47 }</pre></div><div><div>Download</div></div></div>

Exemple de requête pour convertir du Francs CFA au Yuan chinois:

Parameters

Cancel

Name	Description
<b>from</b> * required string (query)	Code ISO de la devise source (ex: USD) <input type="text" value="XAF"/>
<b>to</b> * required string (query)	Code ISO de la devise cible (ex: XAF) <input type="text" value="CNY"/>
<b>amount</b> * required number(\$double) (query)	Montant à convertir <input type="text" value="5000"/>

Execute

Clear

Responses

Curl

```
curl -X 'GET' \
'http://localhost:8080/api/convert?from=XAF&to=CNY&amount=5000' \
-H 'accept: */*'
```

Request URL

```
http://localhost:8080/api/convert?from=XAF&to=CNY&amount=5000
```

Server response

Code	Details
200	<div><div>Response body</div><div><pre>{   "from": "XAF",   "to": "CNY",   "amount": 5000,   "rate": 0.01254,   "result": 62.7 }</pre></div><div><div>Download</div></div></div>