```
!
no ip domain-lookup
!
!
spanning-tree mode pvst
!
!
!
!
!
!
interface GigabitEthernet0/0
 ip address 172.16.1.1 255.255.255.0
 duplex auto
 speed auto
!
interface GigabitEthernet0/1
 ip address 172.31.1.1 255.255.255.0
 duplex auto
 speed auto
 shutdown
!
interface Vlan1
 no ip address
 shutdown
!
ip classless
!
ip flow-export version 9
!
!
!
banner motd ^C!! Warning - Authorized Access Only !!^C
!
!
!
!
line con 0
 password cisco
 logging synchronous
 login
!
line aux 0
!
line vty 0 4
 password cisco
 login
line vty 5 15
 password cisco
 login
!
!
!
end


RTA#
```

```
RTA# show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet0/0     172.16.1.1      YES manual up                    up
GigabitEthernet0/1     172.31.1.1      YES manual administratively down down
Vlan1                  unassigned      YES unset  administratively down down
RTA#S
```

```
RTA(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/1, changed state to up

RTA(config-if)#end
RTA#
%SYS-5-CONFIG_I: Configured from console by console

RTA#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
RTA(config)#hostname
% Incomplete command.
RTA(config)#hostname RTA-1
RTA-1(config)#end
RTA-1#
%SYS-5-CONFIG_I: Configured from console by console

RTA-1# copy running-config startup-config
Destination filename [startup-config]?
Building configuration...
[OK]
RTA-1# copy running-config startup-config
Destination filename [startup-config]?
Building configuration...
[OK]
RTA-1#copy running-config
% Incomplete command.
RTA-1#copy running-config tftp:
Address or name of remote host []? 172.16.1.2
Destination filename [RTA-1-confg]?

Writing running-config...!!
[OK - 849 bytes]

849 bytes copied in 0 secs
RTA-1#show flash

System flash directory:
File  Length   Name/status
  3   33591768 c1900-universalk9-mz.SPA.151-4.M4.bin
  2   28282    sigdef-category.xml
  1   227537   sigdef-default.xml
[33847587 bytes used, 221896413 available, 255744000 total]
249856K bytes of processor board System flash (Read/Write)


RTA-1#copy flash tftp:
Source filename []? c1900-universalk9-mz.SPA.151-4.M4.bin
Address or name of remote host []? 172.16.1.2
Destination filename [c1900-universalk9-mz.SPA.151-4.M4.bin]?

Writing c1900-universalk9-mz.SPA.
151-4.M4.bin...!!!
```

คำถามข้อ 1: What changes were made? (มีการเปลี่ยนแปลงอะไรบ้าง)

> Configuration ที่เก็บไว้บน TFTP Server ถูกโหลดเข้ามาที่ router และ hostname ของ router เปลี่ยนจาก "Router" เป็น "RTA"

คำถามข้อ 2: Are all interfaces active? (interface ทำงานครบทุกพอร์ตหรือไม่)

> ไม่ครบ — G0/1 (GigabitEthernet0/1) อยู่ในสถานะ administratively down

คำถามข้อ 3: What special character repeatedly displays indicating that the IOS file is being copied to the TFTP server successfully? (สัญลักษณ์อะไรที่แสดงซ้ำๆ ระหว่างการก็อปปี้ไฟล์ IOS สำเร็จ)

> เครื่องหมายตกใจ (!) — exclamation point