

# Machine Learning Engineer Nanodegree

---

## Capstone Proposal

---

Jiri Vransky Jun 9th, 2017

### Using deep learning for anomaly detection in geophysical survey

---

The usual result of any geophysical survey is a dataset with the description of features hidden under the Earth surface. Analysis of such dataset requires a lot of skills and specific knowledge. Precise analysis takes long time even for a skilled geophysicist. There are a lot of situations, where we need to do a quick survey on site. For example the detection of damaged infrastructure after an earthquake or flooding. The rescue team needs to be able to do a quick survey, with the instant result if possible. Some level of precision can be traded for speed in such situation.

Recent research shows that the methods of computer vision can be used for analysis of potential field provided by the gravimeter. This includes the machine learning methods. The potential field model of gravitation anomaly [1] can be visualized as a 2D or 3D image. The final goal, beyond the scope of this project is to create a fast but reliable anomaly detection and classification model.

#### Problem Statement

Gravity anomaly is the difference between expected and observed gravity value. The anomaly indicates, that under the earth surface are objects with different density. The contrast of densities can show us heavy objects or cavities. Various anomalies generate the various potential field. In this project, I would like to create the anomaly (object) type classifier.

#### Datasets and Inputs

Traditional geophysical surveys do not provide enough data to train the machine learning models. Either the datasets are small or not available for public or both. Thus the artificial dataset with several anomaly types was created. This dataset is based on the models described in [1]. The real field data do not correspond with the artificial model, but can be interpolated to the same format with the gridding process.

Dataset consists of 47890 synthetical models for the area of size 100x100 meters. The sampling step in measuring is 1 m. Modeled anomalies are: spherical anomaly, vertical cylinder, horizontal cylinder and rectangular prism. All anomalies have random size, and each model contains a random level of noise. Each of the models can be represented with 100x100x1 tensor with a known label. Dataset also contains a subset of the random noise only data - without any modeled anomaly.

#### Solution Statement

I would like to use methods of deep learning, especially the Convolutional Neural Networks (CNN) to create the classifier. The CNN are a very effective solution for finding patterns in the images and for the image classification. They should work well for the potential field too. I would like to explore several CNN architectures, to achieve best possible accuracy and training speed on test data. Benchmark Model

I will use two benchmark models. First one will be the simple linear model  $Wx + b$ . The second one will be older model published in [2]. This is classic computer vision model, with methods such as edge and line detection.

#### Evaluation Metrics

I will compare the accuracy, training time and prediction time of all models trained on the same dataset. The main evaluation metrics will be the accuracy. I will shuffle and then split the data to the train validation and test set before training. I will use 80% of data for training, 10% for validation and 10% for a final test.

#### Project Design

I will use Python 3 with Numpy, Scipy, Pandas and TensorFlow packages to solve the project. As a first step, I will convert the dataset to the Tensorflow records. Currently, the data are in text files, each file is labeled by anomaly type and location. This format was required for the other experiments with the dataset. I will grab the label from the file name, and store it to the record together with the dimensions and the potential field. Then I have to look closer to the data and check if the normalization will help in the future classifier training. The potential values are different from the traditional image data. Still the normalization may help to get better results.

Then I will train the basic linear benchmark model. In this step, I will create necessary tools for loading the TensorFlow records and test if all software packages are working as expected.

I'm planning to test several CNN architectures. As my knowledge of CNN is not deep enough to design brand new architecture, my plan is start with CNN that I created during the DeepLearning project - digit recognizer. That means that I will start with three convolutional layers and two fully connected layers with dropout.

During the training of model, I will measure accuracy on the validation set. I will tune the model hyperparameters until the model will start to minimize the error and increase the accuracy. I will also record the training time on the whole dataset.

## Sources

[1]: Salem, A: Multi-deconvolution analysis of potential field data, Journal of Applied Geophysics, 2011, Vol. 74, Issue 2-3, Pages 151-156.

[2]: Koskova Triskova L., Novak J.: Application of edge and line detection to detect the near surface anomalies in potential data, 2013, International conference on Pattern recognition Applications and Methods 2013, Barcelona, poster and paper