| | |
|---|---|
| **Started on** | Monday, 28 September 2026, 9:12 PM |
| **State** | Finished |
| **Completed on** | Monday, 28 September 2026, 9:21 PM |
| **Time taken** | 9 mins 36 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

**Answer:** (penalty regime: 0 %)

```
#include<stdio.h>
#include<stdlib.h>
int cmp(const void*a,const void*b){
int x=*(int*)a,y=*(int*)b;
return(x>y)-(x<y);
}
int main(){
int n;
long long s=0;
scanf("%d",&n);
int*a=malloc(n*sizeof(int));
for(int i=0;i<n;i++)scanf("%d",&a[i]);
qsort(a,n,sizeof(int),cmp);
for(int i=0;i<n;i++)s+=(long long)a[i]*i;
printf("%lld",s);
return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 5<br>2<br>5<br>3<br>4<br>0 | 40 | 40 | ✔ |

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 10<br>2<br>2<br>2<br>4<br>4<br>3<br>3<br>5<br>5<br>5 | 191 | 191 | ✔ |
| ✔ | 2<br>45<br>3 | 45 | 45 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.