

Lab 12

```
countData <- read.csv("airway_scaledcounts.csv", row.names=1)
metadata <- read.csv("airway_metadata.csv")
```

```
head(countData)
```

	SRR1039508	SRR1039509	SRR1039512	SRR1039513	SRR1039516
ENSG00000000003	723	486	904	445	1170
ENSG00000000005	0	0	0	0	0
ENSG000000000419	467	523	616	371	582
ENSG000000000457	347	258	364	237	318
ENSG000000000460	96	81	73	66	118
ENSG000000000938	0	0	1	0	2

	SRR1039517	SRR1039520	SRR1039521
ENSG00000000003	1097	806	604
ENSG00000000005	0	0	0
ENSG000000000419	781	417	509
ENSG000000000457	447	330	324
ENSG000000000460	94	102	74
ENSG000000000938	0	0	0

```
head(metadata)
```

	id	dex	celltype	geo_id
1	SRR1039508	control	N61311	GSM1275862
2	SRR1039509	treated	N61311	GSM1275863
3	SRR1039512	control	N052611	GSM1275866
4	SRR1039513	treated	N052611	GSM1275867
5	SRR1039516	control	N080611	GSM1275870
6	SRR1039517	treated	N080611	GSM1275871

Q1. How many genes are in this dataset?

```
nrow(countData)
```

```
[1] 38694
```

Q2. How many 'control' cell lines do we have?

```
sum(metadata$dex == "control")
```

```
[1] 4
```

```
control.inds <- metadata$dex == "control"
```

b. Extract all the control columns from `countData` and call it `control.counts`

Q3. How would you make the above code in either approach more robust?

```
control.counts <- (countData[, control.inds])
```

c. Calculate the mean value across the rows of control counts o.e calculate the mean count values for each gene in the control samples

```
control.means <- rowMeans(control.counts)
head(control.means)
```

```
ENSG00000000003 ENSG00000000005 ENSG000000000419 ENSG000000000457 ENSG000000000460
      900.75           0.00           520.50           339.75           97.25
ENSG000000000938
      0.75
```

-Step 2 Calculate the mean of the treated samples

Q4. Follow the same procedure for the treated samples (i.e. calculate the mean per gene across drug treated samples and assign to a labeled vector called `treated.mean`)

```
treated.mean <- rowMeans (countData[, metadata$dex == "treated"])
head(treated.mean)
```


```
ENSG00000000003 ENSG00000000005 ENSG000000000419 ENSG000000000457 ENSG000000000460
      658.00           0.00           546.00           316.50           78.75
ENSG000000000938
      0.00
```

```
meancounts <- data.frame(control.means, treated.mean)
colSums(meancounts)
```

```
control.means  treated.mean
      23005324      22196524
```


Q5 (a). Create a scatter plot showing the mean of the treated samples against the mean of the control samples. Your plot should look something like the following.

```
plot(meancounts)
```



Q5 (b). You could also use the ggplot2 package to make this figure producing the plot below. What `geom_?()` function would you use for this plot?

```
library(ggplot2)
ggplot(meancounts, aes(x= control.means, y= treated.mean)) +
  geom_point()
```




Q6. Try plotting both axes on a log scale. What is the argument to `plot()` that allows you to do this?

```
plot(meancounts, log="xy")
```

Warning in `xy.coords(x, y, xlabel, ylabel, log)`: 15032 x values ≤ 0 omitted from logarithmic plot

Warning in `xy.coords(x, y, xlabel, ylabel, log)`: 15281 y values ≤ 0 omitted from logarithmic plot



```
log2(20/20)
```

```
[1] 0
```

```
log2(20/10)
```

```
[1] 1
```

```
log2(10/20)
```

```
[1] -1
```

```
log2(40/10)
```

```
[1] 2
```

```
meancounts$log2fc <- log2(meancounts$treated.mean/meancounts$control.means)
head(meancounts)
```

	control.means	treated.mean	log2fc
ENSG00000000003	900.75	658.00	-0.45303916

ENSG000000000005	0.00	0.00	NaN
ENSG0000000000419	520.50	546.00	0.06900279
ENSG0000000000457	339.75	316.50	-0.10226805
ENSG0000000000460	97.25	78.75	-0.30441833
ENSG0000000000938	0.75	0.00	-Inf

Q8. How many genes are up regulated at the common threshold of +2 log2FC values?

```
sum(meancounts$log2fc >= 2, na.rm=TRUE)
```

```
[1] 1910
```

Q9. Using the down.ind vector above can you determine how many down regulated genes we have at the greater than 2 fc level?

```
sum(up.ind <- meancounts$log2fc > 2, na.rm=TRUE)
```

```
[1] 1846
```

```
sum(down.ind <- meancounts$log2fc < (-2), na.rm=TRUE)
```

```
[1] 2212
```

Q10. Do you trust these results? Why or why not?

Yes, I wouldn't trust these results just yet because fold change can be large (e.g. >>two-fold up- or down-regulation) without being statistically significant (e.g. based on p-values). We have not done anything yet to determine whether the differences we are seeing are significant. These results in their current form are likely to be very misleading.

```
library(DESeq2)
```

Loading required package: S4Vectors

Loading required package: stats4

Loading required package: BiocGenerics

Attaching package: 'BiocGenerics'

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

```
anyDuplicated, aperm, append, as.data.frame, basename, cbind,  
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,  
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,  
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,  
Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,  
table, tapply, union, unique, unsplit, which.max, which.min
```

Attaching package: 'S4Vectors'

The following objects are masked from 'package:base':

```
expand.grid, I, unname
```

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

```
colAlls, colAnyNAs, colAnys, colAvgPerRowSet, colCollapse,  
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,  
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,  
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,  
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,  
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,  
colWeightedMeans, colWeightedMedians, colWeightedSds,  
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgPerColSet,  
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,  
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,  
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,  
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,  
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,  
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,  
rowWeightedSds, rowWeightedVars
```

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with
'browseVignettes()'. To cite Bioconductor, see
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

To use DESeq we need our input `countData` and `ColData` in a specific format that DESeq wants:

```
dds <- DESeqDataSetFromMatrix(countData = countData,  
                              colData = metadata,  
                              design = ~dex)
```

converting counts to integer mode

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in
design formula are characters, converting to factors

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

To get the results out of this `dds` object we can use the `results()` function from the package.

```
res <- results(dds)  
head(res)
```

log2 fold change (MLE): dex treated vs control


Wald test p-value: dex treated vs control

DataFrame with 6 rows and 6 columns


	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG000000000003	747.194195	-0.3507030	0.168246	-2.084470	0.0371175
ENSG000000000005	0.000000	NA	NA	NA	NA
ENSG0000000000419	520.134160	0.2061078	0.101059	2.039475	0.0414026
ENSG0000000000457	322.664844	0.0245269	0.145145	0.168982	0.8658106
ENSG0000000000460	87.682625	-0.1471420	0.257007	-0.572521	0.5669691
ENSG0000000000938	0.319167	-1.7322890	3.493601	-0.495846	0.6200029
	padj				
	<numeric>				
ENSG000000000003	0.163035				
ENSG000000000005	NA				
ENSG0000000000419	0.176032				
ENSG0000000000457	0.961694				
ENSG0000000000460	0.815849				
ENSG0000000000938	NA				

Let's make a final (for today) plot of log2 fold-change vs the adjusted P-value

```
plot(res$log2FoldChange, res$padj)
```



```
plot(res$log2FoldChange, -log(res$padj))
abline(v=c(+2, -2), col="blue")
abline(h=-log(0.05), col="blue")
```



Finally we can make a color vector to use in the plot to better highlight the genes we care about.

```
mycols <- rep("gray", nrow(res))
mycols[abs(res$log2FoldChange) >= 2] <- "red"
mycols[res$padj > 0.05] <- "gray"

plot(res$log2FoldChange, -log(res$padj), col= mycols)
abline(v=c(+2, -2), col="blue")
abline(h=-log(0.05), col="blue")
```

