Ex: 11
Date: 10/09/26

# ROUTing at Network Layer

a.) Simulates statics routing protocol configuration using CISCO Packet Tracer.

AIM:-

To configure static routing between different network using Cisco packet tracer and verify communication between the network.

Steps :-

1.) Open Cisco packet tracer
2.) Place 2 router, 2 switches and PC's
3.) Connect PC's to switches and switches to routers using Cables.
4.) Assign IP addresses to all PC's and router Interfaces
5.) Configure the router interface and enable the using no shutdown
6.) Configure static routers using the command.
7.) Configure static routers on both router
8.) Set the appropriate default gateway on each PC.
9.) Use the ping command to test communication between different network
10.) Use simulation Mode to observe the packet path.

RESULT:-

That the static routing was successfully configured between the network using Cisco packet tracer and Communication between the networkes was successfully verified using the ping Command.

11.b)
10/09/26

# Simulate RIP Using Cisco Packet Tracer

**AIM:-**

To Configure and simulate the routing information protocol (RIP) between routers using Cisco packet Tracer and verify network connectivity.

**Steps :-**

1.) Open Cisco Packet Tracer
2.) place 2 or 3 routers, switches and PC's
3.) Connect the devices using Ethernet cables
4.) Assign IP addresses to PC's and router interfaces
5.) Enable all router interfaces using no shutdown
6.) Configure RIP on the Routers
7.) Configure the appropriate network addresses on each router according to the topology.
8.) Check the routing table using : shows ip route
9.) ~~check~~ Use the ping command to test communication between PC's in different networks.
10.) Use Simulation mode to observe how RIP learns and select routers.

**RESULT :-**

RIP was successfully configured between the routers using Cisco packet Tracer. The routers learned the required network routers dynamically and Communication between different networks was successfully verified.