13

24/09/26

Implement Own Ping Program

AIM :-

To implement a user-defined Ping Program to check the reachability of a host & obtain its responsive time.

Algorithm :-

1. Start the Program
2. Get the hostname or IP address from the user
3. Execute a ping request to the specified host
4. Wait for response from the host.
5. If a reply is received, display the host is reachable and response details
6. If no reply is received, display the host is unreachable.
7. Stop the program.

Program :-

```
import java.io.*;
public class MyPing {
    public static void main (String [] a)
throws Exception {
    BufferedReader br = new BufferedReader
(new InputStreamReader (System.in));
System.out.print ("Enter host:");
String h = br.readline ();
Process P = Runtime.getRuntime().exec (new
    String [] { "Ping", "h", "4", h.});
BufferedReader r = new BufferedReader (new
InputStreamReader (P.getInputStream()));
String S;
```

Output :-

Enter host : google.com

Pinging google.com [142.251.223.235] with 32 bytes of data

Reply from 142.251.223.238 : byte = 32 time =

Reply from 142.251.223.238 : byte = 32 time = 6

Reply from 142.251.223.238 : byte = 32 time = 7

Reply from 142.251.223.238 : byte = 32 time = 7

Ping statistics for 142.251.223.238 :

Packet : sent = 4, Received = 4, Lost = 0

Approximate round trip times in ms = 6ms.

```
while ((s = r.readline()) != null)
        System.out.println(s);
    }
}
```

Result:

Thus, the java program was successfully implemented to check the reachability of a host & obtain its response information.