

Date : 05-Jun-21

Spring Boot 9AM

Mr. RAGHU

Full Cloud Workspace:

https://www.mediafire.com/file/kmlpmsgeny95x112/SpringBoot9AM_CLOUD_RAGHU_05062021.zip/file

Spring Cloud : Distributed Tracing {Sleuth and Zipkin}

Download Link:

<https://www.mediafire.com/file/jmpqrenm0yudehy/ZipkinExecutable.zip/file>

*) Distributed Tracing:- it is a process of finding execution path for a request for all MS# (which are executed).

=> Consider in realtime, one application contains multiple MS#. In that finding execution PATH for a request is not so easy. That can be traced using 'Sleuth and Zipkin'.

*) Sleuth supports 'FINDING EXECUTION TRACE' by giving one unique Id for that request ie called as TraceId (one id for complete path).

*) Sleuth supports 'FINDING ONE MS#' execution details by spanId.

*) All these details are printed at console/log file.
But I want to print all these at UI ie Zipkin Server(UI)

*) From Sleuth , Zipkin Client collects data (Sampling) and send to UI ie Zipkin server.

=====Zipkin Server Setup=====

S#1 Download Zipkin Server

<https://www.mediafire.com/file/jmpqrenm0yudehy/ZipkinExecutable.zip/file>

S#2 Extract to a folder and open folder

S#3 Open cmd location here

S#4 Enter command

> java -jar zipkin-server-2.12.9-exec.jar

S#5 Goto browser and enter URL

<http://localhost:9411/zipkin/>

S#6 To Stop Service : ctrl+C

----- (code) -----

MS#1

a.

Name: SpringCloudAppOneTest
Dep : Web, Sleuth and Zipkin Client

pom.xml

```
spring-cloud-starter-sleuth,  
spring-cloud-starter-sleuth
```

b. application.properties

```
server.port=8081  
spring.application.name=APP-ONE-TEST  
logging.file.name=D:/mylogs/appone.log
```

c. AppConfig

```
package in.nareshit.raghu.config;
```

```
import org.springframework.context.annotation.Bean;  
import org.springframework.context.annotation.Configuration;  
import org.springframework.web.client.RestTemplate;
```

```
import brave.sampler.Sampler;
```

```
@Configuration
```

```
public class AppConfig {
```

```
    @Bean
```

```
    public RestTemplate rt() {  
        return new RestTemplate();  
    }
```

```
    @Bean
```

```
    public Sampler alwaysSampler() {  
        return Sampler.ALWAYS_SAMPLE; //TURN ON  
        //return Sampler.NEVER_SAMPLE; //TURN OFF  
    }
```

```
}
```

d. RestController

```
package in.nareshit.raghu.rest;
```

```
import org.slf4j.Logger;  
import org.slf4j.LoggerFactory;  
import org.springframework.beans.factory.annotation.Autowired;  
import org.springframework.web.bind.annotation.GetMapping;  
import org.springframework.web.bind.annotation.RestController;  
import org.springframework.web.client.RestTemplate;
```

```
@RestController
```

```
public class AppOneRestController {
```

```
    private static final Logger LOG =  
    LoggerFactory.getLogger(AppOneRestController.class);
```

```
    @Autowired
```

```
    private RestTemplate rt;
```

```

        @GetMapping("/showA")
        public String showA() {
            LOG.info("WELCOME TO SERVICE #1 ");
            String msg =
rt.getForObject("http://localhost:8082/showB", String.class);
            LOG.info("BACK TO SERVICE #1 : MSG {}", msg);
            return "DONE";
        }
    }

}

=====
*** Repeate same for AppTwo and AppThree
** Start Zipkin server
** Run All MS and Enter URL
http://localhost:8081/showA
** Goto
http://localhost:9411/zipkin
>> click on find trace
> click on blue colorbar
> view all details

```

Q) What is TraceId? when is it generated?

A) TraceId is given for one request made to App.

That is used to find out complete path and associated log lines
[On request it is generated by Sleuth]

Q) What is SpanId and ParentId?

A) For one MS# in trace, is identified using SpandId.

If MS#2 is called by MS#1 then MS#1 SpandId is called as MS#2
ParentId.

Q) What is Sampling?

A) All Ids generated and execution paths are collected by Sleuth,
these are need to be given to Zipkin Client for sending to UI
[Zipkin Server UI], such collecting process is called as Sampling.

Q) Why RestController? can we use any other?

A) RestController is to make HTTP calls.

We can use Eureka and any one client.

MS#	App name	TraceId	spanId	Sample(Zipkin)
[APP-ONE-TEST,	57dc6425765f178b,	57dc6425765f178b,	true]	

Q) How Zipkin Client is Connected to Zipkin Server?

A)

> In Our MS# we need to add Zipkin Client along with Sleuth
> Zipkin Client contains default location of Zipkin Server
spring.zipkin.base-url=http://localhost:9411/

> If Zipkin server is running in Diff IP/PORT then we need to provide
externall in MS# above key=val

--