

Date
27/04/2019

Auto Refresh the PHP Page :

```
<?php
```

```
$page = $_SERVER['PHP_SELF'];
```

```
$sec = "10";
```

```
header("Refresh: $sec; url = $page");
```

```
echo "Watch the page reload itself in 10 seconds";
```

```
?>
```

Date
07/02/2017

Sorting Arrays

bool sort() array & \$array

Sort an array. Return TRUE on success or FALSE

Example: and reset index on failure.

<?php

```
$fruits = array("lemon", "orange", "banana",
```

```
    "apple");
```

```
sort($fruits);
```

```
foreach($fruits as $key => $val) {
```

```
    echo "fruits[" . $key . "] = " . $val . "\n";
```

Output:

```
fruits[0] = apple
```

```
fruits[1] = banana
```

```
fruits[2] = lemon
```

```
fruits[3] = orange
```

Example:

```
$arr = array(45, 32, 21, 101);
```

```
$resultArr = sort($arr);
```

```
print_r($arr);
```

```
echo "<br>";
```

```
print_r($resultArr);
```

Output:

```
Array ([0] => 21 [1] => 32 [2] => 45 [3] => 101)
```

1

Date
07/02/2017

~~ksort()~~

bool ksort(array &array) : Sort an array by key.

bool asort(array &array) : Sort an array and maintain index association.

bool rsort(array &array) : Sort an array in reverse order.

(Opposite of sort())

bool krsort(array &array) : Sort an array by key in reverse order.

(Opposite of ksort())

bool arsort(array &array) : Sort an array in reverse order and maintain index association.

(Opposite of asort())

Date
07/02/2017

file_get_contents()

Reads a file & storing it in a string variable.

Example: `$xyz = file_get_contents("http://blog.aajindia.com");`

An amp thing

~~`$xyz = 123 ;
echo '$xyz'; // $xyz
echo '{ $xyz }' // '123'`~~

An amp thing

`$x = 123 ;
$aa = 'a' ;
$ab = 2 ;`

`echo $x; // 123
echo "$x"; // 123
echo "'$x'"; // '123'
echo '$x'; // $x
echo ${$aa-$b}; // 2`

Date
09/02/2017

bool is-numeric()

To check whether a variable is numeric or not.

Example:

```
echo is-numeric("123"); //1
echo is-numeric(123); //1
echo is-numeric("Hi"); //0
echo is-numeric(9.1); //1
echo is-numeric(array()); //0
```

Nothing
Nothing (not even 0 to)

bool is-bool()

Finds whether a variable is boolean or not.

Remember boolean type only has values

TRUE or true or True & FALSE or false or False

Example:

```
is-bool(false); //return TRUE On echo //1
is-bool(0); //return False On echo //0
    ↑ zero
```

0 = Nothing

bool is-int()

bool is-float()

bool is-double()

bool is-array()

bool is-null()

bool is-object()

Example:

```
error_reporting(E_ALL);
```

```
$foo = NULL;
```

```
var_dump(is-null($x));
```

```
var_dump(is-null($foo));
```

-40-

Output:

Notice: Undefined variable: x

// bool(true)

// bool(true)