

High Altitude Performance Optimization and Robust Design of an Anti-Drone System

1. Introduction:

The increasing use of unmanned aerial vehicles (UAVs) creates a need for reliable anti-drone systems capable of detecting, identifying, tracking, and responding to unauthorized drones. This becomes particularly challenging in high-altitude environments, where extreme cold, high wind, dust, snow, low atmospheric pressure, vibration, and thermal cycling can affect system performance.

Our project proposes a robust, modular, and environment-aware anti-drone system that combines FMCW radar, RF, and EO/IR sensing for comprehensive target detection. Micro-Doppler signatures and sensor fusion are used for reliable drone identification, while tracking and prediction maintain awareness of target movement. A feedback-controlled gimbal stabilization system helps maintain accurate pointing despite wind and vibration.

The system continuously considers environmental conditions and sensor health, allowing sensor confidence and operating parameters to adapt to changing conditions. The proposed architecture also incorporates a layered response framework with HPM integration and an interceptor fallback, while following a Simulation → Hardware → Field Validation approach for progressive development and testing.

2. Abstract:

The proposed system presents an environment-aware anti-drone system designed for reliable operation in high-altitude environments where extreme cold, low air pressure, high wind, dust, and snow can affect sensor and system performance. The system combines FMCW radar, RF sensing, EO/IR and thermal imaging, acoustic sensing, and sensor fusion for robust drone detection and identification. Micro-Doppler analysis is used to distinguish drones from objects such as birds, while LTMU-based tracking supports reliable long-term target tracking and re-detection. A stabilized gimbal system maintains accurate target pointing under wind and vibration. Environmental monitoring and a liquid cooling/thermal management system are incorporated to maintain suitable operating conditions for critical components. The response layer is designed around HPM-based neutralization with a mechanical fallback, providing a layered approach to counter-UAS operation. The overall architecture aims to improve reliability, adaptability, and tracking accuracy under challenging environmental conditions and provides a foundation for future real-world high-altitude deployment.

3. Problem Statement :

Existing anti-drone systems may suffer from false detection, unreliable identification, tracking difficulties, and gimbal pointing errors, especially when individual sensors are affected by environmental conditions.

The key challenge is to develop a system that fuses multiple sensors, maintains reliable tracking and stabilization, and adapts to changing conditions.

4. Objectives:

- Develop a robust anti-drone system for high-altitude environments.
- Improve detection and identification using FMCW radar, RF, EO/IR, and micro-Doppler features.
- Enable reliable tracking and prediction of moving drone targets.
- Maintain accurate pointing using a stabilized gimbal with feedback control.
- Adapt to environmental conditions through sensor fusion and environment-aware decision-making.
- Integrate a layered response architecture including the HPM response layer and fallback mechanism.
- Validate progressively through simulation, hardware demonstration, and future field testing.

5. Proposed Solution

Our proposed system is a modular, closed-loop anti-drone architecture designed for reliable operation in high-altitude conditions.

- Detection: Uses FMCW radar, RF, and EO/IR sensing to detect potential aerial targets.
- Identification: Uses micro-Doppler signatures and sensor fusion to distinguish drones from other objects.
- Tracking & Prediction: Uses LTMU-based tracking and state estimation to maintain the target and predict its movement.
- Gimbal Stabilization: Uses IMU/encoder feedback with a servo-driven gimbal to maintain accurate pointing despite wind and vibration.
- Environmental Monitoring: Monitors temperature, pressure, wind, vibration, and sensor health to adapt system operation.
- Temperature & Cooling: Monitors surface temperature of critical components and uses cooling to maintain safe operating conditions.
- Ultrasonic Sensing: Provides target-distance measurement in the physical prototype to demonstrate the sensing concept.
- Neutralization: Includes an HPM integration layer as part of the proposed layered response architecture.

5.1 Cooling System

At high altitudes, reduced atmospheric density limits convective heat dissipation from the camera and its electronic components. This can cause temperature variations, thermal stress, reduced processing performance, and consequently lower tracking reliability.

To address this, the proposed system uses a **closed-loop liquid-cooling system**. The camera is enclosed in a **polyurethane-insulated enclosure**, with small coolant tubes positioned near heat-generating surfaces. The coolant absorbs heat and carries it to an **external radiator**, where a fan removes the heat before the cooled liquid is circulated back to the camera.

The system uses a **glycol-based coolant mixture** for low-temperature operation. Temperature sensors monitor the enclosure air temperature, while a thermistor measures the camera or processor surface temperature. A microcontroller continuously monitors these readings and automatically adjusts the radiator fan speed according to the thermal condition.

This approach provides controlled heat removal while reducing dependence on the low-density surrounding air, helping maintain stable operating temperatures for the camera and processing electronics.

5.2 Identification using Micro – Doppler Effect

In the proposed anti-drone system, **micro-Doppler analysis is used for drone identification**. The rotating propellers of a drone produce additional small Doppler frequency variations in the radar return. These variations form a characteristic **micro-Doppler signature** that can help distinguish a drone from other aerial objects.

The system uses **FMCW radar** to obtain the reflected signal. The radar signal is processed to extract the micro-Doppler characteristics, which can be represented using a **time-frequency spectrogram**. These features are then combined with information from **RF and EO/IR sensors** through sensor fusion to improve identification reliability.

FMCW Radar → Radar Return → Micro-Doppler Extraction → Spectrogram → Feature Analysis → Drone Identification → Sensor Fusion

5.3 LTMU-Based Tracking and Prediction

Long-Term Tracking with Meta-Updater (LTMU) is a computer-vision-based tracking framework designed for reliable long-term UAV tracking. It combines a **local tracker, Meta-Updater, verifier, and re-detector** to maintain the target even when it becomes difficult to track.

The **local tracker** follows the UAV between consecutive frames, while the **verifier** evaluates whether the tracking result is reliable. The **Meta-Updater** controls when the target model should be updated, reducing tracking drift caused by incorrect updates. If the UAV is lost, the **SiamRPN-based re-detector** performs a wider search to locate it again.

Working:

Camera → Initial Detection → Local Tracking → Verification → Model Update → Re-detection if Lost → Continued Tracking

LTMU is suitable for our anti-drone system because UAVs may become small, change appearance, move rapidly, or temporarily disappear from the camera's field of view. Its verification and re-detection mechanism helps maintain reliable tracking.


6. Simulation & Software Implementation

The advanced parts of the proposed system are currently developed and evaluated through simulation.

- FMCW Radar: Simulates target detection and radar signal processing.
- Micro-Doppler Analysis: Uses rotor-induced motion signatures for drone identification.
- Sensor Fusion: Combines radar, RF, and EO/IR information to improve identification reliability.
- Tracking & Prediction: Implements LTMU-based tracking and state estimation to maintain target position and predict movement.
- Environmental Adaptation: Simulates the effect of temperature, wind, vibration, pressure, and sensor degradation on system reliability.
- HPM Integration: Represents the proposed HPM response layer within the overall system architecture.

7. System Architecture

The proposed system follows a closed-loop, multi-layer architecture:



8. Hardware Prototype

The physical prototype demonstrates the key concepts of environmental protection, target sensing, and stabilization.

- Polyurethane foam insulation: Provides thermal insulation for the enclosed components.
- Silicone-neutral sealant: Helps seal and protect the components from dust and moisture.
- Servo-driven gimbal: Demonstrates active stabilization and pointing correction.
- Ultrasonic sensor: Provides physical target-distance measurement for the sensing demonstration.
- Temperature monitoring & cooling: Used to monitor surface temperature and support thermal management of critical components.

9. Feasibility, Challenges & Viability

9.1. Feasibility

Sensor Fusion: Combines multiple sensor inputs and adapts their contribution according to environmental and system-health conditions.

Tracking & Prediction: Uses target confidence, sensor health, environmental conditions, and tracking confidence for reliable tracking.

Gimbal Stabilization: IMU-based stabilization helps maintain accurate pointing under disturbances.

HPM Integration: Provides a response layer within the proposed anti-drone architecture.

9.2. Challenges

- Real-time sensor fusion: Combining radar, RF, thermal, camera, and acoustic data with different sampling rates and confidence levels.
- Micro-Doppler reliability: Maintaining accurate drone classification when radar signals are affected by clutter, noise, wind, or changing target orientation.
- Small-target tracking: Maintaining continuous tracking when the UAV becomes very small, temporarily occluded, or moves out of the camera's field of view.
- Gimbal accuracy: Maintaining stable and precise pointing despite vibration and rapid target movement.
- Hardware integration: Synchronizing multiple sensors, Raspberry Pi processing, communication interfaces, and the gimbal into one reliable system.
- Environmental validation: Testing the complete system under actual high-altitude conditions is difficult and requires specialized environmental testing.

9.3 Viability

- Modular & Upgradeable: Sensors and subsystems can be added or replaced.
- Scalable: Architecture can extend from single- to multi-drone scenarios.
- Environment-aware: System adapts as operating conditions change.
- Progressive Validation: Simulation → Sensor Integration → Hardware → Controlled Testing.
- Deployable: Hardware and AI are co-designed for practical high-altitude operation.

10 Testing & Validation

- Simulation Validation: Test radar detection, micro-Doppler identification, sensor fusion, tracking, prediction, and environmental effects in simulation.
- Hardware Validation: Validate the physical gimbal stabilization, ultrasonic sensing, enclosure, and temperature-management concepts.
- Sensor Integration: Progressively connect simulated algorithms with real sensor inputs.
- Controlled Environmental Testing: Evaluate performance under controlled temperature, wind, vibration, dust/snow, and pressure-related conditions.
- Performance Evaluation: Measure detection reliability, identification confidence, tracking accuracy, gimbal pointing stability, and system response.

Simulation → Sensor Integration → Physical Hardware → Controlled Testing → Field Validation.

11 Improvements and Future Scope:

- Real-Time Autonomous Operation – Fully automate detection, identification, tracking, and response to reduce dependence on continuous human intervention.
- System Miniaturization – Reduce the system's size, weight, and power consumption while maintaining performance for practical field deployment.
- Extended Temperature Range – Expand system operation and validation to more extreme temperatures, improving reliability in harsh high-altitude environments.
- Predictive Environmental Adaptation – Predict sensor degradation caused by changing environmental conditions and dynamically compensate to maintain system performance.
- Advanced AI Classification – Improve UAV identification using larger and more diverse datasets, enabling more accurate classification across different drone types and operating conditions.
- Secure Data & Communication – Introduce authenticated communication and protected data handling to improve the security and integrity of sensor data and system communication.

12. Literature Survey

No.	Literature	Key Contribution	Relevance to Our Project
1	Oh et al., 2019, “ A UAV Classification System Based on FMCW Radar Micro-Doppler Signature Analysis ”	Developed UAV classification using FMCW radar and micro-Doppler signatures .	Supports our FMCW radar + micro-Doppler identification .
2	Rahman and Robertson, 2020, “ Classification of Drones and Birds Using Convolutional Neural Networks Applied to Radar Micro-Doppler Spectrogram Images ”	Used micro-Doppler spectrograms and CNNs for drone, bird, clutter and noise classification.	Supports our spectrogram processing and ML-based classification .
3	Medaiyese et al., 2022, “ Wavelet Transform Analytics for RF-Based UAV Detection and Identification Using Machine Learning ”	Used RF fingerprints, wavelet features and ML for UAV identification.	Supports our RF identification layer and fusion with radar.
4	González-Jorge et al., 2024, “ Counter Drone Technology: A Review ”	Reviews C-UAS technologies for detection, tracking, classification and mitigation .	Supports our multi-sensor and layered C-UAS architecture .
5	Park et al., 2021, “ Survey on Anti-Drone Systems: Components, Designs, and Challenges ”	Reviews anti-drone components, architectures and challenges .	Supports our detection–tracking–identification–response architecture .
6	Castrillo et al., 2022, “ A Review of Counter-UAS Technologies for Cooperative Defensive Teams of Drones ”	Reviews C-UAS technologies for single and multiple drone threats .	Supports our scalable architecture and multiple response options .
7	Zidane et al., 2024, “ Jamming and Spoofing Techniques for Drone Neutralization: An Experimental Study ”	Investigated jamming and spoofing for UAV neutralization.	Supports our electronic neutralization/response layer .
8	Heuchamps et al., 2026, “ Review of C-(s)UAS Effector Technologies and Models ”	Reviews kinetic, electronic-warfare and directed-energy effectors .	Supports our HPM-based response layer and modular effector integration.
9	Selvamuthu et al., 2024, “ Reliability Analysis of an Anti-Drone System by Considering Random Environmental Factors ”	Studies anti-drone reliability under environmental factors .	Supports our focus on high-altitude environmental degradation and reliability .

No.	Literature	Key Contribution	Relevance to Our Project
10	Abbas et al., 2024, “ Investigating the Influence of Temperature on UAV Signal Quality ”	Examines the effect of temperature on UAV signal quality , including SNR and RSSI.	Supports temperature-dependent RF/sensor performance .
11	Zhao et al., 2022, “ Vision-Based Anti-UAV Detection and Tracking ”	Developed and evaluated vision-based UAV detection and tracking .	Supports our EO/IR detection and tracking layer .
12	Xie et al., 2025, “ CST Anti-UAV: A Thermal Infrared Benchmark for Tiny UAV Tracking in Complex Scenes ”	Developed a thermal-infrared benchmark for tiny UAV tracking.	Supports thermal sensing and robust tracking under difficult conditions.
13	Toma et al., 2022, “ Onboard Audio and Video Processing for Secure Detection, Localization, and Tracking in Counter-UAV Applications ”	Investigated video detection and acoustic localization/tracking .	Supports multi-modal sensing for detection and tracking.

12.1. Research Gap

Existing studies mainly focus on drone identification, RF/radar sensing, EO/IR tracking, neutralization, or environmental reliability individually. Limited work integrates these technologies into a single adaptive anti-drone system designed specifically for harsh high-altitude conditions.

Our project addresses this gap by combining FMCW radar, RF and EO/IR sensor fusion, micro-Doppler identification, tracking and prediction, gimbal stabilization, and HPM-based response, while considering extreme cold, high wind, dust/snow, low pressure, vibration, and sensor degradation.

13. Results

The developed system demonstrates the feasibility of an **environment-aware anti-drone architecture** integrating FMCW radar, RF, EO/IR, micro-Doppler identification, LTMU tracking, gimbal stabilization, environmental monitoring and response integration.

The insulation test showed that with the freezer set to -23°C , the temperature inside the enclosure reduced from 32.7°C to 12.2°C over 56 minutes before the battery discharged. The PU foam provided effective insulation, while the outer acrylic surface froze and the foam remained comparatively less cool.

14. Conclusion

The project demonstrates the feasibility of the proposed anti-drone system through simulation, software implementation, and a physical prototype. The simulations evaluate key functions such as FMCW radar processing, micro-Doppler identification, sensor fusion, LTMU-based tracking, environmental adaptation, and HPM integration. The hardware prototype demonstrates thermal insulation, environmental protection, target-distance sensing, gimbal stabilization, and temperature monitoring with cooling support. Together, these implementations provide a foundation for integrating the complete system and conducting further real-world high-altitude testing.