METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-01	Product Name	O-RING	Size	M16	Drawing No.	OR-0M	Date:	02-11-2026
Wo No.	26000349	Total Quantity	30	Lot Quantity	30	Sample Size	2	Variable & Gauging	2PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	NA	NA	NA	-	-	-		ASM No :- CEX261028-02	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-		
		THICKNESS	2.50	2.00	2.50	2.40	2.39	-	-	-		
		I.D	12.00	11.50	12.50	12.05	12.07	-	-	-		

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING CA PASSED

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

METAL MECH
THE SAFEST CONNECTIONS

INSP. No.	FIR-01	**Product Name**	ADAPTOR	**Size**	M16xM20	**Drawing No.**	AD0M1M	**Date:**	02-11-2026
Wo No.	26000349	**Total Quantity**	30	**Lot Quantity**	30	**Sample Size**	2	**Variable & Gauging**	2PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER		OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA	1	2	-	-	-			
1	Visual	Surface	Fine, Clean	FINE	FINE	-	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts 2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing NICKEL	OK	OK	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG. NA	NA	NA	-	-	-			
		Marking	WO Ref. No. Metalmech Logo MM-EX-AD0M1MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X			-	-	-		ASM No :- CEX261028-02	
		Assembly Perfection	As per Drg.	OK	OK	-	-	-			
		Inner Packing	Labeling & Printing	OK	OK	-	-	-			
		Outer Packing	Printing & Stamping	OK	OK	-	-	-			
		All Dimensions Are In MM									
2	DIMENSION		VALUE - +	1	2	-	-	-			
		A/F	25.00 24.87 25.00	24.96	24.95	-	-	-			
		T.L	36.50 36.50 37.00	36.66	36.67	-	-	-			
		TH.L	13.00 13.00 13.50	13.03	13.05	-	-	-			
		LENGTH	16.00 16.00 16.50	16.09	16.08	-	-	-			
		GR.OD	14.00 13.50 14.50	14.03	14.04	-	-	-			
		GR.LE	1.50 1.30 1.70	1.51	1.53	-	-	-			
		H.L	6.00 5.70 6.30	6.11	6.13	-	-	-			
		O.D	24.50 24.00 25.00	24.55	24.54	-	-	-			
		I.D	11.00 10.50 11.50	11.04	11.06	-	-	-			
		INT.THL	17.50 17.00 18.00	17.58	17.56	-	-	-			
		THREAD	M16x1.5 AS PER T.R.G GO NOT GO	OK	OK	-	-	-			
		INT.THREAD	M20x1.5 AS PER P.G GO NOT GO	OK	OK	-	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND	OK	OK	-	-	-			
		GR.ANGLE	67° AS PER PP FOUND	OK	OK	-	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING CA PASSED