METAL MECA®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-05	Product Name	O-RING	Size	M50	Drawing No.	OR-5M	Date:	04-11-2026
Wo No.	26000337	Total Quantity	2	Lot Quantity	2	Sample Size	2	Variable & Gauging	2PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	NA	NA	NA	-	-	-		ASM No :- CEX261030-09	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-		
		THICKNESS	2.50	2.00	2.50	2.06	2.09	-	-	-		
		I.D	45.00	44.20	45.80	45.03	45.05	-	-	-		

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING CA PASSED

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-05	**Product Name**	PLUG	**Size**	M50	**Drawing No.**	PLG5M	**Date:**	04-11-2026
Wo No.	26000337	**Total Quantity**	2	**Lot Quantity**	2	**Sample Size**	2	Variable & Gauging	2PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments I.D No:-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NICKEL	OK	OK	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG5MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X		-	-	-		ASM No :- CEX261030-09	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-			
		T.L	24.00	23.50	24.50	24.08	24.06	-	-	-		
		O.D	60.00	59.20	60.80	60.03	60.02	-	-	-		
		O.D.L	6.00	5.70	6.30	5.95	5.94	-	-	-		
		TH.L	15.00	14.50	15.50	15.01	15.03	-	-	-		
		LENGTH	18.00	17.50	18.50	18.06	18.09	-	-	-		
		GR.OD	48.00	47.50	48.50	47.93	47.95	-	-	-		
		GR.LE	1.50	1.30	1.70	1.55	1.54	-	-	-		
		INT-(A/F)	14.00	14.00	14.20	14.08	14.10	-	-	-		
		INT-(A/F).LE	10.00	9.50	10.50	10.07	10.09	-	-	-		
		GR.ID	17.50	17.00	18.00	17.55	17.57	-	-	-		
		GR.LE	4.00	3.70	4.30	4.08	4.06	-	-	-		
		DEPTH	14.00	13.50	14.50	14.06	14.09	-	-	-		
		CH.DIA	17 MM AS PER PP FOUND			OK	OK	-	-	-		
		THREAD	M50x1.5 AS PER T.R.G GO NOT GO			OK	OK	-	-	-		
		CH.ANGLE	1.5x45° AS PER PP FOUND			OK	OK	-	-	-		
		CH.ANGLE	2x45° AS PER PP FOUND			OK	OK	-	-	-		
		GR.ANGLE	67° AS PER PP FOUND			OK	OK	-	-	-		

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERS PVT. LTD. CA PASSED