# MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

| INSP. No. | FIR-04 | Product Name | O-RING | Size | M20 | Drawing No. | OR-1M | Date: | 20-10-2026 |
|---|---|---|---|---|---|---|---|---|---|
| Wo No. | 26000282 | Total Quantity | 200 | Lot Quantity | 200 | Sample Size- | 3 | Variable & Gauging | 3PCS |

| Sr. No. | Checking Parameter | REQUIRED PARAMETER | | | OBSERVED RESULTS | | | | | REJECTION REWORK DETAIL | REMARK | CHECKED BY |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | PARAMETER | CRITERIA | | 1 | 2 | 3 | - | - | | | |
| 1 | Visual | Surface | Fine, Clean | | FINE | FINE | FINE | - | - | | Measuring Instruments I.D No- | |
| | | Sizewise No of Pcs. With Internal Parts | As per Drg. No. of Parts | 2 | 2 | 2 | 2 | - | - | | (1) DV-55 | |
| | | Washing & Plating | Surface Finishing | NA | NA | NA | NA | - | - | | (2) PP-01 | |
| | | RUBBER MARKING | AS PER DRG. | NA | NA | NA | NA | - | - | | | |
| | | Marking | WO Ref. No. | NA | NA | NA | NA | - | - | | ASM No:- CEX261015-01 | |
| | | Assembly Perfection | As per Drg. | | OK | OK | OK | - | - | | | |
| | | Inner Packing | Labeling & Printing | | OK | OK | OK | - | - | | | |
| | | Outer Packing | Printing & Stamping | | OK | OK | OK | | - | | | |
| | | All Dimensions Are In MM | | | | | | | | | | |

| | | | VALUE | - | + | 1 | 2 | 3 | - | - | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 2 | DIMENSION | THICKNESS | 2.50 | 2.00 | 2.50 | 2.08 | 2.06 | 2.05 | - | - | | | |
| | | I.D | 16.00 | 15.50 | 16.50 | 16.05 | 16.04 | 16.03 | - | - | | | |
| | | | | | | | | | | | | | |

| *INSPECTED BY:* | *Jay Hadiyal* | *APPROVED BY:* | *Shreekant* |
|---|---|---|---|

**Conclusion :**

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

METAL MECA
THE SAFEST CONNECTIONS

# MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

| INSP. No. | FIR-04 | Product Name | PLUG | Size | M20 | Drawing No. | PLG1M | Date: | 20-10-2026 |
|---|---|---|---|---|---|---|---|---|---|
| Wo No. | 26000282 | Total Quantity | 200 | Lot Quantity | 200 | Sample Size- | 3 | Variable & Gauging | 3PCS |

| Sr. No. | Checking Parameter | REQUIRED PARAMETER | | | OBSERVED RESULTS | | | | | REJECTION REWORK DETAIL | REMARK | CHECKED BY |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | PARAMETER | CRITERIA | | 1 | 2 | 3 | - | - | | | |
| 1 | Visual | Surface | Fine, Clean | | FINE | FINE | FINE | - | - | | Measuring Instruments I.D No- | |
| | | Sizewise No of Pcs. With Internal Parts | As per Drg. No. of Parts | 2 | 2 | 2 | 2 | - | - | | (1) DV-55 | |
| | | Washing & Plating | Surface Finishing | NICKEL | OK | OK | OK | - | - | | (2) PP-01 | |
| | | RUBBER MARKING | AS PER DRG. | NA | NA | NA | NA | - | - | | | |
| | | Marking | WO Ref. No. | Metalmech Logo MM-EX-PLG1MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X | | | - | - | | ASM No:- CEX261015-01 | |
| | | Assembly Perfection | As per Drg. | | OK | OK | OK | - | - | | | |
| | | Inner Packing | Labeling & Printing | | OK | OK | OK | - | - | | | |
| | | Outer Packing | Printing & Stamping | | OK | OK | OK | - | - | | | |
| | | All Dimensions Are In MM | | | | | | | | | | |
| 2 | DIMENSION | | VALUE | - | + | 1 | 2 | 3 | - | - | | | |
| | | T.L | 21.00 | 20.50 | 21.50 | 21.13 | 21.12 | 21.11 | - | - | | | |
| | | LENGTH | 16.00 | 15.50 | 16.50 | 16.05 | 16.06 | 16.04 | - | - | | | |
| | | TH.L | 13.00 | 12.50 | 13.50 | 13.03 | 13.05 | 13.05 | - | - | | | |
| | | GR.OD | 18.00 | 17.50 | 18.50 | 17.95 | 17.94 | 17.96 | - | - | | | |
| | | GR.LE | 1.50 | 1.30 | 1.70 | 1.54 | 1.56 | 1.58 | - | - | | | |
| | | O.D | 26.00 | 25.50 | 26.50 | 26.03 | 26.03 | 26.06 | - | - | | | |
| | | O.D.L | 5.00 | 4.70 | 5.30 | 5.05 | 5.03 | 5.05 | - | - | | | |
| | | GR.ID | 13.50 | 13.00 | 14.00 | 13.58 | 13.55 | 13.56 | - | - | | | |
| | | GR.LE | 4.00 | 3.70 | 4.30 | 4.06 | 4.09 | 4.05 | - | - | | | |
| | | INT-(A/F) | 10.00 | 10.00 | 10.20 | 10.12 | 10.11 | 10.13 | - | - | | | |
| | | INT-(A/F)-LENGTH | 10.00 | 9.50 | 10.50 | 10.08 | 10.07 | 10.09 | - | - | | | |
| | | DEPTH | 14.00 | 13.50 | 14.50 | 14.13 | 14.15 | 14.12 | - | - | | | |
| | | THREAD | M20x1.5 AS PER T.R.G GO NOT GO | | | OK | OK | OK | - | - | | | |
| | | CH.ANGLE | 1.5x45° AS PER PP FOUND | | | OK | OK | OK | - | - | | | |
| | | CH.ANGLE | 2x45° AS PER PP FOUND | | | OK | OK | OK | - | - | | | |
| | | GR.ANGLE | 67° AS PER PP FOUND | | | OK | OK | OK | - | - | | | |
| | | | | | | | | | | | | | |

| INSPECTED BY: | Jay Hadiyal | APPROVED BY: | Shreekant |
|---|---|---|---|

**Conclusion :**

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING
QA PASSED