METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-08	Product Name	O-RING	Size	M32	Drawing No.	OR-3M	Date:	20-10-2026
Wo No.	26000289	Total Quantity	20	Lot Quantity	20	Sample Size-	2	Variable & Gauging	2PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	NA	NA	NA	-	-	-		ASM No :- CEX261010-04	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-		
		THICKNESS	2.50	2.00	2.50	2.04	2.06	-	-	-		
		I.D	29.00	28.50	29.50	29.03	29.05	-	-	-		

INSPECTED BY:	Jay Hadiyal	APPROVED BY:	Shreekant

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-08	**Product Name**	PLUG	**Size**	M32	**Drawing No.**	PLG3M	**Date:**	20-10-2026
Wo No.	26000289	**Total Quantity**	20	**Lot Quantity**	20	**Sample Size-**	2	Variable & Gauging	2PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments LD No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NICKEL	OK	OK	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG3MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X		-	-	-		ASM No :- CEX261010-04	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-			
		T.L	22.00	21.50	22.50	22.15	22.12	-	-	-			
		O.D	40.00	39.20	40.80	39.95	39.94	-	-	-			
		O.D.L	6.00	5.70	6.30	6.05	6.04	-	-	-			
		TH.L	13.00	12.50	13.50	12.99	12.98	-	-	-			
		LENGTH	16.00	15.50	16.50	16.04	16.06	-	-	-			
		GR.OD	30.00	29.50	30.50	29.95	29.94	-	-	-			
		GR.LE	1.50	1.30	1.70	1.52	1.51	-	-	-			
		INT-(A/F)	14.00	14.00	14.20	14.05	14.04	-	-	-			
		INT-(A/F).LE	10.00	9.50	10.50	10.03	10.05	-	-	-			
		GR.ID	17.50	17.00	18.00	17.53	17.54	-	-	-			
		GR.LE	4.00	3.70	4.30	4.02	4.01	-	-	-			
		DEPTH	14.00	13.50	14.50	14.03	14.05	-	-	-			
		CH.DIA	17 MM AS PER PP FOUND			OK	OK	-	-	-			
		THREAD	M32x1.5 AS PER T.R.G GO NOT GO			OK	OK	-	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND			OK	OK	-	-	-			
		CH.ANGLE	2x45° AS PER PP FOUND			OK	OK	-	-	-			
		GR.ANGLE	67° AS PER PP FOUND			OK	OK	-	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING CA PASSED