METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-01	Product Name	REDUCER	Size	3/4" NPT x 1/2" NPT	Drawing No.	RD2N1N	Date:	06-11-2026
Wo No.	26100117	Total Quantity	290	Lot Quantity	290	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	NA	NA	NA	NA	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NICKEL	OK	OK	OK	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-RD2N1NB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X			-	-		ASM No :- CEX261106-01	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	-	-			
		A/F	30.00	29.87	30.00	29.95	29.94	29.93	-	-			
		T.L	29.00	28.50	29.50	29.13	29.15	29.14	-	-			
		LENGTH	21.00	20.50	21.50	21.13	21.16	21.13	-	-			
		H.L	8.00	7.50	8.50	8.00	7.99	8.01	-	-			
		I.D	14.00	13.50	14.50	14.07	14.06	14.09	-	-			
		INT.THL	18.00	17.50	18.50	18.13	18.12	18.11	-	-			
		THREAD	3/4" NPT AS PER T.R.G GO NOT GO			OK	OK	OK	-	-			
		INT.THREAD	1/2" NPT AS PER P.G GO NOT GO			OK	OK	OK	-	-			
		CH.ANGLE	1.6x45° AS PER PP FOUND			OK	OK	OK	-	-			

INSPECTED BY:	Jay Hadiyal	APPROVED BY:	Shreekant

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING QA PASSED