MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-03	**Product Name**	O-RING	**Size**	M20	**Drawing No.**	OR-1M	**Date:**	05-11-2026
Wo No.	26100100	**Total Quantity**	3000	**Lot Quantity**	3000	**Sample Size-**	5	Variable & Gauging	5PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	4	5			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	FINE	FINE		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	2	2		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	NA	NA	NA		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	NA	NA			
		Marking	WO Ref. No.	NA	NA	NA	NA	NA	NA		ASM No:- CEX261029-02	
		Assembly Perfection	As per Drg.		OK	OK	OK	OK	OK			
		Inner Packing	Labeling & Printing		OK	OK	OK	OK	OK			
		Outer Packing	Printing & Stamping		OK	OK	OK	OK	OK			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	4	5			
		THICKNESS	2.50	2.00	2.50	2.08	2.06	2.05	2.05	2.04		
		I.D	16.00	15.50	16.50	16.05	16.04	16.03	16.04	16.08		

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

METAL MECH
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-03	Product Name	PLUG	Size	M20	Drawing No.	PLG1M	Date:	05-11-2026
Wo No.	26100100	Total Quantity	3000	Lot Quantity	3000	Sample Size-	5	Variable & Gauging	5PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	4	5			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	FINE	FINE		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	2	2		(1) DV-55	
		Washing & Plating	Surface Finishing	NICKEL	OK	OK	OK	OK	OK		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	NA	NA			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG1MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X						ASM No:- CEX261029-02	
		Assembly Perfection	As per Drg.		OK	OK	OK	OK	OK			
		Inner Packing	Labeling & Printing		OK	OK	OK	OK	OK			
		Outer Packing	Printing & Stamping		OK	OK	OK	OK	OK			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	4	5			
		T.L	21.00	20.50	21.50	21.13	21.12	21.11	21.11	21.12			
		LENGTH	16.00	15.50	16.50	16.05	16.06	16.04	16.06	16.05			
		TH.L	13.00	12.50	13.50	13.03	13.05	13.05	13.05	13.04			
		GR.OD	18.00	17.50	18.50	17.95	17.94	17.96	17.95	17.98			
		GR.LE	1.50	1.30	1.70	1.54	1.56	1.58	1.55	1.58			
		O.D	26.00	25.50	26.50	26.03	26.03	26.06	26.05	26.04			
		O.D.L	5.00	4.70	5.30	5.05	5.03	5.05	5.03	5.05			
		GR.ID	13.50	13.00	14.00	13.58	13.55	13.56	13.55	13.54			
		GR.LE	4.00	3.70	4.30	4.06	4.09	4.05	4.03	4.05			
		INT-(A/F)	10.00	10.00	10.20	10.12	10.11	10.13	10.12	10.11			
		INT-(A/F)-LENGTH	10.00	9.50	10.50	10.08	10.07	10.09	10.07	10.09			
		DEPTH	14.00	13.50	14.50	14.13	14.15	14.12	14.12	14.11			
		THREAD	M20x1.5 AS PER T.R.G GO NOT GO			OK	OK	OK	OK	OK			
		CH.ANGLE	1.5x45° AS PER PP FOUND			OK	OK	OK	OK	OK			
		CH.ANGLE	2x45° AS PER PP FOUND			OK	OK	OK	OK	OK			
		GR.ANGLE	67° AS PER PP FOUND			OK	OK	OK	OK	OK			

INSPECTED BY:	Jay Hadiyal	APPROVED BY:	Shreekant

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING QA PASSED