METAL MECA®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-02	**Product Name**	O-RING	**Size**	M25	**Drawing No.**	OR-2M	**Date:**	04-11-2026
Wo No.	26000337	**Total Quantity**	82	**Lot Quantity**	82	**Sample Size-**	3	**Variable & Gauging**	3PCS

Sr. No.	**Checking Parameter**	**REQUIRED PARAMETER**			**OBSERVED RESULTS**					**REJECTION REWORK DETAIL**	**REMARK**	**CHECKED BY**
		PARAMETER	**CRITERIA**		**1**	**2**	**3**	**-**	**-**			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	-	-		**(1) DV-55**	
		Washing & Plating	Surface Finishing	NA	NA	NA	NA	-	-		**(2) PP-01**	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	NA	NA	NA	NA	-	-		**ASM No :- CEX261030-07**	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	- +	1	2	3	-	-			
		THICKNESS	2.50	2.00 2.50	2.05	2.03	2.06	-	-			
		I.D	20.00	19.50 20.50	20.03	20.02	20.05	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-02	Product Name	PLUG	Size	M25	Drawing No.	PLG2M	Date:	04-11-2026
Wo No.	26000337	Total Quantity	82	Lot Quantity	82	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NICKEL	OK	OK	OK	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG1NB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X			-	-		ASM No :- CEX261030-07	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										

			VALUE	-	+	1	2	3	-	-			
2	DIMENSION	T.L	22.00	21.50	22.50	22.09	22.08	22.06	-	-			
		TH.L	13.00	12.50	13.50	12.99	12.97	12.98	-	-			
		LENGTH	16.00	15.50	16.50	16.10	16.09	16.08	-	-			
		GR.OD	23.00	22.50	23.50	22.99	22.98	22.97	-	-			
		GR.LE	1.50	1.30	1.70	1.52	1.50	1.51	-	-			
		O.D	30.00	29.50	30.50	30.03	30.00	30.02	-	-			
		O.D.L	6.00	5.70	6.30	6.02	6.01	6.03	-	-			
		GR.ID	13.50	13.00	14.00	5.98	5.97	5.98	-	-			
		GR.LE	4.00	3.70	4.30	4.03	4.02	4.05	-	-			
		INT-(A/F)	10.00	10.00	10.20	10.11	10.13	10.12	-	-			
		INT-(A/F)-LENGTH	10.00	9.50	10.50	10.02	10.01	10.05	-	-			
		DEPTH	14.00	13.50	14.50	14.03	14.02	14.06	-	-			
		THREAD	M25x1.5 AS PER T.R.G GO NOT GO			OK	OK	OK	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND			OK	OK	OK	-	-			
		CH.ANGLE	2x45° AS PER PP FOUND			OK	OK	OK	-	-			
		GR.ANGLE	67° AS PER PP FOUND			OK	OK	OK	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING CA PASSED