MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-03	**Product Name**	O-RING	**Size**	M40	**Drawing No.**	OR-4M	**Date:**	15-10-2026
Wo No.	26000278	**Total Quantity**	500	**Lot Quantity**	500	**Sample Size-**	3	**Variable & Gauging**	3PCS

Sr. No.	**Checking Parameter**	**REQUIRED PARAMETER**			**OBSERVED RESULTS**					**REJECTION REWORK DETAIL**	**REMARK**	**CHECKED BY**
		PARAMETER	**CRITERIA**		**1**	**2**	**3**	**-**	**-**			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	NA	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	NA	NA	NA	NA	-	-		ASM No :- CEX261011-02	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	-	-			
		THICKNESS	2.50	2.00	2.50	2.06	2.05	2.04	-	-		
		I.D	30.00	29.50	30.50	30.03	30.04	30.05	-	-		

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING CA PASSED

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

METAL MECA — THE SAFEST CONNECTIONS

INSP. No.	FIR-03	Product Name	PLUG	Size	M40	Drawing No.	PLG4M	Date:	15-10-2026
Wo No.	26000278	Total Quantity	500	Lot Quantity	500	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER		OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA	1	2	3	-	-			
1	Visual	Surface	Fine, Clean	FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts: 2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing: NICKEL	OK	OK	OK	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG. / NA	NA	NA	NA	-	-			
		Marking	WO Ref. No. / Metalmech Logo MM-EX-PLG4MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X				-	-		ASM No :- CEX261011-02	
		Assembly Perfection	As per Drg.	OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing	OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping	OK	OK	OK	-	-			
		All Dimensions Are In MM									
2	DIMENSION		VALUE / - / +	1	2	3	-	-			
		T.L	24.00 / 23.50 / 24.50	24.10	24.09	24.08	-	-			
		TH.L	15.00 / 14.50 / 15.50	15.03	15.05	15.04	-	-			
		LENGTH	18.00 / 17.50 / 18.50	18.10	18.08	18.09	-	-			
		GR.OD	38.00 / 37.20 / 38.80	37.97	37.96	37.93	-	-			
		GR.LE	1.50 / 1.30 / 1.70	1.54	1.53	1.55	-	-			
		O.D	48.00 / 47.20 / 48.80	48.08	48.05	48.06	-	-			
		O.D.L	6.00 / 5.70 / 6.30	6.05	6.03	6.04	-	-			
		GR.ID	17.50 / 17.00 / 18.00	17.55	17.53	17.56	-	-			
		GR.LE	4.00 / 3.70 / 4.30	4.07	4.05	4.03	-	-			
		INT-(A/F)	14.00 / 14.00 / 14.20	14.09	14.08	14.09	-	-			
		INT-(A/F)-LENGTH	10.00 / 9.50 / 10.50	10.07	10.05	10.05	-	-			
		DEPTH	14.00 / 13.50 / 14.50	14.06	14.04	14.05	-	-			
		THREAD	M40x1.5 AS PER T.R.G GO NOT GO	OK	OK	OK	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND	OK	OK	OK	-	-			
		CH.ANGLE	3x45° AS PER PP FOUND	OK	OK	OK	-	-			
		ANGLE	67° AS PER PP FOUND	OK	OK	OK	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING — QA PASSED