MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-022	**Product Name**	O-RING	**Size**	M20	**Drawing No.**	OR-1M	**Date:**	04-11-2026
Wo No.	26100096	**Total Quantity**	400	**Lot Quantity**	400	**Sample Size-**	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	NA	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	NA	NA	NA	NA	-	-		ASM No:- CEX260923-01	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK		-			
		All Dimensions Are In MM										

			VALUE	-	+	1	2	3	-	-			
2	DIMENSION	THICKNESS	2.50	2.00	2.50	2.08	2.06	2.05	-	-			
		I.D	16.00	15.50	16.50	16.05	16.04	16.03	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

METAL MECH
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-022	Product Name	PLUG	Size	M20	Drawing No.	PLG1M	Date:	04-11-2026
Wo No.	26100096	Total Quantity	400	Lot Quantity	400	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NICKEL	OK	OK	OK	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG1MB2 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X				-	-		ASM No:- CEX260923-01	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	-	-			
		T.L	21.00	20.50	21.50	21.13	21.12	21.11	-	-			
		LENGTH	16.00	15.50	16.50	16.05	16.06	16.04	-	-			
		TH.L	13.00	12.50	13.50	13.03	13.05	13.05	-	-			
		GR.OD	18.00	17.50	18.50	17.95	17.94	17.96	-	-			
		GR.LE	1.50	1.30	1.70	1.54	1.56	1.58	-	-			
		O.D	26.00	25.50	26.50	26.03	26.03	26.06	-	-			
		O.D.L	5.00	4.70	5.30	5.05	5.03	5.05	-	-			
		GR.ID	13.50	13.00	14.00	13.58	13.55	13.56	-	-			
		GR.LE	4.00	3.70	4.30	4.06	4.09	4.05	-	-			
		INT-(A/F)	10.00	10.00	10.20	10.12	10.11	10.13	-	-			
		INT-(A/F)-LENGTH	10.00	9.50	10.50	10.08	10.07	10.09	-	-			
		DEPTH	14.00	13.50	14.50	14.13	14.15	14.12	-	-			
		THREAD	M20x1.5 AS PER T.R.G GO NOT GO			OK	OK	OK	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND			OK	OK	OK	-	-			
		CH.ANGLE	2x45° AS PER PP FOUND			OK	OK	OK	-	-			
		GR.ANGLE	67° AS PER PP FOUND			OK	OK	OK	-	-			

INSPECTED BY:	Jay Hadiyal	APPROVED BY:	Shreekant

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING
QA PASSED