METAL MECA®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-05	Product Name	O-RING	Size	M16	Drawing No.	OR-0M	Date:	04-11-2026
Wo No.	26000343	Total Quantity	30	Lot Quantity	30	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	NA	NA	NA	-	-	-		ASM No :- CSEX261101-08	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-		
		THICKNESS	2.50	2.00	2.50	2.43	2.41	-	-	-		
		I.D	12.00	11.50	12.50	12.05	12.07	-	-	-		

INSPECTED BY:	Jay Hadiyal	APPROVED BY:	Shreekant

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-05	Product Name	PLUG	Size	M16	Drawing No.	PLG0M	Date:	04-11-2026
Wo No.	26000343	Total Quantity	30	Lot Quantity	30	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	-	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	-	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	-	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	-	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	-	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG0MX6 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X		-	-	-		ASM No :- CSEX261101-08	
		Assembly Perfection	As per Drg.		OK	OK	-	-	-			
		Inner Packing	Labeling & Printing		OK	OK	-	-	-			
		Outer Packing	Printing & Stamping		OK	OK	-	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	-	-	-			
		T.L	21.00	20.50	21.50	21.01	21.00	-	-	-			
		TH.L	13.00	12.50	13.50	12.99	13.01	-	-	-			
		LENGTH	16.00	15.50	16.50	16.07	16.06	-	-	-			
		GR.OD	14.00	13.50	14.50	14.05	14.04	-	-	-			
		GR.LE	1.50	1.30	1.70	1.55	1.54	-	-	-			
		O.D	22.00	21.50	22.50	21.91	21.93	-	-	-			
		O.D.L	5.00	4.70	5.30	4.95	4.94	-	-	-			
		GR.ID	11.50	11.00	12.00	11.55	11.54	-	-	-			
		GR.LE	4.00	3.70	4.30	4.08	4.06	-	-	-			
		INT-(A/F)	8.00	8.00	8.20	8.04	8.06	-	-	-			
		INT-(A/F)-LENGTH	10.00	9.50	10.50	10.05	10.04	-	-	-			
		DEPTH	14.00	13.50	14.50	14.08	14.06	-	-	-			
		THREAD	M16x1.5 AS PER T.R.G GO NOT GO			OK	OK	-	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND			OK	OK	-	-	-			
		CH.ANGLE	2x45° AS PER PP FOUND			OK	OK	-	-	-			
		GR.ANGLE	67° AS PER PP FOUND			OK	OK	-	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METAL MECH ENGINEERING CA PASSED