METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-03	Product Name	PLUG	Size	1/2" NPT	Drawing No.	PLG1N	Date:	17-10-2026
Wo No.	26000283	Total Quantity	200	Lot Quantity	200	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	NA	NA	NA	NA	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	NA	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	Metalmech Logo MM-EX-PLG1NX6 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X P538496/3			-	-		ASM No :- CSEX261003-08	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing Matters		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	-	-			
		T.L	14.00	13.50	14.50	14.01	14.00	14.02	-	-			
		GR.ID	13.50	13.00	14.00	13.53	13.55	13.54	-	-			
		GR.LE	3.00	2.80	3.20	3.05	3.04	3.03	-	-			
		INT-(A/F)	10.00	10.00	10.20	10.08	10.07	10.05	-	-			
		INT-(A/F)-LENGTH	8.00	7.70	8.30	8.05	8.07	8.09	-	-			
		DEPTH	11.00	10.50	11.50	11.06	11.05	11.04	-	-			
		CH.DIA	13 MM AS PER PP FOUND			OK	OK	OK	-	-			
		THREAD	1/2" NPT AS PER T.R.G GO NOT GO			OK	OK	OK	-	-			
		CH.ANGLE	1.6x45° AS PER PP FOUND			OK	OK	OK	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED