METAL MECH®
THE SAFEST CONNECTIONS

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-07	Product Name	O-RING	Size	M25	Drawing No.	OR-2M	Date:	04-11-2026
Wo No.	26000343	Total Quantity	150	Lot Quantity	150	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER			OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA		1	2	3	-	-			
1	Visual	Surface	Fine, Clean		FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts	2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing	NA	NA	NA	NA	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG.	NA	NA	NA	NA	-	-			
		Marking	WO Ref. No.	NA	NA	NA	NA	-	-		ASM No :- CSEX261101-10	
		Assembly Perfection	As per Drg.		OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing		OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping		OK	OK	OK	-	-			
		All Dimensions Are In MM										
2	DIMENSION		VALUE	-	+	1	2	3	-	-			
		THICKNESS	2.50	2.00	2.50	2.11	2.13	2.12	-	-		
		I.D	20.00	19.50	20.50	20.03	20.02	20.05	-	-		

INSPECTED BY:	Jay Hadiyal	APPROVED BY:	Shreekant

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

METALMECH ENGINEERING QA PASSED

MM-086000-SXUA-QCZA-FR-02-01-Final Inspection Report-Ex-V26I01

INSP. No.	FIR-07	Product Name	PLUG	Size	M25	Drawing No.	PLG2M	Date:	04-11-2026
Wo No.	26000343	Total Quantity	150	Lot Quantity	150	Sample Size-	3	Variable & Gauging	3PCS

Sr. No.	Checking Parameter	REQUIRED PARAMETER		OBSERVED RESULTS					REJECTION REWORK DETAIL	REMARK	CHECKED BY
		PARAMETER	CRITERIA	1	2	3	-	-			
1	Visual	Surface	Fine, Clean	FINE	FINE	FINE	-	-		Measuring Instruments I.D No-	
		Sizewise No of Pcs. With Internal Parts	As per Drg. No. of Parts: 2	2	2	2	-	-		(1) DV-55	
		Washing & Plating	Surface Finishing: NA	NA	NA	NA	-	-		(2) PP-01	
		RUBBER MARKING	AS PER DRG. / NA	NA	NA	NA	-	-			
		Marking	WO Ref. No. / Metalmech Logo MM-EX-PLG2MX6 2026 CE Logo 2460 Ex Logo II 2 GD Ex db IIC Gb, Ex eb IIC Gb, Ex tb IIIC Db, IP66/68 -55°C ≤ Ta ≤ +160°C Presafe 20 ATEX 24571X IECEx PRE 20.0123X				-	-		ASM No :- CSEX261101-10	
		Assembly Perfection	As per Drg.	OK	OK	OK	-	-			
		Inner Packing	Labeling & Printing	OK	OK	OK	-	-			
		Outer Packing	Printing & Stamping	OK	OK	OK	-	-			
		All Dimensions Are In MM									
2	DIMENSION		VALUE / - / +	1	2	3	-	-			
		T.L	22.00 / 21.50 / 22.50	22.03	22.02	22.02	-	-			
		TH.L	13.00 / 12.50 / 13.50	13.02	13.01	13.05	-	-			
		LENGTH	16.00 / 15.50 / 16.50	16.03	16.04	16.05	-	-			
		GR.OD	23.00 / 22.50 / 23.50	23.04	23.03	23.03	-	-			
		GR.LE	1.50 / 1.30 / 1.70	1.55	1.54	1.56	-	-			
		O.D	30.00 / 29.50 / 30.50	30.00	29.99	29.99	-	-			
		O.D.L	6.00 / 5.70 / 6.30	5.91	5.91	5.95	-	-			
		GR.ID	13.50 / 13.00 / 14.00	13.55	13.54	13.55	-	-			
		GR.LE	4.00 / 3.70 / 4.30	4.05	4.03	4.05	-	-			
		INT-(A/F)	10.00 / 10.00 / 10.20	10.06	10.05	10.03	-	-			
		INT-(A/F)-LENGTH	10.00 / 9.50 / 10.50	10.09	10.03	10.05	-	-			
		DEPTH	14.00 / 13.50 / 14.50	14.16	14.15	14.12	-	-			
		THREAD	M25x1.5 AS PER T.R.G GO NOT GO	OK	OK	OK	-	-			
		CH.ANGLE	1.5x45° AS PER PP FOUND	OK	OK	OK	-	-			
		CH.ANGLE	2x45° AS PER PP FOUND	OK	OK	OK	-	-			
		GR.ANGLE	67° AS PER PP FOUND	OK	OK	OK	-	-			

INSPECTED BY:	*Jay Hadiyal*	*APPROVED BY:*	*Shreekant*

Conclusion :

☑ **Accept** ☐ **Reject** ☐ **Hold**

