

Bansidhar Metals

Plot No. 16, R.S. NO - 89, Near-G.I.D.C., Phase-III, Beside Mahavir Circle, Vi. kansumara, Jamnagar. -361004

GSTIN : 24AAUFB1285E1ZG

EMAIL : bansidharmetals16@gmail.com

MOB. No. 9824080410

Test Certificate

Customer :	MTC No.	45	Date :	16-04-2026
MetalMech Engineering Jamanagar GIDC Phase III Road E Plot No 4246 ,Jamnagar ,Gujrat,	Invoice No .	58/2026-27		
	Po.No	EX-PO26/26100020		
	Qty.Kgs	760.300		

Particular	As Required By Specification	Specification Of Supplied Material				
I. Chemical Composition	EN 12164 CW614N CuZn39Pb3	Size	Size	Size	Size	Size
		80.00 X 65.00 MM HEX	76.00 X 58.00 MM HEX	80.00 X 60.00 MM HEX	85.00 X 70.00 MM HEX	30.00 MM HEX SOLID
		HEAT NO.	HEAT NO.	HEAT NO.	HEAT NO.	HEAT NO.
		4	4	4	4	4
1. COPPER (Cu) %	57.00 - 59.00	57.92	57.92	57.92	57.92	57.92
2. LEAD (Pb) %	2.50 - 3.50	2.89	2.89	2.89	2.89	2.89
3. IRON (Fe)%	0.30 Max	0.27	0.27	0.27	0.27	0.27
4. ZINC (Zn) %	Remainder	38.22	38.22	38.22	38.22	38.22
5. ALUMINIUM (Al)%	0.05 Max	0	0	0	0	0
6. MANGANESE (Mn)%	-	-	-	-	-	-
7. NICKLE (Ni)%	0.30 Max	0.29	0.29	0.29	0.29	0.29
8. TIN (Sn)%	0.30 Max	0.27	0.27	0.27	0.27	0.27
9. SILICON (Si)%	-	-	-	-	-	-
10. PHOSPHORUS (P)%	-	-	-	-	-	-
11. SULPHAR (S) %	-	-	-	-	-	-
12. TOTAL IMPURITIES %	0.20 Max	0.14	0.14	0.14	0.14	0.14

1. UTS- MIIN (Mpa)	360 MIN	361	361	361	361	361
2. ELONGATION %	20 MIN	23	23	23	23	23
3. HARDNESS (HV5)	-	-	-	-	-	-
4. IZOD	-	-	-	-	-	-
5. 0.2% PROOF STRESS	350 MAX	341	341	341	341	341

1. CONDUCTIVITY	-					
-----------------	---	--	--	--	--	--



For Banshidhar Metal



Authorised Signature

Bansidhar Metals

Plot No. 16, R.S. NO - 89, Near-G.I.D.C., Phase-III, Beside Mahavir Circle, Vi. kansumara, Jamnagar.-361004

GSTIN : 24AAUFB1285E1ZG

EMAIL : bansidharmetals16@gmail.com

MOB. No. 9824080410

Test Certificate

Customer :	MTC No.	45	Date :	16-04-2026
MetalMech Engineering Jamnagar GIDC Phase III Road E Plot No 4246 ,Jamnagar ,Gujrat,	Invoice No .	58/2026-27		
	Po.No	EX-PO26/26100020		
	Qty.Kgs	1202.300		

Particular	As Required By Specifcattion	Specification Of Supplied Material				
I. Chemical Composition	EN 12164 CW614N CuZn39Pb3	Size	Size	Size	Size	Size
		85.00 X 66.00 MM HEX	25.00 MM HEX SOLID	36.00 X 1800 MM HEX		
		HEAT NO.	HEAT NO.	HEAT NO.		
		4	4	4		
1. COPPER (Cu) %	57.00 - 59.00	57.92	57.92	57.92		
2. LEAD (Pb) %	2.50 - 3.50	2.89	2.89	2.89		
3. IRON (Fe)%	0.30 Max	0.27	0.27	0.27		
4. ZINC (Zn) %	Remainder	38.22	38.22	38.22		
5. ALUMINIUM (Al)%	0.05 Max	0	0	0		
6. MANGANESE (Mn)%	-	-	-	-		
7.NICKLE (Ni)%	0.30 Max	0.29	0.29	0.29		
8.TIN (Sn)%	0.30 Max	0.27	0.27	0.27		
9.SILICON (Si)%	-	-	-	-		
10.PHOSPHORUS (P)%	-	-	-	-		
11.SULPHAR (S) %	-	-	-	-		
12. TOTAL IMPURITIES %	0.20 Max	0.14	0.14	0.14		

1. UTS- MIIN (Mpa)	360 MIN	361	361	361		
2. ELONGATION %	20 MIN	23	23	23		
3. HARDNESS (HV5)	-	-	-	-		
4.IZOD	-	-	-	-		
5. 0.2% PROOF STRESS	350 MAX	341	341	341		

1.CONDUCTIVITY	-					
----------------	---	--	--	--	--	--



For Banshidhar Metal



Authorised Signature