

# Bansidhar Metals

Plot No. 16, R.S. NO - 89, Near-G.I.D.C., Phase-III, Beside Mahavir Circle, Vi. kansumara, Jamnagar.-361004

GSTIN : 24AAUFB1285E1ZG

EMAIL : bansidharmetals16@gmail.com

MOB. No. 9824080410

## Test Certificate

|                                                                                                                                 |              |                  |        |            |
|---------------------------------------------------------------------------------------------------------------------------------|--------------|------------------|--------|------------|
| Customer :                                                                                                                      | MTC No.      | 449              | Date : | 25-06-2026 |
| METALMECH ENGINEERING<br>R/S NO. 580, PLOT NO.1, NEAR<br>BHARAT PETROLEUM, SASOI DAM<br>ROAD, KHOJABERAJA, JAMNAGAR -<br>361012 | Invoice No . | 386/2026-27      |        |            |
|                                                                                                                                 | Po.No        | EX-PO26/26100211 |        |            |
|                                                                                                                                 | Qty.Kgs      | 79.050           |        |            |

| Particular              | As Required By<br>Specification | Specification Of Supplied Material |      |      |      |      |
|-------------------------|---------------------------------|------------------------------------|------|------|------|------|
| I. Chemical Composition | EN 12164<br>CW614N<br>CuZn39Pb3 | Size                               | Size | Size | Size | Size |
|                         |                                 | 70.00 X 61.00<br>MM ROUND          |      |      |      |      |
|                         |                                 | HEAT NO.                           |      |      |      |      |
|                         |                                 | 2                                  |      |      |      |      |
| 1. COPPER (Cu) %        | 57.00 - 59.00                   | 57.86                              |      |      |      |      |
| 2. LEAD (Pb) %          | 2.50 - 3.50                     | 2.93                               |      |      |      |      |
| 3. IRON (Fe)%           | 0.30 Max                        | 0.23                               |      |      |      |      |
| 4. ZINC (Zn) %          | Remainder                       | 38.39                              |      |      |      |      |
| 5. ALUMINIUM (Al)%      | 0.05 Max                        | 0                                  |      |      |      |      |
| 6. MANGANESE (Mn)%      | -                               | -                                  |      |      |      |      |
| 7. NICKLE (Ni)%         | 0.30 Max                        | 0.16                               |      |      |      |      |
| 8. TIN (Sn)%            | 0.30 Max                        | 0.27                               |      |      |      |      |
| 9. SILICON (Si)%        | -                               | -                                  |      |      |      |      |
| 10. PHOSPHORUS (P)%     | -                               | -                                  |      |      |      |      |
| 11. SULPHAR (S) %       | -                               | -                                  |      |      |      |      |
| 12. TOTAL IMPURITIES %  | 0.20 Max                        | 0.16                               |      |      |      |      |

|                      |         |     |  |  |  |  |
|----------------------|---------|-----|--|--|--|--|
| 1. UTS- MIIN (Mpa)   | 360 MIN | 365 |  |  |  |  |
| 2. ELONGATION %      | 20 MIN  | 25  |  |  |  |  |
| 3. HARDNESS (HV5)    | -       | -   |  |  |  |  |
| 4. IZOD              | -       | -   |  |  |  |  |
| 5. 0.2% PROOF STRESS | 350 MAX | 342 |  |  |  |  |

|                 |   |  |  |  |  |  |
|-----------------|---|--|--|--|--|--|
| 1. CONDUCTIVITY | - |  |  |  |  |  |
|-----------------|---|--|--|--|--|--|



For Banshidhar Metal



Authorised Signature



# Bansidhar Metals

Plot No. 16, R.S. NO - 89, Near-G.I.D.C., Phase-III, Beside Mahavir Circle, Vi. kansumara, Jamnagar.-361004

GSTIN : 24AAUFB1285E1ZG

EMAIL : bansidharmetals16@gmail.com

MOB. No. 9824080410

## Test Certificate

|                                                                                                                                 |              |                  |        |            |
|---------------------------------------------------------------------------------------------------------------------------------|--------------|------------------|--------|------------|
| Customer :                                                                                                                      | MTC No.      | 449              | Date : | 25-06-2026 |
| METALMECH ENGINEERING<br>R/S NO. 580, PLOT NO.1, NEAR<br>BHARAT PETROLEUM, SASOI DAM<br>ROAD, KHOJABERAJA, JAMNAGAR -<br>361012 | Invoice No . | 386/2026-27      |        |            |
|                                                                                                                                 | Po.No        | EX-PO26/26100211 |        |            |
|                                                                                                                                 | Qty.Kgs      | 1513.750         |        |            |

| Particular              | As Required By<br>Specifcattion | Specification Of Supplied Material |                        |                            |                         |                         |
|-------------------------|---------------------------------|------------------------------------|------------------------|----------------------------|-------------------------|-------------------------|
| I. Chemical Composition | EN 12164<br>CW614N<br>CuZn39Pb3 | Size                               | Size                   | Size                       | Size                    | Size                    |
|                         |                                 | 25.00 MM HEX<br>SOLID              | 25.00 X 14.00<br>MMHEX | 80.00 X<br>64.00 MM<br>HEX | 76.00 X 58.00<br>MM HEX | 80.00 X 69.00<br>MM HEX |
|                         |                                 | HEAT NO.                           | HEAT NO.               | HEAT NO.                   | HEAT NO.                | HEAT NO.                |
|                         |                                 | 2                                  | 2                      | 2                          | 2                       | 2                       |
| 1. COPPER (Cu) %        | 57.00 - 59.00                   | 57.86                              | 57.86                  | 57.86                      | 57.86                   | 57.86                   |
| 2. LEAD (Pb) %          | 2.50 - 3.50                     | 2.93                               | 2.93                   | 2.93                       | 2.93                    | 2.93                    |
| 3. IRON (Fe)%           | 0.30 Max                        | 0.23                               | 0.23                   | 0.23                       | 0.23                    | 0.23                    |
| 4. ZINC (Zn) %          | Remainder                       | 38.39                              | 38.39                  | 38.39                      | 38.39                   | 38.39                   |
| 5. ALUMINIUM (Al)%      | 0.05 Max                        | 0                                  | 0                      | 0                          | 0                       | 0                       |
| 6. MANGANESE (Mn)%      | -                               | -                                  | -                      | -                          | -                       | -                       |
| 7. NICKLE (Ni)%         | 0.30 Max                        | 0.16                               | 0.16                   | 0.16                       | 0.16                    | 0.16                    |
| 8. TIN (Sn)%            | 0.30 Max                        | 0.27                               | 0.27                   | 0.27                       | 0.27                    | 0.27                    |
| 9. SILICON (Si)%        | -                               | -                                  | -                      | -                          | -                       | -                       |
| 10. PHOSPHORUS (P)%     | -                               | -                                  | -                      | -                          | -                       | -                       |
| 11. SULPHAR (S) %       | -                               | -                                  | -                      | -                          | -                       | -                       |
| 12. TOTAL IMPURITIES %  | 0.20 Max                        | 0.16                               | 0.16                   | 0.16                       | 0.16                    | 0.16                    |
| 1. UTS- MIIN (Mpa)      | 360 MIN                         | 365                                | 365                    | 365                        | 365                     | 365                     |
| 2. ELONGATION %         | 20 MIN                          | 25                                 | 25                     | 25                         | 25                      | 25                      |
| 3. HARDNESS (HV5)       | -                               | -                                  | -                      | -                          | -                       | -                       |
| 4. IZOD                 | -                               | -                                  | -                      | -                          | -                       | -                       |
| 5. 0.2% PROOF STRESS    | 350 MAX                         | 342                                | 342                    | 342                        | 342                     | 342                     |

|                 |   |  |  |  |  |  |
|-----------------|---|--|--|--|--|--|
| 1. CONDUCTIVITY | - |  |  |  |  |  |
|-----------------|---|--|--|--|--|--|



For Banshidhar Metal



Authorised Signature