Features

- Low On-Resistance
  - 60mΩ @ V_{GS} = -4.5V
  - 90mΩ @ V_{GS} = -2.5V
  - 113mΩ @ V_{GS} = -1.8V
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT23
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish — Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208 e3
- Terminals Connections: See Diagram Below
- Weight: 0.008 grams (approximate)

Top View



Internal Schematic



Top View

Ordering Information (Note 4)

Part Number	Qualification	Case	Packaging
DMP2305U-7	Commercial	SOT23	3000/Tape & Reel
DMP2305UQ-7	Automotive	SOT23	3000/Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at http://www.diodes.com.

Marking Information



23P = Product Type Marking Code
YM = Date Code Marking
Y = Year (ex: W = 2009)
M = Month (ex: 9 = September)

Date Code Key

Year	2009	2010	2011	2012	2013	2014	2015
Code	W	X	Y	Z	A	B	C

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic			Symbol	Value	Units
Drain-Source Voltage			V_{DSS}	-20	V
Gate-Source Voltage			V_{GSS}	±8	V
Continuous Drain Current (Note 5)	Steady State	T_A = 25°C T_A = 70°C	I_D	-4.2 -3.4	A
Pulsed Drain Current (Note 6)			I_{DM}	-10	A

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 5)	P_D	1.4	W
Thermal Resistance, Junction to Ambient @T_A = 25°C	$R_{\theta JA}$	90	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 7)							
Drain-Source Breakdown Voltage		BV_{DSS}	-20	—	—	V	V_{GS} = 0V, I_D = -250μA
Zero Gate Voltage Drain Current	T_J = 25°C	I_{DSS}	—	—	-1.0	μA	V_{DS} = -20V, V_{GS} = 0V
Gate-Source Leakage		I_{GSS}	—	—	±100	nA	V_{GS} = ±8V, V_{DS} = 0V
ON CHARACTERISTICS (Note 7)							
Gate Threshold Voltage		$V_{GS(th)}$	-0.5	-	-0.9	V	V_{DS} = V_{GS}, I_D = -250μA
Static Drain-Source On-Resistance		$R_{DS\ (ON)}$	—	45	60	mΩ	V_{GS} = -4.5V, I_D = -4.2A
				60	90		V_{GS} = -2.5V, I_D = -3.4A
				87	113		V_{GS} = -1.8V, I_D = -2.0A
Forward Transfer Admittance		$\|Y_{fs}\|$	—	9	—	S	V_{DS} = -5V, I_D = -4A
DYNAMIC CHARACTERISTICS							
Input Capacitance		C_{iss}	—	727	—	pF	V_{DS} = -20V, V_{GS} = 0V f = 1.0MHz
Output Capacitance		C_{oss}	—	69	—	pF	
Reverse Transfer Capacitance		C_{rss}	—	64	—	pF	
Gate Resistance		R_G		23		Ω	V_{GS} = 0V, V_{DS} = 0V, f = 1.0MHz
SWITCHING CHARACTERISTICS							
Total Gate Charge		Q_g	—	7.6	—	nC	V_{GS} = -4.5V, V_{DS} = -4V, I_D = -3.5A
Gate-Source Charge		Q_{gs}	—	1.4	—	nC	
Gate-Drain Charge		Q_{gd}	—	1.2	—	nC	
Turn-On Delay Time		$t_{D(on)}$	—	14.0	—	ns	V_{DS} = -4V, V_{GS} = -4.5V, R_L = 4Ω, R_G = 6Ω, I_D = -1A
Turn-On Rise Time		t_r	—	13.0	—	ns	
Turn-Off Delay Time		$t_{D(off)}$	—	53.8	—	ns	
Turn-Off Fall Time		t_f	—	23.2	—	ns	

Notes:
5. Device mounted on FR-4 PCB with 2oz. Copper and test pulse width t ≤ 10s.
6. Repetitive rating, pulse width limited by junction temperature.
7. Short duration pulse test used to minimize self-heating effect.



Fig. 1 Typical Output Characteristic



Fig. 2 Typical Transfer Characteristic



Fig. 3 Typical On-Resistance
vs. Drain Current and Gate Voltage



Fig. 4 Typical On-Resistance
vs. Drain Current and Temperature



Fig. 5 On-Resistance Variation with Temperature



Fig. 6 On-Resistance Variation with Temperature



Fig. 7 Gate Threshold Variation vs. Ambient Temperature



Fig. 8 Diode Forward Voltage vs. Current



Fig. 9 Typical Total Capacitance



Fig. 10 Typical Leakage Current vs. Drain-Source Voltage



Fig. 11 SOA, Safe Operation Area



Fig. 12 Transient Thermal Response

Package Outline Dimensions



SOT23			
Dim	**Min**	**Max**	**Typ**
A	0.37	0.51	0.40
B	1.20	1.40	1.30
C	2.30	2.50	2.40
D	0.89	1.03	0.915
F	0.45	0.60	0.535
G	1.78	2.05	1.83
H	2.80	3.00	2.90
J	0.013	0.10	0.05
K	0.903	1.10	1.00
K1	-	-	0.400
L	0.45	0.61	0.55
M	0.085	0.18	0.11
α	0°	8°	-
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
Z	2.9
X	0.8
Y	0.9
C	2.0
E	1.35

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

www.diodes.com