# EM74LVC11

**Triple 3-input AND gate**

Product datasheet, Rev. 1.1 May 30, 2025

# 1. General Description

The EM74LVC11 provides three 3-input AND functions. Inputs can be driven from either 3.3 V or 5 V devices. This feature allows the use of these devices as translators in mixed 3.3 V and 5 V environments.

Schmitt-trigger action at all inputs makes the circuit tolerant of slower input rise and fall times.

This device is fully specified for partial power down applications using $I_{OFF}$. The $I_{OFF}$ circuitry disables the output, preventing the potentially damaging backflow current through the device when it is powered down.

# 2. Features and Benefits

- Wide supply voltage range from 1.2 V to 5.5 V
- Overvoltage tolerant inputs to 5.5 V
- CMOS low power dissipation
- $I_{OFF}$ circuitry provides partial Power-down mode operation
- Latch-up performance exceeds 250 mA
- Direct interface with TTL levels
- Complies with JEDEC standard:
  - JESD8-7A (1.65 V to 1.95 V)
  - JESD8-5A (2.3 V to 2.7 V)
  - JESD8-C (2.7 V to 3.6 V)
  - JESD36 (4.5 V to 5.5 V)
- ESD protection:
  - HBM ANSI/ESDA/JEDEC JS-001 Class 3A exceeds 6000 V
  - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options


# 3. Ordering Information

**Table 1. Ordering information**

| Type number | Topside marking | Package | | |
|---|---|---|---|---|
| | | Name | Description | Quantity |
| EM74LVC11D | LVC11<br>XYYWW | SOP-14L | plastic small outline package; 14 leads; body width 3.9 mm | 3000 |
| EM74LVC11PW | LVC11<br>XYYWW | TSSOP-14L | plastic thin shrink small outline package; 14 leads; body width 4.4 mm | 3000 |

**MARKING INFORMATION**

NOTE: XYYWW = Vendor Code and Data Code.




# 4. Function Diagram





Fig. 1. Logic symbol





Fig. 2. IEC logic symbol





Fig. 3. Logic diagram (one gate)

# 5. Pinning Information

## 5.1. Pinning





Fig. 4. Top view pin configuration SOP and TSSOP

## 5.2. Pin description

**Table 2. Pin description**

| Symbol | Pin | Description |
|---|---|---|
| 1A, 2A, 3A | 1, 3, 9 | Data input |
| 1B, 2B, 3B | 2, 4, 10 | Data input |
| 1C, 2C, 3C | 13, 5, 11 | Data input |
| 1Y, 2Y, 3Y | 12, 6, 8 | Data output |
| GND | 7 | Ground (0V) |
| $V_{CC}$ | 14 | Supply voltage |

# 6. Functional Description

**Table 3. Function table**

H = HIGH voltage level; L = LOW voltage level; X = don't care.

| Input | | | Output |
|---|---|---|---|
| **nA** | **nB** | **nC** | **nY** |
| L | X | X | L |
| X | L | X | L |
| X | X | L | L |
| H | H | H | H |

# 7. Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

**Table 4. Absolute Maximum Ratings**

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

| Symbol | Parameter | Conditions | Min | Max | Unit |
|---|---|---|---|---|---|
| $V_{CC}$ | supply voltage | | -0.5 | 6.5 | V |
| $I_{IK}$ | input clamping current | $V_I < 0$ V | -50 | | mA |
| $V_I$ | input voltage | [1] | -0.5 | 6.5 | V |
| $I_{OK}$ | output clamping current | $V_O > V_{CC}$ or $V_O < 0$ V | | ±50 | mA |
| $V_O$ | output voltage | Activemode [1] | -0.5 | $V_{CC}$ + 0.5 | V |
| | | Power-down mode; $V_{CC}$ = 0 V [1] | -0.5 | 6.5 | V |
| $I_O$ | output current | $V_O$ = 0 V to $V_{CC}$ | | ±50 | mA |
| $I_{CC}$ | supply current | | | 100 | mA |
| $I_{GND}$ | ground current | | -100 | | mA |
| $P_{tot}$ | total power dissipation | $T_{amb}$ = -40 °C to + 125 °C | | 500 | mW |
| $T_{stg}$ | storage temperature | | -65 | 150 | °C |

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

# 8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

**Table 5. Recommended Operating Conditions**

| Symbol | Parameter | Conditions | Min | Max | Unit |
|---|---|---|---|---|---|
| $V_{CC}$ | supply voltage | | 1.65 | 5.5 | V |
| | | functional | 1.2 | | V |
| $V_I$ | input voltage | | 0 | 5.5 | V |
| $V_O$ | output voltage | Active mode | 0 | $V_{CC}$ | V |
| | | Power-down mode; $V_{CC}$ = 0 V | 0 | 5.5 | V |
| $T_{amb}$ | ambient temperature | | -40 | 125 | °C |
| Δt/ΔV | input transition rise and fall rate | $V_{CC}$ = 1.65 V to 2.7 V | 0 | 20 | ns/V |
| | | $V_{CC}$ = 2.7 V to 3.6 V | 0 | 10 | ns/V |
| | | $V_{CC}$ = 4.5 V to 5.5 V | 0 | 5 | ns/V |

# 9.Static Characteristics

**Table 6. Static characteristics**

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ[1] | Max | Min | Max | |
| $V_{IH}$ | HIGH-level input voltage | $V_{CC}$ = 1.2 V | 1.08 | | | 1.08 | | V |
| | | $V_{CC}$ = 1.65 V to 1.95 V | 0.65$V_{CC}$ | | | 0.65$V_{CC}$ | | V |
| | | $V_{CC}$ = 2.3 V to 2.7 V | 1.7 | | | 1.7 | | V |
| | | $V_{CC}$ = 2.7 V to 3.6 V | 2.0 | | | 2.0 | | V |
| | | $V_{CC}$ = 4.5 V to 5.5 V | 0.7$V_{CC}$ | | | 0.7$V_{CC}$ | | V |
| $V_{IL}$ | LOW-level input voltage | $V_{CC}$ = 1.2 V | | | 0.12 | | 0.12 | V |
| | | $V_{CC}$ = 1.65 V to 1.95 V | | | 0.35$V_{CC}$ | | 0.35$V_{CC}$ | V |
| | | $V_{CC}$ = 2.3 V to 2.7 V | | | 0.7 | | 0.7 | V |
| | | $V_{CC}$ = 2.7 V to 3.6 V | | | 0.8 | | 0.8 | V |
| | | $V_{CC}$ = 4.5 V to 5.5 V | | | 0.3$V_{CC}$ | | 0.3$V_{CC}$ | V |
| $V_{OH}$ | HIGH-level output voltage | $V_I$ = $V_{IH}$ or $V_{IL}$ | | | | | | |
| | | $I_O$ = -100µA; $V_{CC}$ = 1.65 V to 5.5 V | $V_{CC}$ - 0.1 | | | $V_{CC}$ - 0.1 | | V |
| | | $I_O$ = -4 mA; $V_{CC}$ = 1.65 V | 1.2 | | | 1.05 | | V |
| | | $I_O$ = -8 mA; $V_{CC}$ = 2.3 V | 1.9 | | | 1.7 | | V |
| | | $I_O$ = -12 mA; $V_{CC}$ = 2.7 V | 2.2 | | | 2.05 | | V |
| | | $I_O$ = -24 mA; $V_{CC}$ = 3.0 V | 2.2 | | | 2.0 | | V |
| | | $I_O$ = -32 mA; $V_{CC}$ = 4.5 V | 3.8 | | | 3.5 | | V |
| $V_{OL}$ | LOW-level output voltage | $V_I$ = $V_{IH}$ or $V_{IL}$ | | | | | | |
| | | $I_O$ = 100 µA; $V_{CC}$ = 1.65 V to 5.5 V | | | 0.10 | | 0.10 | V |
| | | $I_O$ = 4 mA; $V_{CC}$ = 1.65 V | | | 0.45 | | 0.65 | V |
| | | $I_O$ = 8 mA; $V_{CC}$ = 2.3 V | | | 0.30 | | 0.45 | V |
| | | $I_O$ = 12 mA; $V_{CC}$ = 2.7 V | | | 0.40 | | 0.60 | V |
| | | $I_O$ = 24 mA; $V_{CC}$ = 3.0 V | | | 0.55 | | 0.80 | V |
| | | $I_O$ = 32 mA; $V_{CC}$ = 4.5 V | | | 0.55 | | 0.80 | V |
| $I_I$ | input leakage current | $V_I$ = 5.5 V or GND ; $V_{CC}$ = 0 V to 5.5 V | | ±0.1 | ±5 | | ±20 | µA |

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ[1] | Max | Min | Max | |
| $I_{OFF}$ | power-off leakage current | $V_{CC}$ = 0 V; $V_I$ or $V_O$ = 5.5 V | | ±0.1 | ±10 | | ±20 | µA |
| $I_{CC}$ | supply current | $V_{CC}$ = 1.65 V to 5.5 V ; $V_I$ = $V_{CC}$ or GND ; $I_O$ = 0 A ; | | 0.01 | 10 | | 40 | µA |
| $\Delta I_{CC}$ | additional supply current | per input pin ; $V_{CC}$ = 2.3 V to 5.5 V ; $V_I$ = $V_{CC}$ - 0.6 V ; $I_O$ = 0 A | | 0.2 | 500 | | 5000 | µA |
| $C_I$ | input capacitance | $V_{CC}$ = 3.3 V ; $V_I$ = GND to $V_{CC}$ | | 4 | | | | pF |

[1]All typical values are measured at $V_{CC}$ = 3.3V and $T_{amb}$ = 25 °C.

# 10. Dynamic Characteristics

**Table 7. Dynamic characteristics**

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 6.

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | Min | Typ[1] | Max | Min | Max | |
| $t_{pd}$ | propagation delay | nA to nY; see Fig. 5 [2] | | | | | | |
| | | $V_{CC}$ = 1.2 V | | 36 | | | | ns |
| | | $V_{CC}$ = 1.65 V to 1.95 V | 3.4 | 11.4 | 22 | 3.4 | 22.5 | ns |
| | | $V_{CC}$ = 2.3 V to 2.7 V | 2.7 | 6.3 | 10.5 | 2.7 | 11 | ns |
| | | $V_{CC}$ = 3.0 V to 3.6 V | 2.0 | 4.6 | 7.5 | 2.0 | 8.0 | ns |
| | | $V_{CC}$ = 4.5 V to 5.5 V | 1.5 | 3.3 | 5 | 1.5 | 5.5 | ns |
| $C_{PD}$ | power dissipation capacitance | per gate ; $V_I$ = GND to $V_{CC}$ [3] | | | | | | |
| | | $V_{CC}$ = 1.65 V to 1.95 V | | 12.7 | | | | pF |
| | | $V_{CC}$ = 2.3 V to 2.7 V | | 13.4 | | | | pF |
| | | $V_{CC}$ = 3.0 V to 3.6 V | | 14.3 | | | | pF |
| | | $V_{CC}$ = 4.5 V to 5.5 V | | 16.2 | | | | pF |

[1] Typical values are measured at $T_{amb}$ = 25 °C and $V_{CC}$ = 1.2 V, 1.8 V, 2.5 V, 3.3 V and 5.0 V respectively.

[2] $t_{pd}$ is the same as $t_{PLH}$ and $t_{PHL}$.

[3] $C_{PD}$ is used to determine the dynamic power dissipation ($P_D$ in µW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

$f_i$ = input frequency in MHz;

$f_o$ = output frequency in MHz;


$C_L$ = output load capacitance in pF;

$V_{CC}$ = supply voltage in V;

N = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

## 10.1. Waveforms and test circuit





Measurement points are given in Table 8.
$V_{OL}$ and $V_{OH}$ are typical output voltage levels that occur with the output load.

Fig. 5. The input nA,nB,nC to output nY propagation delays

**Table 8. Measurement points**

| Supply voltage | Input | Output |
|---|---|---|
| $V_{CC}$ | $V_M$ | $V_M$ |
| 1.2 V | $0.5V_{CC}$ | $0.5V_{CC}$ |
| 1.65 V to 1.95 V | $0.5V_{CC}$ | $0.5V_{CC}$ |
| 2.3 V to 2.7 V | $0.5V_{CC}$ | $0.5V_{CC}$ |
| 3.0 V to 3.6 V | 1.5 V | 1.5 V |
| 4.5 V to 5.5 V | $0.5V_{CC}$ | $0.5V_{CC}$ |







Test data is given in Table 9.
Definitions for test circuit:
$R_L$ = Load resistance.
$C_L$ = Load capacitance including jig and probe capacitance.
$R_T$ = Termination resistance should be equal to the output impedance $Z_o$ of the pulse generator.


Fig. 6. Test circuit for measuring switching times

**Table 9. Test data**

| Supply voltage | Input | | Load | |
|---|---|---|---|---|
| $V_{CC}$ | $V_I$ | $t_r = t_f$ | $C_L$ | $R_L$ |
| 1.2 V | $V_{CC}$ | ≤ 2.0 ns | 15 pF | 500 Ω |
| 1.65 V to 1.95 V | $V_{CC}$ | ≤ 2.0 ns | 15 pF | 500 Ω |
| 2.3 V to 2.7 V | $V_{CC}$ | ≤ 2.0 ns | 15 pF | 500 Ω |
| 3.0 V to 3.6 V | 3 V | ≤ 2.0 ns | 15 pF | 500 Ω |
| 4.5 V to 5.5 V | $V_{CC}$ | ≤ 2.0 ns | 15 pF | 500 Ω |


# 11. Package Outline

**SOP-14L**




| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | — — | 1.750 | — — | 0.069 |
| A1 | 0.100 | 0.250 | 0.004 | 0.010 |
| A2 | 1.250 | — — | 0.049 | — — |
| b | 0.310 | 0.510 | 0.012 | 0.020 |
| c | 0.100 | 0.250 | 0.004 | 0.010 |
| D | 8.450 | 8.850 | 0.333 | 0.348 |
| E | 5.800 | 6.200 | 0.228 | 0.244 |
| E1 | 3.800 | 4.000 | 0.150 | 0.157 |
| e | 1.270(BSC) | | 0.050(BSC) | |
| L | 0.400 | 1.270 | 0.016 | 0.050 |
| θ | 0° | 8° | 0° | 8° |

**TSSOP-14L**




| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|---|---|---|---|---|
| | Min. | Max. | Min. | Max. |
| D | 4.900 | 5.100 | 0.193 | 0.201 |
| E | 4.300 | 4.500 | 0.169 | 0.177 |
| b | 0.190 | 0.300 | 0.007 | 0.012 |
| c | 0.090 | 0.200 | 0.004 | 0.008 |
| E1 | 6.250 | 6.550 | 0.246 | 0.258 |
| A | — | 1.200 | — | 0.047 |
| A2 | 0.800 | 1.000 | 0.031 | 0.039 |
| A1 | 0.050 | 0.150 | 0.002 | 0.006 |
| e | 0.65 (BSC) | | 0.026 (BSC) | |
| L | 0.500 | 0.700 | 0.020 | 0.028 |
| H | 0.25(TYP) | | 0.01(TYP) | |
| θ | 1° | 7° | 1° | 7° |

# 12. Tape and Reel Information

## 12.1. Carrier tape dimensions





**Table 10. Carrier tape dimensions**

| Package version | A0(mm) | B0(mm) | K0(mm) | T(mm) | P1(mm) | W(mm) | P0(mm) | PIN 1 |
|---|---|---|---|---|---|---|---|---|
| SOP-14L | 6.35 | 9.1 | 1.9 | 0.22 | 8 | 16 | 4 | Q1 |
| TSSOP-14L | 6.7 | 5.45 | 1.6 | 0.25 | 8 | 12 | 4 | Q1 |

## 12.2. Reel and box dimensions





**Table 11. Dimensions and quantities**

| Package version | Type NO. ending | Reel Dimension A (mm) | Reel Width W1 (mm) | MPQ (pcs) | Reels per box | Outer box dimensions L×W×H(mm) |
|---|---|---|---|---|---|---|
| SOP-14L | D | 330 | 22.4 | 3000 | 1 | 358x340x50 |
| TSSOP-14L | PW | 330 | 18.4 | 3000 | 1 | 358x340x50 |

# 13. Abbreviations

**Table 12. Abbreviations**

| Acronym | Description |
|---|---|
| CMOS | Complementary Metal-Oxide Semiconductor |
| DUT | Device Under Test |
| ESD | ElectroStatic Discharge |
| HBM | Human Body Model |
| CDM | Charged Device Model |
| TTL | Transistor-Transistor Logic |

# 14. Revision History

**Table 13. Revision history**

| Document ID | Release Date | Data sheet status | Change notice | Supersedes |
|---|---|---|---|---|
| EM74LVC11 Rev. 1.1 | May 30, 2025 | Product datasheet | | EM74LVC11 Rev. 1.0 |
| Modifications: | • Table 5 updated.<br>• Section 12 added tape and reel information. | | | |
| EM74LVC11 Rev. 1.0 | Oct 30, 2023 | Product datasheet | | |