EM74LVC14A

Hex inverting Schmitt trigger with 5 V tolerant input

Product datasheet, Rev. 1.2 Jul 29, 2025

1. General Description

The EM74LVC14A is a hex inverter with Schmitt-trigger inputs. Inputs can be driven from either 3.3 V or 5 V devices. This feature allows the use of these devices as translators in mixed 3.3 V and 5 V environments.

This device is fully specified for partial power down applications using I_{OFF}. The I_{OFF} circuitry disables the output, preventing the potentially damaging backflow current through the device when it is powered down.

2. Features and Benefits

- Wide supply voltage range from 1.2 V to 5.5 V
- Overvoltage tolerant inputs to 5.5 V
- CMOS low power dissipation
- I_{OFF} circuitry provides partial Power-down mode operation
- Latch-up performance exceeds 250 mA
- Direct interface with TTL levels
- Complies with JEDEC standard:
  - JESD8-7A (1.65 V to 1.95 V)
  - JESD8-5A (2.3 V to 2.7 V)
  - JESD8-C (2.7 V to 3.6 V)
  - JESD36 (4.5 V to 5.5 V)
- ESD protection:
  - HBM ANSI/ESDA/JEDEC JS-001 Class 3A exceeds 6000 V
  - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options


3. Ordering Information

Table 1. Ordering information

Type number	Topside marking	Package		
		Name	Description	Quantity
EM74LVC14AD	LVC14A XYYWW	SOP-14L	plastic small outline package; 14 leads; body width 3.9 mm	3000
EM74LVC14APW	LVC14A XYYWW	TSSOP-14L	plastic thin shrink small outline package; 14 leads; body width 4.4 mm	3000

MARKING INFORMATION

NOTE: XYYWW = Vendor Code and Date Code.



4. Function Diagram




Fig. 1. Logic symbol




Fig. 2. IEC logic symbol




Fig. 3. Logic diagram(one gate)

5. Pinning Information

5.1. Pinning




Fig. 4. Top view pin configuration SOP and TSSOP

5.2. Pin description

Table 2. Pin description

Symbol	Pin	Description
1A, 2A, 3A, 4A, 5A, 6A	1, 3, 5, 9, 11, 13	Data input
1Y, 2Y, 3Y, 4Y, 5Y, 6Y	2, 4, 6, 8, 10, 12	Data output
GND	7	Ground (0V)
V_{CC}	14	Supply voltage

6. Functional Description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level.

Input nA	Output nY
L	H
H	L

7. Absolute Maximum Ratings

Stresses exceeding the absolut`e maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Table 4. Absolute Maximum Ratings

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		-0.5	6.5	V
I_{IK}	input clamping current	$V_I < 0$ V	-50		mA
V_I	input voltage	[1]	-0.5	6.5	V
I_{OK}	output clamping current	$V_O > V_{CC}$ or $V_O < 0$ V		±50	mA
V_O	output voltage	Active mode [1]	-0.5	V_{CC} + 0.5	V
		Power-down mode; V_{CC} = 0 V [1]	-0.5	6.5	V
I_O	output current	V_O = 0 V to V_{CC}		±50	mA
I_{CC}	supply current			100	mA
I_{GND}	ground current		-100		mA
P_{tot}	total power dissipation	T_{amb} = -40 °C to + 125 °C		500	mW
T_{stg}	storage temperature		-65	150	°C

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

Table 5. Recommended Operating Conditions

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		1.65	5.5	V
		functional	1.2		V
V_I	input voltage		0	5.5	V
V_O	output voltage	Active mode	0	V_{CC}	V
		Power-down mode; V_{CC} = 0 V	0	5.5	V
T_{amb}	ambient temperature		-40	125	°C
$\Delta t/\Delta V$	Input transition rise and fall rate	V_{CC} = 3.7 V to 5.5 V	0	30	ns/V

9. Static Characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
V_{OH}	HIGH-level output voltage	$V_I = V_{T+}$ or V_{T-}						
		I_O = -100µA; V_{CC} = 1.65 V to 5.5 V	V_{CC} - 0.1			V_{CC} - 0.1		V
		I_O = -4 mA; V_{CC} = 1.65 V	1.2			1.05		V
		I_O = -8 mA; V_{CC} = 2.3 V	1.9			1.7		V
		I_O = -12 mA; V_{CC} = 2.7 V	2.2			2.05		V
		I_O = -24 mA; V_{CC} = 3.0 V	2.2			2.0		V
		I_O = -32 mA; V_{CC} = 4.5 V	3.8			3.5		V
V_{OL}	LOW-level output voltage	$V_I = V_{T+}$ or V_{T-}						
		I_O = 100µA; V_{CC} = 1.65 V to 5.5 V			0.10		0.10	V
		I_O = 4 mA; V_{CC} = 1.65 V			0.45		0.65	V
		I_O = 8 mA; V_{CC} = 2.3 V			0.30		0.45	V
		I_O = 12 mA; V_{CC} = 2.7 V			0.40		0.60	V
		I_O = 24 mA; V_{CC} = 3.0 V			0.55		0.80	V
		I_O = 32 mA; V_{CC} = 4.5 V			0.55		0.80	V
I_I	input leakage current	V_I = 5.5 V or GND ; V_{CC} = 0 V to 5.5 V		±0.1	±5		±20	µA
I_{OFF}	power-off leakage current	V_{CC} = 0V ; V_I or V_O = 5.5 V		±0.1	±10		±20	µA
I_{CC}	supply current	V_I = 5.5V or GND ; I_O = 0A ; V_{CC} = 1.65V to 5.5V		0.03	10		40	µA
ΔI_{CC}	additional supply current	per input pin ; V_{CC} = 2.3V to 5.5V ; $V_I = V_{CC}$ -0.6V ; I_O = 0A		0.8	500		5000	µA
C_I	input capacitance	V_{CC} = 3.3V ; V_I = GND to V_{CC}		4				pF

[1]All typical values are measured at V_{CC} = 3.3V and T_{amb} = 25°C.

10. Dynamic Characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 6.

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
t_{pd}	propagation delay	nA to nY; see Fig. 5 [2]						
		V_{CC} = 1.2 V		46				ns
		V_{CC} = 1.65 V to 1.95 V	4	12.3	24	4	25	ns
		V_{CC} = 2.3 V to 2.7 V	2.5	7.4	12	2.5	13	ns
		V_{CC} = 3.0 V to 3.6 V	1.5	5.7	8.5	1.5	9	ns
		V_{CC} = 4.5 V to 5.5 V	1	3.5	6	1	6.5	ns
$t_{sk(o)}$	output skew time	V_{CC} = 3.0 V to 3.6 V [3]			1.0		1.5	ns
C_{PD}	power dissipation capacitance	per buffer ; V_I = GND to V_{CC} [4]						
		V_{CC} = 1.65 V to 1.95 V		12.7				pF
		V_{CC} = 2.3 V to 2.7 V		13.3				pF
		V_{CC} = 3.0 V to 3.6 V		14.3				pF
		V_{CC} = 4.5 V to 5.5 V		16.5				pF

[1] Typical values are measured at T_{amb} = 25 °C and V_{CC} = 1.2 V, 1.8 V, 2.5 V, 3.3 V and 5.0 V respectively.

[2] t_{pd} is the same as t_{PLH} and t_{PHL}.

[3] Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.

[4] C_{PD} is used to determine the dynamic power dissipation (P_D in µW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz;

f_o = output frequency in MHz;


C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

10.1. Waveforms and test circuit




Measurement points are given in Table 8.
V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig. 5. The input nA to output nY propagation delays

Table 8. Measurement points

Supply voltage	Input	Output
V_{CC}	V_M	V_M
1.2 V	$0.5V_{CC}$	$0.5V_{CC}$
1.65 V to 1.95 V	$0.5V_{CC}$	$0.5V_{CC}$
2.3 V to 2.7 V	$0.5V_{CC}$	$0.5V_{CC}$
3.0 V to 3.6 V	1.5 V	1.5 V
4.5 V to 5.5 V	$0.5V_{CC}$	$0.5V_{CC}$



Test data is given in Table 9.
Definitions for test circuit:
R_L = Load resistance.
C_L = Load capacitance including jig and probe capacitance.
R_T = Termination resistance should be equal to the output impedance Z_o of the pulse generator.

Fig. 6. Test circuit for measuring switching times

Table 9. Test data

Supply voltage	Input		Load	
V_{CC}	V_I	$t_r = t_f$	C_L	R_L
1.2 V	V_{CC}	≤ 2.0 ns	15 pF	500 Ω
1.65 V to 1.95 V	V_{CC}	≤ 2.0 ns	15 pF	500 Ω
2.3 V to 2.7 V	V_{CC}	≤ 2.0 ns	15 pF	500 Ω
3.0 V to 3.6 V	3 V	≤ 2.0 ns	15 pF	500 Ω
4.5 V to 5.5 V	V_{CC}	≤ 2.0 ns	15 pF	500 Ω

11. Transfer characteristics

Table 10. Transfer characteristics

Voltages are referenced to GND (ground = 0 V); see Fig. 7.

Symbol	Parameter	Conditions	-40 °C to +85 °C		-40 °C to +125 °C		Unit
			Min	Max	Min	Max	
V_{T+}	positive-going threshold voltage	V_{CC} = 1.2 V	0.2	1.0	0.2	1.0	V
		V_{CC} = 1.65 V	0.4	1.3	0.4	1.3	V
		V_{CC} = 1.95 V	0.6	1.5	0.6	1.5	V
		V_{CC} = 2.3 V	0.8	1.7	0.8	1.7	V
		V_{CC} = 2.5 V	0.9	1.7	0.9	1.7	V
		V_{CC} = 2.7 V	1.1	2.0	1.1	2.0	V
		V_{CC} = 3.0 V	1.2	2.0	1.2	2.0	V
		V_{CC} = 3.6 V	1.2	2.0	1.2	2.0	V
		V_{CC} = 4.5 V	1.84	2.36	1.81	2.36	V
		V_{CC} = 5.5 V	2.19	2.79	2.16	2.79	V
V_{T-}	negative-going threshold voltage	V_{CC} = 1.2 V	0.12	0.75	0.12	0.75	V
		V_{CC} = 1.65 V	0.15	0.85	0.15	0.85	V
		V_{CC} = 1.95 V	0.25	0.95	0.25	0.95	V
		V_{CC} = 2.3 V	0.4	1.1	0.4	1.1	V
		V_{CC} = 2.5 V	0.4	1.2	0.4	1.2	V
		V_{CC} = 2.7 V	0.8	1.4	0.8	1.4	V
		V_{CC} = 3.0 V	0.8	1.5	0.8	1.5	V
		V_{CC} = 3.6 V	0.8	1.5	0.8	1.5	V
		V_{CC} = 4.5 V	1.32	1.84	1.32	1.87	V
		V_{CC} = 5.5 V	1.58	2.24	1.58	2.27	V
V_H	hysteresis voltage (V_{T+} - V_{T-})	V_{CC} = 1.2 V	0.1	1.0	0.1	1.0	V
		V_{CC} = 1.65 V	0.2	1.15	0.2	1.15	V
		V_{CC} = 1.95 V	0.2	1.25	0.2	1.25	V
		V_{CC} = 2.3 V	0.3	1.3	0.3	1.3	V
		V_{CC} = 2.5 V	0.3	1.3	0.3	1.3	V
		V_{CC} = 2.7 V	0.3	1.1	0.3	1.1	V
		V_{CC} = 3.0 V	0.3	1.2	0.3	1.2	V
		V_{CC} = 3.6 V	0.3	1.2	0.3	1.2	V
		V_{CC} = 4.5 V	0.4	0.77	0.34	0.77	V
		V_{CC} = 5.5 V	0.47	0.88	0.41	0.88	V

11.1. Waveforms transfer characteristics





Fig. 7. Definition of V_{T+}, V_{T-} and V_H


12. Package Outline

SOP-14L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	— —	1.750	— —	0.069
A1	0.100	0.250	0.004	0.010
A2	1.250	— —	0.049	— —
b	0.310	0.510	0.012	0.020
c	0.100	0.250	0.004	0.010
D	8.450	8.850	0.333	0.348
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
e	1.270(BSC)		0.050(BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

TSSOP-14L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
D	4.900	5.100	0.193	0.201
E	4.300	4.500	0.169	0.177
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
E1	6.250	6.550	0.246	0.258
A	—	1.200	—	0.047
A2	0.800	1.000	0.031	0.039
A1	0.050	0.150	0.002	0.006
e	0.65 (BSC)		0.026 (BSC)	
L	0.500	0.700	0.020	0.028
H	0.25(TYP)		0.01(TYP)	
θ	1°	7°	1°	7°

13. Tape and Reel Information

13.1. Carrier tape dimensions




Table 11. Carrier tape dimensions

Package version	A0(mm)	B0(mm)	K0(mm)	T(mm)	P1(mm)	W(mm)	P0(mm)	PIN 1
SOP-14L	6.35	9.1	1.9	0.22	8	16	4	Q1
TSSOP-14L	6.7	5.45	1.6	0.25	8	12	4	Q1

13.2. Reel and box dimensions




Table 12. Dimensions and quantities

Package version	Type NO. ending	Reel Dimension A (mm)	Reel Width W1 (mm)	MPQ (pcs)	Reels per box	Outer box dimensions L×W×H(mm)
SOP-14L	D	330	22.4	3000	1	358x340x50
TSSOP-14L	PW	330	18.4	3000	1	358x340x50

14. Abbreviations

Table 13. Abbreviations

Acronym	Description
CMOS	Complementary Metal-Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
HBM	Human Body Model
CDM	Charged Device Model
TTL	Transistor-Transistor Logic

15. Revision History

Table 14. Revision history

Document ID	Release Date	Data sheet status	Change notice	Supersedes
EM74LVC14A Rev. 1.2	Jul 29, 2025	Product datasheet		EM74LVC14A Rev. 1.1
Modifications:	• Section 3 updated: Added marking information. • Section 13 added tape and reel information.			
EM74LVC14A Rev. 1.1	Aug 30, 2024	Product datasheet		EM74LVC14A Rev. 1.0
Modifications:	• Table 6: V_{OH} and V_{OL} updated. • Table 7: t_{pd} and C_{pd} updated.			
EM74LVC14A Rev. 1.0	Oct 30, 2023	Product datasheet		