

1. General Description

The EM74HC540 and EM74HCT540 are octal inverting buffer/line drivers with 3-state outputs. The device features two output enables ($\overline{OE}1$ and $\overline{OE}2$). A HIGH on $\overline{OE}n$ causes the outputs to assume a high-impedance OFF-state. Inputs include clamp diodes that enable the use of current limiting resistors to interface inputs to voltages in excess of V_{CC} .

2. Features and Benefits

- Wide supply voltage range from 2.0 V to 6.0 V
- High noise immunity
- CMOS low power dissipation
- Latch-up performance exceeds 250 mA
- Complies with JEDEC standards:
 - JESD8C (2.7 V to 3.6 V)
 - JESD7A (2.0 V to 6.0 V)
- Input levels:
 - For EM74HC540: CMOS level
 - For EM74HCT540: TTL level
- ESD protection:
 - HBM ANSI/ESDA/JEDEC JS-001 Class 3A exceeds 6000 V
 - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

3.Ordering Information

Table 1. Ordering information

Type number	Topside Marking	Package		
		Name	Description	Quantity
EM74HC540D	HC540□ XYZWW	SOP-20L	plastic small outline package; 20 leads; body width 7.5 mm	2000
EM74HCT540D	HCT540□ XYZWW			
EM74HC540PW	HC540□ XYZWW	TSSOP-20L	plastic thin shrink small outline package; 20 leads;body width 4.4 mm	3000
EM74HCT540PW	HCT540□ XYZWW			

MARKING INFORMATION

NOTE: HC540□ = Serial number and Internal code; XYZWW = Vendor Code and Date Code.

HC540 □
 Internal Code
 Serial number

X YY WW
 Date Code -Week
 Date Code -Year
 Vendor Code

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state; inverting




Fig. 1. Logic symbol




Fig. 2. IEC logic symbol

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state; inverting




Fig. 3. Functional diagram





Fig. 4. Logic diagram

4. Pinning Information

4.1. Pinning



4.2. Pin description

Table 2. Pin description

Symbol	Pin	Description
$\overline{OE}1$	1	Output enable input (active LOW)
A0 to A7	2, 3, 4, 5, 6, 7, 8, 9	Data input
GND	10	Ground (0 V)
$\overline{Y}0$ to $\overline{Y}7$	18, 17, 16, 15, 14, 13, 12, 11	Data output
$\overline{OE}2$	19	Output enable input (active LOW)
V_{CC}	20	Supply voltage

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

5.Functional Description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

Control		Input	Output
$\overline{OE}1$	$\overline{OE}2$	A_n	$\overline{Y}_n$
L	L	L	H
L	L	H	L
X	H	X	Z
H	X	X	Z

6.Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Table 4. Absolute Maximum Ratings

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		-0.5	7.0	V
I_{IK}	input clamping current	$V_I < -0.5\text{ V}$ or $V_I > V_{CC} + 0.5\text{ V}$ [1]		± 20	mA
I_{OK}	output clamping current	$V_O < -0.5\text{ V}$ or $V_O > V_{CC} + 0.5\text{ V}$ [1]		± 20	mA
I_O	output current	$V_O = -0.5\text{ V}$ to $(V_{CC} + 0.5\text{ V})$		± 25	mA
I_{CC}	supply current			50	mA
I_{GND}	ground current		-50		mA
P_{tot}	total power dissipation			500	mW
T_{stg}	storage temperature		-65	150	°C

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

7.Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

Table 5. Recommended Operating Conditions

Symbol	Parameter	Conditions	EM74HC540			EM74HCT540			Unit
			Min	Typ	Max	Min	Typ	Max	
V _{CC}	supply voltage		2.0	5.0	6.0	4.5	5.0	5.5	V
V _I	input voltage		0		V _{CC}	0		V _{CC}	V
V _O	output voltage		0		V _{CC}	0		V _{CC}	V
T _{amb}	ambient temperature		-40		125	-40		125	°C
$\Delta t/\Delta V$	input transition rise and fall rate	V _{CC} = 2.0 V			625				ns/V
		V _{CC} = 4.5 V		1.67	139		1.67	139	ns/V
		V _{CC} = 6.0 V			83				ns/V

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state; inverting

8. Static Characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V). Typical values measured at $T_{amb} = 25^{\circ}\text{C}$ (unless otherwise noted).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HC540								
V _{IH}	HIGH-level input voltage	V _{CC} = 2.0 V	1.5			1.5		V
		V _{CC} = 4.5 V	3.15			3.15		V
		V _{CC} = 6.0 V	4.2			4.2		V
V _{IL}	LOW-level input voltage	V _{CC} = 2.0 V			0.5		0.5	V
		V _{CC} = 4.5 V			1.35		1.35	V
		V _{CC} = 6.0 V			1.8		1.8	V
V _{OH}	HIGH-level output voltage	V _I = V _{IH} or V _{IL}						
		I _O = -20 μA; V _{CC} = 2.0 V	1.9			1.9		V
		I _O = -20 μA; V _{CC} = 4.5 V	4.4			4.4		V
		I _O = -20 μA; V _{CC} = 6.0 V	5.9			5.9		V
		I _O = -6.0 mA; V _{CC} = 4.5 V	3.84			3.7		V
		I _O = -7.8 mA; V _{CC} = 6.0 V	5.34			5.2		V
V _{OL}	LOW-level output voltage	V _I = V _{IH} or V _{IL}						
		I _O = 20 μA; V _{CC} = 2.0 V			0.1		0.1	V
		I _O = 20 μA; V _{CC} = 4.5 V			0.1		0.1	V
		I _O = 20 μA; V _{CC} = 6.0 V			0.1		0.1	V
		I _O = 6.0 mA; V _{CC} = 4.5 V			0.33		0.4	V
		I _O = 7.8 mA; V _{CC} = 6.0 V			0.33		0.4	V
I _I	input leakage current	V _I = V _{CC} or GND ; V _{CC} = 6.0 V			±1		±1	μA
I _{OZ}	OFF-state output current	V _I = V _{IH} or V _{IL} ; V _{CC} = 6.0 V ; V _O = V _{CC} or GND			±5		±10	μA
I _{CC}	supply current	V _I = V _{CC} or GND ; I _O = 0 A ; V _{CC} = 6.0 V			20		40	μA
C _I	input capacitance	$\overline{OE}1, \overline{OE}2$ input		4.0				pF
		An input		7.7				pF

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HCT540								
V _{IH}	HIGH-level input voltage	V _{CC} = 4.5 V to 5.5 V	2.1			2.1		V
V _{IL}	LOW-level input voltage	V _{CC} = 4.5 V to 5.5 V			0.8		0.8	V
V _{OH}	HIGH-level output voltage	V _I = V _{IH} or V _{IL} ; V _{CC} = 4.5 V						
		I _O = -20 µA;	4.4		4.4		V	
		I _O = -6.0 mA;	3.84		3.7		V	
V _{OL}	LOW-level output voltage	V _I = V _{IH} or V _{IL} ; V _{CC} = 4.5 V						
		I _O = 20 µA;			0.1		0.1	V
		I _O = 6.0 mA;			0.33		0.4	V
I _I	input leakage current	V _I = V _{CC} or GND ; V _{CC} = 5.5 V			±1		±1	µA
I _{OZ}	OFF-state output current	V _I = V _{IH} or V _{IL} ; V _{CC} = 5.5 V ; V _O = V _{CC} or GND			±5		±10	µA
I _{CC}	supply current	V _I = V _{CC} or GND; I _O = 0 A; V _{CC} = 5.5 V			20		40	µA
ΔI _{CC}	additional supply current	per pin ; V _I = V _{CC} - 2.1 V; I _O = 0 A; other inputs at V _{CC} or GND; V _{CC} = 4.5 V to 5.5 V			315		343	mA
C _I	input capacitance	$\overline{OE}1, \overline{OE}2$ input		4.0				pF
		An input		7.7				pF

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

9.Dynamic Characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 8. Typical values measured at $T_{amb} = 25^{\circ}\text{C}$ (unless otherwise noted).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HC540								
t _{pd}	propagation delay	An to $\bar{Y}_n$; see Fig. 6 [1]						
		V _{CC} = 2.0 V			35		40	ns
		V _{CC} = 4.5 V			20		25	ns
		V _{CC} = 6.0 V			15		20	ns
t _{en}	enable time	$\overline{OE}_n$ to $\bar{Y}_n$; see Fig. 7 [2]						
		V _{CC} = 2.0 V			35		40	ns
		V _{CC} = 4.5 V			20		25	ns
		V _{CC} = 6.0 V			15		20	ns
t _{dis}	disable time	$\overline{OE}_n$ to $\bar{Y}_n$; see Fig. 7 [3]						
		V _{CC} = 2.0 V			35		40	ns
		V _{CC} = 4.5 V			20		25	ns
		V _{CC} = 6.0 V			15		20	ns
t _t	transition time	see Fig. 6 [4]						
		V _{CC} = 2.0 V			9		11	ns
		V _{CC} = 4.5 V			6		8	ns
		V _{CC} = 6.0 V			4		5	ns
C _{PD}	power dissipation capacitance	f = 1 MHz; V _I = GND to V _{CC} [5]		18				pF

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HCT540								
t _{pd}	propagation delay	An to $\bar{Y}_n$; V _{CC} = 4.5 V; see Fig. 6 [1]			20		25	ns
t _{en}	enable time	$\overline{OEn}$ to $\bar{Y}_n$; V _{CC} = 4.5 V; see Fig. 7 [2]			20		25	ns
t _{dis}	disable time	$\overline{OEn}$ to $\bar{Y}_n$; V _{CC} = 4.5 V; see Fig. 7 [3]			20		25	ns
t _t	transition time	V _{CC} = 4.5 V; see Fig. 6 [4]			6		8	ns
C _{PD}	power dissipation capacitance	f = 1 MHz; V _I = GND to (V _{CC} -1.5 V) [5]		18				pF

[1] t_{pd} is the same as t_{PHL} and t_{PLH} .

[2] t_{en} is the same as t_{PZH} and t_{PZL} .

[3] t_{dis} is the same as t_{PLZ} and t_{PHZ} .

[4] t_t is the same as t_{THL} and t_{TLH} .

[5] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;


N = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state; inverting


9.1. Waveforms and test circuit



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig. 6. Input to output propagation delays



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.



Fig. 7. 3-state enable and disable times

Table 8. Measurement points

Type	Input	Output		
	V_M	V_M	V_X	V_Y
EM74HC540	$0.5V_{CC}$	$0.5V_{CC}$	$0.1V_{CC}$	$0.9V_{CC}$
EM74HCT540	1.3 V	1.3 V	$0.1V_{CC}$	$0.9V_{CC}$

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state; inverting



Test data is given in Table 9.

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} = External voltage for measuring switching times.


Fig. 8. Test circuit for measuring switching times

Table 9. Test data

Type	Input		Load		V_{EXT}		
	V_I	$t_r = t_f$	C_L	R_L	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
EM74HC540	V_{CC}	≤ 2.5 ns	50 pF	500 Ω	open	GND	$2V_{CC}$
EM74HCT540	3 V	≤ 2.5 ns	50 pF	500 Ω	open	GND	$2V_{CC}$

10. Package Outline


SOP-20L



EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

TSSOP-20L



11. Tape and Reel Information

11.1. Carrier tape dimensions




Table 10. Carrier tape dimensions

Package version	A0(mm)	B0(mm)	K0(mm)	T(mm)	P1(mm)	W(mm)	P0(mm)	PIN 1
SOP-20L	10.65	13.2	3.2	0.3	12	24	4	Q1
TSSOP-20L	6.85	6.85	1.7	0.22	8	12	4	Q1

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

11.2. Reel and box dimensions




Table 11. Dimensions and quantities

Package version	Type NO. ending	Reel Dimension A (mm)	Reel Width W1 (mm)	SPQ (pcs) [1]	Reels per box	Outer box dimensions L×W×H(mm) [2]
SOP-20L	D	330	30.4	2000	1	358x340x50
TSSOP-20L	PW	330	18.4	3000	1	358x340x50

[1] Packing quantity dependent on specific product type. Please contact your local Energymath representative for ordering.

[2] Dimensions for reference only.

EM74HC540; EM74HCT540

Octal buffer/line driver; 3-state;inverting

12. Abbreviations

Table 12. Abbreviations

Acronym	Description
CMOS	Complementary Metal-Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
HBM	Human Body Model
CDM	Charged Device Model
TTL	Transistor-Transistor Logic

13. Revision History

Table 13. Revision history

Document ID	Release Date	Data sheet status	Change notice	Supersedes
EM74HC_HCT540 Rev. 1.1	Aug 11, 2025	Product datasheet		EM74HC_HCT540 Rev. 1.0
Modifications:	- Table 1 ordering information updated. - Section 12: Added tape and reel information.			
EM74HC_HCT540 Rev. 1.0	Feb 21, 2025	Product datasheet		