

## 1. General Description

---

The EM74LVC1G332 is a single 3-input OR gate. Inputs can be driven from either 3.3 V or 5 V devices. This feature allows the use of these devices as translators in mixed 3.3 V and 5 V applications.

Schmitt trigger action at all inputs makes the circuit tolerant of slower input rise and fall time. This device is fully specified for partial power-down applications using  $I_{OFF}$ . The  $I_{OFF}$  circuitry disables the output, preventing the damaging backflow current through the device when it is powered down.

## 2. Features and Benefits

---

- Wide supply voltage range from 1.65 V to 5.5 V
- High noise immunity
- Overvoltage tolerant inputs to 5.5 V
- $\pm 24$  mA output drive ( $V_{CC} = 3.0$  V)
- CMOS low power dissipation
- Direct interface with TTL levels
- $I_{OFF}$  circuitry provides partial Power-down mode operation
- Latch-up performance exceeds 100 mA
- Complies with JEDEC standard:
  - JESD8-7 (1.65 V to 1.95 V)
  - JESD8-5 (2.3 V to 2.7 V)
  - JESD8C (2.7 V to 3.6 V)
  - JESD36 (4.5 V to 5.5 V)
- ESD protection:
  - HBM ANSI/ESDA/JEDEC JS-001 Class 3B exceeds 8000 V
  - MM JESD22-A115C Class C exceeds 550 V
  - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options

## EM74LVC1G332

Single 3-input OR gate


### 3. Ordering Information

Table 1. Ordering information


| Type number    | Topside marking | Package      |                                                                  |          |
|----------------|-----------------|--------------|------------------------------------------------------------------|----------|
|                |                 | Name         | Description                                                      | Quantity |
| EM74LVC1G332GV | VSYW            | SOT23-6L     | SOT23 package, 6 pins<br>2.92 mm × 1.6 mm; 1.25 mm (Max) height  | 3000     |
| EM74LVC1G332GW | VSYW            | SOT363       | SOT363 package, 6 pins<br>2.1 mm × 1.25 mm; 1.1 mm (Max) height  | 3000     |
| EM74LVC1G332GS | VS              | DFN1x1-6L    | DFN1×1 package, 6 pins<br>1 mm × 1 mm; 0.42 mm (Max) height      | 3000     |
| EM74LVC1G332GM | VSYW            | DFN1x1.45-6L | DFN1.45×1 package, 6 pins<br>1.45 mm × 1 mm; 0.6 mm (Max) height | 3000     |

#### MARKING INFORMATION

NOTE: YW = Date Code.




### 4. Function Diagram



## 5. Pinning Information

### 5.1. Pin map



### 5.2. Pin description

**Table 2. Pin description**

| Symbol          | Pin | Description    |
|-----------------|-----|----------------|
| A               | 1   | Data input     |
| GND             | 2   | Ground (0V)    |
| B               | 3   | Data input     |
| Y               | 4   | Data output    |
| V <sub>CC</sub> | 5   | Supply voltage |
| C               | 6   | Data input     |

## 6. Functional Description

**Table 3. Function table**

H = HIGH voltage level; L = LOW voltage level; X = don't care.

| Input |   |   | Output |
|-------|---|---|--------|
| A     | B | C | Y      |
| H     | X | X | H      |
| X     | H | X | H      |
| X     | X | H | H      |
| L     | L | L | L      |

## 7. Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

**Table 4. Absolute Maximum Ratings**

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

| Symbol    | Parameter               | Conditions                          | Min  | Max            | Unit |
|-----------|-------------------------|-------------------------------------|------|----------------|------|
| $V_{CC}$  | supply voltage          |                                     | -0.5 | 6.5            | V    |
| $I_{IK}$  | input clamping current  | $V_I < 0$ V                         | -50  |                | mA   |
| $V_I$     | input voltage           | [1]                                 | -0.5 | 6.5            | V    |
| $I_{OK}$  | output clamping current | $V_O > V_{CC}$ or $V_O < 0$ V       |      | $\pm 50$       | mA   |
| $V_O$     | output voltage          | Active mode [1]                     | -0.5 | $V_{CC} + 0.5$ | V    |
|           |                         | Power-down mode; $V_{CC} = 0$ V [1] | -0.5 | 6.5            | V    |
| $I_O$     | output current          | $V_O = 0$ V to $V_{CC}$             |      | $\pm 50$       | mA   |
| $I_{CC}$  | supply current          |                                     |      | 100            | mA   |
| $I_{GND}$ | ground current          |                                     | -100 |                | mA   |
| $P_{tot}$ | total power dissipation | $T_{amb} = -40$ °C to $+125$ °C     |      | 250            | mW   |
| $T_{stg}$ | storage temperature     |                                     | -65  | 150            | °C   |

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

## 8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

**Table 5. Recommended Operating Conditions**

| Symbol              | Parameter                           | Conditions                             | Min  | Typ | Max             | Unit |
|---------------------|-------------------------------------|----------------------------------------|------|-----|-----------------|------|
| V <sub>CC</sub>     | supply voltage                      |                                        | 1.65 |     | 5.5             | V    |
| V <sub>I</sub>      | input voltage                       |                                        | 0    |     | 5.5             | V    |
| V <sub>O</sub>      | output voltage                      | Active mode                            | 0    |     | V <sub>CC</sub> | V    |
|                     |                                     | Power-down mode; V <sub>CC</sub> = 0 V | 0    |     | 5.5             | V    |
| T <sub>amb</sub>    | ambient temperature                 |                                        | -40  |     | 125             | °C   |
| $\Delta t/\Delta V$ | Input transition rise and fall rate | V <sub>CC</sub> = 1.65 V to 2.7 V      |      |     | 20              | ns/V |
|                     |                                     | V <sub>CC</sub> = 2.7 V to 5.5 V       |      |     | 10              | ns/V |

## 9.Static Characteristics

**Table 6. Static characteristics**

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol   | Parameter                 | Conditions                                                           | -40 °C to +85 °C |           |              | -40 °C to +125 °C |              | Unit          |
|----------|---------------------------|----------------------------------------------------------------------|------------------|-----------|--------------|-------------------|--------------|---------------|
|          |                           |                                                                      | Min              | Typ[1]    | Max          | Min               | Max          |               |
| $V_{IH}$ | HIGH-level input voltage  | $V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$                         | $0.65V_{CC}$     |           |              | $0.65V_{CC}$      |              | V             |
|          |                           | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$                           | 1.7              |           |              | 1.7               |              | V             |
|          |                           | $V_{CC} = 2.7 \text{ V to } 3.6 \text{ V}$                           | 2.0              |           |              | 2.0               |              | V             |
|          |                           | $V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$                           | $0.7V_{CC}$      |           |              | $0.7V_{CC}$       |              | V             |
| $V_{IL}$ | LOW-level input voltage   | $V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$                         |                  |           | $0.35V_{CC}$ |                   | $0.35V_{CC}$ | V             |
|          |                           | $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$                           |                  |           | 0.7          |                   | 0.7          | V             |
|          |                           | $V_{CC} = 2.7 \text{ V to } 3.6 \text{ V}$                           |                  |           | 0.8          |                   | 0.8          | V             |
|          |                           | $V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$                           |                  |           | $0.3V_{CC}$  |                   | $0.3V_{CC}$  | V             |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH} \text{ or } V_{IL}$                                    |                  |           |              |                   |              |               |
|          |                           | $I_O = -100\mu\text{A}; V_{CC} = 1.65 \text{ V to } 5.5 \text{ V}$   | $V_{CC} - 0.1$   |           |              | $V_{CC} - 0.1$    |              | V             |
|          |                           | $I_O = -4 \text{ mA}; V_{CC} = 1.65 \text{ V}$                       | 1.2              | 1.54      |              | 0.95              |              | V             |
|          |                           | $I_O = -8 \text{ mA}; V_{CC} = 2.3 \text{ V}$                        | 1.9              | 2.15      |              | 1.7               |              | V             |
|          |                           | $I_O = -12 \text{ mA}; V_{CC} = 2.7 \text{ V}$                       | 2.2              | 2.50      |              | 1.9               |              | V             |
|          |                           | $I_O = -24 \text{ mA}; V_{CC} = 3.0 \text{ V}$                       | 2.3              | 2.62      |              | 2.0               |              | V             |
|          |                           | $I_O = -32 \text{ mA}; V_{CC} = 4.5 \text{ V}$                       | 3.8              | 4.11      |              | 3.4               |              | V             |
| $V_{OL}$ | LOW-level output voltage  | $V_I = V_{IH} \text{ or } V_{IL}$                                    |                  |           |              |                   |              |               |
|          |                           | $I_O = 100\mu\text{A}; V_{CC} = 1.65 \text{ V to } 5.5 \text{ V}$    |                  |           | 0.10         |                   | 0.10         | V             |
|          |                           | $I_O = 4 \text{ mA}; V_{CC} = 1.65 \text{ V}$                        |                  | 0.07      | 0.45         |                   | 0.70         | V             |
|          |                           | $I_O = 8 \text{ mA}; V_{CC} = 2.3 \text{ V}$                         |                  | 0.12      | 0.30         |                   | 0.45         | V             |
|          |                           | $I_O = 12 \text{ mA}; V_{CC} = 2.7 \text{ V}$                        |                  | 0.17      | 0.40         |                   | 0.60         | V             |
|          |                           | $I_O = 24 \text{ mA}; V_{CC} = 3.0 \text{ V}$                        |                  | 0.33      | 0.55         |                   | 0.80         | V             |
|          |                           | $I_O = 32 \text{ mA}; V_{CC} = 4.5 \text{ V}$                        |                  | 0.39      | 0.55         |                   | 0.80         | V             |
| $I_i$    | Input leakage current     | $V_I = 5.5 \text{ V or GND}; V_{CC} = 0 \text{ V to } 5.5 \text{ V}$ |                  | $\pm 0.1$ | $\pm 1$      |                   | $\pm 1$      | $\mu\text{A}$ |

## EM74LVC1G332

### Single 3-input OR gate

| Symbol          | Parameter                 | Conditions                                                                  | -40 °C to +85 °C |           |         | -40 °C to +125 °C |         | Unit    |
|-----------------|---------------------------|-----------------------------------------------------------------------------|------------------|-----------|---------|-------------------|---------|---------|
|                 |                           |                                                                             | Min              | Typ[1]    | Max     | Min               | Max     |         |
| $I_{OFF}$       | power-off leakage current | $V_{CC} = 0V$ ; $V_I$ or $V_O = 5.5V$                                       |                  | $\pm 0.1$ | $\pm 2$ |                   | $\pm 2$ | $\mu A$ |
| $I_{CC}$        | supply current            | $V_I = 5.5V$ or GND ; $I_O = 0A$ ;<br>$V_{CC} = 1.65V$ to $5.5V$            |                  | 0.1       | 4       |                   | 4       | $\mu A$ |
| $\Delta I_{CC}$ | additional supply current | per pin ; $V_{CC} = 2.3V$ to $5.5V$ ;<br>$V_I = V_{CC} - 0.6V$ ; $I_O = 0A$ |                  | 5         | 500     |                   | 500     | $\mu A$ |
| $C_i$           | input capacitance         | $V_{CC} = 3.3V$ ; $V_I = GND$ to $V_{CC}$                                   |                  | 5         |         |                   |         | pF      |

[1] All typical values are measured at  $V_{CC} = 3.3V$  and  $T_{amb} = 25^\circ C$ .

## 10. Dynamic Characteristics

**Table 7. Dynamic characteristics**

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 7.

| Symbol   | Parameter                     | Conditions                                    | -40 °C to +85 °C |        |      | -40 °C to +125 °C |      | Unit |
|----------|-------------------------------|-----------------------------------------------|------------------|--------|------|-------------------|------|------|
|          |                               |                                               | Min              | Typ[1] | Max  | Min               | Max  |      |
| $t_{pd}$ | propagation delay             | A,B,C to Y; see Fig. 6 [2]                    |                  |        |      |                   |      |      |
|          |                               | $V_{CC} = 1.65V$ to $1.95V$                   | 3.4              | 9.4    | 15.9 | 3.4               | 16.3 | ns   |
|          |                               | $V_{CC} = 2.3V$ to $2.7V$                     | 2.4              | 5.0    | 8.6  | 2.4               | 9.1  | ns   |
|          |                               | $V_{CC} = 3.0V$ to $3.6V$                     | 1.8              | 3.9    | 6.0  | 1.8               | 6.3  | ns   |
|          |                               | $V_{CC} = 4.5V$ to $5.5V$                     | 1.4              | 2.6    | 3.6  | 1.4               | 3.8  | ns   |
| $C_{PD}$ | power dissipation capacitance | $V_I = GND$ to $V_{CC}$ ; $V_{CC} = 3.3V$ [3] |                  | 24     |      |                   |      | pF   |

[1] Typical values are measured at  $T_{amb} = 25^\circ C$  and  $V_{CC} = 1.8V, 2.5V, 3.3V$  and  $5.0V$  respectively.

[2]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ .

[3]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu W$ ).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$  where:

$f_i$  = input frequency in MHz;

$f_o$  = output frequency in MHz;


$C_L$  = output load capacitance in pF;

$V_{CC}$  = supply voltage in V;

$N$  = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$  = sum of outputs.

## 10.1. Waveforms and test circuit



Measurement points are given in Table 8.

$V_{OL}$  and  $V_{OH}$  are typical output voltage levels that occur with the output load.


Fig 6. The input A, B, C to output Y propagation delays

**Table 8. Measurement points**

| Supply voltage   | Input       | Output      |
|------------------|-------------|-------------|
| $V_{CC}$         | $V_M$       | $V_M$       |
| 1.65 V to 1.95 V | $0.5V_{CC}$ | $0.5V_{CC}$ |
| 2.3 V to 2.7 V   | $0.5V_{CC}$ | $0.5V_{CC}$ |
| 3.0 V to 3.6 V   | 1.5 V       | 1.5 V       |
| 4.5 V to 5.5 V   | $0.5V_{CC}$ | $0.5V_{CC}$ |

## EM74LVC1G332

### Single 3-input OR gate



Test data is given in Table 9.

Definitions for test circuit:

$R_L$  = Load resistance.

$C_L$  = Load capacitance including jig and probe capacitance.

$R_T$  = Termination resistance should be equal to the output impedance  $Z_o$  of the pulse generator.

$V_{EXT}$  = External voltage for measuring switching times.


Fig 7. Test circuit for measuring switching times

Table 9. Test data

| Supply voltage   | Input    |               | Load  |              | $V_{EXT}$          |
|------------------|----------|---------------|-------|--------------|--------------------|
| $V_{CC}$         | $V_I$    | $t_r = t_f$   | $C_L$ | $R_L$        | $t_{PLH}, t_{PHL}$ |
| 1.65 V to 1.95 V | $V_{CC}$ | $\leq 2.0$ ns | 30 pF | 1 k $\Omega$ | open               |
| 2.3 V to 2.7 V   | $V_{CC}$ | $\leq 2.0$ ns | 30 pF | 500 $\Omega$ | open               |
| 3.0 V to 3.6 V   | 3 V      | $\leq 2.5$ ns | 50 pF | 500 $\Omega$ | open               |
| 4.5 V to 5.5 V   | $V_{CC}$ | $\leq 2.5$ ns | 50 pF | 500 $\Omega$ | open               |

## 11. Package Outline

SOT23-6L




# EM74LVC1G332

Single 3-input OR gate

SOT363

## SOT-363 (16R) PACKAGE OUTLINE DIMENSIONS




| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min.                      | Max.  | Min.                 | Max.  |
| A      | 0.900                     | 1.100 | 0.035                | 0.043 |
| A1     | 0.000                     | 0.100 | 0.000                | 0.004 |
| A2     | 0.900                     | 1.000 | 0.035                | 0.039 |
| b      | 0.150                     | 0.350 | 0.006                | 0.014 |
| c      | 0.110                     | 0.175 | 0.004                | 0.007 |
| D      | 2.000                     | 2.200 | 0.079                | 0.087 |
| E      | 1.150                     | 1.350 | 0.045                | 0.053 |
| E1     | 2.150                     | 2.450 | 0.085                | 0.096 |
| e      | 0.650 TYP.                |       | 0.026 TYP.           |       |
| e1     | 1.200                     | 1.400 | 0.047                | 0.055 |
| L      | 0.525 REF.                |       | 0.021 REF.           |       |
| L1     | 0.260                     | 0.460 | 0.010                | 0.018 |
| θ      | 0°                        | 8°    | 0°                   | 8°    |

# EM74LVC1G332

Single 3-input OR gate


DFN1x1-6L



# EM74LVC1G332


## Single 3-input OR gate

### DFN1x1.45-6L



## 12. Tape and Reel Information


### 12.1. Carrier tape dimensions



**Table 10. Carrier tape dimensions**

| Package version | A0(mm) | B0(mm) | K(mm) | T(mm) | P1(mm) | W(mm) | P0(mm) | PIN 1 |
|-----------------|--------|--------|-------|-------|--------|-------|--------|-------|
| SOT23-6L        | 3.23   | 3.17   | 1.37  | 0.25  | 4      | 8     | 4      | Q3    |
| SOT363          | 2.55   | 2.55   | 1.2   | 0.2   | 4      | 8     | 4      | Q3    |
| DFN1x1-6L       | 1.16   | 1.16   | 0.5   | 0.23  | 4      | 8     | 4      | Q1    |
| DFN1x1.45-6L    | 1.15   | 1.6    | 0.75  | 0.2   | 4      | 8     | 4      | Q1    |

## 12.2. Reel and box dimensions


**Table11.Dimensions and quantities**

| Package version | Type NO. ending | Reel Dimension A (mm) | Reel Width W1 (mm) | SPQ (pcs)[1] | Reels per box | Outer box dimensions L×W×H(mm)[2] |
|-----------------|-----------------|-----------------------|--------------------|--------------|---------------|-----------------------------------|
| SOT23-6L        | GV              | 180                   | 12.2               | 3000         | 1             | 210x200x40                        |
| SOT363          | GW              | 180                   | 12.2               | 3000         | 1             | 210x200x40                        |
| DFN1x1-6L       | GS              | 180                   | 12.2               | 3000         | 1             | 210x200x40                        |
| DFN1x1.45-6L    | GM              | 180                   | 12.2               | 3000         | 1             | 210x200x40                        |

[1] Packing quantity dependent on specific product type. Please contact your local Energymath representative for ordering.

[2] Dimensions for reference only.

## 13. Abbreviations

Table 12. Abbreviations

| Acronym | Description                             |
|---------|-----------------------------------------|
| CMOS    | Complementary Metal-Oxide Semiconductor |
| DUT     | Device Under Test                       |
| ESD     | Electro Static Discharge                |
| HBM     | Human Body Model                        |
| MM      | Machine Model                           |
| TTL     | Transistor-Transistor Logic             |

## 14. Revision History

Table 13. Revision history

| Document ID         | Release Date                                                                                                                                     | Data sheet status | Change notice | Supersedes          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------|---------------------|
| EM74LVC1G332 Rev1.1 | Dec 15, 2025                                                                                                                                     | Product datasheet |               | EM74LVC1G332 Rev1.0 |
| Modifications:      | <ul style="list-style-type: none"><li>Table 1: Added topside marking information.</li><li>Section 12: Added tape and reel information.</li></ul> |                   |               |                     |
| EM74LVC1G332 Rev1.0 | Oct 30, 2023                                                                                                                                     | Product datasheet |               |                     |