

1. General Description

The EM74HC368; EM74HCT368 is a hex inverting buffer/line driver with 3-state outputs controlled by the output enable inputs ($\overline{\text{nOE}}$). A HIGH on $\overline{\text{nOE}}$ causes the outputs to assume a high impedance OFF-state. Inputs include clamp diodes. This enables the use of current limiting resistors to interface inputs to voltages in excess of V_{CC} .

2. Features and Benefits

- Wide supply voltage range from 2.0 V to 6.0 V
- High noise immunity
- CMOS low power dissipation
- Latch-up performance exceeds 250 mA
- Complies with JEDEC standards:
 - JESD8C (2.7 V to 3.6 V)
 - JESD7A (2.0 V to 6.0 V)
- Input levels:
 - For EM74HC368: CMOS level
 - For EM74HCT368: TTL level
- ESD protection:
 - HBM ANSI/ESDA/JEDEC JS-001 Class 2 exceeds 3500 V
 - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options

EM74HC368; EM74HCT368

Hex buffer/line driver; 3-state; inverting

3. Ordering Information

Table 1. Ordering information

Type number	Topside marking	Package		
		Name	Description	Quantity
EM74HC368D	HC368□ XYYWW	SOP-16L	plastic small outline package; 16 leads; body width 3.9 mm	3000
EM74HCT368D	HCT368□ XYYWW			
EM74HC368PW	HC368□ XYYWW	TSSOP-16L	plastic thin shrink small outline package; 16 leads; body width 4.4 mm	3000
EM74HCT368PW	HCT368□ XYYWW			

MARKING INFORMATION

NOTE: HC368□ = Serial number and Internal code; XYYWW = Vendor Code and Date Code.

HC368 □

Internal Code
Serial number

X YY WW

Vendor Code
Date Code -Year
Date Code -Week

4. Function Diagram




Fig. 1. Functional diagram




Fig. 2. IEC logic symbol




Fig. 3. Logic diagram

5. Pinning Information

5.1. Pinning




Fig. 4. Top view pin configuration SOP and TSSOP

5.2. Pin description

Table 2. Pin description

Symbol	Pin	Description
$\overline{1OE}$	1	output enable input 1 (active LOW)
1A	2	data input 1
$\overline{1Y}$	3	data output 1
2A	4	data input 2
$\overline{2Y}$	5	data output 2
3A	6	data input 3
$\overline{3Y}$	7	data output 3
GND	8	ground (0 V)
$\overline{4Y}$	9	data output 4
4A	10	data input 4
$\overline{5Y}$	11	data output 5
5A	12	data input 5
$\overline{6Y}$	13	data output 6
6A	14	data input 6
$\overline{2OE}$	15	output enable input 2 (active LOW)
V _{CC}	16	supply voltage

6. Functional Description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

Input		Output
$\overline{nOE}$	nA	$\overline{nY}$
L	L	H
L	H	L
H	X	Z

7. Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Table 4. Absolute Maximum Ratings

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		-0.5	7.0	V
I_{IK}	input clamping current	$V_I < -0.5\text{ V}$ or $V_I > V_{CC} + 0.5\text{ V}$ [1]		± 20	mA
I_{OK}	output clamping current	$V_O < -0.5\text{ V}$ or $V_O > V_{CC} + 0.5\text{ V}$ [1]		± 20	mA
I_O	output current	$V_O = -0.5\text{ V}$ to $(V_{CC} + 0.5\text{ V})$		± 35	mA
I_{CC}	supply current			70	mA
I_{GND}	ground current		-70		mA
P_{tot}	total power dissipation			500	mW
T_{stg}	storage temperature		-65	150	°C

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

Table 5. Recommended Operating Conditions

Symbol	Parameter	Conditions	EM74HC368			EM74HCT368			Unit
			Min	Typ	Max	Min	Typ	Max	
V_{CC}	supply voltage		2.0	5.0	6.0	4.5	5.0	5.5	V
V_i	input voltage		0		V_{CC}	0		V_{CC}	V
V_o	output voltage		0		V_{CC}	0		V_{CC}	V
T_{amb}	ambient temperature		-40		125	-40		125	°C
$\Delta t/\Delta V$	input transition rise and fall rate	$V_{CC} = 2.0\text{ V}$			625				ns/V
		$V_{CC} = 4.5\text{ V}$		1.67	139		1.67	139	ns/V
		$V_{CC} = 6.0\text{ V}$			83				ns/V

9. Static Characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V). Typical values measured at $T_{amb} = 25^{\circ}\text{C}$ (unless otherwise noted).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HC368								
V _{IH}	HIGH-level input voltage	V _{CC} = 2.0 V	1.5			1.5		V
		V _{CC} = 4.5 V	3.15			3.15		V
		V _{CC} = 6.0 V	4.2			4.2		V
V _{IL}	LOW-level input voltage	V _{CC} = 2.0 V			0.5		0.5	V
		V _{CC} = 4.5 V			1.35		1.35	V
		V _{CC} = 6.0 V			1.8		1.8	V
V _{OH}	HIGH-level output voltage	V _i = V _{IH} or V _{IL}						
		I _O = -20 μA; V _{CC} = 2.0 V	1.9			1.9		V
		I _O = -20 μA; V _{CC} = 4.5 V	4.4			4.4		V
		I _O = -20 μA; V _{CC} = 6.0 V	5.9			5.9		V
		I _O = -6.0 mA; V _{CC} = 4.5 V	3.84			3.7		V
		I _O = -7.8 mA; V _{CC} = 6.0 V	5.34			5.2		V
V _{OL}	LOW-level output voltage	V _i = V _{IH} or V _{IL}						
		I _O = 20 μA; V _{CC} = 2.0 V			0.1		0.1	V
		I _O = 20 μA; V _{CC} = 4.5 V			0.1		0.1	V
		I _O = 20 μA; V _{CC} = 6.0 V			0.1		0.1	V
		I _O = 6.0 mA; V _{CC} = 4.5 V			0.33		0.4	V
		I _O = 7.8 mA; V _{CC} = 6.0 V			0.33		0.4	V
I _i	input leakage current	V _i = V _{CC} or GND ; V _{CC} = 6.0 V			±1		±1	μA
I _{OZ}	OFF-state output current	V _i = V _{IH} or V _{IL} ; V _{CC} = 6.0 V ; V _O = V _{CC} or GND			±5		±10	μA
I _{CC}	supply current	V _i = V _{CC} or GND ; I _O = 0 A ; V _{CC} = 6.0 V			20		40	μA
C _i	input capacitance			7				pF

EM74HC368; EM74HCT368

Hex buffer/line driver; 3-state; inverting

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HCT368								
V _{IH}	HIGH-level input voltage	V _{CC} = 4.5 V to 5.5 V	2.0			2.0		V
V _{IL}	LOW-level input voltage	V _{CC} = 4.5 V to 5.5 V			0.8		0.8	V
V _{OH}	HIGH-level output voltage	V _I = V _{IH} or V _{IL} ; V _{CC} = 4.5 V						
		I _O = -20 μA;	4.4		4.4		V	
		I _O = -6.0 mA;	3.84		3.7		V	
V _{OL}	LOW-level output voltage	V _I = V _{IH} or V _{IL} ; V _{CC} = 4.5 V						
		I _O = 20 μA;			0.1		0.1	V
		I _O = 6.0 mA;			0.33		0.4	V
I _i	input leakage current	V _I = V _{CC} or GND ; V _{CC} = 5.5 V			±1		±1	μA
I _{OZ}	OFF-state output current	V _I = V _{IH} or V _{IL} ; V _{CC} = 5.5 V ; V _O = V _{CC} or GND			±5		±10	μA
I _{CC}	supply current	V _I = V _{CC} or GND; I _O = 0 A; V _{CC} = 5.5 V			20		40	μA
ΔI _{CC}	additional supply current	per pin ; V _I = V _{CC} - 2.1 V; I _O = 0 A; other inputs at V _{CC} or GND; V _{CC} = 4.5 V to 5.5 V			1.55		1.85	mA
C _i	input capacitance			10				pF

10. Dynamic Characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 7. Typical values measured at $T_{amb} = 25^{\circ}\text{C}$ (unless otherwise noted).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HC368								
t _{pd}	propagation delay	nA to nȳ; see Fig. 5 [1]						
		V _{CC} = 2.0 V			35		40	ns
		V _{CC} = 4.5 V			20		25	ns
		V _{CC} = 6.0 V			15		20	ns
t _{en}	enable time	nȐE to nȳ; see Fig. 6 [2]						
		V _{CC} = 2.0 V			35		40	ns
		V _{CC} = 4.5 V			20		25	ns
		V _{CC} = 6.0 V			15		20	ns
t _{dis}	disable time	nȐE to nȳ; see Fig. 6 [3]						
		V _{CC} = 2.0 V			35		40	ns
		V _{CC} = 4.5 V			20		25	ns
		V _{CC} = 6.0 V			15		20	ns
t _t	transition time	see Fig. 5 [4]						
		V _{CC} = 2.0 V			9		11	ns
		V _{CC} = 4.5 V			6		8	ns
		V _{CC} = 6.0 V			4		5	ns
C _{PD}	power dissipation capacitance	C _L = 15 pF; f = 1 MHz; V _i = GND to V _{CC} [5]		18				pF

EM74HC368; EM74HCT368

Hex buffer/line driver; 3-state; inverting

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
EM74HCT368								
t _{pd}	propagation delay	nA to nȳ; V _{CC} = 4.5 V; see Fig. 5 [1]			20		25	ns
t _{en}	enable time	nȌE to nȳ; V _{CC} = 4.5 V; see Fig. 6 [2]			20		25	ns
t _{dis}	disable time	nȌE to nȳ; V _{CC} = 4.5 V; see Fig. 6 [3]			20		25	ns
t _t	transition time	V _{CC} = 4.5 V; see Fig. 5 [4]			6		8	ns
C _{PD}	power dissipation capacitance	C _L = 15 pF; f = 1 MHz; V _I = GND to (V _{CC} -1.5 V) [5]		37				pF

[1] t_{pd} is the same as t_{PLH} and t_{PLH} .

[2] t_{en} is the same as t_{ON} and t_{ON} .

[3] t_{dis} is the same as t_{OFF} and t_{OFF} .

[4] t_t is the same as t_{rH} and t_{rL} .

[5] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \sum (C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz;

f_o = output frequency in MHz;


C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;

$\sum (C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.


10.1. Waveforms and test circuit



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig. 5. The input nA to output n $\bar{Y}$ propagation delays



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.


Fig. 6. 3-state enable and disable times

Table 8. Measurement points

Type	Input	Output		
	V_M	V_M	V_X	V_Y
EM74HC368	$0.5V_{CC}$	$0.5V_{CC}$	$0.1V_{CC}$	$0.9V_{CC}$
EM74HCT368	1.3 V	1.3 V	$0.1V_{CC}$	$0.9V_{CC}$

EM74HC368; EM74HCT368

Hex buffer/line driver; 3-state; inverting



Test data is given in Table 9.

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to the output impedance Z_o of the pulse generator.


V_{EXT} = External voltage for measuring switching times.

Fig. 7. Test circuit for measuring switching times

Table 9. Test data

Type	Input		Load		V_{EXT}		
	V_I	$t_r = t_f$	C_L	R_L	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
EM74HC368	V_{CC}	≤ 2.5 ns	15 pF	500 Ω	open	GND	$2V_{CC}$
EM74HCT368	3 V	≤ 2.5 ns	15 pF	500 Ω	open	GND	$2V_{CC}$


11. Package Outline

SOP-16L


EM74HC368; EM74HCT368

Hex buffer/line driver; 3-state; inverting

TSSOP-16L



12. Tape and Reel Information

12.1. Carrier tape dimensions




Table 10. Carrier tape dimensions

Package version	A0(mm)	B0(mm)	K0(mm)	T(mm)	P1(mm)	W(mm)	P0(mm)	PIN 1
SOP-16L	6.5	10.45	2.1	0.22	8	16	4	Q1
TSSOP-16L	6.7	5.45	1.6	0.25	8	12	4	Q1

12.2. Reel and box dimensions




Table 11. Dimensions and quantities

Package version	Type NO. ending	Reel Dimension A (mm)	Reel Width W1 (mm)	SPQ (pcs) [1]	Reels per box	Outer box dimensions L×W×H(mm) [2]
SOP-16L	D	330	22.4	3000	1	358x340x50
TSSOP-16L	PW	330	18.4	3000	1	358x340x50

[1] Packing quantity dependent on specific product type. Please contact your local Energymath representative for ordering.

[2] Dimensions for reference only.

13. Abbreviations

Table 12. Abbreviations

Acronym	Description
CMOS	Complementary Metal-Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
HBM	Human Body Model
CDM	Charged Device Model
TTL	Transistor-Transistor Logic

14. Revision History

Table 13. Revision history

Document ID	Release Date	Data sheet status	Change notice	Supersedes
EM74HC_HCT368 Rev. 1.1	Dec 15, 2025	Product datasheet		EM74HC_HCT368 Rev. 1.0
Modifications:	- Table 1: topside marking information updated. - Section 12 added Tape and Reel Information.			
EM74HC_HCT368 Rev. 1.0	Aug 30, 2024	Product datasheet		