

1. General Description

The EM74LVC1G240 is a 1-bit inverting buffer/line driver with 3-state output. The device features an output enable $\overline{OE}$. A HIGH on $\overline{OE}$ causes the output to assume a high-impedance OFF-state. Inputs can be driven from either 3.3 V or 5 V devices. This feature allows the use of these devices as translators in mixed 3.3 V and 5 V environments.

Schmitt-trigger action at all inputs makes the circuit tolerant of slower input rise and fall times. This device is fully specified for partial power down applications using I_{OFF} . The I_{OFF} circuitry disables the output, preventing the potentially damaging backflow current through the device when it is powered down.

2. Features and Benefits

- Wide supply voltage range from 1.65 V to 5.5 V
- Inputs accept voltages up to 5 V
- High noise immunity
- CMOS low power dissipation
- ± 24 mA output drive ($V_{CC} = 3.0$ V)
- Latch-up performance exceeds 100 mA
- Direct interface with TTL levels
- Complies with JEDEC standard:
 - JESD8-7 (1.65 V to 1.95 V)
 - JESD8-5 (2.3 V to 2.7 V)
 - JESD8-B/JESD36 (2.7 V to 3.6 V)
- ESD protection:
 - HBM ANSI/ESDA/JEDEC JS-001 Class 3B exceeds 8000 V
 - MM JESD22-A115C Class C exceeds 550 V
 - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options

EM74LVC1G240

Single inverting buffer/line driver; 3-state


3. Ordering Information

Table 1. Ordering information


Type number	Topside marking	Package		
		Name	Description	Quantity
EM74LVC1G240GV	VRYW	SOT23-5L	SOT23 package, 5 pins 2.92 mm × 1.6 mm; 1.25 mm (Max) height	3000
EM74LVC1G240GW	VRYW	SOT353	SOT353 package, 5 pins 2.1 mm × 1.25 mm; 1.1 mm (Max) height	3000
EM74LVC1G240GS	VR	DFN1x1-6L	DFN1×1 package, 6 pins 1 mm × 1 mm; 0.42 mm (Max) height	3000
EM74LVC1G240GM	VRYW	DFN1x1.45-6L	DFN1.45×1 package, 6 pins 1.45 mm × 1 mm; 0.6 mm (Max) height	3000
EM74LVC1G240GX	VR	DFN0.8x0.8-4L	DFN0.8×0.8 package, 5 pins 0.8 mm × 0.8 mm; 0.4 mm (Max) height	3000

MARKING INFORMATION

NOTE: YW = Date Code.



4. Function Diagram



5. Pinning Information

5.1. Pin map




Fig 4. Top view pin configuration SOT23-5 and SOT353




Fig 5. Top view pin configuration DFN6L




Fig 6. Top view pin configuration DFN4L

5.2. Pin description

Table 2. Pin description

Symbol	Pin		Description
	SOT23-5, SOT353 and DFN4L	DFN6L	
$\overline{OE}$	1	1	Output enable input
A	2	2	Data input
GND	3	3	Ground (0V)
Y	4	4	Data output
NC	-	5	Not connected
V _{CC}	5	6	Supply voltage

6. Functional Description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

Input		Output
$\overline{\text{OE}}$	A	Y
L	L	H
L	H	L
H	X	Z

7. Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Table 4. Absolute Maximum Ratings

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		-0.5	6.5	V
I_{IK}	input clamping current	$V_I < 0$ V	-50		mA
V_I	input voltage	[1]	-0.5	6.5	V
I_{OK}	output clamping current	$V_O > V_{CC}$ or $V_O < 0$ V		± 50	mA
V_O	output voltage	Active mode [1]	-0.5	$V_{CC} + 0.5$	V
		Power-down mode; $V_{CC} = 0$ V [1]	-0.5	6.5	V
I_O	output current	$V_O = 0$ V to V_{CC}		± 50	mA
I_{CC}	supply current			100	mA
I_{GND}	ground current		-100		mA
P_{tot}	total power dissipation	$T_{amb} = -40$ °C to $+125$ °C		250	mW
T_{stg}	storage temperature		-65	150	°C

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

Table 5. Recommended Operating Conditions

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{CC}	supply voltage		1.65		5.5	V
V_I	input voltage		0		5.5	V
V_O	output voltage	Active mode	0		V_{CC}	V
		Power-down mode; $V_{CC} = 0$ V	0		5.5	V
T_{amb}	ambient temperature		-40		125	°C
$\Delta t/\Delta V$	Input transition rise and fall rate	$V_{CC} = 1.65$ V to 2.7 V			20	ns/V
		$V_{CC} = 2.7$ V to 5.5 V			10	ns/V

9.Static Characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
V_{IH}	HIGH-level input voltage	$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	$0.65V_{CC}$			$0.65V_{CC}$		V
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	1.7			1.7		V
		$V_{CC} = 2.7 \text{ V to } 3.6 \text{ V}$	2.0			2.0		V
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	$0.7V_{CC}$			$0.7V_{CC}$		V
V_{IL}	LOW-level input voltage	$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$			$0.35V_{CC}$		$0.35V_{CC}$	V
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$			0.7		0.7	V
		$V_{CC} = 2.7 \text{ V to } 3.6 \text{ V}$			0.8		0.8	V
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$			$0.3V_{CC}$		$0.3V_{CC}$	V
V_{OH}	HIGH-level output voltage	$V_I = V_{IH} \text{ or } V_{IL}$						
		$I_O = -100\mu\text{A}; V_{CC} = 1.65 \text{ V to } 5.5 \text{ V}$	$V_{CC} - 0.1$			$V_{CC} - 0.1$		V
		$I_O = -4 \text{ mA}; V_{CC} = 1.65 \text{ V}$	1.2			0.95		V
		$I_O = -8 \text{ mA}; V_{CC} = 2.3 \text{ V}$	1.9			1.7		V
		$I_O = -12 \text{ mA}; V_{CC} = 2.7 \text{ V}$	2.2			1.9		V
		$I_O = -24 \text{ mA}; V_{CC} = 3.0 \text{ V}$	2.3			2.0		V
		$I_O = -32 \text{ mA}; V_{CC} = 4.5 \text{ V}$	3.8			3.4		V
V_{OL}	LOW-level output voltage	$V_I = V_{IH} \text{ or } V_{IL}$						
		$I_O = 100\mu\text{A}; V_{CC} = 1.65 \text{ V to } 5.5 \text{ V}$			0.10		0.10	V
		$I_O = 4 \text{ mA}; V_{CC} = 1.65 \text{ V}$			0.45		0.70	V
		$I_O = 8 \text{ mA}; V_{CC} = 2.3 \text{ V}$			0.30		0.45	V
		$I_O = 12 \text{ mA}; V_{CC} = 2.7 \text{ V}$			0.40		0.60	V
		$I_O = 24 \text{ mA}; V_{CC} = 3.0 \text{ V}$			0.55		0.80	V
		$I_O = 32 \text{ mA}; V_{CC} = 4.5 \text{ V}$			0.55		0.80	V
I_i	Input leakage current	$V_I = 5.5 \text{ V or GND}; V_{CC} = 0 \text{ V to } 5.5 \text{ V}$		± 0.1	± 1		± 1	μA

EM74LVC1G240

Single inverting buffer/line driver; 3-state

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
I_{OZ}	OFF-state output current	$V_{CC} = 3.6 \text{ V}$; $V_I = V_{IH}$ or V_{IL} ; $V_O = 5.5 \text{ V}$ or GND		± 0.1	± 2		± 2	μA
I_{OFF}	power-off leakage current	$V_{CC} = 0 \text{ V}$; V_I or $V_O = 5.5 \text{ V}$		± 0.1	± 2		± 2	μA
I_{CC}	supply current	$V_I = 5.5 \text{ V}$ or GND; $I_O = 0 \text{ A}$; $V_{CC} = 1.65 \text{ V}$ to 5.5 V		0.1	4		4	μA
ΔI_{CC}	additional supply current	per pin; $V_{CC} = 2.3 \text{ V}$ to 5.5 V ; $V_I = V_{CC} - 0.6 \text{ V}$; $I_O = 0 \text{ A}$		5	500		500	μA
C_I	input capacitance	$V_{CC} = 3.3 \text{ V}$; $V_I = \text{GND}$ to V_{CC}		5				pF

[1] All typical values are measured at $V_{CC} = 3.3 \text{ V}$ and $T_{AMB} = 25^\circ\text{C}$.

10. Dynamic Characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 9.

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
t_{pd}	propagation delay	A to Y; see Fig. 7 [2]						
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	2.8	8.1	14.1	2.8	14.5	ns
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	1.8	4.8	7.3	1.8	7.6	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	1.4	3.6	5.3	1.4	5.6	ns
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	1.1	2.6	3.6	1.1	3.8	ns
t_{en}	enable time	$\overline{OE}$ to Y; see Fig. 8 [3]						
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	2.5	7.5	12.2	2.5	12.5	ns
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	1.6	4.4	6.6	1.6	6.9	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	1.3	3.8	5.2	1.3	5.5	ns
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	1.1	2.4	3.4	1.1	3.7	ns
t_{dis}	disable time	$\overline{OE}$ to Y; see Fig. 8 [4]						
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	4.1	7.4	14.6	4.1	14.9	ns
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	2.9	5.6	10.3	2.9	10.5	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	2.2	4.3	7.6	2.2	7.8	ns
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	1.7	4.0	5.0	1.7	5.2	ns
C_{PD}	power dissipation capacitance	$V_i = \text{GND to } V_{CC};$ $f_i = 10 \text{ MHz}$ [5]						
		output enabled		24				pF
		output disabled		0.8				pF

[1] Typical values are measured at $T_{amb} = 25 \text{ °C}$ and $V_{CC} = 1.8 \text{ V}, 2.5 \text{ V}, 3.3 \text{ V}$ and 5.0 V respectively.

[2] t_{pd} is the same as t_{PLH} and t_{PHL} .

[3] t_{en} is the same as t_{ZHL} and t_{ZHL} .

[4] t_{dis} is the same as t_{PLZ} and t_{PHZ} .

[5] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \sum (C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz;

f_o = output frequency in MHz;


C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;

$\sum (C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.


10.1. Waveforms and test circuit



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig 7. The input A to output Y propagation delays



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.


Fig 8. 3-state enable and disable times

EM74LVC1G240

Single inverting buffer/line driver; 3-state

Table 8. Measurement points

Supply voltage	Input	Output		
V_{CC}	V_M	V_M	V_X	V_Y
1.65 V to 1.95 V	$0.5V_{CC}$	$0.5V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
2.3 V to 2.7 V	$0.5V_{CC}$	$0.5V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
3.0 V to 3.6 V	1.5 V	1.5 V	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$
4.5 V to 5.5 V	$0.5V_{CC}$	$0.5V_{CC}$	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$



Test data is given in Table 9.

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} = External voltage for measuring switching times.


Fig 9. Test circuit for measuring switching times

Table 9. Test data

Supply voltage	Input		Load		V_{EXT}		
V_{CC}	V_I	$t_r = t_f$	C_L	R_L	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
1.65 V to 1.95 V	V_{CC}	≤ 2.0 ns	30 pF	1 k Ω	open	GND	$2 \times V_{CC}$
2.3 V to 2.7 V	V_{CC}	≤ 2.0 ns	30 pF	500 Ω	open	GND	$2 \times V_{CC}$
3.0 V to 3.6 V	3 V	≤ 2.5 ns	50 pF	500 Ω	open	GND	6V
4.5 V to 5.5 V	V_{CC}	≤ 2.5 ns	50 pF	500 Ω	open	GND	$2 \times V_{CC}$

11. Package Outline

SOT23-5L




EM74LVC1G240

Single inverting buffer/line driver; 3-state

SOT353

SOT-353 (16R) PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.110	0.175	0.004	0.007
D	2.000	2.200	0.079	0.087
E	2.150	2.450	0.085	0.096
E1	1.150	1.350	0.045	0.053
e	0.650 TYP.		0.026 TYP.	
e1	1.200	1.400	0.047	0.055
L	0.260	0.460	0.010	0.018
L1	0.525 REF.		0.021 REF.	
θ	0°	8°	0°	8°

EM74LVC1G240

Single inverting buffer/line driver; 3-state


DFN1x1-6L



EM74LVC1G240

Single inverting buffer/line driver; 3-state


DFN1x1.45-6L



EM74LVC1G240

Single inverting buffer/line driver; 3-state

DFN0.8x0.8-4L



12. Tape and Reel Information

12.1. Carrier tape dimensions




Table 10. Carrier tape dimensions

Package version	A0(mm)	B0(mm)	K(mm)	T(mm)	P1(mm)	W(mm)	P0(mm)	PIN 1
SOT23-5L	3.23	3.17	1.37	0.25	4	8	4	Q3
SOT353	2.55	2.55	1.2	0.2	4	8	4	Q3
DFN1x1-6L	1.16	1.16	0.5	0.23	4	8	4	Q1
DFN1x1.45-6L	1.15	1.6	0.75	0.2	4	8	4	Q1
DFN0.8x0.8-4L	0.91	0.91	0.5	0.2	2	8	4	Q1

EM74LVC1G240

Single inverting buffer/line driver; 3-state

12.2. Reel and box dimensions




Table11.Dimensions and quantities

Package version	Type NO. ending	Reel Dimension A (mm)	Reel Width W1 (mm)	SPQ (pcs)[1]	Reels per box	Outer box dimensions L×W×H(mm)[2]
SOT23-5L	GV	180	12.2	3000	1	210x200x40
SOT353	GW	180	12.2	3000	1	210x200x40
DFN1x1-6L	GS	180	12.2	3000	1	210x200x40
DFN1x1.45-6L	GM	180	12.2	3000	1	210x200x40
DFN0.8x0.8-4L	GX	180	12.2	3000	1	210x200x40

[1] Packing quantity dependent on specific product type. Please contact your local Energymath representative for ordering.

[2] Dimensions for reference only.

13. Abbreviations

Table 12. Abbreviations

Acronym	Description
CMOS	Complementary Metal-Oxide Semiconductor
DUT	Device Under Test
ESD	Electro Static Discharge
HBM	Human Body Model
MM	Machine Model
TTL	Transistor-Transistor Logic

14. Revision History

Table 13. Revision history

Document ID	Release Date	Data sheet status	Change notice	Supersedes
EM74LVC1G240 Rev1.1	Dec 15, 2025	Product datasheet		EM74LVC1G240 Rev1.0
Modifications:	• Table 1: Added topside marking information. • Section 12: Added tape and reel information.			
EM74LVC1G240 Rev1.0	Oct 30, 2023	Product datasheet		