

1. General Description

The EM74LVC4245A is an octal dual supply translating transceiver featuring 3-state bus compatible outputs in both send and receive directions. It is designed to interface between a 3 V and 5 V bus in a mixed 3 V and 5 V supply environment. The device features an output enable input ($\overline{OE}$) and a send/receive input (DIR) for direction control. A HIGH on $\overline{OE}$ causes the outputs to assume a high-impedance OFF-state, effectively isolating the buses. In suspend mode, when either supply is zero, there is no current path between supplies. $V_{CCA} \geq V_{CCB}$, except in suspend mode. Schmitt-trigger action at all inputs makes the circuit tolerant of slower input rise and fall times.

2. Features and Benefits

■ Wide supply voltage range

- $V_{CC(A)}$: 1.2 V to 5.5 V
- $V_{CC(B)}$: 1.2 V to 5.5 V

■ High noise immunity

■ Complies with JEDEC standards:

- JESD8-7 (1.2 V to 1.95 V)
- JESD8-5 (1.8 V to 2.7 V)
- JESD8C (2.7 V to 3.6 V)
- JESD36 (4.5 V to 5.5 V)

■ Suspend mode

■ Latch-up performance exceeds 250 mA

■ ± 24 mA output drive ($V_{CC} = 3.0$ V)

■ Inputs accept voltages up to 5.5 V

■ Low power consumption: 30 μ A maximum I_{CC}

■ I_{OFF} circuitry provides partial Power-down mode operation

■ ESD protection:

EM74LVC4245A



Octal dual supply translating transceiver; 3-state

Product datasheet, Rev. 1.4

Oct 20, 2025

- HBM ANSI/ESDA/JEDEC JS-001 Class 2 exceeds 2500 V
 - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V
- Multiple package options

EM74LVC4245A

Octal dual supply translating transceiver; 3-state

3. Ordering Information

Table 1. Ordering information

Type number	Topside marking	Package		
		Name	Description	Quantity
EM74LVC4245APW	LVC4245A□ XYWW	TSSOP-24L	plastic thin shrink small outline package; 24 leads; body width 4.4 mm	3000

MARKING INFORMATION

NOTE: LVC4245A□ = Serial number and Internal code; XYWW = Vendor Code and Date Code.

LVC4245A □

Internal Code

Serial number


X YY WW

Date Code -Week

Date Code -Year


Vendor Code

4. Function Diagram



5. Pinning Information

5.1. Pinning



5.2. Pin description

Table 2. Pin description

Symbol	Pin	Description
$V_{CC(A)}$	1	Supply voltage A (An inputs/outputs, $\overline{OE}$ and DIR inputs are referenced to $V_{CC(A)}$)
DIR	2	Direction control
A0, A1, A2, A3, A4, A5, A6, A7	3, 4, 5, 6, 7, 8, 9, 10	Data input or output
GND [1]	11, 12, 13	Ground (0 V)
B0, B1, B2, B3, B4, B5, B6, B7	21, 20, 19, 18, 17, 16, 15, 14	Data input or output
$\overline{OE}$	22	Output enable input (active LOW)
$V_{CC(B)}$	23, 24	Supply voltage B (Bn inputs/outputs are referenced to $V_{CC(B)}$)

[1] All GND pins must be connected to ground (0V).

6. Functional Description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

Supply voltage	Input		Input/output	
$V_{CC(A)}$, $V_{CC(B)}$	$\overline{OE}$ [2]	DIR [2]	An [2]	Bn [2]
1.2 V to 5.5 V	L	L	A = B	input
1.2 V to 5.5 V	L	H	input	B = A
1.2 V to 5.5 V	H	X	Z	Z
GND [1]	X	X	Z	Z

[1] If at least one of $V_{CC(A)}$ or $V_{CC(B)}$ is at GND level, the device goes into suspend mode.

[2] The An inputs/outputs, DIR and OE input circuit is referenced to $V_{CC(A)}$; The Bn inputs/outputs circuit is referenced to $V_{CC(B)}$.

7. Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Table 4. Absolute Maximum Ratings

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{CC(A)}$	supply voltage A		-0.5	6.5	V
$V_{CC(B)}$	supply voltage B		-0.5	6.5	V
I_{IK}	input clamping current	$V_I < 0$ V	-50		mA
V_I	input voltage	[1]	-0.5	6.5	V
I_{OK}	output clamping current	$V_O < 0$ V	-50		mA
V_O	output voltage	Active mode [1][2][3]	-0.5	$V_{CCO} + 0.5$	V
		Suspend or 3-state mode [1]	-0.5	6.5	V
I_O	output current	$V_O = 0$ V to V_{CCO} [2]		± 50	mA
I_{CC}	supply current	$I_{CC(A)}$ or $I_{CC(B)}$; per V_{CC} pin		100	mA
I_{GND}	ground current	per GND pin	-100		mA
P_{tot}	total power dissipation			500	mW
T_{stg}	storage temperature		-65	150	°C

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

[2] V_{CCO} is the supply voltage associated with the output port.

[3] $V_{CCO} + 0.5$ V should not exceed 6.5 V.

8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

Table 5. Recommended Operating Conditions

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{CC(A)}$	supply voltage A		1.4	5.5	V
		Functional	1.2		V
$V_{CC(B)}$	supply voltage B		1.4	5.5	V
		Functional	1.2		V
V_I	input voltage		0	5.5	V
V_O	output voltage	Active mode [1]	0	V_{CCO}	V
		Suspend or 3-state mode	0	5.5	V
T_{amb}	ambient temperature		-40	125	°C
$\Delta t/\Delta V$	input transition rise and fall rate	$V_{CCI} = 1.2\text{ V}$ [2]		20	ns/V
		$V_{CCI} = 1.4\text{ V to }1.95\text{ V}$		20	ns/V
		$V_{CCI} = 2.3\text{ V to }2.7\text{ V}$		20	ns/V
		$V_{CCI} = 3\text{ V to }3.6\text{ V}$		10	ns/V
		$V_{CC} = 4.5\text{ V to }5.5\text{ V}$		5	ns/V

[1] V_{CCO} is the supply voltage associated with the output port.

[2] V_{CCI} is the supply voltage associated with the input port.

9.Static Characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V). Typical values measured at $T_{amb} = 25^{\circ}\text{C}$ (unless otherwise noted).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
V_{IH}	HIGH-level input voltage	data input [1]						
		$V_{CCI} = 1.2\text{ V}$	$0.8V_{CCI}$			$0.8V_{CCI}$		V
		$V_{CCI} = 1.4\text{ V to }1.95\text{ V}$	$0.65V_{CCI}$			$0.65V_{CCI}$		V
		$V_{CCI} = 2.3\text{ V to }2.7\text{ V}$	1.7			1.7		V
		$V_{CCI} = 3\text{ V to }3.6\text{ V}$	2.2			2.2		V
		$V_{CCI} = 4.5\text{ V to }5.5\text{ V}$	$0.7V_{CCI}$			$0.7V_{CCI}$		V
		DIR, $\overline{OE}$ input						
		$V_{CCI} = 1.2\text{ V}$	$0.8V_{CC(A)}$			$0.8V_{CC(A)}$		V
		$V_{CCI} = 1.4\text{ V to }1.95\text{ V}$	$0.65V_{CC(A)}$			$0.65V_{CC(A)}$		V
		$V_{CCI} = 2.3\text{ V to }2.7\text{ V}$	1.7			1.7		V
		$V_{CCI} = 3\text{ V to }3.6\text{ V}$	2.0			2.0		V
		$V_{CCI} = 4.5\text{ V to }5.5\text{ V}$	$0.7V_{CC(A)}$			$0.7V_{CC(A)}$		V
V_{IL}	LOW-level input voltage	data input [1]						
		$V_{CCI} = 1.2\text{ V}$			$0.2V_{CCI}$		$0.2V_{CCI}$	V
		$V_{CCI} = 1.4\text{ V to }1.95\text{ V}$			$0.35 V_{CCI}$		$0.35 V_{CCI}$	V
		$V_{CCI} = 2.3\text{ V to }2.7\text{ V}$			0.7		0.7	V
		$V_{CCI} = 3\text{ V to }3.6\text{ V}$			0.8		0.8	V
		$V_{CCI} = 4.5\text{ V to }5.5\text{ V}$			$0.3V_{CCI}$		$0.3V_{CCI}$	V
		DIR, $\overline{OE}$ input						
		$V_{CCI} = 1.2\text{ V}$			$0.2V_{CC(A)}$		$0.2V_{CC(A)}$	V
		$V_{CCI} = 1.4\text{ V to }1.95\text{ V}$			$0.35 V_{CC(A)}$		$0.35 V_{CC(A)}$	V
		$V_{CCI} = 2.3\text{ V to }2.7\text{ V}$			0.7		0.7	V
		$V_{CCI} = 3\text{ V to }3.6\text{ V}$			0.8		0.8	V
		$V_{CCI} = 4.5\text{ V to }5.5\text{ V}$			$0.3V_{CC(A)}$		$0.3V_{CC(A)}$	V

EM74LVC4245A
Octal dual supply translating transceiver; 3-state

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
V_{OH}	HIGH-level output voltage	$V_I = V_{IH}$						
		$I_O = -100 \mu A$; $V_{CCO} = 1.2 V$ to $4.5 V$	$V_{CCO} - 0.1$			$V_{CCO} - 0.1$		V
		$I_O = -3 mA$; $V_{CCO} = 1.4 V$	1.0			1.0		V
		$I_O = -5.5 mA$; $V_{CCO} = 1.65 V$	1.2			1.2		V
		$I_O = -10 mA$; $V_{CCO} = 2.3 V$	1.9			1.8		V
		$I_O = -20 mA$; $V_{CCO} = 3.0 V$	2.4			2.3		V
		$I_O = -32 mA$; $V_{CCO} = 4.5 V$	3.8			3.7		V
V_{OL}	LOW-level output voltage	$V_I = V_{IL}$						
		$I_O = 100 \mu A$; $V_{CCO} = 1.2 V$ to $4.5 V$			0.1		0.1	V
		$I_O = 3 mA$; $V_{CCO} = 1.4 V$			0.3		0.3	V
		$I_O = 5.5 mA$; $V_{CCO} = 1.65 V$			0.45		0.45	V
		$I_O = 10 mA$; $V_{CCO} = 2.3 V$			0.3		0.4	V
		$I_O = 20 mA$; $V_{CCO} = 3.0 V$			0.55		0.55	V
		$I_O = 32 mA$; $V_{CCO} = 4.5 V$			0.55		0.6	V
I_I	input leakage current	DIR, $\overline{OE}$ input; $V_I = 0 V$ to $5.5 V$; $V_{CCI} = 1.2 V$ to $5.5 V$			± 2		± 10	μA
I_{OZ}	OFF-state output current	A or B port; $V_O = 0 V$ or V_{CCO} ; $V_{CCO} = 1.2 V$ to $5.5 V$ [2]			± 2		± 10	μA
		suspend mode A port; $V_O = 0 V$ or V_{CCO} ; $V_{CC(A)} = 5.5 V$; $V_{CC(B)} = 0 V$ [2]			± 2		± 10	μA
		suspend mode B port; $V_O = 0 V$ or V_{CCO} ; $V_{CC(A)} = 0 V$; $V_{CC(B)} = 5.5 V$ [2]			± 2		± 10	μA
I_{OFF}	power-off leakage current	A port; V_I or $V_O = 0 V$ to $5.5 V$; $V_{CC(A)} = 0 V$; $V_{CC(B)} = 1.2 V$ to $5.5 V$			± 3		± 10	μA
		B port; V_I or $V_O = 0 V$ to $5.5 V$; $V_{CC(B)} = 0 V$; $V_{CC(A)} = 1.2 V$ to $5.5 V$			± 3		± 10	μA

EM74LVC4245A

Octal dual supply translating transceiver; 3-state

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ	Max	Min	Max	
I_{CC}	supply current	A port; $V_I = 0\text{ V}$ or V_{CCI} ; $I_O = 0\text{ A}$ [1]						
		$V_{CC(A)}, V_{CC(B)} = 1.2\text{ V to } 5.5\text{ V}$			15		20	μA
		$V_{CC(A)} = 5.5\text{ V}; V_{CC(B)} = 0\text{ V}$			15		20	μA
		$V_{CC(A)} = 0\text{ V}; V_{CC(B)} = 5.5\text{ V}$	-2			-4		μA
		B port; $V_I = 0\text{ V}$ or V_{CCI} ; $I_O = 0\text{ A}$						
		$V_{CC(A)}, V_{CC(B)} = 1.2\text{ V to } 5.5\text{ V}$			15		20	μA
		$V_{CC(B)} = 0\text{ V}; V_{CC(A)} = 5.5\text{ V}$	-2			-4		μA
		$V_{CC(B)} = 5.5\text{ V}; V_{CC(A)} = 0\text{ V}$			15		20	μA
		A plus B port ($I_{CC(A)} + I_{CC(B)}$); $I_O = 0\text{ A}; V_I = 0\text{ V}$ or V_{CCI}						
		$V_{CC(A)}, V_{CC(B)} = 1.2\text{ V to } 5.5\text{ V}$			25		30	μA
ΔI_{CC}	additional supply current	per input; $V_{CC(A)}, V_{CC(B)} = 3.0\text{ V to } 5.5\text{ V}$						
		DIR and $\overline{OE}$ input; DIR or $\overline{OE}$ input at $V_{CC(A)} - 0.6\text{ V}$; A port at $V_{CC(A)}$ or GND; B port = open			50		75	μA
		A port; A port at $V_{CC(A)} - 0.6\text{ V}$; DIR at $V_{CC(A)}$; B port = open			50		75	μA
		B port; B port at $V_{CC(B)} - 0.6\text{ V}$; DIR at $V_{CC(B)}$; A port = open			50		75	μA

[1] V_{CCI} is the supply voltage associated with the data input port.

[2] V_{CCO} is the supply voltage associated with the output port.

EM74LVC4245A

Octal dual supply translating transceiver; 3-state

10. Dynamic Characteristics

Table 7. Dynamic characteristics for temperature range -40 °C to +85 °C

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 6. for waveforms see Fig. 3 and Fig. 4. [1]

Symbol	Parameter	Conditions	V _{CC(B)}										Unit
			1.5V±0.1V		1.8V±0.15V		2.5V±0.2V		3.3V±0.3V		5.0V±0.5V		
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
V _{CC(A)} = 1.5 V ± 0.1 V													
t _{pd}	propagation time	An to Bn	0.9	43.2	0.9	39.2	0.8	36.3	0.7	35.1	0.7	35.1	ns
		Bn to An	0.9	43.2	0.9	39.2	0.8	36.3	0.7	35.1	0.7	35.1	ns
t _{dis}	disable time	$\overline{OE}$ to An	1.5	72.5	1.5	72.5	1.5	72.5	1.5	72.5	1.4	72.5	ns
		$\overline{OE}$ to Bn	1.5	72.5	1.5	72.5	1.5	72.5	1.5	72.5	1.4	72.5	ns
t _{en}	enable time	$\overline{OE}$ to An	0.4	92.2	0.4	92.2	0.4	92.2	0.4	92.2	0.4	92.2	ns
		$\overline{OE}$ to Bn	0.4	92.2	0.4	92.2	0.4	92.2	0.4	92.2	0.4	92.2	ns
V _{CC(A)} = 1.8 V ± 0.15 V													
t _{pd}	propagation time	An to Bn	0.9	38.6	0.9	30.5	0.8	26.9	0.7	26.3	0.7	25.8	ns
		Bn to An	0.9	38.6	0.9	30.5	0.8	26.9	0.7	26.3	0.7	25.8	ns
t _{dis}	disable time	$\overline{OE}$ to An	1.5	46.3	1.5	46.3	1.5	46.3	1.5	46.3	1.4	46.3	ns
		$\overline{OE}$ to Bn	1.5	46.3	1.5	46.3	1.5	46.3	1.5	46.3	1.4	46.3	ns
t _{en}	enable time	$\overline{OE}$ to An	0.4	63.2	0.4	58.1	0.4	54.6	0.4	54.1	0.4	53.1	ns
		$\overline{OE}$ to Bn	0.4	63.2	0.4	58.1	0.4	54.6	0.4	54.1	0.4	53.1	ns
V _{CC(A)} = 2.5 V ± 0.2 V													
t _{pd}	propagation time	An to Bn	1.2	33.0	1.2	24.7	1.0	19.7	1.0	18.3	0.9	17.1	ns
		Bn to An	1.2	33.0	1.2	24.7	1.0	19.7	1.0	18.3	0.9	17.1	ns
t _{dis}	disable time	$\overline{OE}$ to An	1.4	25.1	1.4	25.1	1.4	25.1	1.4	25.1	1.4	25.1	ns
		$\overline{OE}$ to Bn	1.4	25.1	1.4	25.1	1.4	25.1	1.4	25.1	1.4	25.1	ns
t _{en}	enable time	$\overline{OE}$ to An	1.0	38.3	1.0	33.1	1.0	29.5	1.0	28.0	1.0	27.0	ns
		$\overline{OE}$ to Bn	1.0	38.3	1.0	33.1	1.0	29.5	1.0	28.0	1.0	27.0	ns
V _{CC(A)} = 3.3 V ± 0.3 V													
t _{pd}	propagation time	An to Bn	0.8	31.2	0.8	22.6	0.8	16.2	0.7	14.5	0.6	13.6	ns
		Bn to An	0.8	31.2	0.8	22.6	0.8	16.2	0.7	14.5	0.6	13.6	ns
t _{dis}	disable time	$\overline{OE}$ to An	1.6	20.2	1.6	20.2	1.6	20.2	1.6	20.2	1.6	20.2	ns
		$\overline{OE}$ to Bn	1.6	20.2	1.6	20.2	1.6	20.2	1.6	20.2	1.6	20.2	ns
t _{en}	enable time	$\overline{OE}$ to An	0.8	31.5	0.8	25.8	0.8	22.4	0.8	21.1	0.8	20.8	ns
		$\overline{OE}$ to Bn	1.8	31.5	0.8	25.8	0.8	22.4	0.8	21.1	0.8	20.8	ns
V _{CC(A)} = 5.0 V ± 0.5 V													
t _{pd}	propagation time	An to Bn	0.7	29.8	0.7	21.3	0.4	14.8	0.3	12.6	0.3	11.2	ns
		Bn to An	0.7	29.8	0.7	21.3	0.4	14.8	0.3	12.6	0.3	11.2	ns
t _{dis}	disable time	$\overline{OE}$ to An	0.3	15.6	0.3	15.6	0.3	15.6	0.3	15.6	0.3	15.6	ns
		$\overline{OE}$ to Bn	0.3	15.6	0.3	15.6	0.3	15.6	0.3	15.6	0.3	15.6	ns
t _{en}	enable time	$\overline{OE}$ to An	0.7	29.1	0.7	21.2	0.7	18.5	0.7	16.8	0.7	15.9	ns
		$\overline{OE}$ to Bn	0.7	29.1	0.7	21.2	0.7	18.5	0.7	16.8	0.7	15.9	ns

[1] t_{pd} is the same as t_{PLH} and t_{PHL} ; t_{dis} is the same as t_{PLZ} and t_{PHZ} ; t_{en} is the same as t_{PZL} and t_{PZH} .

EM74LVC4245A

Octal dual supply translating transceiver; 3-state

Table 8. Dynamic characteristics for temperature range -40 °C to +125 °C

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 6. for waveforms see Fig. 3 and Fig. 4. [1]

Symbol	Parameter	Conditions	V _{CC(B)}										Unit
			1.5V±0.1V		1.8V±0.15V		2.5V±0.2V		3.3V±0.3V		5.0V±0.5V		
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
V _{CC(A)} = 1.5 V ± 0.1 V													
t _{pd}	propagation time	An to Bn	0.9	43.3	0.9	38.9	0.8	36.3	0.7	35.1	0.7	35.1	ns
		Bn to An	0.9	43.3	0.9	38.9	0.8	36.3	0.7	35.1	0.7	35.1	ns
t _{dis}	disable time	$\overline{\text{OE}}$ to An	1.5	74.5	1.5	74.5	1.5	74.5	1.5	74.5	1.4	74.5	ns
		$\overline{\text{OE}}$ to Bn	1.5	74.5	1.5	74.5	1.5	74.5	1.5	74.5	1.4	74.5	ns
t _{en}	enable time	$\overline{\text{OE}}$ to An	0.4	94.2	0.4	94.2	0.4	94.2	0.4	94.2	0.4	94.2	ns
		$\overline{\text{OE}}$ to Bn	0.4	94.2	0.4	94.2	0.4	94.2	0.4	94.2	0.4	94.2	ns
V _{CC(A)} = 1.8 V ± 0.15 V													
t _{pd}	propagation time	An to Bn	0.9	38.4	0.9	30.8	0.8	27.8	0.7	26.4	0.7	25.3	ns
		Bn to An	0.9	38.4	0.9	30.8	0.8	27.8	0.7	26.4	0.7	25.3	ns
t _{dis}	disable time	$\overline{\text{OE}}$ to An	1.5	50.3	1.5	50	1.5	50.2	1.5	50.4	1.4	50.3	ns
		$\overline{\text{OE}}$ to Bn	1.5	50.3	1.5	50	1.5	50.2	1.5	50.4	1.4	50.3	ns
t _{en}	enable time	$\overline{\text{OE}}$ to An	0.4	67.2	0.4	61.8	0.4	58.5	0.4	58.2	0.4	57.1	ns
		$\overline{\text{OE}}$ to Bn	0.4	67.2	0.4	61.8	0.4	58.5	0.4	58.2	0.4	57.1	ns
V _{CC(A)} = 2.5 V ± 0.2 V													
t _{pd}	propagation time	An to Bn	1.2	33.4	1.2	25.4	1.0	19.7	1.0	18.5	0.9	17.3	ns
		Bn to An	1.2	33.4	1.2	25.4	1.0	19.7	1.0	18.5	0.9	17.3	ns
t _{dis}	disable time	$\overline{\text{OE}}$ to An	1.4	29.1	1.4	28.8	1.4	29	1.4	29.2	1.4	29.1	ns
		$\overline{\text{OE}}$ to Bn	1.4	29.1	1.4	28.8	1.4	29	1.4	29.2	1.4	29.1	ns
t _{en}	enable time	$\overline{\text{OE}}$ to An	1.0	42.3	1.0	36.8	1.0	33.4	1.0	32.1	1.0	31.0	ns
		$\overline{\text{OE}}$ to Bn	1.0	42.3	1.0	36.8	1.0	33.4	1.0	32.1	1.0	31.0	ns
V _{CC(A)} = 3.3 V ± 0.3 V													
t _{pd}	propagation time	An to Bn	0.8	32.2	0.8	23.2	0.8	16.8	0.7	15.5	0.6	14.6	ns
		Bn to An	0.8	32.2	0.8	23.2	0.8	16.8	0.7	15.5	0.6	14.6	ns
t _{dis}	disable time	$\overline{\text{OE}}$ to An	1.6	24.2	1.6	23.9	1.6	24.1	1.6	24.3	1.6	24.2	ns
		$\overline{\text{OE}}$ to Bn	1.6	24.2	1.6	23.9	1.6	24.1	1.6	24.3	1.6	24.2	ns
t _{en}	enable time	$\overline{\text{OE}}$ to An	0.8	35.5	0.8	29.5	0.8	26.3	0.8	25.2	0.8	24.8	ns
		$\overline{\text{OE}}$ to Bn	0.8	35.5	0.8	29.5	0.8	26.3	0.8	25.2	0.8	24.8	ns
V _{CC(A)} = 5.0 V ± 0.5 V													
t _{pd}	propagation time	An to Bn	0.7	30.4	0.7	22.1	0.4	15.5	0.3	13.4	0.3	11.9	ns
		Bn to An	0.7	30.4	0.7	22.1	0.4	15.5	0.3	13.4	0.3	11.9	ns
t _{dis}	disable time	$\overline{\text{OE}}$ to An	0.3	19.6	0.3	19.3	0.3	19.5	0.3	19.7	0.3	19.6	ns
		$\overline{\text{OE}}$ to Bn	0.3	19.6	0.3	19.3	0.3	19.5	0.3	19.7	0.3	19.6	ns
t _{en}	enable time	$\overline{\text{OE}}$ to An	0.7	33.1	0.7	24.9	0.7	22.4	0.7	20.9	0.7	19.9	ns
		$\overline{\text{OE}}$ to Bn	0.7	33.1	0.7	24.9	0.7	22.4	0.7	20.9	0.7	19.9	ns

[1] t_{pd} is the same as t_{PLH} and t_{PHL}; t_{dis} is the same as t_{PLZ} and t_{PHZ}; t_{en} is the same as t_{PZL} and t_{PZH}.

EM74LVC4245A

Octal dual supply translating transceiver; 3-state

Table 9. Typical power dissipation capacitance at $V_{CC(A)} = V_{CC(B)}$ and $T_{amb} = 25\text{ }^{\circ}\text{C}$

Voltages are referenced to GND (ground = 0 V). [1][2]

Symbol	Parameter	Conditions	$V_{CC(A)}$ and $V_{CC(B)}$				Unit
			1.8 V	2.5 V	3.3 V	5.0 V	
C_{PD}	power dissipation capacitance	A port: (direction A to B); B port: (direction B to A)	1	1	1	1	pF
		A port: (direction B to A); B port: (direction A to B)	16	16	17	18	pF

[1] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;


$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

[2] $f_i = 10\text{ MHz}$; $V_i = \text{GND to } V_{CC}$; $t_r = t_f = 1\text{ ns}$; $C_L = 0\text{ pF}$; $R_L = \infty\text{ }\Omega$.

EM74LVC4245A

Octal dual supply translating transceiver; 3-state


10.1. Waveforms and test circuit



Measurement points are given in Table 10.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig. 4. The input An, Bn to output Bn, An propagation delays



Measurement points are given in Table 10.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig. 5. 3-state enable and disable times

Table 10. Measurement points



Supply voltage	Input [1]	Output [2]		
$V_{CC(A)}, V_{CC(B)}$	V_M	V_M	V_X	V_Y
1.2 V to 1.6 V	$0.5V_{CCI}$	$0.5V_{CCO}$	$V_{OL} + 0.1 \text{ V}$	$V_{OH} - 0.1 \text{ V}$
1.65 V to 2.7 V	$0.5V_{CCI}$	$0.5V_{CCO}$	$V_{OL} + 0.15 \text{ V}$	$V_{OH} - 0.15 \text{ V}$
3.0 V to 5.5 V	$0.5V_{CCI}$	$0.5V_{CCO}$	$V_{OL} + 0.3 \text{ V}$	$V_{OH} - 0.3 \text{ V}$

[1] V_{CCI} is the supply voltage associated with the data input port.

[2] V_{CCO} is the supply voltage associated with the output port.

EM74LVC4245A

Octal dual supply translating transceiver; 3-state



Test data is given in Table 11.

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} = External voltage for measuring switching times.

Fig. 6. Test circuit for measuring switching times

Table 11. Test data


Supply voltage	Input		Load		V_{EXT}		
$V_{CC(A)}, V_{CC(B)}$	V_I [1]	$t_r = t_f$	C_L	R_L	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ} [2]
1.2 V to 5.5 V	V_{CCI}	≤ 2.5 ns	15 pF	2k Ω	open	GND	$2V_{CCO}$

[1] V_{CCI} is the supply voltage associated with the data input port.

[2] V_{CCO} is the supply voltage associated with the output port.

11. Package Outline

TSSOP-24L



12. Tape and Reel Information

12.1.Carrier tape dimensions




Table 12. Carrier tape dimensions

Package version	A0(mm)	B0(mm)	K0(mm)	T(mm)	P1(mm)	W(mm)	P0(mm)	PIN 1
TSSOP-24L	6.8	8.6	1.9	0.3	8	16	4	Q1

EM74LVC4245A

Octal dual supply translating transceiver; 3-state

12.2.Reel and box dimensions




Table 13. Dimensions and quantities

Package version	Type NO. ending	Reel Dimension A (mm)	Reel Width W1 (mm)	SPQ (pcs) [1]	Reels per box	Outer box dimensions L×W×H(mm) [2]
TSSOP-24L	PW	330	22.4	3000	1	358x340x50

[1] Packing quantity dependent on specific product type. Please contact your local Energymath representative for ordering.

[2] Dimensions for reference only.

13. Abbreviations

Table 14. Abbreviations

Acronym	Description
CMOS	Complementary Metal-Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
HBM	Human Body Model
CDM	Charged Device Model

14. Revision History

Table 15. Revision history

Document ID	Release Date	Data sheet status	Change notice	Supersedes
EM74LVC4245A Rev. 1.4	Oct 20, 2025	Product datasheet		EM74LVC4245A Rev. 1.3
Modifications:	- Section 3: ordering information updated. - Section 12: Added tape and reel information.			
EM74LVC4245A Rev. 1.3	Aug 25, 2025	Product datasheet		EM74LVC4245A Rev. 1.2
Modifications:	Updated the I_{OFF} spec.			
EM74LVC4245A Rev. 1.2	Aug 20, 2025	Product datasheet		EM74LVC4245A Rev. 1.1
Modifications:	Section 11: Updated the package outline.			
EM74LVC4245A Rev. 1.1	Aug 12, 2025	Product datasheet		EM74LVC4245A Rev. 1.0
Modifications:	- Updated the V_{OH} and V_{OL} spec. - Added the topside marking information.			
EM74LVC4245A Rev. 1.0	Feb 10, 2025	Product datasheet		