

1. General Description

The EM74LVC244A and EM74LVCH244A are 8-bit buffer/line drivers with 3-state outputs. The devices can be used as two 4-bit buffers or one 8-bit buffer. Both devices features two output enables ($\overline{1OE}$ and $\overline{2OE}$), each controlling four of the 3-state outputs. A HIGH on $\overline{nOE}$ and causes the outputs to assume a high-impedance OFF-state. Inputs can be driven from either 3.3 V or 5 V devices. This feature allows the use of these devices as translators in mixed 3.3 V and 5 V environments.

Schmitt-trigger action at all inputs makes the circuit tolerant of slower input rise and fall times.

This device is fully specified for partial power down applications using I_{OFF} . The I_{OFF} circuitry disables the output, preventing the potentially damaging backflow current through the device when it is powered down.

2. Features and Benefits

- Wide supply voltage range from 1.2 V to 5.5 V
- Direct interface with TTL levels
- CMOS low power dissipation
- Overvoltage tolerant inputs to 5.5 V
- Bus hold on all data inputs (EM74LVCH244A only)
- I_{OFF} circuitry provides partial Power-down mode operation
- Latch-up performance exceeds 250 mA
- Complies with JEDEC standards:
 - JESD8-7A (1.65 V to 1.95 V)
 - JESD8-5A (2.3 V to 2.7 V)
 - JESD8-C/JESD36 (2.7 V to 3.6 V)
 - JESD36 (4.5 V to 5.5 V)
- ESD protection:
 - HBM ANSI/ESDA/JEDEC JS-001 Class 3A exceeds 4000 V
 - CDM ANSI/ESDA/JEDEC JS-002 Class C3 exceeds 2000 V

EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state

3. Ordering Information

Table 1. Ordering information

Type number	Topside marking	Package		
		Name	Description	Quantity
EM74LVC244AD	LVC244A□ XYWW	SOP-20L	plastic small outline package; 20 leads; body width 7.5 mm	2000
EM74LVCH244AD	LVCH244A□ XYWW			
EM74LVC244APW	LVC244A□ XYWW	TSSOP-20L	plastic thin shrink small outline package; 20 leads; body width 4.4 mm	3000
EM74LVCH244APW	LVCH244A□ XYWW			
EM74LVC244ADB	LVC244A□ XYWW	SSOP-20L	plastic small outline package; 20 leads; body width 5.3 mm	2000
EM74LVCH244ADB	LVCH244A□ XYWW			

MARKING INFORMATION

NOTE: LVC244A□ = Serial number and Internal code; XYWW = Vendor Code and Date Code.

LVC244A □

Internal Code

Serial number

X YY WW

Date Code -Week

Date Code -Year

Vendor Code

4.Function Diagram




Fig. 1. Functional diagram




Fig. 2. Logic symbol





Fig. 3. IEC logic symbol

5. Pinning Information

5.1. Pinning



5.2. Pin description

Table 2. Pin description

Symbol	Pin	Description
$\overline{1OE}$, $\overline{2OE}$	1, 19	Output enable input(active LOW)
1A0, 1A1, 1A2, 1A3	2, 4, 6, 8	Data input
2Y0, 2Y1, 2Y2, 2Y3	3, 5, 7, 9	Bus output
GND	10	Ground (0V)
2A0, 2A1, 2A2, 2A3	17, 15, 13, 11	Data input
1Y0, 1Y1, 1Y2, 1Y3	18, 16, 14, 12	Bus output
V _{CC}	20	Supply voltage

EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state

6. Functional Description

Table 3. Function table

H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

Input		Output
$\overline{nOE}$	nAn	nYn
L	L	L
L	H	H
H	X	Z

7. Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Table 4. Absolute Maximum Ratings

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND.

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CC}	supply voltage		-0.5	6.5	V
I_{IK}	input clamping current	$V_I < 0$ V	-50		mA
V_I	Input voltage	[1]	-0.5	6.5	V
I_{OK}	output clamping current	$V_O < 0$ V or $V_O > V_{CC}$		± 50	mA
V_O	output voltage	output HIGH or LOW [2]	-0.5	$V_{CC}+0.5$	V
		output 3-state [2]	-0.5	6.5	V
I_O	output current	$V_O = 0$ V to V_{CC}		± 50	mA
I_{CC}	supply current			100	mA
I_{GND}	ground current		-100		mA
P_{tot}	total power dissipation			500	mW
T_{stg}	storage temperature		-65	150	°C

[1] The minimum input voltage ratings may be exceeded if the input current ratings are observed.

[2] The output voltage ratings may be exceeded if the output current ratings are observed.

8. Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. EnergyMath does not recommend exceeding them or designing to Absolute Maximum Ratings.

Table 5. Recommended Operating Conditions

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V _{CC}	supply voltage		1.65		5.5	V
		functional	1.2			V
V _I	input voltage		0		5.5	V
V _O	output voltage	output HIGH or LOW	0		V _{CC}	V
		output 3-state	0		5.5	V
T _{amb}	ambient temperature		-40	25	125	°C
$\Delta t/\Delta V$	input transition rise and fall rate	V _{CC} = 1.2 V to 2.7 V			20	ns/V
		V _{CC} = 2.7 V to 3.6 V			10	ns/V
		V _{CC} = 4.5 V to 5.5 V			5	ns/V

9.Static Characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V). Typical values measured at $T_{amb} = 25^{\circ}\text{C}$ (unless otherwise noted).

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
V_{IH}	HIGH-level input voltage	$V_{CC} = 1.2\text{ V}$	1.08			1.08		V
		$V_{CC} = 1.65\text{ V to }1.95\text{ V}$	$0.65V_{CC}$			$0.65V_{CC}$		V
		$V_{CC} = 2.3\text{ V to }2.7\text{ V}$	1.7			1.7		V
		$V_{CC} = 2.7\text{ V to }3.6\text{ V}$	2.0			2.0		V
		$V_{CC} = 4.5\text{ V to }5.5\text{ V}$	$0.7V_{CC}$			$0.7V_{CC}$		V
V_{IL}	LOW-level input voltage	$V_{CC} = 1.2\text{ V}$			0.12		0.12	V
		$V_{CC} = 1.65\text{ V to }1.95\text{ V}$			$0.35V_{CC}$		$0.35V_{CC}$	V
		$V_{CC} = 2.3\text{ V to }2.7\text{ V}$			0.7		0.7	V
		$V_{CC} = 2.7\text{ V to }3.6\text{ V}$			0.8		0.8	V
		$V_{CC} = 4.5\text{ V to }5.5\text{ V}$			$0.3V_{CC}$		$0.3V_{CC}$	V
V_{OH}	HIGH-level output voltage	$V_I = V_{IH}\text{ or }V_{IL}$						
		$I_O = -100\text{ }\mu\text{A}$; $V_{CC} = 1.65\text{ V to }5.5\text{ V}$	$V_{CC} - 0.1$			$V_{CC} - 0.1$		V
		$I_O = -4\text{ mA}$; $V_{CC} = 1.65\text{ V}$	1.2			1.05		V
		$I_O = -8\text{ mA}$; $V_{CC} = 2.3\text{ V}$	1.9			1.7		V
		$I_O = -12\text{ mA}$; $V_{CC} = 2.7\text{ V}$	2.2			2.1		V
		$I_O = -24\text{ mA}$; $V_{CC} = 3.0\text{ V}$	2.4			2.2		V
		$I_O = -32\text{ mA}$; $V_{CC} = 4.5\text{ V}$	3.8			3.4		V
V_{OL}	LOW-level output voltage	$V_I = V_{IH}\text{ or }V_{IL}$						
		$I_O = 100\text{ }\mu\text{A}$; $V_{CC} = 1.65\text{ V to }5.5\text{ V}$			0.1		0.1	V
		$I_O = 4\text{ mA}$; $V_{CC} = 1.65\text{ V}$			0.45		0.65	V
		$I_O = 8\text{ mA}$; $V_{CC} = 2.3\text{ V}$			0.3		0.45	V
		$I_O = 12\text{ mA}$; $V_{CC} = 2.7\text{ V}$			0.4		0.6	V
		$I_O = 24\text{ mA}$; $V_{CC} = 3.0\text{ V}$			0.55		0.8	V
		$I_O = 32\text{ mA}$; $V_{CC} = 4.5\text{ V}$			0.55		0.8	V
I_I	input leakage current	$V_I = V_{CC}\text{ or GND}$; $V_{CC} = 5.5\text{ V}$			± 2		± 10	μA

EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
I_{OZ}	OFF-state output current	$V_I = V_{IH}$ or V_{IL} ; $V_{CC} = 5.5$ V ; $V_O = V_{CC}$ or GND [2]			± 5		± 10	μA
I_{OFF}	power-off leakage current	V_I or $V_O = 5.5$ V ; $V_{CC} = 0$ V			± 10		± 20	μA
I_{CC}	supply current	$V_I = V_{IH}$ or GND ; $I_O = 0$ A ; $V_{CC} = 5.5$ V			10		20	μA
ΔI_{CC}	additional supply current	per input pin ; $V_I = V_{CC} - 0.6$ V ; $I_O = 0$ A ; $V_{CC} = 2.7$ V to 5.5 V			500		5000	μA
C_i	input capacitance	Pin $\overline{OE}$		8				pF
		Pin nAn		14				pF
I_{BHL}	bus hold LOW current	$V_{CC} = 1.65$ V ; $V_I = 0.58$ V ; [3][4]	10			10		μA
		$V_{CC} = 2.3$ V ; $V_I = 0.70$ V	25			20		μA
		$V_{CC} = 3.0$ V ; $V_I = 0.80$ V	75			60		μA
		$V_{CC} = 4.5$ V ; $V_I = 1.35$ V	100			85		μA
I_{BHH}	bus hold HIGH current	$V_{CC} = 1.65$ V ; $V_I = 1.07$ V [3][4]	-10			-10		μA
		$V_{CC} = 2.3$ V ; $V_I = 1.70$ V	-25			-20		μA
		$V_{CC} = 3.0$ V ; $V_I = 2.00$ V	-75			-60		μA
		$V_{CC} = 4.5$ V ; $V_I = 3.15$ V	-100			-85		μA
I_{BHLO}	bus hold LOW overdrive current	$V_{CCI} = 1.95$ V [3][5]	200			200		μA
		$V_{CCI} = 2.7$ V	300			300		μA
		$V_{CCI} = 3.6$ V	500			500		μA
		$V_{CCI} = 5.5$ V	900			900		μA
I_{BHHO}	bus hold HIGH overdrive current	$V_{CCI} = 1.95$ V [3][5]	-200			-200		μA
		$V_{CCI} = 2.7$ V	-300			-300		μA
		$V_{CCI} = 3.6$ V	-500			-500		μA
		$V_{CCI} = 5.5$ V	-900			-900		μA

[1] All typical values are measured at $V_{CC} = 3.3$ V (unless stated otherwise) and $T_{amb} = 25$ °C.

[2] The bus hold circuit is switched off when $V_I > V_{CC}$ allowing 5.5 V on the input terminal.

[3] Valid for data inputs of bus hold parts only (EM74LVCH244A). Note that control inputs do not have a bus hold circuit.

[4] The specified sustaining current at the data input holds the input below the specified V_I level.

[5] The specified overdrive current at the data input forces the data input to the opposite input state.

EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state

10. Dynamic Characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V); for test circuit see Fig. 7.

Symbol	Parameter	Conditions	-40 °C to +85 °C			-40 °C to +125 °C		Unit
			Min	Typ[1]	Max	Min	Max	
t_{pd}	propagation delay	nAn to nYn; see Fig. 5 [2]						
		$V_{CC} = 1.2 \text{ V}$		70				
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	3.0	19.2	33.2	3.0	33.6	ns
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	2.0	10.1	14.7	2.0	16.8	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	1.5	7.0	9.7	1.5	11.3	ns
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	1.0	4.8	6.5	1.0	7.6	ns
t_{en}	enable time	nOE to nYn; see Fig. 6 [2]						
		$V_{CC} = 1.2 \text{ V}$		90				
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	3.5	24.5	65.0	3.5	65.5	ns
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	2.5	12.8	30.4	2.5	31.3	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	2.0	8.9	20.1	2.0	20.7	ns
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	1.5	6.0	13.9	1.5	15.0	ns
t_{dis}	disable time	nOE to nYn; see Fig. 6 [2]						
		$V_{CC} = 1.2 \text{ V}$		72				
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$	3.5	21.1	63.1	3.5	63.9	ns
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	2.5	11.6	30.6	2.5	31.1	ns
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$	2.0	8.9	20.7	2.0	22.0	ns
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	1.5	5.6	13.3	1.5	14.1	ns
$t_{sk(o)}$	output skew time	[3]			1		1.5	ns
C_{PD}	power dissipation capacitance	Per input; $V_I = \text{GND to } V_{CC}$ [4]						
		$V_{CC} = 1.65 \text{ V to } 1.95 \text{ V}$		17.9				pF
		$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$		18.5				pF
		$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$		18.9				pF
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$		20.4				pF

[1] Typical values are measured at $T_{amb} = 25 \text{ °C}$ and $V_{CC} = 1.8 \text{ V}, 2.5 \text{ V}, 3.3 \text{ V}, \text{ and } 5 \text{ V}$ respectively.

[2] t_{pd} is the same as t_{PLH} and t_{PHL} . t_{en} is the same as t_{PZL} and t_{PHZ} . t_{dis} is the same as t_{PLZ} and t_{PHZ} .

[3] Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.

[4] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz; f_o = output frequency in MHz


C_L = output load capacitance in pF

V_{CC} = supply voltage in Volts

N = number of inputs switching

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of the outputs.


10.1. Waveforms and test circuit



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig. 5. The input nAn to output nYn propagation delays



Measurement points are given in Table 8.

V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.


Fig. 6. 3-state enable and disable times

Table 8. Measurement points

Supply voltage	Input		Output		
V_{CC}	V_I	V_M	V_M	V_X	V_Y
1.65 V to 1.95 V	V_{CC}	$0.5V_{CC}$	$0.5V_{CC}$	$V_{OL} + 0.15\text{ V}$	$V_{OH} - 0.15\text{ V}$
2.3 V to 2.7 V	V_{CC}	$0.5V_{CC}$	$0.5V_{CC}$	$V_{OL} + 0.15\text{ V}$	$V_{OH} - 0.15\text{ V}$
3.0 V to 3.6 V	3.0 V	1.5 V	1.5 V	$V_{OL} + 0.3\text{ V}$	$V_{OH} - 0.3\text{ V}$
4.5 V to 5.5 V	V_{CC}	$0.5V_{CC}$	$0.5V_{CC}$	$V_{OL} + 0.3\text{ V}$	$V_{OH} - 0.3\text{ V}$

EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state



Test data is given in Table 9.

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} = External voltage for measuring switching times.


Fig. 7. Test circuit for measuring switching times

Table 9. Test data

Supply voltage	Input		Load		V_{EXT}		
	V_I	$t_r = t_f$	C_L	R_L	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
1.2 V	V_{CC}	≤ 2 ns	15 pF	1k Ω	open	GND	$2V_{CC}$
1.65V to 1.95V	V_{CC}	≤ 2 ns	15 pF	1k Ω	open	GND	$2V_{CC}$
2.3 V to 2.7 V	V_{CC}	≤ 2 ns	15 pF	500 Ω	open	GND	$2V_{CC}$
3.0 V to 3.6 V	3.0 V	≤ 2 ns	15 pF	500 Ω	open	GND	6.0 V
4.5 V to 5.5 V	V_{CC}	≤ 2 ns	15 pF	500 Ω	open	GND	$2V_{CC}$

11. Package Outline


SOP-20L



EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state


TSSOP-20L



EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state

SSOP-20L



12. ape and Reel Information

12.1. Carrier tape dimensions




Table 10. Carrier tape dimensions

Package version	A0(mm)	B0(mm)	K0(mm)	T(mm)	P1(mm)	W(mm)	P0(mm)	PIN 1
SOP-20L	10.65	13.2	3.2	0.3	12	24	4	Q1
TSSOP-20L	6.85	6.85	1.7	0.22	8	12	4	Q1
SSOP-20L	8.4	7.75	2.5	0.3	12	16	4	Q1

EM74LVC244A; EM74LVCH244A

Octal buffer/line driver; 3-state

12.2. Reel and box dimensions




Table 11. Dimensions and quantities

Package version	Type NO. ending	Reel Dimension A (mm)	Reel Width W1 (mm)	SPQ (pcs) [1]	Reels per box	Outer box dimensions L×W×H(mm) [2]
SOP-20L	D	330	30.4	2000	1	358x340x50
TSSOP-20L	PW	330	18.4	3000	1	358x340x50
SSOP-20L	DB	330	22.4	2000	1	358x340x50

[1] Packing quantity dependent on specific product type. Please contact your local Energymath representative for ordering.

[2] Dimensions for reference only.

13. Abbreviations

Table 12. Abbreviations

Acronym	Description
CMOS	Complementary Metal-Oxide Semiconductor
DUT	Device Under Test
ESD	ElectroStatic Discharge
HBM	Human Body Model
CDM	Charged Device Model

14. Revision History

Table 13. Revision history

Document ID	Release Date	Data sheet status	Change notice	Supersedes
EM74LVC_LVCH244A Rev. 1.0	Jul 12, 2025	Product datasheet		