ANAEROBIC WORKSTATION

MAKE: BIOXIA



MODEL: A-100

BiOxia

www.bioxia.co.in

Construction & Design:

- Durable, non-corrosive Acrylic Resin Sheet construction for better visibility and insulation.
- 10% sloped front viewing panel for ergonomic observation.
- Leak-proof front transparent panel with easy glove system for comfortable handling.
- Condensate controller technology.
- Resettable over-current breaker for protection

Approximate overall dimensions

Component	Length (L)	Height (H)	Depth (D)
External	620	770	650
Internal	600	500	500

Weight: Approx. 70 Kg

Working Chamber & Capacity

- **Main Workstation:**
  a) Holds up to 100 plates (90mm x 15mm)
  b) Additional inoculation space for regular work
  c) One power supply port inside the chamber

Environmental Control

- Inoculation working temperature range: 25°C to 45°C
- Temperature Uniformity: ±2°C at 37°C
- Heating Element with controller
- Humidity Controlled with Display
- Internal Temperature and Humidity Control Display
- Heater for dehumidification
- retention for at least 30 days.
- Data download capability via USB/pen drive.

Gas Handling and Purging System

- **Inlet for two separate gases:**
  a) Premixed anaerobic gas
  b) Nitrogen gas

- **Purging System:**

  a) Automatic forced amplifying purging system for both main and interlock chambers

  b) Adjustable purging periods

  c) Foot switch operation for purging

  d) Utility port with flexible hose for manual nitrogen purging

- **Atmosphere Conditioning:**

  a) Palladium Catalyst for oxygen-free environment

  b) Activated Detox (Charcoal) to absorb odors

Monitoring and Display Features

- Inbuilt Digital Oxygen Display inside chamber
- **LCD Touchscreen Display showing:**

  a) Chamber pressure

  b) Temperature

  c) Gas pressure

  d) Fluorescent light status

  e) Visual alarms for gas cylinder pressure, chamber pressure, and temperature

  f) Low gas alarm with indicator

Electrical and Safety Features

- **Power Supply:** 230 V ±15%, 50 Hz ±3%
- Temperature overshoot controller
- Excess pressure relief valve
- Auto excess pressure control system
- Resettable over-current breaker
- Two electric sockets inside the chamber

Additional Utilities and Operations

- Internal main socket
- Positive Pressure Display: Constant positive pressure (0.15 KPA / 0.0015 bar) maintained inside chamber.