“Laminar Air Flow”



Product Highlights

Laminar Air Flow

Micro Safe Vertical Laminar Air Flow

Make – IMSET

Size: 2ft X 2ft X 2ft / 3ft X 2ft X 2ft / 4ft X 2ft X 2ft/ 6ft X 2ft X 2ft

Model : MS VLAF

An ISO 9001 : 2015 Certified
CE Marked : CE marked product
GMP Certified Product
ISO 13485 Certified
ISO 14644-1 Certified
EN 12469 : 2000

Main body	Constructed in Mild Steel with Epoxy Powder Coated
Inner SS	Back wall & Sidewall made in stainless steel SS 304
Work Surface (Tray)	Solid one piece dished, Seamless, Scratch-free, high quality 18 gauge stainless steel, grade 304. Autoclavable & Removable stainless steel work surface for easy cleaning

Filter type	HEPA filter with integral metal guards & frame gaskets. Supply of HEPA filter 99.997% at 0.3 micron / ULPA Filter 99.999% at 0.1-to-0.3-micron.
Primary Filter	Specially designed pre filter to increase the life of HEPA filter
LCD Display	For Operating Fluorescent, UV Light & Blower With Audio and Visual alarm for HEPA filters blockage and life of the HEPA filter. And also for Static Pressure Measurement of HEPA Filter. Conveniently located display on outside of the Laminar Air Flow for easy use & also easy to reach from a seated working position.
UV Light programming	Available with timer
Ultra violet tube light	Germicidal i.e. 254 nm
Electrical socket	Internal electrical socket inside the chamber. 5/15 Amp
Ergonomic tilt	Exceptionally comfortable 10 deg ergonomic design improves comfort, prevents user fatigue & promotes safe working techniques.
Front control panel	Provided to avoid exposure of UV Light & Lamp outside, making eyes more comfortable.
Front sash door	fully closing with hinged Manual sliding sash door made up of Imported poly carbonate sheet or toughened glass with sloping front for better access of samples Front sash door height can be easily adjusted as per required by end-user. The transparent sash door maximizes light & visibility inside the cabinet, providing a bright & open working environment. The closing/opening of front door is integrated with the UV ON/OFF. The UV will automatically switch “OFF” when the sash

	door is opened & switch "ON" when door is closed to avoid accidental exposure of UV light to the operator.
Air velocity	100 ft/min ± 10
Down flow velocity	40-70 fpm
Air volume	Up to 500 CFM
Gauges	for monitoring the condition of all HEPA filters as well as work space.
Sleep Mode Operation	Automatically blower speed reduced up to 30%, this will help to save energy as well as help to maintain sterile work area during Biosafety Cabinet is not in operation
Intelligence Alarm System	Safety purpose Audio & Visual alarm for air fluctuation and for life of the HEPA filter and UV light
Illumination of work surface	Fluorescent tube light (intensity > 600 lux) provides excellent illumination for work surface & reduces operator fatigue
Working Noise level	Low/ should be < 65 dB
Electronic / Electrical panel	From clean chamber to give better contamination free results.
Electrical safety	Electrical components used are standard for better electrical safety for the operator.
CE & ISO 9001 : 2015	System is certified with CE & ISO 9001 : 2015
Power supply	230 V ± 15%, 50 Hz ± 3%
Arm rest bar	To avoid contamination from outside to inside contamination & for easy working with comfort. Secure & comfortable armrests enhance your comfort during extended work sessions
Drainage port	Provide beneath work surface to facilitate easy & better cleaning of the interior & handling of spillage inside the chamber

Blower-Motor Assembly	Dynamically & statistically balanced aluminum centrifugal impeller driven by single phase, 2800 RPM motor Double inlet blower fitted in such a way to reduces vibration. Blower is positioned in such a way that, to create an even filter loading, it helps to prolong the life of HEPA filters.
Trolley (Base Stand)	Provided with lockable castor wheels
Certificates	IQ, OQ & PQ Certificates will give Calibration & Traceability certificate
Applicable Standards	EN ISO 14971:2012, EN ISO 13485 : 2012 , EN 980:2008 , EN 1041 : 2008 , EN 61010-1:2010, EN 61326-1:2013, EN 12469:2000

Salient Features:-

- Seamless stainless steel removable work surface.
- The cabinet designed with curved frond edge for maximum operator comfort.
- The closing/opening of front door is integrated with the UV ON/OFF. The UV will automatically switch "OFF" when the sash door is opened & switch "ON" when door is closed to avoid accidental exposure of UV light to the operator.
- Double inlet blower fitted in such a way to reduces vibration.
- UV absorbent counterbalanced front sash door made up of toughened glass or polycarbonate sheet provided with channel locks for adjustment at particular level.
- Fluorescent tube light positioned at the front side.
- Operational Instruction Manual is provided along with equipment.

Applicable Standards : EN ISO 14971:2012,EN ISO 13485 : 2012 , EN 980:2008 , EN 1041 : 2008 , EN 61010-1:2010, EN 61326-1:2013, EN 12469:2000

Comfortable Ergonomic
10
Degree Sloped Front
Allows easy cleaning





ISO 9001 : 2015 Certified Company

CE Marked : CE marked product

www.imset.co.in