


# Lecture 3: Loss Functions and Optimization

# Recall from last time: Challenges of recognition

Viewpoint



Illumination



[This image](#) is [CC0 1.0](#) public domain

Deformation




[This image](#) by [Umberto Salvagnin](#) is licensed under [CC-BY 2.0](#)

Occlusion



[This image](#) by [jonsson](#) is licensed under [CC-BY 2.0](#)

Clutter



[This image](#) is [CC0 1.0](#) public domain

Intraclass Variation



[This image](#) is [CC0 1.0](#) public domain

# Recall from last time: data-driven approach, kNN

airplane

automobile

bird

cat

deer


dog

frog


horse

ship


truck



1-NN classifier



5-NN classifier




train

test


train

validation

test




# Recall from last time: Linear Classifier



$$f(x, W) = Wx + b$$

## Algebraic Viewpoint

$$f(x, W) = Wx$$




## Visual Viewpoint

One template per class



## Geometric Viewpoint

Hyperplanes cutting up space




**Class 1:**

$1 \leq L2 \text{ norm} \leq 2$

**Class 2:**

Everything else




**Class 1:**

Three modes

**Class 2:**

Everything else



# Recall from last time: Linear Classifier




airplane	-3.45	-0.51	3.42
automobile	-8.87	<b>6.04</b>	4.64
bird	0.09	5.31	2.65
cat	<b>2.9</b>	-4.22	5.1
deer	4.48	-4.19	2.64
dog	8.02	3.58	5.55
frog	3.78	4.49	<b>-4.34</b>
horse	1.06	-4.37	-1.5
ship	-0.36	-2.09	-4.79
truck	-0.72	-2.93	6.14

TODO:

1. Define a **loss function** that quantifies our unhappiness with the scores across the training data.
2. Come up with a way of efficiently finding the parameters that minimize the loss function.  
**(optimization)**

Cat image by Nikita is licensed under CC-BY 2.0; Car image is CC0 1.0 public domain; Frog image is in the public domain


Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	<b>1.3</b>	<b>2.2</b>
car	<b>5.1</b>	<b>4.9</b>	<b>2.5</b>
frog	<b>-1.7</b>	<b>2.0</b>	<b>-3.1</b>



Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>

A **loss function** tells how good our current classifier is

Given a dataset of examples


$$\{(x_i, y_i)\}_{i=1}^N$$

Where  $x_i$  is image and  
 $y_i$  is (integer) label

Loss over the dataset is a  
sum of loss over examples:

$$L = \frac{1}{N} \sum_i L_i(f(x_i, W), y_i)$$

Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
 where  $x_i$  is the image and  
 where  $y_i$  is the (integer) label,

and using the shorthand for the  
 scores vector:  $s = f(x_i, W)$


the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$

$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$




Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>


## Multiclass SVM loss:



$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$

$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>

## Multiclass SVM loss:


Given an example  $(x_i, y_i)$   
where  $x_i$  is the image and  
where  $y_i$  is the (integer) label,

and using the shorthand for the  
scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	<b>2.9</b>		

## Multiclass SVM loss:


Given an example  $(x_i, y_i)$   
where  $x_i$  is the image and  
where  $y_i$  is the (integer) label,

and using the shorthand for the  
scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned} L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\ &= \max(0, 5.1 - 3.2 + 1) \\ &\quad + \max(0, -1.7 - 3.2 + 1) \\ &= \max(0, 2.9) + \max(0, -3.9) \\ &= 2.9 + 0 \\ &= 2.9 \end{aligned}$$

Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	

## Multiclass SVM loss:


Given an example  $(x_i, y_i)$   
 where  $x_i$  is the image and  
 where  $y_i$  is the (integer) label,

and using the shorthand for the  
 scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned}
 L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\
 &= \max(0, 1.3 - 4.9 + 1) \\
 &\quad + \max(0, 2.0 - 4.9 + 1) \\
 &= \max(0, -2.6) + \max(0, -1.9) \\
 &= 0 + 0 \\
 &= 0
 \end{aligned}$$

Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	<b>12.9</b>

## Multiclass SVM loss:


Given an example  $(x_i, y_i)$   
 where  $x_i$  is the image and  
 where  $y_i$  is the (integer) label,

and using the shorthand for the  
 scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned}
 L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\
 &= \max(0, 2.2 - (-3.1) + 1) \\
 &\quad + \max(0, 2.5 - (-3.1) + 1) \\
 &= \max(0, 6.3) + \max(0, 6.6) \\
 &= 6.3 + 6.6 \\
 &= 12.9
 \end{aligned}$$

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
where  $x_i$  is the image and  
where  $y_i$  is the (integer) label,

and using the shorthand for the  
scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Loss over full dataset is average:

$$L = \frac{1}{N} \sum_{i=1}^N L_i$$

$$L = (2.9 + 0 + 12.9)/3 \\ = \mathbf{5.27}$$



Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
 where  $x_i$  is the image and  
 where  $y_i$  is the (integer) label,


and using the shorthand for the  
 scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q: What happens to  
 loss if car scores  
 change a bit?

Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
 where  $x_i$  is the image and  
 where  $y_i$  is the (integer) label,


and using the shorthand for the  
 scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q2: what is the  
 min/max possible  
 loss?

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
where  $x_i$  is the image and  
where  $y_i$  is the (integer) label,


and using the shorthand for the  
scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q3: At initialization  $W$   
is small so all  $s \approx 0$ .  
What is the loss?

Suppose: 3 training examples, 3 classes.  
 With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
 where  $x_i$  is the image and  
 where  $y_i$  is the (integer) label,


and using the shorthand for the  
 scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q4: What if the sum  
 was over all classes?  
 (including  $j = y_i$ )

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
where  $x_i$  is the image and  
where  $y_i$  is the (integer) label,


and using the shorthand for the  
scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q5: What if we used  
mean instead of  
sum?

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	12.9

## Multiclass SVM loss:

Given an example  $(x_i, y_i)$   
where  $x_i$  is the image and  
where  $y_i$  is the (integer) label,

and using the shorthand for the  
scores vector:  $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q6: What if we used

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)^2$$