

【별표 8】

1차측 배관재 규격

(제14조 제1항 관련) <개정 12.11.5., 17.11.24., 25.09.01.>

RATING	TEMP.(°C)	-29 TO 38	93	149	204	316	371	399
	PRESS(bar)	19.6	17.9	15.9	13.8	9.6	7.5	6.6
ITEM	NOM. SIZE FROM-TO	MATERIAL	DESCRIPTION			REMARK		
			PRODUCT		END/TYPE			
PIPE	50A이하	SPPS 250	S or E		PE	SCH.40		
	65A-150A	SPPS 250	S or E		BE	SCH.40		
	200A이상	SPPS 250	E		BE	STD		
FITTING (ELBOW, TEE, RED.)	50A이하	SF 440A	-		SW	TO MATCH PIPE		
	65A이상	PS 380	-		BW	TO MATCH PIPE		
FLANGE	FROM-TO	MATERIAL	RATING		TYPE			
	50A이하	SF 440A	ANSI#300		SW,FF			
	65A이상	SF 440A	ANSI#300		SO,RF			
GASKET	50A이하	COMPRESSED NON ASBESTOS			1.5mmTHK			
	65A이상	COMPRESSED NON ASBESTOS			3.0mmTHK			
BOLT		ASTM A 193 B7 or KSD 3755 SNB7			STUD			
NUT		ASTM A 194 2H or KSD3752 SM45C			HEAVY HEX			