What will be the output of the following code

Lets follow outout number link

```c
#include <stdio.h>

int main() {
    int num = 7;
    for (int i = 0; i < 10; i++) {
        if (i % 2 == 0) {
            num++;
        } else {
            num--;
            num += 10;
        }
    }
    printf("Link NO %d", num);
    return 0;
}
```

Output: ?????????

pigglywiggly

pigglywiggly
pigglywiggly
pigglywiggly
pigglywiggly
pigglywiggly
pigglywiggly
pigglywiggly
pigglywiggly
pigglywiggly

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

[pigglywiggly](#)

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly

pigglywiggly