SQLITE3 CRUD

```
import sqlite3
conn = sqlite3.connect("student.db")
cursor = conn.cursor()
cursor.execute("""
CREATE TABLE IF NOT EXISTS emp(
  RollNo INTEGER,
  Name TEXT,
  Age INTEGER)""")
print("Table created successfully.")
cursor.execute("""
INSERT INTO emp VALUES(13, 'Jiya', 20),(14, 'Manu', 19),(15, 'Komu', 20)""")
conn.commit()
print("Records inserted successfully.")
print("\nEmp Records:")
cursor.execute("SELECT * FROM emp")
rows = cursor.fetchall()
for row in rows:
  print(row)
cursor.execute("""UPDATE emp SET Age = 21 WHERE RollNo = 14""")
conn.commit()
print("\nRecord updated successfully.")
print("\nUpdated Emp Records:")
cursor.execute("SELECT * FROM emp")
rows = cursor.fetchall()

for row in rows:
  print(row)
```

```
cursor.execute("DELETE FROM emp WHERE RollNo = 13")
conn.commit()
print("\nRecord deleted successfully.")
print("\nFinal Emp Records:")
cursor.execute("SELECT * FROM emp")
rows = cursor.fetchall()
for row in rows:
   print(row)
cursor.close()
conn.close()
print("\nDatabase connection closed.")
```

SQLITE3 CMD CRUD

```
sqlite3 student.db
 CREATE TABLE emp(RollNo INTEGER,Name TEXT,Age INTEGER);
INSERT INTO emp VALUES(13,'Jiya',20);
INSERT INTO emp VALUES(14,'Manu',19);
INSERT INTO emp VALUES(15,'Komu',20);
SELECT * FROM emp;
UPDATE emp SET Age=21 WHERE RollNo=14;
DELETE FROM emp WHERE RollNo=13; SELECT * FROM emp;
```

MONGODB CRUD CMD

```
Mongosh
use clg1
db
db.createCollection("student")
 db.student.insertOne ({name: "jiya", age: 20, course: "bsc cs"})
```

```
db.student.insertMany([ {name:"jiya", age:20, course:"bsc cs", marks:85},
{name:"komal", age:21, course:"it", marks:90}, {name:"manasvi", age:19, course:"ca",
marks:75}])

db.student.find()

 db.student.findOne({name:"jiya"})

db.student.updateOne({name:"jiya"}, {$set:{marks:95}})

db.student.findOne({name:"jiya"})

db.student.deleteOne({name:"komal"})

 db.student.find()
```

MONGODB CRUD

```
from pymongo import MongoClient

client = MongoClient("mongodb://localhost:27017")

db = client["college"]

collection = db["student"]

students = [ {"name": "jiya", "age": 20, "course": "bsc cs"}, {"name": "komal", "age": 21,
"course": "it"}, {"name": "manasvi", "age": 19, "course": "ca"} ]

collection.insert_many(students)

print("Data inserted successfully")

print("\nAll Students:")

for student in collection.find():

print(student)

print("\nSingle Student:")

student = collection.find_one({"name": "jiya"})

print(student)

collection.update_one( {"name": "jiya"}, {"$set": {"age": 21}})

print("\nData updated successfully")


collection.delete_one( {"name": "komal"})
```

```
print("Data deleted successfully")


print("\nFinal Student Data:")
 for student in collection.find():
print(student)
```

EXPORT AND IMPORT

Emport

```
sqlite3 college.db
```

create and insert

```
CREATE TABLE stud ( id INTEGER, name TEXT, age INTEGER, course TEXT );
INSERT INTO stud VALUES (1, 'Jiya', 20, 'BSc CS');
INSERT INTO stud VALUES (2, 'Riya', 21, 'BSc CS');
INSERT INTO stud VALUES (3, 'Neha', 20, 'BCA');
.mode csv
.headers on
.output filename.csv
id,name,age,course 1,Jiya,20,BSc CS 2,Riya,21,BSc CS 3,Neha,20,BCA
select * from stud;
.output stdout
```

import

```
kdata.csv
id,name,age,course 4,Krisha,20,BSc CS 5,Hetvi,21,BCA 6,Diya,20,BSc IT
```

create csv and sqlite3 table same headers on that

```
CREATE TABLE stud ( id INTEGER, name TEXT, age INTEGER, course TEXT );
.mode csv
.import --skip 1 kdata.csv stud
select * from stud;
```

FATCHALL AN FATCHONE

```
import sqlite3
conn = sqlite3.connect("student1.db")
cursor = conn.cursor()
cursor.execute("""
CREATE TABLE IF NOT EXISTS emp (
   RollNo INTEGER,
   Name TEXT,
   Age INTEGER
)""")
print("Table created successfully.")
cursor.execute("""
INSERT INTO emp VALUES(13, 'Jiya', 20),(14, 'Manu', 19),(15, 'Komu', 20)""")
conn.commit()
print("Records inserted successfully.")

# fetchall()
print("\nAll Student Records:")
cursor.execute("SELECT * FROM emp")
print(cursor.fetchall())
# fetchone()
print("\nOne Student Record:")
cursor.execute("SELECT * FROM emp")
print(cursor.fetchone())
conn.close()
```