



# ouees-201906 talks Part 2/3: Routing and transport protocols

# Kenji Rikitake

18-JUN-2019

School of Engineering Science

Osaka University

Toyonaka, Osaka, Japan

@jj1bdx

Copyright ©2018-2019 Kenji Rikitake.

This work is licensed under a [Creative Commons Attribution 4.0 International License](#).



# Lecture notes

- <https://github.com/jj1bdx/oueees-201906-public/>
- Check out the README.md file and the issues!

# Reporting

- Keyword at the end of the talk
- URL for submitting the report at the end of the talk


# Today's topic: flexible packet routing and transport protocols

# Various aspects of routing

- Delivery
- Addresses
- Static or dynamic
- Route aggregation
- Security


# Delivery schemes

- Unicast
- Broadcast/Multicast/Anycast




Unicast






Broadcast



Multicast



Anycast

# Internet protocol (IP) and IP addresses

# Role of IP addresses

- Network numbers
- Interfaces: connected to the networks
- Host IDs in the numbered networks
- Global uniqueness
- Special addresses (private, broadcast, multicast, loopback, etc.)

# IPv4 addresses: 32 bits

# 192.168.100.20

In hexadecimal notation: 0xC0A86414

- 4 x 0~255 numbers split with dots
- Relatively easy to remember, but already being used up

# IPv4 address with netmask 192.168.100.20/24

- Network: 192.168.100.0/24
- Host: number 20 (0~255) ( $32-24=8$ )
- Host 0 = network itself
- Host 255 = broadcast

# Address in another netmask

## 192.168.100.20/28

- Network: 192.168.100.16/28
- Host: number 2 (0~15) ( $32-24=4$ )
- Host 0 = network itself
- Host 15 = broadcast
- Different netmask = different address interpretation



# Private addresses (RFC1918)

No global routing for these address blocks

- 10.0.0.0/8
- 172.16.0.0/12 (172.{16~31}.\*.\*)
- 192.168.0.0/16 (192.168.\*.\*)

# Other special addresses (RFC6890)

- 0.0.0.0/8: "This" network
- 100.64.0.0/10: Shared address
- 127.0.0.0/8: Loopback
- 169.254.0.0/16: Link local
- 192.0.0.0/24: IANA specific
- 192.0.2.0/24, 198.51.100.0/24, 203.0.113.0/24: Documentation
- 192.88.99.0/24: 6to4 Relay Anycast
- 198.18.0.0/15: Benchmarking
- 240.0.0.0/4: Reserved
- 255.255.255.255/32: Limited broadcast

# IPv6 addresses: 128 bits

## 2404:6800:400a:808::2004

= 2404:6800:400a:0808:0000:0000:0000:2004

- [www.google.com](http://www.google.com) as of 17-JUN-2019 0505UTC
- :xxxx: = up to 4 hex digits
- :: = arbitrary number of 0, appearing only once in an address

# IPv6 addresses with netmask

## 2404:6800:400a:808::2004/64


- Network: 2404:6800:400a:808::/64
- Host number: 0x000000000000002004
- Host number: 64 bits (0: network)
- Broadcast -> multicast addresses
- ff02::1 = all hosts, ff02::2 = all routers, etc.

# Why IPv4 to IPv6?

- Because we've used up the 32-bit IPv4 addresses already
- No more new address block for IPv4
- You need to buy unused blocks from other users
- Took ~20 years (1996-2016) for the transition from IPv4 to IPv6

# Routing







# Static routing

- Set the default route for nodes which are not directly reachable
- Works well on simple networks or star networks
- Static routing may cause *ping-pong*

→ Default static route



→ Default static route




# Dynamic routing

- Hop count: count the hops between nodes
- Link cost: determined by the speed and quality
- Administrative policies

# Simple hop counting


- Assume every link costs the same with each other






# Evaluating link cost


- What if the cost of each link varies?
- If two or more paths have the equal cost, all of the links will be utilized for load balancing





# Simulating link failures


- What if the link suddenly degrades or is disconnected?
- Largely increasing the cost of degraded or disconnected links will give an easy solution





# Administrative policies

- For many reasons, you don't want to accept packets from some nodes, depending on the relay paths
- For example: passing C is OK, but passing E is not: A-B-C-G and A-B-C-F-G are OK, but A-D-E-F-G is blocked
- Common among interconnection of the autonomous systems (internet service providers and organizations)



# Routing information dissemination protocols

- Link-state protocol: flooding link cost information of each node throughout the network
- Path vector protocol: exchanging path of nodes for each network instead of the link costs
- Highly vulnerable to external attacks

# Routing aggregation

- The following four networks
  - 192.168.100.0/24
  - 192.168.101.0/24
  - 192.168.102.0/24
  - 192.168.103.0/24
- -> aggregated as 192.168.100.0/22
- 4 networks together as one aggregated network

# Network transports

# IP address and the port number

- Each service has a 16-bit port number
- HTTPS = 443, DNS = 53, SSH = 22, etc.
- A pair of IP address and port number defines an endpoint of communication

# UDP and TCP

- Two major transport protocols on the internet
- User Datagram Protocol (UDP): connection-less
- Transport Control Protocol (TCP): connection-oriented

# Packet exchange limitation

- Packets are not always delivered
- Sending sequence is not preserved
- The same packet may be received multiple times
- The content of the packet may get altered or damaged
- Packet size has the limitation



# What UDP does

- Add a header with the port number
- Send it in an IP packet
- ... and that's it

# UDP's pros and cons

- UDP datagrams are still not always delivered and may get lost
- Sequence is not preserved
- The same datagram may be received multiple times and may cause duplicate delivery
- The errors in the contents of UDP datagrams are detectable
- UDP datagram has the size limit: suitable for relatively small messages
- Very small additional latency

# Transport control protocol (TCP)

- Detect packet loss by timeout
- Split stream into segments
- Put sequence numbers to the segments
- Reassemble segments to the stream
- Perform congestion control

# TCP's pros and cons

- Loss is detected and recovered so long as the connection is alive
- Sequence is preserved
- No content repetition
- Errors are detected and fixed by retransmission
- The stream will accept data so long as the connection is alive
- Data delivery may delay if retransmission occurs

# Web: HTTP/2 (TCP) .vs. QUIC (UDP)

- People wants *speed*
- HTTP/2: stream aggregation and content compression
- HTTP/2 is still bound by TCP
- QUIC: tightly integrated to HTTP/2 and specific congestion control
- Google is migrating to HTTP/2 + QUIC

# Topics on next talk

- Cloud computing .vs. endpoint computing
- Sharing .vs. message passing
- Centralization .vs. decentralization

# Photo credits

- All photos are modified and edited by Kenji Rikitake
- Title: Denis Nevozhai via Unsplash
- Unicast/broadcast/multicast/anycast diagrams: By Easyas12c~commonswiki / Perhelion, via Wikimedia Commons, CC0 (Public Domain)