

oueees-202006 topic 06:

Routing in details

Kenji Rikitake

10-JUN-2020

School of Engineering Science, Osaka University

On the internet

@jj1bdx

Copyright ©2018-2020 Kenji Rikitake.

This work is licensed under a [Creative Commons Attribution 4.0 International License](#).

CAUTION

Osaka University School of Engineering Science prohibits copying/redistribution of the lecture series video/audio files used in this lecture series.


大阪大学基礎工学部からの要請により、本講義で使用するビデオ/音声ファイルの複製や再配布は禁止されています。

Lecture notes and reporting

- <https://github.com/jj1bdx/oueees-202006-public/>
- Check out the README.md file and the issues!
- Keyword at the end of the talk
- URL for submitting the report at the end of the talk

Topic of this video:


Routing in details




Static routing

- Set the default route for nodes which are not directly reachable
- Works well on simple networks or star networks
- Static routing may cause *ping-pong*

→ Default static route



→ Default static route




Dynamic routing

- Hop count: count the hops between nodes
- Link cost: determined by the speed and quality
- Administrative policies


Simple hop counting


- Assume every link costs the same with each other



Evaluating link cost


- What if the cost of each link varies?
- If two or more paths have the equal cost, all of the links will be utilized for load balancing






Simulating link failures

- What if the link suddenly degrades or is disconnected?
- Largely increasing the cost of degraded or disconnected links will give an easy solution



Administrative policies

- For many reasons, you don't want to accept packets from some nodes, depending on the relay paths
- For example: passing C is OK, but passing E is not: A-B-C-G and A-B-C-F-G are OK, but A-D-E-F-G is blocked
- Common among interconnection of the autonomous systems (internet service providers and organizations)



Routing information dissemination protocols

- Link-state protocol: flooding link cost information of each node throughout the network
- Path vector protocol: exchanging path of nodes for each network instead of the link costs
- Highly vulnerable to external attacks

Routing aggregation

- The following four networks
 - 192.168.100.0/24
 - 192.168.101.0/24
 - 192.168.102.0/24
 - 192.168.103.0/24
- -> aggregated as 192.168.100.0/22
- 4 networks together as one aggregated network

Photo and image credits

- All photos and images are modified and edited by Kenji Rikitake
- Photos are from Unsplash.com unless otherwise noted